

## Find the Number Occurring Odd Number of Times

Given an array of positive integers. All numbers occur even number of times except one number which occurs odd number of times. Find the number in  $O(n)$  time & constant space.

### Example:

I/P = [1, 2, 3, 2, 3, 1, 3]

O/P = 3

### Algorithm:

Do bitwise XOR of all the elements. Finally we get the number which has odd occurrences.

### Program:

```
#include <stdio.h>

int getOddOccurrence(int ar[], int ar_size)
{
    int i;
    int res = 0;
    for (i=0; i < ar_size; i++)
        res = res ^ ar[i];

    return res;
}

/* Diver function to test above function */
int main()
{
    int ar[] = {2, 3, 5, 4, 5, 2, 4, 3, 5, 2, 4, 4, 2};
    int n = sizeof(ar)/sizeof(ar[0]);
    printf("%d", getOddOccurrence(ar, n));
}
```


Google™ Custom Search



GeeksforGeeks



53,526 people like [GeeksforGeeks](#).



[Interview Experiences](#)

[Advanced Data Structures](#)

[Dynamic Programming](#)

[Greedy Algorithms](#)

[Backtracking](#)

[Pattern Searching](#)

[Divide & Conquer](#)


[Mathematical Algorithms](#)

[Recursion](#)

[Geometric Algorithms](#)

```
return 0;
}
```

**Time Complexity:**  $O(n)$



## Popular Posts

All permutations of a given string

Memory Layout of C Programs

Understanding “extern” keyword in C

Median of two sorted arrays

Tree traversal without recursion and without stack!

Structure Member Alignment, Padding and

Data Packing

Intersection point of two Linked Lists

Lowest Common Ancestor in a BST.

Check if a binary tree is BST or not

Sorted Linked List to Balanced BST

## Related Topics:

- Remove minimum elements from either side such that  $2 \times \min$  becomes more than max
- Divide and Conquer | Set 6 (Search in a Row-wise and Column-wise Sorted 2D Array)
- Bucket Sort
- Kth smallest element in a row-wise and column-wise sorted 2D array | Set 1
- Find the number of zeroes
- Find if there is a subarray with 0 sum
- Divide and Conquer | Set 5 (Strassen's Matrix Multiplication)
- Count all possible groups of size 2 or 3 that have sum as multiple of 3



2



Tweet 0



1

**Writing code in comment?** Please use [ideone.com](https://ideone.com) and share the link here.

37 Comments

GeeksforGeeks

Sort by Newest ▾



Join the discussion...



**groomnestle** · 5 months ago

There is a similar post here (find the element that appeared once, method 2):

```
int getOddOccurrence(int ar[], int ar_size)
```

```
{
```

```
int result = 0;
```

```
int x, sum;
```

```
// Iterate through every bit
```

```
for (int i = 0; i < ar_size; i++)
```

[see more](#)

^ | ▾ ·



**Amit Baghel** · 6 months ago

Visited

UP TO **70% OFF**  
Everything home

wayfair.com **SHOP NOW**



visited :D

^ | v .



**guest** → Amit Baghel · 6 months ago

so u are marking all the posts as visited:p

15 ^ | v .



**Pratik Sahoo** · 7 months ago

We can also do it by Hash Map where the hash array would keep the no of occ  
Complexity

1 ^ | v .



**Vinod** → Pratik Sahoo · 6 months ago

@Pratik...In case of Hash map you are considering only the time comp

1 ^ | v .



**Pratik Sahoo** → Vinod · 6 months ago

Since there is no restriction on the Space... we can use it..

^ | v .



**hookah** → Pratik Sahoo · 5 months ago

The question mentions Find the number in O(n) time &

3 ^ | v .



**Avinash Nigam** · 7 months ago

```
public static int getOddOccuringElement(int[] arr)
```

```
{
```

705



Subscribe

## Recent Comments

Abhi You live US or India?

Google (Mountain View) interview · 20 minutes ago

**Aman** Hi, Why arent we checking for conditions...

Write a C program to Delete a Tree. · 59 minutes ago

kzs please provide solution for the problem...

Backtracking | Set 2 (Rat in a Maze) · 1 hour ago

**Sanjay Agarwal** bool

tree::Root\_to\_leaf\_path\_given\_sum(tree...

Root to leaf path sum equal to a given number · 1 hour ago

**GOPI GOPINATH** @admin Highlight this sentence "We can easily...

Count trailing zeroes in factorial of a number · 1 hour ago

**newCoder3006** If the array contains negative numbers also. We...

Find subarray with given sum · 1 hour ago

AdChoices

► [Java Array](#)

► [Odd Number](#)

► [Memory Array](#)

```

    int oddOccuringElement = 0;

    for (int i = 0; i < arr.length - 1; i = i + 2)

    {

        oddOccuringElement = oddOccuringElement + arr[i];

    }


    oddOccuringElement = oddOccuringElement + arr[arr.length - 1];

    oddOccuringElement = Util.mod(oddOccuringElement);

    return oddOccuringElement;

}


```

AdChoices 

[▶ Memory Array](#)

[▶ Numbers Number](#)

[▶ Even Number](#)

AdChoices 

[▶ Print Number](#)

[▶ Odd Even](#)

[▶ Log Me Int](#)

^ | v ·



**Marsha Donna** · 8 months ago

the prblm can be solved by subtractng elemnts of the array in sequence, in the end only the ele ocring odd no of times will be left....pls corrcet me if anything is wrong..see the follwing code

```

#include <stdio.h>
#include<math.h>
int getOddOccurrence(int ar[], int ar_size)
{

```

```

int i;
int res = 0;
ar[ar_size]=0;
for (i=0; i <= ar_size; i=i+2)
res = ar[i+1]-ar[i];

return abs(res);
}

/* Diver function to test above function */
int main()
{
int ar[] = {55,77,44,55,77,44,44};
int n = sizeof(ar)/sizeof(ar[0]);
printf("%d", getOddOccurrence(ar, n));
return 0;
}
^ | v .

```



**Sourin Sutradhar** → Marsha Donna · 7 months ago

This wont work as you are totally neglecting the initial calculated values  
example, if ar[] = {1,2,1,2,0,2,1,2,0}, this gives output as '0' , which is w

^ | v .



**Marsha Donna** → Sourin Sutradhar · 7 months ago

thanks i dint notice that case

^ | v .



**Sourin Sutradhar** → Marsha Donna · 7 months ago

you are welcome

^ | v .



**Guest** · 8 months ago

the prblm can be solved by subtractng elemnts of the array in sequence in the times will be left....pls corrcet me if anything is wrong

```
#include <stdio.h>
```

```
#include<math.h>
```

```
int getOddOccurrence(int ar[], int ar_size)
```

```
{
```

```
int i;
```

```
int res = 0;
```

```
ar[ar_size]=0;
```

```
for (i=0; i <= ar_size; i=i+2)
```

```
res = ar[i+1]-ar[i];
```

```
return abs(res);
```

```
}
```

```
/* Diver function to test above function */
```

```
int main()
```

```
{
```

```
int ar[] = {55,77,44,55,77,44,44};
```

```
int n = sizeof(ar)/sizeof(ar[0]);
```

```
printf("%d", getOddOccurrence(ar, n));
```

```
return 0;
```

```
}
```

^ | v ·



**Chinmaya** · a year ago

Nice Question. Thanks..

^ | v ·



**Ujjwal** → Chinmaya · a year ago

yeah gud 1 but i guess its a standard problem so chances are that eve

^ | v .



**dazer** · a year ago

sorry i didn read the question properly :( i missed "other elements occuring even any suggestion for finding out the odd occurrence of element in  $O(n)$  time with  $O(1)$  space complexity ??

^ | v .



**Ankit Sablok** → **dazer** · a year ago

There we will have to use auxiliary memory in the form of a hashmap for  $O(1)$  time performance.

```
/* Paste your code here (You may delete these lines if not writing code)
```

^ | v .



**dazer** · a year ago

i guess your algo doesnt work for input : {1,2,1,1}  
answer should be 1 but its giving 3 .  
so this algorithm works wrong :P

```
/* Paste your code here (You may delete these lines if not writing code)
```

^ | v .



**Ankit Sablok** → **dazer** · a year ago

I think you didn't read the question carefully it says all other elements occur an even number of times.  
case both 1 and 2 occur odd number of times.

1 ^ | v .



**Nishant Kumar** · a year ago

Please suggest me an algo in Time Complexity:  $O(n)$  and space Complexity:  $O(1)$   
large i.e instead of only one odd time repeating no. if we have suppose 15 odd



large i.e. instead of only one odd time repeating no. if we have suppose 15 odd repeating). if possible

e.g - {2, 3, 5, 4, 5, 2, 3, 5, 2};

^ | v .



**nick** → Nishant Kumar · a year ago

What is that you exactly want ? Do you want to print all the odd numbe  
have 15 odd time repeating no so you want to store them and print it ?'

^ | v .



**Nishant** → nick · a year ago

@nick yes, i want to print all numbers occurring odd numbers c

^ | v .



**geekyboy** → Nishant · a year ago

even i have the same question.

How do we go about finding all the odd no of times occu

in that case xor won't work

and what if we want  $O(n)$  solution

^ | v .



**Nishant Kumar** → geekyboy · a year ago

@geekyboy if you don't bother abt space Complexity:  $O$   
using HashMap

```
/* Paste your code here (You may delete these li
```

1 ^ | v .



**Saurabh** · 2 years ago



@geeksForGeeks: I think your algo would n't work for the sequence:

int ar[] = {7, 3, 5, 4, 5, 2, 2, 4, 3, 5, 2, 6, 6, 2, 7};

please tell me if I am wrong.

^ | v .



abcd → Saurabh · a year ago

@saurabh:

Its not working as 2,5 i.e. 2 nos. r there odd no. of time but as per the q

```
/* Paste your code here (You may delete these lines if not wri
```

^ | v .



Sumeet → Saurabh · a year ago

@Saurabh: It is working for this case also. Answer is 5. Take a closer

```
/* Paste your code here (You may delete these lines if not wri
```

^ | v .



GeeksforGeeks → Saurabh · 2 years ago

Take a closer look at the algorithm. It's a simple and standard algorithm

^ | v .



rohith → GeeksforGeeks · 10 months ago

Could you please explain the logic behind this algorithm.

How does doing XOR of all the elements get me this result, not

Thank you.

2 ^ | v .



Shubham Lakhiwal · 2 years ago

```
int main()
```

```

{
    int a[]={2, 3, 5, 4, 4, 2, 4, 3, 5, 2, 4, 4, 2};
    int maj_index = 0, count = 0,i=0;

    while(count%2==0){
        count = 0;
        for(i = 0; i<13; i++){
            if (a[maj_index] == a[i])
                count++;
        }
        maj_index++;
    }
    printf("%d",a[maj_index-1]);

    scanf("%d",&i);
    return 0;
}

```

1 ^ | v .



**Mo Pu** → Shubham Lakhiwal · a year ago

Correct algo, but time complexity is  $O(n^2)$

```

/* Paste your code here (You may delete these lines if not wr

```

^ | v .



**Saurabh** → Shubham Lakhiwal · 2 years ago

@Shubham Lakhiwal: I think your algo would n't work for the sequence

```
int ar[] = {7, 3, 5, 4, 5, 2,2, 4, 3, 5, 2, 6, 6, 2,7};
```

please tell me if I am wrong

please tell me if I am wrong.

^ | v .



Anuj Bansal · 2 years ago

Here is another solution to this problem.

```
#include <stdio.h>
#include<math.h>
int getOddOccurrence(int ar[], int ar_size)
{
    int i,j,res;
    i = 0; j = ar_size-1; res = 0;
    while(i < ar_size/2)
        res = res - ar[i++] + ar[j--];
    res = res - ar[i];
    return abs(res);
}

int main()
{
    int ar[] = {2, 3, 5, 4, 5, 2, 4, 3, 5, 2, 4, 4, 2};
    printf("%d\n", getOddOccurrence(ar, 13));
    getchar();
}
```

^ | v .



Lakshminarayana → Anuj Bansal · 5 months ago

above solution is not working for { 7,3,5,4,5,2,2,4,3,5,2,6,6,2,7 }. Please

^ | v .



Shashank → Anuj Bansal · 2 years ago

The above solution mentioned in first comment is incorrect as for an a

The above solution mentioned in first comment is incorrect as for an array [2,4,3,3,3,4,2] however it would work if we change the distribution to 2,4,3,3,3,4,2. So only if elements before middle element and elements after middle element are equal. correct me if im wrong.

^ | v .



**Ankita** → Shashank · 10 months ago

```
// Just need a little bit correction in above code. But
#include <stdio.h>
#include <math.h>
int getOddOccurrence(int ar[], int ar_size)
{
    int i=0, res = 0;
    while(i < ar_size)
    {
        (i%2==0)?(res = res + ar[i++]):(res = res - ar[i++]);
    }
    return res;
}
int main()
{
    int a[] = {2,2,2,2,3,3,3,3,3,4,4,4,4};
    int size=sizeof(a)/sizeof(a[0]);
    printf("%d\n", getOddOccurrence(a, size));
    getchar();
}
```

1 ^ | v .



**donbosio** · 4 years ago

thanks but if the ques would ave been to find the even occuring element where

---

 [Subscribe](#)

 [Add Disqus to your site](#)