

## Write you own Power without using multiplication(\*) and division(/) operators

### Method 1 (Using Nested Loops)

We can calculate power by using repeated addition.

For example to calculate  $5^6$ .

- 1) First 5 times add 5, we get 25. ( $5^2$ )
- 2) Then 5 times add 25, we get 125. ( $5^3$ )
- 3) Then 5 time add 125, we get 625 ( $5^4$ )
- 4) Then 5 times add 625, we get 3125 ( $5^5$ )
- 5) Then 5 times add 3125, we get 15625 ( $5^6$ )

```
/* Works only if a >= 0 and b >= 0 */
int pow(int a, int b)
{
    if (b == 0)
        return 1;
    int answer = a;
    int increment = a;
    int i, j;
    for(i = 1; i < b; i++)
    {
        for(j = 1; j < a; j++)
        {
            answer += increment;
        }
        increment = answer;
    }
    return answer;
}
```

Google™ Custom Search



GeeksforGeeks



53,525 people like GeeksforGeeks.



Facebook

Interview Experiences

Advanced Data Structures

Dynamic Programming

Greedy Algorithms

Backtracking

Pattern Searching

Divide & Conquer

Mathematical Algorithms

Recursion

```

/* driver program to test above function */
int main()
{
    printf("\n %d", pow(5, 3));
    getchar();
    return 0;
}

```

### Method 2 (Using Recursion)

Recursively add  $a$  to get the multiplication of two numbers. And recursively multiply to get a raise to the power  $b$ .

```

#include<stdio.h>
/* A recursive function to get a^b
   Works only if a >= 0 and b >= 0 */
int pow(int a, int b)
{
    if(b)
        return multiply(a, pow(a, b-1));
    else
        return 1;
}

/* A recursive function to get x*y */
int multiply(int x, int y)
{
    if(y)
        return (x + multiply(x, y-1));
    else
        return 0;
}

/* driver program to test above functions */
int main()
{
    printf("\n %d", pow(5, 3));
    getchar();
    return 0;
}

```

Please write comments if you find any bug in above code/algorithm, or find other ways to solve the same problem.



### Popular Posts

[All permutations of a given string](#)

[Memory Layout of C Programs](#)

[Understanding "extern" keyword in C](#)

[Median of two sorted arrays](#)

[Tree traversal without recursion and without stack!](#)


[Structure Member Alignment, Padding and Data Packing](#)

[Intersection point of two Linked Lists](#)

[Lowest Common Ancestor in a BST.](#)

[Check if a binary tree is BST or not](#)

[Sorted Linked List to Balanced BST](#)



## Related Tpoics:

- Backtracking | Set 8 (Solving Cryptarithmic Puzzles)
- Tail Recursion
- Find if two rectangles overlap
- Analysis of Algorithm | Set 4 (Solving Recurrences)
- Print all possible paths from top left to bottom right of a mXn matrix
- Generate all unique partitions of an integer
- Russian Peasant Multiplication
- Closest Pair of Points | O(nlogn) Implementation



0



0



0

Writing code in comment? Please use [ideone.com](https://ideone.com) and share the link here.

11 Comments [GeeksforGeeks](#)

Sort by Newest ▼



Join the discussion



with the recursion...

705



Subscribe



Anon · 18 days ago

Nothing is gained in this solution with recursion. Solution still has the same cost stack each recursive step, resulting in higher memory usage.

This solution runs in  $O(a+b)$  time, but it's possible to get it in  $O(\log a + \log b)$  time.

<http://pastebin.com/A1wbNdku>

^ | v ·



Anon · a month ago

can make reduce time complexity by using a divide and conquer approach like

^ | v ·



Ankur Jain · 4 months ago

//

```
#include <stdio>
```

```
#include <cmath>
```

```
#include <stdlib>
```

```
int multiply(int x,int y)
```

```
{
```

```
int ans=0;
```

```
for (int i = 0; i < y; ++i)
```

```
{
```

```
ans+=x;
```

## Recent Comments

Abhi You live US or India?

[Google \(Mountain View\) interview](#) · 17 minutes ago

[Aman](#) Hi, Why arent we checking for conditions...

[Write a C program to Delete a Tree.](#) · 57 minutes ago

kzs please provide solution for the problem...

[Backtracking | Set 2 \(Rat in a Maze\)](#) · 1 hour ago

[Sanjay Agarwal](#) bool

tree::Root\_to\_leaf\_path\_given\_sum(tree...

[Root to leaf path sum equal to a given number](#) · 1 hour ago

[GOPI GOPINATH @admin](#) Highlight this sentence "We can easily...

[Count trailing zeroes in factorial of a number](#) · 1 hour ago

[newCoder3006](#) If the array contains negative numbers also. We...

[Find subarray with given sum](#) · 1 hour ago

AdChoices

[► Math Geeks](#)

[► Multiplication](#)

[► Math Multiply](#)

and then,

```
}
```

see more

1 ^ | v .



**abhishek08aug** · a year ago

```
#include<stdio.h>
```

```
int power(int a, int b) {  
    if(a==0) {  
        return a;  
    }  
  
    if(a==1) {  
        return a;  
    }  
  
    if(b==0) {  
        return 1;  
    }  
  
    if(b==1) {  
        return a;  
    }  
}
```

see more

^ | v .



**Balasubramanian** · a year ago

The following snippet works for negative numbers as well. I tested it with a few find any mistake,please comment.

AdChoices

► [C++ Function](#)

► [Long Int C++](#)

► [Function Math](#)

AdChoices

► [2 Multiplication](#)

► [Function Power](#)

► [Geeks for Geeks](#)

```

double myPow(int m,int n){
    if(n==0)
        return 1;
    bool isNeg=( n<0 )? true : false;
    n=abs(n);
    double ans=m;
    for(int i=2;i<=n;++i)
        ans=multiply(ans,m);
    if(isNeg)
        return 1/ans;
    return ans;
}

int multiply(int x,int y){
    if(y==0)
        return 0;
    if(y>0)
        return x+multiply(x,y-1);
    return -multiply(x,-y);
}

```

Thanks,

^ | v .



help • 3 years ago

what is the complexity of the recursion solution and how to calculate it?

^ | v .



anji.swe → help • 2 years ago

I think for the first method time complexity is  $O(n^2)$  as it is using 2 for |

correct me if iam wrong !!

^ | v .



arjun1296 · 4 years ago

IMHO, Recursion should be avoided as far as possible. Recursion is just a bad design in computers make recursion costly. Time and Space for the creation of inefficient and unpredictable use of system stack. But still i love to see recursion

^ | v .



Nishant · 4 years ago

```
#include<stdio.h>

int multi(int a,int b)
{
    int c=0;
    while(b)
    {
        if((b&1)!=0)
            c=c+a;
        a <>= 1;
    }
    return c;
}

int power(int a,int n)
{
    int i,j=1;
    for(i=1;i<=n;i++)
        j=multi(j,a);
    return j;
}

int main()
{
```

```
    printf("%d\n", power(2, 10));  
    return 0;  
}
```

^ | v .



**Sambasiva** · 4 years ago

Recursion could be write like below

```
int power(int a, int b)  
{  
    if(b == 0)  
        return 1;  
  
    int inc = pow(a, b - 1);  
  
    int ret = 0;  
  
    int i = 0;  
    for(; i < a; ++i)  
        ret += inc;  
  
    return ret;  
}
```

^ | v .



**Ahmet Alp Balkan** · 4 years ago

Recursion is the better and elegant solution imho. Is there a way to handle <0 wondering.

^ | v .



---

 [Subscribe](#)

 [Add Disqus to your site](#)

@geeksforgeeks, **Some rights reserved**

[Contact Us!](#)

Powered by **WordPress** & **MooTools**, customized by geeksforgeeks team