

NP-Completeness | Set 1 (Introduction)

We have been writing about efficient algorithms to solve complex problems, like [shortest path](#), [Euler graph](#), [minimum spanning tree](#), etc. Those were all success stories of algorithm designers. In this post, failure stories of computer science are discussed.

Can all computational problems be solved by a computer? There are computational problems that can not be solved by algorithms even with unlimited time. For example Turing Halting problem (Given a program and an input, whether the program will eventually halt when run with that input, or will run forever). Alan Turing proved that general algorithm to solve the halting problem for all possible program-input pairs cannot exist. A key part of the proof is, Turing machine was used as a mathematical definition of a computer and program (Source [Halting Problem](#)).

Status of **NP Complete** problems is another failure story, NP complete problems are problems whose status is unknown. No polynomial time algorithm has yet been discovered for any NP complete problem, nor has anybody yet been able to prove that no polynomial-time algorithm exist for any of them. The interesting part is, if any one of the NP complete problems can be solved in polynomial time, then all of them can be solved.

What are **NP, **P**, **NP-complete** and **NP-Hard** problems?**

P is set of problems that can be solved by a deterministic Turing machine in **Polynomial** time.

NP is set of decision problems that can be solved by a **Non-deterministic** Turing Machine in **Polynomial** time. **P** is subset of **NP** (any problem that can be solved by deterministic machine in polynomial time can also be solved by non-deterministic machine in polynomial time).

Informally, **NP** is set of decision problems which can be solved by a polynomial time via a “Lucky Algorithm”, a magical algorithm that always makes a right guess among the given set of choices (Source [Ref 1](#)).

Google™ Custom Search



GeeksforGeeks



53,522 people like [GeeksforGeeks](#).



[Interview Experiences](#)

[Advanced Data Structures](#)

[Dynamic Programming](#)

[Greedy Algorithms](#)

[Backtracking](#)

[Pattern Searching](#)

[Divide & Conquer](#)

[Mathematical Algorithms](#)


[Recursion](#)

[Geometric Algorithms](#)

NP-complete problems are the hardest problems in **NP** set. A decision problem L is NP-complete if:

- 1) L is in NP (Any given solution for NP-complete problems can be verified quickly, but there is no efficient known solution).
- 2) Every problem in NP is reducible to L in polynomial time (Reduction is defined below).

A problem is **NP-Hard** if it follows property 2 mentioned above, doesn't need to follow property 1. Therefore, NP-Complete set is also a subset of NP-Hard set.



Decision vs Optimization Problems

NP-completeness applies to the realm of decision problems. It was set up this way because it's easier to compare the difficulty of decision problems than that of optimization problems. In reality, though, being able to solve a decision problem in polynomial time will often permit us to solve the corresponding optimization problem in polynomial time (using a polynomial number of calls to the decision problem). So, discussing the difficulty of decision problems is often really equivalent to discussing the difficulty of optimization problems. (Source [Ref 2](#)).

For example, consider the **vertex cover problem** (Given a graph, find out the minimum sized vertex set that covers all edges). It is an optimization problem. Corresponding decision problem is, given undirected graph G and k, is there a vertex cover of size k?



Popular Posts

[All permutations of a given string](#)

[Memory Layout of C Programs](#)

[Understanding "extern" keyword in C](#)

[Median of two sorted arrays](#)

[Tree traversal without recursion and without stack!](#)

[Structure Member Alignment, Padding and Data Packing](#)

[Intersection point of two Linked Lists](#)

[Lowest Common Ancestor in a BST.](#)


[Check if a binary tree is BST or not](#)

[Sorted Linked List to Balanced BST](#)

What is Reduction?

Let L_1 and L_2 be two decision problems. Suppose algorithm A_2 solves L_2 . That is, if y is an input for L_2 then algorithm A_2 will answer Yes or No depending upon whether y belongs to L_2 or not.

The idea is to find a transformation from L_1 to L_2 so that the algorithm A_2 can be part of an algorithm A_1 to solve L_1 .



Learning reduction in general is very important. For example, if we have library functions to solve certain problem and if we can reduce a new problem to one of the solved problems, we save a lot of time. Consider the example of a problem where we have to find minimum product path in a given directed graph where product of path is multiplication of weights of edges along the path. If we have code for Dijkstra's algorithm to find shortest path, we can take log of all weights and use Dijkstra's algorithm to find the minimum product path rather than writing a fresh code for this new problem.

How to prove that a given problem is NP complete?

From the definition of NP-complete, it appears impossible to prove that a problem L is NP-Complete. By definition, it requires us to show every problem in NP is polynomial time reducible to L . Fortunately, there is an alternate way to prove it. The idea is to take a known NP-Complete problem and reduce it to L . If polynomial time reduction is possible, we can prove that L is NP-Complete by transitivity of reduction (If a NP-Complete problem is reducible to L in polynomial time, then all problems are reducible to L in polynomial time).

What was the first problem proved as NP-Complete?

There must be some first NP-Complete problem proved by definition of NP-Complete problems.

SAT (Boolean satisfiability problem) is the first NP-Complete problem proved by Cook (See CLRS book for proof).

It is always useful to know about NP-Completeness even for engineers. Suppose you are asked to write an efficient algorithm to solve an extremely important problem for your company. After a

**Get notified in
real-time on**
network events and
performance data across
remote sites

Enterprise-ready network,
server and
virtualization monitoring software

ManageEngine **OpManager**

free for 30 days !



lot of thinking, you can only come up exponential time approach which is impractical. If you don't know about NP-Completeness, you can only say that I could not come with an efficient algorithm. If you know about NP-Completeness and prove that the problem as NP-complete, you can proudly say that the polynomial time solution is unlikely to exist. If there is a polynomial time solution possible, then that solution solves a big problem of computer science many scientists have been trying for years.

We will soon be discussing more NP-Complete problems and their proof for NP-Completeness.

References:

[MIT Video Lecture on Computational Complexity](#)

Introduction to Algorithms 3rd Edition by Clifford Stein, Thomas H. Cormen, Charles E.

Leiserson, Ronald L. Rivest

<http://www.ics.uci.edu/~eppstein/161/960312.html>

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above

Free C# Code Generator

 ironspeed.com

Create database & reporting apps straight from your database! Try it



Related Tpoics:

703

 Subscribe

Recent Comments

Aman Hi, Why arent we checking for conditions...

[Write a C program to Delete a Tree.](#) · 29 minutes ago

kzs please provide solution for the problem...

[Backtracking | Set 2 \(Rat in a Maze\)](#) · 32 minutes ago

Sanjay Agarwal bool

tree::Root_to_leaf_path_given_sum(tree...

[Root to leaf path sum equal to a given number](#) · 57 minutes ago

GOPI GOPINATH @admin Highlight this sentence "We can easily...


[Count trailing zeroes in factorial of a number](#) · 59 minutes ago

newCoder3006 If the array contains negative numbers also. We...

[Find subarray with given sum](#) · 1 hour ago

newCoder3006 Code without using while loop. We can do it...

[Find subarray with given sum](#) · 1 hour ago

AdChoices 

[▶ P VS NP](#)

[▶ NP](#)

[▶ Algorithm Design](#)

- [Analysis of Algorithms | Set 4 \(Analysis of Loops\)](#)
- [Analysis of Algorithms | Set 3 \(Asymptotic Notations\)](#)
- [Static and Dynamic Libraries | Set 1](#)
- [The Ubiquitous Binary Search | Set 1](#)
- [Reservoir Sampling](#)
- [Analysis of Algorithms | Set 2 \(Worst, Average and Best Cases\)](#)
- [Analysis of Algorithms | Set 1 \(Asymptotic Analysis\)](#)
- [Scope rules in C](#)



34



Tweet

4



1

AdChoices

[▶ Introduction](#)

[▶ It Solution](#)

[▶ Graph Theory](#)

AdChoices

[▶ Computer Geeks](#)

[▶ Graph Matching](#)

[▶ Graph Library](#)

Writing code in comment? Please use ideone.com and share the link here.

Sort by Newest ▼



Join the discussion...

**functioncall** • 8 months ago

his name is Alan Turing

^ | ▼ •

**GeeksforGeeks** Mod → functioncall • 3 months ago

Thanks for pointing this out. We have corrected the name.

^ | ▼ •

**Mohan Chinna** • 9 months ago<http://gatecsitbooks.blogspot...> you can download DAA book here for frre

2 ^ | ▼ •



Subscribe



Add Disqus to your site