

Write one line C function to find whether a no is power of two

1. A simple method for this is to simply take the log of the number on base 2 and if you get an integer then number is power of 2.
2. Another solution is to keep dividing the number by two, i.e, do $n = n/2$ iteratively. In any iteration, if $n\%2$ becomes non-zero and n is not 1 then n is not a power of 2. If n becomes 1 then it is a power of 2.

```
#include<stdio.h>
#define bool int

/* Function to check if x is power of 2*/
bool isPowerOfTwo(int n)
{
    if (n == 0)
        return 0;
    while (n != 1)
    {
        if (n%2 != 0)
            return 0;
        n = n/2;
    }
    return 1;
}

/*Driver program to test above function*/
int main()
{
    isPowerOfTwo(31)? printf("Yes\n"): printf("No\n");
    isPowerOfTwo(17)? printf("Yes\n"): printf("No\n");
    isPowerOfTwo(16)? printf("Yes\n"): printf("No\n");
}
```


Google™ Custom Search



GeeksforGeeks



53,526 people like [GeeksforGeeks](#).



Interview Experiences

Advanced Data Structures

Dynamic Programming

Greedy Algorithms

Backtracking

Pattern Searching

Divide & Conquer

Mathematical Algorithms

Recursion

Geometric Algorithms

```

isPowerOfTwo(2)? printf("Yes\n"): printf("No\n");
isPowerOfTwo(18)? printf("Yes\n"): printf("No\n");
isPowerOfTwo(1)? printf("Yes\n"): printf("No\n");
return 0;
}

```

Output:

```

No
No
Yes
Yes
No
Yes

```

3. All power of two numbers have only one bit set. So count the no. of set bits and if you get 1 then number is a power of 2. Please see <http://geeksforgeeks.org/?p=1176> for counting set bits.

4. If we subtract a power of 2 numbers by 1 then all unset bits after the only set bit become set; and the set bit become unset.

For example for 4 (100) and 16(10000), we get following after subtracting 1

3 → 011

15 → 01111

So, if a number n is a power of 2 then bitwise & of n and n-1 will be zero. We can say n is a power of 2 or not based on value of n&(n-1). The expression n&(n-1) will not work when n is 0. To handle this case also, our expression will become n&(n&(n-1)) (thanks to [Mohammad](#) for adding this case).

Below is the implementation of this method.

```

#include<stdio.h>
#define bool int

/* Function to check if x is power of 2*/
bool isPowerOfTwo (int x)
{
    /* First x in the below expression is for the case when x is 0 */
    return x && !(x&(x-1));
}

```

HP Chromebook 11

 google.com/chromebook

Everything you need in one laptop.
Made with Google. Learn more.



Popular Posts

[All permutations of a given string](#)

[Memory Layout of C Programs](#)

[Understanding "extern" keyword in C](#)

[Median of two sorted arrays](#)

[Tree traversal without recursion and without stack!](#)

[Structure Member Alignment, Padding and Data Packing](#)

[Intersection point of two Linked Lists](#)

[Lowest Common Ancestor in a BST.](#)

[Check if a binary tree is BST or not](#)

[Sorted Linked List to Balanced BST](#)

```

/*Driver program to test above function*/
int main()
{
    isPowerOfTwo(31)? printf("Yes\n"): printf("No\n");
    isPowerOfTwo(17)? printf("Yes\n"): printf("No\n");
    isPowerOfTwo(16)? printf("Yes\n"): printf("No\n");
    isPowerOfTwo(2)?  printf("Yes\n"): printf("No\n");
    isPowerOfTwo(18)? printf("Yes\n"): printf("No\n");
    isPowerOfTwo(1)?  printf("Yes\n"): printf("No\n");
    return 0;
}

```


Output:

```

No
No
Yes
Yes
No
Yes

```

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above



Related Topics:

- Check if a number is multiple of 9 using bitwise operators
- How to swap two numbers without using a temporary variable?
- Divide and Conquer | Set 4 (Karatsuba algorithm for fast multiplication)
- Find position of the only set bit
- Swap all odd and even bits
- Add two bit strings
- Write your own strcmp that ignores cases
- Binary representation of a given number



0



Tweet

0



0

Writing code in comment? Please use ideone.com and share the link here.

33 Comments

GeeksforGeeks

Sort by Newest ▼



Join the discussion...



Aveek Biswas · a month ago

Is writing an one line Java function for this possible?

^ | v · Reply · Share ›



Guest · 4 months ago

```
int isPowerOfTwo(int n)
```

```
{
```

Recent Comments

Abhi You live US or India?

Google (Mountain View) interview · 27 minutes ago

Aman Hi, Why arent we checking for conditions...

Write a C program to Delete a Tree. · 1 hour ago

kzs please provide solution for the problem...

Backtracking | Set 2 (Rat in a Maze) · 1 hour ago

Sanjay Agarwal bool

tree::Root_to_leaf_path_given_sum(tree...


Root to leaf path sum equal to a given number · 1 hour ago

GOPI GOPINATH @admin Highlight this sentence "We can easily...

Count trailing zeroes in factorial of a number · 1 hour ago

newCoder3006 If the array contains negative numbers also. We...

Find subarray with given sum · 2 hours ago

AdChoices 

► [The Power of 2](#)

► [Math Function](#)

► [Function One](#)

```
while(!(n&1))

n>>=1;

if(n==1)return 1;

else return 0;

}
```

^ | v • Reply • Share ›



Amit Kumar • 4 months ago

```
void main()

{
int value=8,i=1,count=0;
while (i){

if(value & i){ ++count;
}
i=i<<1;
}
printf(" value: %d", count);

if(count == 1) {
printf("Number is power of two");
}

}
```

^ | v • Reply • Share ›



Raman Classes • 7 months ago

```
((n&(n-1))==0) ? printf("Power of 2") :printf("Not power of 2");
```

8 | • Reply • Share ›

AdChoices ▶

▶ [Math Function](#)

▶ [Function One](#)

▶ [Form Function](#)

AdChoices ▶

▶ [Example Code](#)

▶ [Binary Code](#)

▶ [Numbers Number](#)



gargsanjay · 10 months ago

in method 5

at one place u wrote $n \& (!n) \& n - 1$

and at one place $n \& (!n) \& (n - 1)$

```
/* Paste your code here (You may delete these lines if not writing c
```

^ | v · Reply · Share ›



Hanish Bansal · a year ago

There is an error in Method 2.

For numbers of the form $2^x + 1$ (e.g. 17), it returns 1.

Correct function :

```
bool isPowerOfTwo(int n)
```

```
{
```

```
if(n == 0)
```

```
return 0;
```

```
while(n != 1)
```

```
{
```

```
if(n%2 != 0)
```

```
return 0;
```

```
n = n/2;
```

```
}
```

```
return 1;
```

```
}
```

^ | v · Reply · Share ›



amit → Hanish Bansal · a year ago

yesss...method 2 is wrong

7 Paste your code here (you may ~~delete~~ these lines if not w

^ | v • Reply • Share ›



GeeksforGeeks → amit • a year ago

@Hanish Bansal: Thanks for pointing out the issue and solution up!

@amit: Thanks for bringing it to notice.

^ | v • Reply • Share ›



Rohit • 2 years ago

we can find this by checking 2's complement of that number as 2's complement of the number itself.

therefore

if((~x+1)==x)

then power of 2

else

not

simple 1 line solution

1 ^ | v • Reply • Share ›



dgDinkar → Rohit • 7 months ago

2's complement of any number gives its negative number...
then how it can be equal??

^ | v • Reply • Share ›



de-captcher • 2 years ago

I love your blog.. very nice colors & theme. Did you design this website yourself or did you hire someone to do

it for you? Plz reply as I'm looking to design my own blog and would like to find

^ | v • Reply • Share ›



krazykoder • 2 years ago

check if a log2 of the number is an integer or not!!

```
/* Paste your code here (You may delete these lines if not writing c)
#include <stdio.h>
#include <math.h>

int main(){
    int n=9;
    float log=log2(n);
    int check=((int )(log*100))%100;// checking till precision of 2 d
    if(!check)
        printf("yeaa");
    else
        printf("noo");
}
```

^ | v • Reply • Share ›



krazykoder • 2 years ago

check if a log2 of the number is an integer or not!!

```
/* Paste your code here (You may delete these lines if not writing c)
#include <stdio.h>
#include <math.h>

int main(){
    int n=9;
    float log=log2(n);
```



```
int check = ((int )(log *100))/100; // checking till precision of 2 d  
if(!check)  
printf("yeaa");  
else  
printf("nooooo");  
  
}
```

^ | v • Reply • Share ›



krazykoder • 2 years ago

```
/* Paste your code here (You may delete these lines if not writing cor  
#include <stdio.h>  
#include <math.h>  
  
int main(){  
    int n=9;  
    float log=log2(n);  
    int check=((int )(log*100))/100; // checking till precision of 2 d  
    if(!check)  
        printf("yeaa");  
    else  
        printf("nooooo");  
  
}
```

^ | v • Reply • Share ›



ritesh_nitw • 2 years ago



One line and a single BITWISE AND is sufficient

```
x&(x-1)==0?print x is power of two : print Nops!!
```

2 ^ | v • Reply • Share ›



anji.swe • 2 years ago

sorry,....

conditions

$n \& (1-n) == n$

$n \& (2+\sim n) == n$

are giving false for one, and true for zero.

^ | v • Reply • Share ›



anji.swe • 2 years ago

if n is a power of two then ..

$(n \& (-n)) = n$

$(n \& (1+\sim n)) = n$

$(n \& (\sim(n \& (n - 1)))) = n$

$(n \& (n - 1)) = 0$

$\sim(n \& (n - 1)) = -1$

$!(n \& (n - 1)) = 1$

so...

use any one of them in if condition and evaluate n...

:)

0,1 are treated as powers of 2, if dont want put a condition



anji.swe · 2 years ago

if n is a power of two then ..

$$(n \& (1 - n)) = n$$

$$(n \& (1 + \sim n)) = n$$

$$(n \& (\sim(n \& (n - 1)))) = n$$

$$(n \& (2 + \sim n)) = n$$

$$(n \& (n - 1)) = 0$$

$$\sim(n \& (n - 1)) = -1$$

$$!(n \& (n - 1)) = 1$$

so...

use any one of them in if condition and evaluate n...

:)

^ | v · Reply · Share ›



anji.swe · 2 years ago

if n is a power of two then ..

$$(n \& (1 - n)) = n$$

$$(n \& (1 + \sim n)) = n$$

$$(n \& (\sim(n \& (n - 1)))) = n$$

$$(n \& (2 + \sim n)) = n$$

$$(n \& (n - 1)) = 0$$

$$\sim(n \& (n - 1)) = -1$$

$$!(n \& (n - 1)) = 1$$

so...

use any one of then in if condition and evaluate n...

:)

^ | v · Reply · Share ›



ap · 3 years ago

if $(x \& (\sim x + 1) == x)$ then it is a power of two

^ | v · Reply · Share ›



ap → ap · 3 years ago

correct me if i am missing any

^ | v · Reply · Share ›



pnh · 3 years ago

```
void twoPowerN(int n)
```

```
{  
    printf("%d is %s power of 2 \n ",n, (((n)&(n-1))==0?"a":"not a"));  
}
```

^ | v · Reply · Share ›



mm10 · 3 years ago

Correction from my previous comment

```
if((n&1)==1) // not a power of 2  
if((n&1)==0) // power of 2
```

Would this code not be feasible?

Thanks

MM

^ | v · Reply · Share ›



maruti kutre → mm10 · 7 months ago

I am correct above solution is wrong power of 2 means = n/n ranging number/2 ==0. 6 is divisible by 2 but its not power of 2. correct me if I a

^ | v • Reply • Share ›



amit nanda → mm10 • 10 months ago

1 is also a power of 2 but your code give wrong result.

^ | v • Reply • Share ›



Sandeep → mm10 • 3 years ago

@mm10:

This code would check for multiple of 2, not power of 2. For example, s
of 2".

1 ^ | v • Reply • Share ›



geeksforgeeks • 4 years ago

@manoj: We have added few more words in solution 2 to elaborate the point.

^ | v • Reply • Share ›



manoj • 4 years ago

Solution (2) doesn't seem correct. 2's powers are 2,4,8,16,... and solution (2) ' of 2.

^ | v • Reply • Share ›



pnh → manoj • 3 years ago

6 = 110 and 5 = 101

(n)&(n-1) = (110 & 101) is not equal to zero....

so solution (2),

void twoPowerN(int n)

{

printf("%d is %s power of 2 \n ",n, (((n)&(n-1))==0?"a":"not a"));

}

works for all values of n !!

^ | v • Reply • Share ›



geeksforgeeks • 5 years ago

@Mohammad: Thanks very much for suggesting this case. We have added it

^ | v • Reply • Share ›



Mohammad • 5 years ago

Nice solution but you should pay special attention to the case when $x = 0$. The

`return x && !(x&(x-1));`

I just added the term "`x &&` "

Thanks

^ | v • Reply • Share ›



neha → Mohammad • a month ago

pls explain mohammad, how u solve it by using "&&" ?

^ | v • Reply • Share ›



Aveek Biswas → Mohammad • a month ago

Could you suggest an equivalent one line function in JAVA?

^ | v • Reply • Share ›



Subscribe



Add Disqus to your site

@geeksforgeeks, **Some rights reserved**

Contact Us!

Powered by **WordPress** & **MooTools**, customized by geeksforgeeks team