

## Efficient way to multiply with 7

We can multiply a number by 7 using bitwise operator. First left shift the number by 3 bits (you will get  $8n$ ) then subtract the original number from the shifted number and return the difference ( $8n - n$ ).

### Program:

```
# include<stdio.h>

int multiplyBySeven(unsigned int n)
{
    /* Note the inner bracket here. This is needed
       because precedence of '-' operator is higher
       than '<<' */
    return ((n<<3) - n);
}

/* Driver program to test above function */
int main()
{
    unsigned int n = 4;
    printf("%u", multiplyBySeven(n));

    getchar();
    return 0;
}
```

**Time Complexity:**  $O(1)$

**Space Complexity:**  $O(1)$

Note: Works only for positive integers.


Google™ Custom Search



GeeksforGeeks



53,525 people like [GeeksforGeeks](#).



Interview Experiences

Advanced Data Structures

Dynamic Programming

Greedy Algorithms

Backtracking

Pattern Searching


Divide & Conquer

Mathematical Algorithms

Recursion

Geometric Algorithms

Same concept can be used for fast multiplication by 9 or other numbers.



## Related Topics:

- Check if a number is multiple of 9 using bitwise operators
- How to swap two numbers without using a temporary variable?
- Divide and Conquer | Set 4 (Karatsuba algorithm for fast multiplication)
- Find position of the only set bit
- Swap all odd and even bits
- Add two bit strings
- Write your own strcmp that ignores cases
- Binary representation of a given number



Writing code in comment? Please use [ideone.com](https://ideone.com) and share the link here.

7 Comments      GeeksforGeeks

Sort by Newest ▼

## Popular Posts

All permutations of a given string

Memory Layout of C Programs

Understanding "extern" keyword in C

Median of two sorted arrays

Tree traversal without recursion and without stack!

Structure Member Alignment, Padding and Data Packing

Intersection point of two Linked Lists

Lowest Common Ancestor in a BST.

Check if a binary tree is BST or not

Sorted Linked List to Balanced BST

Join the discussion...

**Nimish** · 7 months ago

why not  $n+(n<<1)+(n<<2)$  ?

as bit shifts are still three only, though not don at once, but instead of one "-" w using "+" can be more efficient than using "-" i guess.

1 ^ | v ·

**vindhya** · 2 years ago

someone plz explain this..how does it give  $O(1)$  complexity??sorry i m weak a

```
/* Paste your code here (You may delete these lines if not writing cor
```

^ | v ·

**vindhya** → vindhya · 2 years ago

oh..!!!understood..:)

```
/* Paste your code here (You may delete these lines if not writ
```

^ | v ·

**frankc** · 3 years ago

Is it possible to use divide and conquer and the "clever" multiplication algorithm by 7 or 15?

|

# Deploy Early. Deploy Often.

DevOps from  
Rackspace:

## Automation

FIND OUT HOW ►

 **rackspace**  
the open cloud company

7 Paste your code here (you may delete these lines if not writing code)

^ | v .

705



Subscribe

## Recent Comments

Abhi You live US or India?

[Google \(Mountain View\) interview](#) · 17 minutes ago

**Aman** Hi, Why arent we checking for conditions...

[Write a C program to Delete a Tree.](#) · 57 minutes ago

kzs please provide solution for the problem...

[Backtracking | Set 2 \(Rat in a Maze\)](#) · 1 hour ago

**Sanjay Agarwal** bool

tree::Root\_to\_leaf\_path\_given\_sum(tree...

[Root to leaf path sum equal to a given number](#) · 1 hour ago

**GOPI GOPINATH** @admin Highlight this sentence "We can easily...

[Count trailing zeroes in factorial of a number](#) · 1 hour ago

**newCoder3006** If the array contains negative numbers also. We...

[Find subarray with given sum](#) · 1 hour ago

AdChoices

[▶ How to Multiply](#)

[▶ Multiplication](#)

**bala** · 3 years ago

Sometimes ,we do have to take care of overflow even if multiplication by 7 or 1

^ | v .

**nitesh.gami008** → **bala** · 3 years ago

@bala....Please give some example....

^ | v .

**adsf** → **nitesh.gami008** · a year ago

Consider this binary number

0100 0000


how will you shift 3 times without handling overflow

Correct me if i am wrong

^ | v .

Subscribe


Add Disqus to your site

AdChoices 

▶ [Algorithm](#)

▶ [Java Array](#)

▶ [Binary](#)

AdChoices 

▶ [C++](#)

▶ [Integers](#)

▶ [C Code](#)

@geeksforgeeks, **Some rights reserved**

[Contact Us!](#)

Powered by **WordPress** & **MooTools**, customized by geeksforgeeks team