

Insertion Sort

March 7, 2013

Insertion sort is a simple sorting algorithm that works the way we sort playing cards in our hands.



Algorithm

```
// Sort an arr[] of size n
insertionSort(arr, n)
Loop from i = 1 to n-1.
.....a) Pick element arr[i] and insert it into sorted sequence arr[0...i-1]
```



GeeksQuiz



4,126 people like [GeeksQuiz](#).



[Facebook social plugin](#)



Example:

12, 11, 13, 5, 6

Let us loop for i = 1 (second element of the array) to 5 (Size of input array)

i = 1. Since 11 is smaller than 12, move 12 and insert 11 before 12

11, 12, 13, 5, 6

i = 2. 13 will remain at its position as all elements in A[0..i-1] are smaller than 13

11, 12, 13, 5, 6

i = 3. 5 will move to the beginning and all other elements from 11 to 13 will move one position ahead of their current position.

5, 11, 12, 13, 6

i = 4. 6 will move to position after 5, and elements from 11 to 13 will move one position ahead of their current position.

5, 6, 11, 12, 13

```
// C program for insertion sort
#include <stdio.h>
#include <math.h>

/* Function to sort an array using insertion sort*/
void insertionSort(int arr[], int n)
{
    int i, key, j;
    for (i = 1; i < n; i++)
    {
        key = arr[i];
        j = i-1;

        /* Move elements of arr[0..i-1], that are
        greater than key, to one position ahead
        of their current position */
        while (j >= 0 && arr[j] > key)
        {
            arr[j+1] = arr[j];
            j = j-1;
        }
        arr[j+1] = key;
    }
}
```

Categories

Articles (28)

C (4)

C++ (2)

Data Structures (13)

DBMS (1)

Operating Systems (1)

Searching and Sorting (7)

Programs (7)

Quizzes (1,392)

Aptitude (1)

Computer Science Quizzes (1,391)

Algorithms (146)

C (203)

C++ (123)

Data Structures (131)

GATE (709)

Java (51)

Operating Systems (28)



```
// A utility function to print an array of size n
void printArray(int arr[], int n)
{
    int i;
    for (i=0; i < n; i++)
        printf("%d ", arr[i]);
    printf("\n");
}

/* Driver program to test insertion sort */
int main()
{
    int arr[] = {12, 11, 13, 5, 6};
    int n = sizeof(arr)/sizeof(arr[0]);

    insertionSort(arr, n);
    printArray(arr, n);

    return 0;
}
```

Output:

```
5 6 11 12 13
```

Time Complexity: $O(n^2)$

Auxiliary Space: $O(1)$

Boundary Cases: Insertion sort takes maximum time to sort if elements are sorted in reverse order. And it takes minimum time (Order of n) when elements are already sorted.

Algorithmic Paradigm: Incremental Approach

Sorting In Place: Yes

Stable: Yes

Online: Yes

Uses: Insertion sort is used when number of elements is small. It can also be useful when



Recent Discussions

Sumit Khatri this is the sorting technique which can work...

Insertion Sort · 7 hours ago

Sumit Khatri no, quick sort requires more swaps than...

Selection Sort · 7 hours ago

Sumit Khatri yes, it is the only sorting technique which...

Selection Sort · 7 hours ago

input array is almost sorted, only few elements are misplaced in complete big array.

Quizzes: [Sorting Questions](#)

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

Free C# Code Generator

 ironspeed.com

Create database & reporting apps straight from your database! Try it



Related Questions:

- [Bubble Sort](#)
- [Selection Sort](#)
- [Binary Search](#)
- [QuickSort](#)
- [Heap Sort](#)
- [Merge Sort](#)



0



Tweet

0



0

Sudhakar Mishra I think it should be $2n + 1$


[Data Structures](#) | [Binary Trees](#) | [Question 12](#) · 8 hours ago

Sudhakar Mishra $(2n)!/(n+1)!*n!$

[Data Structures](#) | [Binary Trees](#) | [Question 6](#) · 1 day ago

Sudhakar Mishra Always Y will be more than one because after...


[Data Structures](#) | [Stack](#) | [Question 7](#) · 1 day ago

AdChoices 

[▶ Geeks Quiz](#)

[▶ Personality Quiz to Print](#)


[▶ Test and Quiz](#)

AdChoices 

[▶ Quiz Cards](#)

[▶ The Love Quiz](#)

[▶ A Quiz](#)

AdChoices 

[▶ Insertion Sort](#)

[▶ Memory Quiz](#)

[▶ Quick Quiz](#)

Sort by Best ▼



Join the discussion...

**gwpark** · 4 months ago

I love this sort rather than quick sort.

In real world, an ARRAY or DATA to be sorted is usually NOT static, rather If one element is inserted during sort process, other algorithms cannot res| But, only this algorithm is not interrupted and can respond with the addition

6 ^ | v ·

**Sumit Khatri** · 7 hours ago

this is the sorting technique which can work even all the numbers to be sor time.....hence called online algorithm

^ | v ·



Subscribe



Add Disqus to your site