

Rotate bits of a number

Bit Rotation: A rotation (or circular shift) is an operation similar to shift except that the bits that fall off at one end are put back to the other end.

In left rotation, the bits that fall off at left end are put back at right end.

In right rotation, the bits that fall off at right end are put back at left end.

Example:

Let n is stored using 8 bits. Left rotation of n = 11100101 by 3 makes n = 00101111 (Left shifted by 3 and first 3 bits are put back in last). If n is stored using 16 bits or 32 bits then left rotation of n (000...11100101) becomes 00..00**11100101**000.

Right rotation of n = 11100101 by 3 makes n = 10111100 (Right shifted by 3 and last 3 bits are put back in first) if n is stored using 8 bits. If n is stored using 16 bits or 32 bits then right rotation of n (000...11100101) by 3 becomes **101000**..00**11100**.

```
#include<stdio.h>
#define INT_BITS 32

/*Function to left rotate n by d bits*/
int leftRotate(int n, unsigned int d)
{
    /* In n<<d, last d bits are 0. To put first 3 bits of n at
       last, do bitwise or of n<<d with n >>(INT_BITS - d) */
    return (n << d) | (n >> (INT_BITS - d));
}

/*Function to right rotate n by d bits*/
int rightRotate(int n, unsigned int d)
{
    /* In n>>d, first d bits are 0. To put last 3 bits of at
```

Google™ Custom Search



GeeksforGeeks



53,526 people like [GeeksforGeeks](#).



Interview Experiences

Advanced Data Structures

Dynamic Programming

Greedy Algorithms

Backtracking

Pattern Searching

Divide & Conquer

Mathematical Algorithms

Recursion


```

    first, do bitwise or of n>>d with n <<(INT_BITS - d) */
    return (n >> d) | (n << (INT_BITS - d));
}

/* Driver program to test above functions */
int main()
{
    int n = 16;
    int d = 2;
    printf("Left Rotation of %d by %d is ", n, d);
    printf("%d", leftRotate(n, d));
    printf("\nRight Rotation of %d by %d is ", n, d);
    printf("%d", rightRotate(n, d));
    getchar();
}

```

Please write comments if you find any bug in the above program or other ways to solve the same problem.



Related Topics:

- Check if a number is multiple of 9 using bitwise operators
- How to swap two numbers without using a temporary variable?

Geometric Algorithms



Popular Posts

- All permutations of a given string
- Memory Layout of C Programs
- Understanding "extern" keyword in C
- Median of two sorted arrays
- Tree traversal without recursion and without stack!
- Structure Member Alignment, Padding and Data Packing
- Intersection point of two Linked Lists
- Lowest Common Ancestor in a BST.
- Check if a binary tree is BST or not
- Sorted Linked List to Balanced BST

- Divide and Conquer | Set 4 (Karatsuba algorithm for fast multiplication)
- Find position of the only set bit
- Swap all odd and even bits
- Add two bit strings
- Write your own strcmp that ignores cases
- Binary representation of a given number



4

Tweet

0



1

Writing code in comment? Please use ideone.com and share the link here.

17 Comments

GeeksforGeeks

Sort by Newest ▼



Join the discussion...



Mahesh Devkar · 2 months ago

its awesome.....

Thank you.....:-)

^ | v ·



Haider Ali · 11 months ago

very good

^ | v ·



abhishek08aug · a year ago

Here is the simple approach. Pick a bit and put it in the end:

```
#include<stdio.h>
```

```
#include<stdlib.h>
```

```

char * bit_string = (char *)malloc(sizeof(char)*sizeof(unsigned int)
unsigned int i=1, j;
for(i=i<=(sizeof(unsigned int)*8-1), j=0; i>0; i=i>>1, j++) {
    if(num&i) {
        *(bit_string+j)='1';
    } else {
        *(bit_string+j)='0';
    }
}
*(bit_string+j)='&#92;&#48';
return bit_string;
}

```

see more



abhishek08aug → abhishek08aug · a year ago
Oops I just reversed the bits :-o



gladiator → abhishek08aug · 11 months ago
Intelligent :D

```

/* Paste your code here (You may delete these lines if

```



Hanish · a year ago
It does not work for negative numbers. Because right shifting a negative numb

705



Subscribe

Recent Comments

Abhi You live US or India?

[Google \(Mountain View\) interview](#) · 22 minutes ago

Aman Hi, Why arent we checking for conditions...

[Write a C program to Delete a Tree.](#) · 1 hour ago

kzs please provide solution for the problem...

[Backtracking | Set 2 \(Rat in a Maze\)](#) · 1 hour ago

Sanjay Agarwal bool

tree::Root_to_leaf_path_given_sum(tree...

Root to leaf path sum equal to a given number · 1 hour ago

GOPI GOPINATH @admin Highlight this sentence "We can easily...

Count trailing zeroes in factorial of a number · 1 hour ago

newCoder3006 If the array contains negative numbers also. We...

[Find subarray with given sum](#) · 1 hour ago

AdChoices

► [Java Array](#)

► [Rotate Screen](#)

► [I Rotate](#)

number.

Type casting of n to unsigned int is required in the function argument

^ | v .



Satish · 2 years ago

```
#include
#include
#define value(a)8*sizeof(a)
void main()
{
    int n=3;
    int a=8;
    char a1=8;
    clrscr();

    printf(" left rotates %d",(a<>value(a)-n));
    printf("\n\n Right rotates %d",(a>>n)|(a<<value(a)-n));

    printf("\n\ncharacter left rotates %d",(a1<>value(a1)-n));
    printf("\n\ncharacter Right rotates %d",(a1>>n)|(a1<<value(a1)-n));

    getch() ;

}
```

this program automatic adjust the no. of byte block...

1 ^ | v .



vinay poliseti · 3 years ago

most elegant solution I have ever seen !!

^ | v .



abhishek · 3 years ago

AdChoices

[▶ Bits Byte](#)

[▶ Hex Bits](#)

[▶ Convert Rotate](#)

AdChoices

[▶ Java 32 Bits](#)

[▶ Int Bits](#)

[▶ Binary Bits](#)



This above approach works in following cases only.

1. unsigned integer
2. number to be rotated should occupy whole width of integer.

^ | v .



Suresh Paldia · 3 years ago

```
#include<stdio.h>

void main()
{
    int x=67, y=35;
    int a,b;
    int result;
    a=x/y;
    b=y/x;
    result = (x*(a) + y*(b));
    result = result/(a+b);
    printf("Greater of %d and %d is %d",x,y,result);
}
```

^ | v .



sunny321 · 4 years ago

what happen if num is -ve

^ | v .



sunny → sunny321 · 4 years ago

plzzzz reply my query also

^ | v .



vaibhav · 4 years ago

this implementation has a problem.Take a number 27 (11011) and rotate it left here you can not always take no of bit= 32.You will try to find the position of left

equal to that value.

^ | v .



sureshpaldia22 → vaibhav · 3 years ago

You can have a modification in definition of INT_BITS to get the bits cor

```
#define INT_BITS 8*sizeof(int)
```

^ | v .



Krishna Kishore → sureshpaldia22 · 2 years ago

```
/*we can find the left most set bit as */  
for ( int i = 0 ; n >> 1 ; i++ );  
/* The value of i would be the position of Left Most set
```

^ | v .



GeeksforGeeks → vaibhav · 4 years ago

@vaibhav: The program doesn't return 15 for 27. We have added few l

^ | v .



Silent → GeeksforGeeks · 7 months ago

it does not work for negative numbers as negative numbers are

^ | v .

 [Subscribe](#)

 [Add Disqus to your site](#)

