

Largest Sum Contiguous Subarray

Write an efficient C program to find the sum of contiguous subarray within a one-dimensional array of numbers which has the largest sum.

Kadane's Algorithm:

Initialize:

```
max_so_far = 0
max_ending_here = 0
```

Loop for each element of the array

```
(a) max_ending_here = max_ending_here + a[i]
(b) if(max_ending_here < 0)
    max_ending_here = 0
(c) if(max_so_far < max_ending_here)
    max_so_far = max_ending_here
```

return max_so_far

Explanation:

Simple idea of the Kadane's algorithm is to look for all positive contiguous segments of the array (max_ending_here is used for this). And keep track of maximum sum contiguous segment among all positive segments (max_so_far is used for this). Each time we get a positive sum compare it with max_so_far and update max_so_far if it is greater than max_so_far

Lets take the example:

{-2, -3, 4, -1, -2, 1, 5, -3}

max_so_far = max_ending_here = 0



Google™ Custom Search



GeeksforGeeks



53,521 people like [GeeksforGeeks](#).



Facebook

[Interview Experiences](#)

[Advanced Data Structures](#)

[Dynamic Programming](#)

[Greedy Algorithms](#)

[Backtracking](#)

[Pattern Searching](#)

[Divide & Conquer](#)

[Mathematical Algorithms](#)

[Recursion](#)

[Geometric Algorithms](#)

```

for i=0, a[0] = -2
max_ending_here = max_ending_here + (-2)
Set max_ending_here = 0 because max_ending_here < 0

for i=1, a[1] = -3
max_ending_here = max_ending_here + (-3)
Set max_ending_here = 0 because max_ending_here < 0

for i=2, a[2] = 4
max_ending_here = max_ending_here + (4)
max_ending_here = 4
max_so_far is updated to 4 because max_ending_here greater than max_so_far which was 0 till now

for i=3, a[3] = -1
max_ending_here = max_ending_here + (-1)
max_ending_here = 3

for i=4, a[4] = -2
max_ending_here = max_ending_here + (-2)
max_ending_here = 1

for i=5, a[5] = 1
max_ending_here = max_ending_here + (1)
max_ending_here = 2

for i=6, a[6] = 5
max_ending_here = max_ending_here + (5)
max_ending_here = 7
max_so_far is updated to 7 because max_ending_here is greater than max_so_far

for i=7, a[7] = -3
max_ending_here = max_ending_here + (-3)
max_ending_here = 4

```

Program:



Popular Posts

[All permutations of a given string](#)

[Memory Layout of C Programs](#)

[Understanding "extern" keyword in C](#)

[Median of two sorted arrays](#)

[Tree traversal without recursion and without stack!](#)

[Structure Member Alignment, Padding and Data Packing](#)

[Intersection point of two Linked Lists](#)

[Lowest Common Ancestor in a BST.](#)

[Check if a binary tree is BST or not](#)

[Sorted Linked List to Balanced BST](#)

```

#include<stdio.h>
int maxSubArraySum(int a[], int size)
{
    int max_so_far = 0, max_ending_here = 0;
    int i;
    for(i = 0; i < size; i++)
    {
        max_ending_here = max_ending_here + a[i];
        if(max_ending_here < 0)
            max_ending_here = 0;
        if(max_so_far < max_ending_here)
            max_so_far = max_ending_here;
    }
    return max_so_far;
}

/*Driver program to test maxSubArraySum*/
int main()
{
    int a[] = {-2, -3, 4, -1, -2, 1, 5, -3};
    int n = sizeof(a)/sizeof(a[0]);
    int max_sum = maxSubArraySum(a, n);
    printf("Maximum contiguous sum is %d\n", max_sum);
    getchar();
    return 0;
}

```

Notes:

Algorithm doesn't work for all negative numbers. It simply returns 0 if all numbers are negative. For handling this we can add an extra phase before actual implementation. The phase will look if all numbers are negative, if they are it will return maximum of them (or smallest in terms of absolute value). There may be other ways to handle it though.

Above program can be optimized further, if we compare max_so_far with max_ending_here only if max_ending_here is greater than 0.

```

int maxSubArraySum(int a[], int size)
{
    int max_so_far = 0, max_ending_here = 0;
    int i;
    for(i = 0; i < size; i++)
    {
        max_ending_here = max_ending_here + a[i];
        if(max_ending_here < 0)
            max_ending_here = 0;
    }
    return max_so_far;
}

```



```

    /* Do not compare for all elements. Compare only
    when max_ending_here > 0 */
    else if (max_so_far < max_ending_here)
        max_so_far = max_ending_here;
}
return max_so_far;
}

```

Time Complexity: O(n)

Algorithmic Paradigm: Dynamic Programming

Following is another simple implementation suggested by **Mohit Kumar**. The implementation handles the case when all numbers in array are negative.

```

#include<stdio.h>

int max(int x, int y)
{ return (y > x)? y : x; }

int maxSubArraySum(int a[], int size)
{
    int max_so_far = a[0], i;
    int curr_max = a[0];

    for (i = 1; i < size; i++)
    {
        curr_max = max(a[i], curr_max+a[i]);
        max_so_far = max(max_so_far, curr_max);
    }
    return max_so_far;
}

/* Driver program to test maxSubArraySum */
int main()
{
    int a[] = {-2, -3, 4, -1, -2, 1, 5, -3};
    int n = sizeof(a)/sizeof(a[0]);
    int max_sum = maxSubArraySum(a, n);
    printf("Maximum contiguous sum is %d\n", max_sum);
    return 0;
}

```

Now try below question

Given an array of integers (possibly some of the elements negative), write a C program to find out

Recent Comments

Aman Hi, Why arent we checking for conditions...

Write a C program to Delete a Tree. · 18 minutes ago

kzs please provide solution for the problem...

Backtracking | Set 2 (Rat in a Maze) · 22 minutes ago

Sanjay Agarwal bool

tree::Root_to_leaf_path_given_sum(tree...

Root to leaf path sum equal to a given number · 47 minutes ago

GOPI GOPINATH @admin Highlight this sentence "We can easily...


Count trailing zeroes in factorial of a number · 48 minutes ago

newCoder3006 If the array contains negative numbers also. We...

Find subarray with given sum · 1 hour ago

newCoder3006 Code without using while loop. We can do it..

Find subarray with given sum · 1 hour ago

AdChoices 

[► C++ Code](#)


[► Programming C++](#)

the *maximum product* possible by adding 'n' consecutive integers in the array, $n \leq \text{ARRAY_SIZE}$. Also give where in the array this sequence of n integers starts.

References:

http://en.wikipedia.org/wiki/Kadane%27s_Algorithm

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.



AdChoices

► [SUM Function](#)

► [C++ Array](#)

► [The SUM of All](#)

AdChoices

► [SUM Program](#)

► [Check SUM](#)

► [SUM Time](#)

Related Topics:

- [Remove minimum elements from either side such that \$2 \times \text{min}\$ becomes more than max](#)
- [Divide and Conquer | Set 6 \(Search in a Row-wise and Column-wise Sorted 2D Array\)](#)
- [Bucket Sort](#)
- [Kth smallest element in a row-wise and column-wise sorted 2D array | Set 1](#)
- [Find the number of zeroes](#)
- [Find if there is a subarray with 0 sum](#)
- [Divide and Conquer | Set 5 \(Strassen's Matrix Multiplication\)](#)
- [Count all possible groups of size 2 or 3 that have sum as multiple of 3](#)



47



Tweet

0



8

Writing code in comment? Please use ideone.com and share the link here.

@geeksforgeeks, **Some rights reserved**

Contact Us!

Powered by **WordPress** & **MooTools**, customized by geeksforgeeks team