


Check for Children Sum Property in a Binary Tree.

Given a binary tree, write a function that returns true if the tree satisfies below property.

For every node, data value must be equal to sum of data values in left and right children. Consider data value as 0 for NULL children. Below tree is an example



Algorithm:

Traverse the given binary tree. For each node check (recursively) if the node and both its children satisfy the Children Sum Property, if so then return true else return false.

Implementation:

```

/* Program to check children sum property */
#include <stdio.h>
#include <stdlib.h>

/* A binary tree node has data, left child and right child */
struct node
{

```


Google™ Custom Search



GeeksforGeeks



52,731 people like GeeksforGeeks.



Interview Experiences

Advanced Data Structures

Dynamic Programming

Greedy Algorithms

Backtracking

Pattern Searching

Divide & Conquer

Mathematical Algorithms

Recursion

```

int data;
struct node* left;
struct node* right;
};

/* returns 1 if children sum property holds for the given
   node and both of its children*/
int isSumProperty(struct node* node)
{
    /* left_data is left child data and right_data is for right child da
    int left_data = 0, right_data = 0;

    /* If node is NULL or it's a leaf node then
       return true */
    if(node == NULL ||
       (node->left == NULL && node->right == NULL))
        return 1;
    else
    {
        /* If left child is not present then 0 is used
           as data of left child */
        if(node->left != NULL)
            left_data = node->left->data;

        /* If right child is not present then 0 is used
           as data of right child */
        if(node->right != NULL)
            right_data = node->right->data;

        /* if the node and both of its children satisfy the
           property return 1 else 0*/
        if((node->data == left_data + right_data)&&
           isSumProperty(node->left) &&
           isSumProperty(node->right))
            return 1;
        else
            return 0;
    }
}

/*
   Helper function that allocates a new node
   with the given data and NULL left and right
   pointers.
*/
struct node* newNode(int data)
{

```



Popular Posts

All permutations of a given string

Memory Layout of C Programs

Understanding "extern" keyword in C

Median of two sorted arrays

Tree traversal without recursion and without stack!

Structure Member Alignment, Padding and Data Packing

Intersection point of two Linked Lists

Lowest Common Ancestor in a BST.

Check if a binary tree is BST or not

Sorted Linked List to Balanced BST

```

struct node* newNode(int data)
{
    struct node* node =
        (struct node*)malloc(sizeof(struct node));
    node->data = data;
    node->left = NULL;
    node->right = NULL;
    return node;
}

/* Driver program to test above function */
int main()
{
    struct node *root = newNode(10);
    root->left = newNode(8);
    root->right = newNode(2);
    root->left->left = newNode(3);
    root->left->right = newNode(5);
    root->right->right = newNode(2);
    if(isSumProperty(root))
        printf("The given tree satisfies the children sum property ");
    else
        printf("The given tree does not satisfy the children sum property ");

    getchar();
    return 0;
}

```

Time Complexity: $O(n)$, we are doing a complete traversal of the tree.

As an exercise, extend the above question for an n-ary tree.

This question was asked by Shekhar.

Please write comments if you find any bug in the above algorithm or a better way to solve the same problem.





Integrated
Desktop & Mobile Device
Management

ManageEngine
Desktop Central

Download 



695



Subscribe

Recent Comments

karthik it should have been `max_wrap=`
`max_wrap -...`

[Maximum circular subarray sum](#) · 1 minute ago

affiszerv Your example has two 4s on row 3,
that's why it...

[Backtracking | Set 7 \(Sudoku\)](#) · 45 minutes ago

RVM Can someone please elaborate this Qs
from above...

[Flipkart Interview | Set 6](#) · 1 hour ago

Vishal Gupta I talked about as an Interviewer
in general,...

[Software Engineering Lab, Samsung Interview | Set 2](#) · 1 hour ago

@meya Working solution for question 2 of
4f2f round....

[Amazon Interview | Set 53 \(For SDE-1\)](#) · 1 hour ago

sandeep void rearrange(struct node *head)
{...

Given a linked list, reverse alternate nodes and

Related Topics:

- [Print a Binary Tree in Vertical Order | Set 2 \(Hashmap based Method\)](#)
- [Print Right View of a Binary Tree](#)
- [Red-Black Tree | Set 3 \(Delete\)](#)
- [Construct a tree from Inorder and Level order traversals](#)
- [Print all nodes at distance k from a given node](#)
- [Print a Binary Tree in Vertical Order | Set 1](#)
- [Interval Tree](#)
- [Check if a given Binary Tree is height balanced like a Red-Black Tree](#)



1



Tweet

0



0

Writing code in comment? Please use [ideone.com](#) and share the link here.

15 Comments

GeeksforGeeks

Sort by Newest ▾



Join the discussion...

append at the end · 3 hours ago



AlienOnEarth · 4 days ago

Java Implementation: Routine returns int value = root.data if the tree satisfies c

```
static int isChildSumProperty(BTNode root)
```

```
{
```

```
if(root==null)
```

```
return 0;
```

```
if(isLeaf(root))
```

```
{
```

```
return root.data;
```

```
}
```

```
int l = isChildSumProperty(root.left);
```

```
int r = isChildSumProperty(root.right);
```

see more

^ | v · Reply · Share ›



neelabhsingh · 2 months ago

GeeksforGeeks.

```
if((node->data == left_data + right_data)&&
```

```
isSumProperty(node->left) &&
```

```
isSumProperty(node->right))
```

AdChoices ▶

▶ [SUM Function](#)

▶ [Binary Tree](#)

▶ [Java Tree](#)

AdChoices ▶

▶ [Java to C++](#)

▶ [Tree Root](#)

▶ [Tree View](#)

AdChoices ▶

▶ [Check SUM](#)

▶ [SUM To](#)

▶ [In Memory Tree](#)

```
else  
return 0;  
}
```

Please check it. There is no use of else please remove it..

^ | v • Reply • Share ›



AlienOnEarth → neelabhsingh • 4 days ago

Else is needed. What if the condition is false? what should function ret

^ | v • Reply • Share ›



NAVEEN PRAJAPATI • 2 months ago

we can also do this by using post order traversal . below is the function given..

```
void check_sum_property(struct node *root)  
{  
  
if(root)  
{  
if(root->data = (root->left->data) + (root->right->data))  
{  
printf("node following check sum property %d--",root->data);  
}  
check_sum_property(root->left);  
check_sum_property(root->right);  
}  
}
```

^ | v • Reply • Share ›



invince_guitar • 7 months ago

Similar method..but done in my way.

//.....

```
#include<stdio.h>
#include<stdlib.h>

struct node
{
int data;
struct node *l;
struct node *r;
};

struct node* create_node(int num)
{
struct node *temp=(struct node *)malloc(sizeof(struct node));
temp->data=num;
temp->l=NULL;
temp->r=NULL;
```

[see more](#)

^ | v • Reply • Share ›



Sanjith Sakthivel • 9 months ago

```
int childrensum(node *root).
{
if(root==NULL)
{
return 0;
}
if(root->left==NULL&&root->right==NULL)
{
return root->data;
}
if(root->data==childrensum(root->left)+childrensum(root->right))
```

```
{  
printf("Parent = Sum of Children ");  
return root->data;  
}  
else  
{  
printf("Wrong");  
return -1;  
}  
}
```

^ | v • Reply • Share ›



ubiquitous • 9 months ago

[sourcecode language="java"]

```
int validateChildrenSumProperty(TreeNode t)  
{  
if(t.left == null && t.right == null)  
{  
return t.v;  
}  
int left = 0, right = 0;  
if(t.left != null)  
{  
left = validateChildrenSumProperty(t.left);  
}  
if(t.right != null)  
{  
right = validateChildrenSumProperty(t.right);  
}  
if(left == -1 || right == -1)  
{  

```


^ | v • Reply • Share ›



Nitesh • 10 months ago

```
int sumProperty(node *tree, int sum)
{
    if(tree == NULL && sum != 0)
        return false;

    /*Mease we are on leaf node*/
    if(tree ->left == NULL && tree->right == NULL )
    {
        if((sum-tree->data) ==0)
            return true;
    }
    int subSum = sum - tree->data;
    if(sumProperty(tree->left,subSum) || sumProperty(tree->right, subSum))
        return true;

    return false;
}
```

^ | v • Reply • Share ›



abhishek08aug • a year ago

C++ code:

```
#include <iostream>
#include <stdlib.h>
using namespace std;

class tree_node {
```

```
private:
    int data;
    tree_node * left;
    tree_node * right;
public:
    tree_node() {
        left=NULL;
        right=NULL;
    }
    void set_data(int data) {
        this->data=data;
```

[see more](#)

^ | v • Reply • Share ›



devil_001 • a year ago

this is another method :

```
#include <stdio.h>
#include <stdlib.h>
struct node
{
    int data;
    struct node* left;
    struct node* right;
};
struct node* newNode(int data)
{
    struct node* node =
        (struct node*)malloc(sizeof(struct node));
    node->data = data;
    node->left = NULL;
```

```
node->right = NULL;  
return(node);
```

[see more](#)

^ | v • Reply • Share ›



devil_001 • a year ago

another method :

```
#include <stdio.h>  
#include <stdlib.h>  
struct node  
{  
    int data;  
    struct node* left;  
    struct node* right;  
};  
struct node* newNode(int data)  
{  
    struct node* node =  
        (struct node*)malloc(sizeof(struct node));  
    node->data = data;  
    node->left = NULL;  
    node->right = NULL;
```

[see more](#)

^ | v • Reply • Share ›



Nikin • a year ago

```

bool isSumTree(Node* sr)
{
    if(sr == NULL) return true;
    int lData = 0, rData = 0;
    if(sr->left)
        lData = sr->left->data;
    if(sr->right)
        rData = sr->right->data;

    return ( sr->data == (lData + rData) &&
            isSumTree(sr->left) && isSumTree(sr->right));
}

```

^ | v • Reply • Share ›



Nirdesh → Nikin • a year ago

You are missing one condition in a base case here in the 1st line. Your

```

    if(sr == null || (sr->left==null && sr->right==null)){
        return true;
    }

```

^ | v • Reply • Share ›



Teja • 4 years ago

This qn was asked in Amazon written test.

^ | v • Reply • Share ›



AT → Teja • a year ago

Java Code

```
/* public boolean childSum(Node n) {  
    if (n == null || n.left == null && n.right == null)  
        return true;  
    if (n.left == null || n.right == null)  
        return n.left == null? (n.data == n.right.data)  
        return (n.data == n.left.data + n.right.data) && childSum(n.right);  
} */
```

^ | v • Reply • Share ›

 [Subscribe](#)

 [Add Disqus to your site](#)

@geeksforgeeks, **Some rights reserved**

[Contact Us!](#)

Powered by **WordPress** & **MooTools**, customized by geeksforgeeks team