

Home	Algorithms	DS	GATE	Interview Corner	Q&A	C	C++	Java	Books	Contribute	Ask a Q	About
Array	Bit Magic	C/C++	Articles	GFactS	Linked List	MCQ	Misc	Output	String	Tree	Graph	

## Accessing Grandparent's member in Java

### Directly accessing Grandparent's member in Java:

Predict the output of following Java program.

```
// filename Main.java
class Grandparent {
    public void Print() {
        System.out.println("Grandparent's Print()");
    }
}

class Parent extends Grandparent {
    public void Print() {
        System.out.println("Parent's Print()");
    }
}

class Child extends Parent {
    public void Print() {
        super.super.Print(); // Trying to access Grandparent's Print()
        System.out.println("Child's Print()");
    }
}

public class Main {
    public static void main(String[] args) {
        Child c = new Child();
        c.Print();
    }
}
```

Output: Compiler Error

There is error in line "super.super.print();". In Java, a class cannot directly access the


Google™ Custom Search



GeeksforGeeks



53,527 people like [GeeksforGeeks](#).



Facebook

[Interview Experiences](#)

[Advanced Data Structures](#)

[Dynamic Programming](#)

[Greedy Algorithms](#)

[Backtracking](#)

[Pattern Searching](#)

[Divide & Conquer](#)

[Mathematical Algorithms](#)

[Recursion](#)

[Geometric Algorithms](#)

grandparent's members. It is allowed in C++ though. In C++, we can use scope resolution operator (::) to access any ancestor's member in inheritance hierarchy. ***In Java, we can access grandparent's members only through the parent class.*** For example, the following program compiles and runs fine.

```
// filename Main.java
class Grandparent {
    public void Print() {
        System.out.println("Grandparent's Print()");
    }
}

class Parent extends Grandparent {
    public void Print() {
        super.Print();
        System.out.println("Parent's Print()");
    }
}

class Child extends Parent {
    public void Print() {
        super.Print();
        System.out.println("Child's Print()");
    }
}

public class Main {
    public static void main(String[] args) {
        Child c = new Child();
        c.Print();
    }
}
```

Output:

```
Grandparent's Print()
Parent's Print()
Child's Print()
```

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.



## Popular Posts

[All permutations of a given string](#)

[Memory Layout of C Programs](#)

[Understanding "extern" keyword in C](#)

[Median of two sorted arrays](#)

[Tree traversal without recursion and without stack!](#)


[Structure Member Alignment, Padding and Data Packing](#)

[Intersection point of two Linked Lists](#)

[Lowest Common Ancestor in a BST.](#)

[Check if a binary tree is BST or not](#)

[Sorted Linked List to Balanced BST](#)



## Related Topics:

- Backtracking | Set 8 (Solving Cryptarithmic Puzzles)
- Tail Recursion
- Find if two rectangles overlap
- Analysis of Algorithm | Set 4 (Solving Recurrences)
- Print all possible paths from top left to bottom right of a mXn matrix
- Generate all unique partitions of an integer
- Russian Peasant Multiplication
- Closest Pair of Points | O(nlogn) Implementation



0



Tweet

0



0

Writing code in comment? Please use [ideone.com](https://www.ideone.com) and share the link here.

12 Comments

GeeksforGeeks

Sort by Newest ▼





Can the class access...

705



Subscribe



kartik · 2 years ago

@shadabmast & @Sudhansu:

Thanks for sharing your thoughts. These are mainly indirect ways of accessin is: unlike C++, Java doesn't allow any direct way to access grandparent's mer

^ | v · Reply · Share ›



akhil → kartik · 2 years ago

Java doesn't allow because it's against encapsulation policy and not a

^ | v · Reply · Share ›



shadabmast → akhil · 2 years ago

@akhil : sounds interesting. would you mind elaborating your pr

^ | v · Reply · Share ›



Mrudhul → shadabmast · 9 months ago

If java indeed allow it, what if i code to access parent of

```
/* Paste your code here (You may delete these li
```

^ | v · Reply · Share ›



akhil → shadabmast · 2 years ago

It makes more sense to not access grandparent's data for the child class. So it is a good idea to access grandp

^ | v · Reply · Share ›



shadabmast → akhil · 2 years ago

## Recent Comments

Abhi You live US or India?

Google (Mountain View) interview · 35 minutes ago

Aman Hi, Why arent we checking for conditions...

Write a C program to Delete a Tree. · 1 hour ago

kzs please provide solution for the problem...

Backtracking | Set 2 (Rat in a Maze) · 1 hour ago

Sanjay Agarwal bool

tree::Root\_to\_leaf\_path\_given\_sum(tree...

Root to leaf path sum equal to a given number · 1 hour ago

GOPI GOPINATH @admin Highlight this sentence "We can easily...

Count trailing zeroes in factorial of a number · 1 hour ago

newCoder3006 If the array contains negative numbers also. We...

Find subarray with given sum · 2 hours ago

AdChoices

► [Java Source Code](#)

► [C++ Java](#)

► [Java Script Void](#)

Copy, not confirmed as an idea by, etc.  
^ | v • Reply • Share ›

AdChoices ▶

▶ [Java to C++](#)

▶ [Programming C++](#)

▶ [Java Script Void](#)

AdChoices ▶

▶ [String Java](#)

▶ [Java Public](#)

▶ [Java VS C#](#)



**shadabmast** • 2 years ago

Another Approach : You can directly access GrandParent's method by not overloading and still calling super.print() from child's version print method.

```
[sourcecode language="java"]
// filename Main.java
class Grandparent{
public void Print() {
System.out.println("Grandparent's Print()");
}
}
```

```
class Parent extends Grandparent {
/*public void Print() {
System.out.println("Parent's Print()");
}*/
}
```

```
class Child extends Parent {
public void Print() {
```

[see more](#)

^ | v • Reply • Share ›



**Aniket** → shadabmast • 9 months ago

I guess this is similar to the scope of variable.

If the variable is not found in local block, compiler searches for it in the immediate base class. Similarly if the method is not present in the immediate base class then it is called.

Please correct me if I am wrong!



**sudhansu sekhar nayak**(Gm Odish · 2 years ago

Sir Don't mind I have one solution. The solution is you do not create Print() me create one constructor of Grandparent class. So all the things you declare in G automatically in parent class. It one solution of this Question and it does not need any scope resolution operator(::).

My Code is:

```
[sourcecode language="java"]
/* Paste your code here (You may delete these lines if not writing code) */
[/

// filename Main.java
class Grandparent{
Grandparent(){ //create constructor of Grandparent class
System.out.println("Grandparent's Print()");
}

}
```

[see more](#)

^ | v · [Reply](#) · [Share](#) ›



**trilok** · 2 years ago

good info. please provide C++ example also.

^ | v · [Reply](#) · [Share](#) ›



**Sandeep** → trilok · 2 years ago

Following is an example C++ program

```
#include<iostream>
```

```
using namespace std;

class A
{
public:
    void Print() { cout<<"A's Print()\n"; }
};

class B: public A
{
public:
    void Print() { cout<<"B's Print()\n"; }
};
```

[see more](#)

^ | v • Reply • Share ›



**trilok** ↗ Sandeep • 2 years ago

Thanks

^ | v • Reply • Share ›

 [Subscribe](#)

 [Add Disqus to your site](#)

