


## Shuffle a given array

Given an array, write a program to generate a random permutation of array elements. This question is also asked as “shuffle a deck of cards” or “randomize a given array”.




Let the given array be `arr[]`. A simple solution is to create an auxiliary array `temp[]` which is initially a copy of `arr[]`. Randomly select an element from `temp[]`, copy the randomly selected element to `arr[0]` and remove the selected element from `temp[]`. Repeat the same process `n` times and keep copying elements to `arr[1]`, `arr[2]`, .... The time complexity of this solution will be  $O(n^2)$ .

**Fisher–Yates shuffle Algorithm** works in  $O(n)$  time complexity. The assumption here is, we are given a function `rand()` that generates random number in  $O(1)$  time.

The idea is to start from the last element, swap it with a randomly selected element from the whole array (including last). Now consider the array from 0 to `n-2` (size reduced by 1), and repeat the process till we hit the first element.

Following is the detailed algorithm

```
To shuffle an array a of n elements (indices 0..n-1):
for i from n - 1 downto 1 do
```



53,525 people like [GeeksforGeeks](#).



[Interview Experiences](#)

[Advanced Data Structures](#)

[Dynamic Programming](#)

[Greedy Algorithms](#)

[Backtracking](#)

[Pattern Searching](#)

[Divide & Conquer](#)

[Mathematical Algorithms](#)

[Recursion](#)

[Geometric Algorithms](#)

```
j = random integer with 0 <= j <= i
exchange a[j] and a[i]
```

Following is C++ implementation of this algorithm.

```
// C Program to shuffle a given array
```

```
#include <stdio.h>
#include <stdlib.h>
#include <time.h>
```

```
// A utility function to swap two integers
```

```
void swap (int *a, int *b)
{
    int temp = *a;
    *a = *b;
    *b = temp;
}
```

```
// A utility function to print an array
```

```
void printArray (int arr[], int n)
{
    for (int i = 0; i < n; i++)
        printf("%d ", arr[i]);
    printf("\n");
}
```

```
// A function to generate a random permutation of arr[]
```

```
void randomize ( int arr[], int n )
{
    // Use a different seed value so that we don't get same
    // result each time we run this program
    srand ( time(NULL) );

    // Start from the last element and swap one by one. We don't
    // need to run for the first element that's why i > 0
    for (int i = n-1; i > 0; i--)
    {
        // Pick a random index from 0 to i
        int j = rand() % (i+1);

        // Swap arr[i] with the element at random index
        swap(&arr[i], &arr[j]);
    }
}
```

**Deploy Early.  
Deploy Often.**

DevOps from Rackspace:  
**Automation**

[FIND OUT HOW ►](#)



## Popular Posts

[All permutations of a given string](#)

[Memory Layout of C Programs](#)

[Understanding "extern" keyword in C](#)

[Median of two sorted arrays](#)

[Tree traversal without recursion and without stack!](#)

[Structure Member Alignment, Padding and Data Packing](#)

[Intersection point of two Linked Lists](#)

[Lowest Common Ancestor in a BST.](#)

[Check if a binary tree is BST or not](#)

[Sorted Linked List to Balanced BST](#)

```
// Driver program to test above function.
int main()
{
    int arr[] = {1, 2, 3, 4, 5, 6, 7, 8};
    int n = sizeof(arr) / sizeof(arr[0]);
    randomize (arr, n);
    printArray(arr, n);

    return 0;
}
```

Output:

7 8 4 6 3 1 2 5

The above function assumes that rand() generates a random number.

Time Complexity:  $O(n)$ , assuming that the function rand() takes  $O(1)$  time.

### How does this work?

The probability that  $i$ th element (including the last one) goes to last position is  $1/n$ , because we randomly pick an element in first iteration.

The probability that  $i$ th element goes to second last position can be proved to be  $1/n$  by dividing it in two cases.

*Case 1:  $i = n-1$  (index of last element):*

The probability of last element going to second last position is = (probability that last element doesn't stay at its original position)  $\times$  (probability that the index picked in previous step is picked again so that the last element is swapped)

So the probability =  $((n-1)/n) \times (1/(n-1)) = 1/n$

*Case 2:  $0 < i < n-1$  (index of non-last):*


The probability of  $i$ th element going to second position = (probability that  $i$ th element is not picked in previous iteration)  $\times$  (probability that  $i$ th element is picked in this iteration)

So the probability =  $((n-1)/n) \times (1/(n-1)) = 1/n$

We can easily generalize above proof for any other position.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.





705



## Recent Comments

Abhi You live US or India?

Google (Mountain View) interview · 15 minutes ago

**Aman** Hi, Why arent we checking for conditions...

Write a C program to Delete a Tree. · 55 minutes ago

kzs please provide solution for the problem...

Backtracking | Set 2 (Rat in a Maze) · 58 minutes ago

**Sanjay Agarwal** bool

tree::Root\_to\_leaf\_path\_given\_sum(tree...

Root to leaf path sum equal to a given number · 1 hour ago

**GOPI GOPINATH** @admin Highlight this sentence "We can easily...

Count trailing zeroes in factorial of a number · 1 hour ago

**newCoder3006** If the array contains negative numbers also. We...

Find subarray with given sum · 1 hour ago

AdChoices

► [C++ Code](#)

► [Java Array](#)

► [Java Source Code](#)

## Related Topics:

- Remove minimum elements from either side such that  $2 \times \text{min}$  becomes more than max
- Divide and Conquer | Set 6 (Search in a Row-wise and Column-wise Sorted 2D Array)
- Bucket Sort
- Kth smallest element in a row-wise and column-wise sorted 2D array | Set 1
- Find the number of zeroes
- Find if there is a subarray with 0 sum
- Divide and Conquer | Set 5 (Strassen's Matrix Multiplication)
- Count all possible groups of size 2 or 3 that have sum as multiple of 3



9



Tweet

2



0

Writing code in comment? Please use [ideone.com](https://ideone.com) and share the link here.

20 Comments

GeeksforGeeks

Sort by Newest ▼



Join the discussion...

AdChoices

► [An Array](#)

► [Int in Array](#)

► [String Array](#)

AdChoices

► [Array Element](#)

► [Array Function](#)

► [Array of Arrays](#)



**Manni** • 2 months ago

Manni's probabilistic approach:

Select 2 random number between 0-n, swap the two elements at the the index  
Repeat the step n/2 times atleast. Contact Manpreet Singh, NIT Durgapur for r

<https://www.facebook.com/manpr...>

1 ^ | v .



**Ankur Jain** • 3 months ago

Q1 why mod we take mod rand() % (i+1);and not like rand() % (n) ?

Q2 and why didn't take the element at zeroth index ?

^ | v .



**alien** → Ankur Jain • a month ago

A1: because once you have shuffled nth element, dont replace it again

A2: with what will you replace 0th element with?

^ | v .



**Ankur Jain** → alien • a month ago

Q1 comment : in the above solution you are swapping with its l  
position is only replace with 0,1,2,3,4 and why cant 6 th ,7th , th

Q2 comment : as 0th element is only replace when rand fun giv  
for i 0 to n

j=rand()%n;

shuffle the whole array in equal proportion

^ | v .



**Sumit Gera** • 11 months ago



How did we arrive at the probability for  $I = n - 1$  case?

^ | v .



K.kaushik · 11 months ago

A simple java implementation of the above program with  $O(n)$  time complexity

```
public class Shuffle {  
  
    public static int randomize(int min, int max)  
    {  
        return (int) (Math.random() * (max-min+1) + min);  
    }  
  
    public static void shuffleCards(int cards[], int n)  
    {  
        int i;  
  
        for(i = 0; i < n; i++)  
        {  
            int j = randomize(i, n-1-i);
```

see more

^ | v .



Poorvank Bhatia · a year ago

why don't we need to run it for the first element?

^ | v .



Poorvank Bhatia · a year ago

why don't we need to run it for the first element?

^ | v .



**Praveen** · 2 years ago

Also a better explanation is here - <http://bost.ocks.org/mike/shuf...>

^ | v .



**Mahesh** · 2 years ago

Can you explain how the first case is order  $n^2$  ?

^ | v .



**Kartik** → Mahesh · 2 years ago

In first method, we need to remove the selected element from temp. R  
c(m-1) time where m is the number of elements in temp[] and c is a cc  
 $2 + \dots + 1)c = O(n^2)$

^ | v .



**Ishant Gaurav** → Kartik · a year ago

class Main

```
{  
    public static void main (String[] args) throws java.lang.Exceptio  
    {  
        int a[]={0,1,2,3,4,5,6,7,8,9};  
        int randarray[]=new int[10];  
        int flag[] = new int[10];  
        for(int i=0;i<10;i++)  
        {  
            randarray[i]=a[i];  
        }  
        SecureRandom rand = new SecureRandom();
```

```
        int i=0;  
        while(i<=9)
```

```
{  
int num = rand.nextInt(10);  
if(i<=9 && flag[num]!=0)
```

[see more](#)

^ | v .



**Ishant Gaurav** → Ishant Gaurav · a year ago

I have written acc to first method suggested by geeks f  
complexity is  $O(n^2)$ . Can u plz suggest if m wrong som

^ | v .



**raj** → Ishant Gaurav · a year ago

In First method..

instead of removing selected element and then moving  
to left by 1...we can just simply swap it with the last eler  
As a result first algorithm will also be  $O(n)$  time..

^ | v .



**GeeksforGeeks** · 2 years ago

@V: Thanks for the suggestion. We have added `srand(time(NULL))` to the orig

@Apeirogon: Thanks for the inputs. We have added a comment before 'for' lo  
last only as it makes the program more readable and matches with the standa

^ | v .



**V** · 2 years ago

You need to call `srand(time(NULL))` before your call to `randomize()` otherwise  
on each program execution.

/\* Paste your code here (You may **delete** these lines **if not** writing c



^ | v .



Aish · 2 years ago

Hi,

It appears like the same output is generated each time when I try executing the

Output:

3 6 4 7 1 5 8 2

Is there any way by which we can get different set of array output each time?

```
/* Paste your code here (You may delete these lines if not writing code)
```

^ | v .



adarsh → Aish · 2 years ago

you must have forgot to write `srand()` **function**

^ | v .



Apeirogon · 2 years ago

It is a C implementation and not C++ implementation as stated in the post.

The loop iteration in randomize function need not be in reverse order, it is better

When the code leaves out one iteration, write a comment about the same.

```
void randomize (int *a, int n) {  
    for (int i = 0; i < n - 1; i++) { // off-by-one intentional, we do not  
        swap (&a[i], &a[i + rand()%(n - i)]);  
    }  
}
```



**Rajeev** · 2 years ago

Nice



Subscribe



Add Disqus to your site

@geeksforgeeks, **Some rights reserved**

**Contact Us!**

Powered by **WordPress & MooTools**, customized by geeksforgeeks team