

Find the two numbers with odd occurrences in an unsorted array

Given an unsorted array that contains even number of occurrences for all numbers except two numbers. Find the two numbers which have odd occurrences in $O(n)$ time complexity and $O(1)$ extra space.

Examples:

Input: {12, 23, 34, 12, 12, 23, 12, 45}

Output: 34 and 45

Input: {4, 4, 100, 5000, 4, 4, 4, 4, 100, 100}

Output: 100 and 5000

Input: {10, 20}

Output: 10 and 20

A **naive method** to solve this problem is to run two nested loops. The outer loop picks an element and the inner loop counts the number of occurrences of the picked element. If the count of occurrences is odd then print the number. The time complexity of this method is $O(n^2)$.

We can **use sorting** to get the odd occurring numbers in $O(n \log n)$ time. First sort the numbers using an $O(n \log n)$ sorting algorithm like Merge Sort, Heap Sort.. etc. Once the array is sorted, all we need to do is a linear scan of the array and print the odd occurring number.

We can also **use hashing**. Create an empty hash table which will have elements and their counts. Pick all elements of input array one by one. Look for the picked element in hash table. If


Google™ Custom Search



GeeksforGeeks



53,521 people like [GeeksforGeeks](#).



[Interview Experiences](#)

[Advanced Data Structures](#)

[Dynamic Programming](#)

[Greedy Algorithms](#)

[Backtracking](#)

[Pattern Searching](#)

[Divide & Conquer](#)

[Mathematical Algorithms](#)

[Recursion](#)



Popular Posts

[All permutations of a given string](#)

[Memory Layout of C Programs](#)

[Understanding "extern" keyword in C](#)

[Median of two sorted arrays](#)

[Tree traversal without recursion and without stack!](#)

[Structure Member Alignment, Padding and Data Packing](#)

[Intersection point of two Linked Lists](#)

[Lowest Common Ancestor in a BST.](#)

[Check if a binary tree is BST or not](#)

[Sorted Linked List to Balanced BST](#)

the element is found in hash table, increment its count in table. If the element is not found, then enter it in hash table with count as 1. After all elements are entered in hash table, scan the hash table and print elements with odd count. This approach may take $O(n)$ time on average, but it requires $O(n)$ extra space.

A $O(n)$ time and $O(1)$ extra space solution:

The idea is similar to method 2 of [this](#) post. Let the two odd occurring numbers be x and y . We **use bitwise XOR** to get x and y . The first step is to do XOR of all elements present in array. XOR of all elements gives us XOR of x and y because of the following properties of XOR operation.

- 1) XOR of any number n with itself gives us 0, i.e., $n \wedge n = 0$
- 2) XOR of any number n with 0 gives us n , i.e., $n \wedge 0 = n$
- 3) XOR is cumulative and associative.

So we have XOR of x and y after the first step. Let the value of XOR be $xor2$. Every set bit in $xor2$ indicates that the corresponding bits in x and y have values different from each other. For example, if $x = 6$ (0110) and y is 15 (1111), then $xor2$ will be (1001), the two set bits in $xor2$ indicate that the corresponding bits in x and y are different. In the second step, we pick a set bit of $xor2$ and divide array elements in two groups. Both x and y will go to different groups. In the following code, the rightmost set bit of $xor2$ is picked as it is easy to get rightmost set bit of a number. If we do XOR of all those elements of array which have the corresponding bit set (or 1), then we get the first odd number. And if we do XOR of all those elements which have the corresponding bit 0, then we get the other odd occurring number. This step works because of the same properties of XOR. All the occurrences of a number will go in same set. XOR of all occurrences of a number which occur even number number of times will result in 0 in its set. And the xor of a set will be one of the odd occurring elements.

```
// Program to find the two odd occurring elements
#include<stdio.h>
```

```
/* Prints two numbers that occur odd number of times. The
function assumes that the array size is at least 2 and
there are exactly two numbers occurring odd number of times. */
void printTwoOdd(int arr[], int size)
{
    int xor2 = arr[0]; /* Will hold XOR of two odd occurring elements */
    int set_bit_no; /* Will have only single set bit of xor2 */
    int i;
```

```

int n = size - 2;
int x = 0, y = 0;

/* Get the xor of all elements in arr[]. The xor will basically
   be xor of two odd occurring elements */
for(i = 1; i < size; i++)
    xor2 = xor2 ^ arr[i];

/* Get one set bit in the xor2. We get rightmost set bit
   in the following line as it is easy to get */
set_bit_no = xor2 & ~(xor2-1);

/* Now divide elements in two sets:
   1) The elements having the corresponding bit as 1.
   2) The elements having the corresponding bit as 0. */
for(i = 0; i < size; i++)
{
    /* XOR of first set is finally going to hold one odd
       occurring number x */
    if(arr[i] & set_bit_no)
        x = x ^ arr[i];

    /* XOR of second set is finally going to hold the other
       odd occurring number y */
    else
        y = y ^ arr[i];
}

printf("\n The two ODD elements are %d & %d ", x, y);
}

/* Driver program to test above function */
int main()
{
    int arr[] = {4, 2, 4, 5, 2, 3, 3, 1};
    int arr_size = sizeof(arr)/sizeof(arr[0]);
    printTwoOdd(arr, arr_size);
    getchar();
    return 0;
}

```

Output:

The two ODD elements are 5 & 1

Time Complexity: $O(n)$

Deploy Early. Deploy Often.

DevOps from
Rackspace:

Automation

FIND OUT HOW ►



Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

Free C# Code Generator

 ironspeed.com

Create database & reporting apps straight from your database! Try it



Related Topics:

- Remove minimum elements from either side such that $2 \times \min$ becomes more than max
- Divide and Conquer | Set 6 (Search in a Row-wise and Column-wise Sorted 2D Array)
- Bucket Sort
- Kth smallest element in a row-wise and column-wise sorted 2D array | Set 1
- Find the number of zeroes
- Find if there is a subarray with 0 sum
- Divide and Conquer | Set 5 (Strassen's Matrix Multiplication)
- Count all possible groups of size 2 or 3 that have sum as multiple of 3



1



0



0

Writing code in comment? Please use ideone.com and share the link here.

Recent Comments

Aman Hi, Why arent we checking for conditions...

Write a C program to Delete a Tree. · 18 minutes ago

kzs please provide solution for the problem...
Backtracking | Set 2 (Rat in a Maze) · 21 minutes ago

Sanjay Agarwal bool
tree::Root_to_leaf_path_given_sum(tree...
Root to leaf path sum equal to a given number · 46 minutes ago


GOPI GOPINATH @admin Highlight this sentence "We can easily...
Count trailing zeroes in factorial of a number · 48 minutes ago

newCoder3006 If the array contains negative numbers also. We...

Find subarray with given sum · 1 hour ago

newCoder3006 Code without using while loop. We can do it...

Find subarray with given sum · 1 hour ago

AdChoices 

► [Java Array](#)

► [VHDL Array](#)


► [Verilog Array](#)

AdChoices 

► [Verilog Array](#)

► [C++ Array](#)

► [Odd Numbers](#)

AdChoices 

► [An Array](#)

► [Numbers Number](#)

► [Even Numbers](#)

@geeksforgeeks, **Some rights reserved**

Contact Us!

Powered by **WordPress** & **MooTools**, customized by geeksforgeeks team