


Tree Traversals

Unlike linear data structures (Array, Linked List, Queues, Stacks, etc) which have only one logical way to traverse them, trees can be traversed in different ways. Following are the generally used ways for traversing trees.



Depth First Traversals:

- (a) Inorder
- (b) Preorder
- (c) Postorder

Breadth First or Level Order Traversal

Please see [this](#) post for Breadth First Traversal.

Inorder Traversal:

Algorithm Inorder(tree)

1. Traverse the left subtree, i.e., call Inorder(left-subtree)


Google™ Custom Search



GeeksforGeeks



52,731 people like [GeeksforGeeks](#).



Facebook

[Interview Experiences](#)

[Advanced Data Structures](#)

[Dynamic Programming](#)

[Greedy Algorithms](#)

[Backtracking](#)

[Pattern Searching](#)

[Divide & Conquer](#)

[Mathematical Algorithms](#)

[Recursion](#)

[Geometric Algorithms](#)

2. Visit the root.
3. Traverse the right subtree, i.e., call `Inorder(right-subtree)`

Uses of Inorder

In case of binary search trees (BST), Inorder traversal gives nodes in non-decreasing order. To get nodes of BST in non-increasing order, a variation of Inorder traversal where Inorder traversal is reversed, can be used.

Example: Inorder traversal for the above given figure is 4 2 5 1 3.

Preorder Traversal:

Algorithm `Preorder(tree)`

1. Visit the root.
2. Traverse the left subtree, i.e., call `Preorder(left-subtree)`
3. Traverse the right subtree, i.e., call `Preorder(right-subtree)`

Uses of Preorder

Preorder traversal is used to create a copy of the tree. Preorder traversal is also used to get prefix expression on of an expression tree. Please see

http://en.wikipedia.org/wiki/Polish_notation to know why prefix expressions are useful.

Example: Preorder traversal for the above given figure is 1 2 4 5 3.

Postorder Traversal:

Algorithm `Postorder(tree)`

1. Traverse the left subtree, i.e., call `Postorder(left-subtree)`
2. Traverse the right subtree, i.e., call `Postorder(right-subtree)`
3. Visit the root.

Uses of Postorder

Postorder traversal is used to delete the tree. Please see [the question for deletion of tree](#) for details. Postorder traversal is also useful to get the postfix expression of an expression tree. Please see http://en.wikipedia.org/wiki/Reverse_Polish_notation to for the usage of postfix expression.

Example: Postorder traversal for the above given figure is 4 5 2 3 1.



Popular Posts

[All permutations of a given string](#)

[Memory Layout of C Programs](#)

[Understanding “extern” keyword in C](#)

[Median of two sorted arrays](#)

[Tree traversal without recursion and without stack!](#)

[Structure Member Alignment, Padding and Data Packing](#)

[Intersection point of two Linked Lists](#)

[Lowest Common Ancestor in a BST.](#)

[Check if a binary tree is BST or not](#)

[Sorted Linked List to Balanced BST](#)

```

#include <stdio.h>
#include <stdlib.h>

/* A binary tree node has data, pointer to left child
   and a pointer to right child */
struct node
{
    int data;
    struct node* left;
    struct node* right;
};

/* Helper function that allocates a new node with the
   given data and NULL left and right pointers. */
struct node* newNode(int data)
{
    struct node* node = (struct node*)
                        malloc(sizeof(struct node));

    node->data = data;
    node->left = NULL;
    node->right = NULL;

    return(node);
}

/* Given a binary tree, print its nodes according to the
   "bottom-up" postorder traversal. */
void printPostorder(struct node* node)
{
    if (node == NULL)
        return;

    // first recur on left subtree
    printPostorder(node->left);

    // then recur on right subtree
    printPostorder(node->right);

    // now deal with the node
    printf("%d ", node->data);
}

/* Given a binary tree, print its nodes in inorder*/
void printInorder(struct node* node)
{
    if (node == NULL)
        return;

```



```

/* first recur on left child */
printInorder(node->left);

/* then print the data of node */
printf("%d ", node->data);

/* now recur on right child */
printInorder(node->right);
}

/* Given a binary tree, print its nodes in inorder*/
void printPreorder(struct node* node)
{
    if (node == NULL)
        return;

    /* first print data of node */
    printf("%d ", node->data);

    /* then recur on left subtree */
    printPreorder(node->left);

    /* now recur on right subtree */
    printPreorder(node->right);
}

/* Driver program to test above functions*/
int main()
{
    struct node *root = newNode(1);
    root->left = newNode(2);
    root->right = newNode(3);
    root->left->left = newNode(4);
    root->left->right = newNode(5);

    printf("\n Preorder traversal of binary tree is \n");
    printPreorder(root);

    printf("\n Inorder traversal of binary tree is \n");
    printInorder(root);

    printf("\n Postorder traversal of binary tree is \n");
    printPostorder(root);

    getchar();
    return 0;
}

```

Recent Comments

karthik it should have been max_wrap=
max_wrap -...

Maximum circular subarray sum · 2 minutes ago

affiszerv Your example has two 4s on row 3,
that's why it...

Backtracking | Set 7 (Sudoku) · 46 minutes ago

RVM Can someone please elaborate this Qs
from above...

Flipkart Interview | Set 6 · 1 hour ago

Vishal Gupta I talked about as an Interviewer
in general,...

Software Engineering Lab, Samsung Interview | Set
2 · 1 hour ago

@meya Working solution for question 2 of
4f2f round....

Amazon Interview | Set 53 (For SDE-1) · 1 hour ago

sandeep void rearrange(struct node *head)
{...

Given a linked list, reverse alternate nodes and
append at the end · 3 hours ago

AdChoices 

[▶ Binary Tree](#)

[▶ C++ Algorithms](#)

[▶ Linked List](#)


AdChoices 

}

► [C++ Code](#)

► [C++ Example](#)

► [Null Pointer](#)

AdChoices 

► [Root Tree](#)

► [Tree Trees](#)

► [In the Tree](#)

Time Complexity: $O(n)$

Let us prove it:

Complexity function $T(n)$ — for all problem where tree traversal is involved — can be defined as:

$$T(n) = T(k) + T(n - k - 1) + c$$

Where k is the number of nodes on one side of root and $n-k-1$ on the other side.

Let's do analysis of boundary conditions

Case 1: Skewed tree (One of the subtrees is empty and other subtree is non-empty)

k is 0 in this case.

$$T(n) = T(0) + T(n-1) + c$$

$$T(n) = 2T(0) + T(n-2) + 2c$$

$$T(n) = 3T(0) + T(n-3) + 3c$$

$$T(n) = 4T(0) + T(n-4) + 4c$$

.....

.....

$$T(n) = (n-1)T(0) + T(1) + (n-1)c$$

$$T(n) = nT(0) + (n)c$$

Value of $T(0)$ will be some constant say d . (traversing a empty tree will take some constants time)

$$T(n) = n(c+d)$$

$$T(n) = O(n) \text{ (Theta of } n)$$

Case 2: Both left and right subtrees have equal number of nodes.

$$T(n) = 2T(\lfloor n/2 \rfloor) + c$$

This recursive function is in the standard form $(T(n) = aT(n/b) + O(n))$ for master method http://en.wikipedia.org/wiki/Master_theorem. If we solve it by master method we get $O(n)$

Auxiliary Space : If we don't consider size of stack for function calls then $O(1)$ otherwise $O(n)$.



Related Topics:

- [Print a Binary Tree in Vertical Order | Set 2 \(Hashmap based Method\)](#)
- [Print Right View of a Binary Tree](#)
- [Red-Black Tree | Set 3 \(Delete\)](#)
- [Construct a tree from Inorder and Level order traversals](#)
- [Print all nodes at distance k from a given node](#)
- [Print a Binary Tree in Vertical Order | Set 1](#)
- [Interval Tree](#)
- [Check if a given Binary Tree is height balanced like a Red-Black Tree](#)



3



Tweet

0



3

Writing code in comment? Please use [ideone.com](https://www.ideone.com) and share the link here.

18 Comments

GeeksforGeeks

Sort by Newest ▼



Join the discussion...



DarkProtocol • 7 months ago

Two Types:

BFS-

1) Inorder - L Root R -- $T(n) = O(n)$, Space used by stack in recursion $S(n) = O(n)$
 Space used by stack in recursion $S(n) = O(n)$ 3) Postorder - L R Root -- $T(n) = O(n)$
 $S(n) = O(n)$

DFS -

1) Level Order - With Recursion $T(n) = O(n^2)$
 - With Queue's - $T(n) = O(n)$ and $S(n) = O(n)$

3 ^ | v • Reply • Share ›



dipak → DarkProtocol • a month ago

preorder space used is $O(n)$...I am a bit confused can someone please

^ | v • Reply • Share ›



initialcoder • 11 months ago

```
#include<stdio.h>
```

```
#include<stdlib.h>
```

```
typedef struct NodeTag{
    char SYMBOL;
    struct NodeTag * LLINK;
    struct NodeTag * RLINK;
} TreeNode;
```

```
typedef enum{Preorder, Inorder, Postorder} OrderOfTraverse;
```

```
void visitNode(TreeNode * node){  
    if(node == NULL)  
        return;  
    printf("%c ", node->SYMBOL);  
}
```

```
void treeTraverse(TreeNode * treeRoot, OrderOfTraverse TraverseOrder){
```

see more

^ | v • Reply • Share ›



abhishek08aug • a year ago

Here is the C++ design/code for BST traversals. Recursive insert is bit tricky.

<http://stackoverflow.com/quest...>

```
#include<iostream>  
using namespace std;  
  
class tree_node {  
private:  
    int data;  
    tree_node * left;  
    tree_node * right;  
public:  
    tree_node() {  
        left=NULL;  
        right=NULL;  
    }  
    void set_data(int data) {  
        this->data=data;
```


see more

1 ^ | v • Reply • Share ›



abhishek08aug • a year ago

Here is the C++ design/code for BST traversals. Recursive insert is bit tricky.

<http://stackoverflow.com/quest...>

```
[sourcecode language="C++"]
```

```
#include<iostream>
```

```
using namespace std;
```

```
class tree_node {
```

```
private:
```

```
int data;
```

```
tree_node * left;
```

```
tree_node * right;
```

```
public:
```

```
tree_node() {
```

```
left=NULL;
```

```
right=NULL;
```

```
}
```

```
void set_data(int data) {
```

see more

^ | v • Reply • Share ›



Marsha Donna → abhishek08aug • 2 months ago

i hav written a simpler code to recursively insert in bst..but it gives erro

Runtime error time: 0 memory: 2288 signal:11

can some1 help me out the link is

<http://ideone.com/HVLJ1q>

• Reply • Share ›



Nikin · a year ago

```
void inorder(node *sr)
{
    if(sr == NULL)
        return;
    inorder(sr->left); cout<<sr->data<<" "; inorder(sr->right);
}
```

^ | v · Reply · Share ›



Deepak · 2 years ago

When inorder traversing a tree resulted E A C K F H D B G; the preorder traverse ... but how does it so..... can u explain it

^ | v · Reply · Share ›



Avinash · 2 years ago

Post order is the toughest out of all the tree traversals when solved iteratively.

```
//Post Order Traversal
public void printpostorder()
{
    Node current = Root;
    Node temp;
    if (current == null)
    {
        Console.WriteLine("Empty Tree");
        return;
    }
    else
    {
        Stack<Node> myStack = new Stack<Node>();
```

```
while (true)
{
    if (current !=null)
```

[see more](#)

^ | v • Reply • Share ›



Jacopo • 3 years ago

Your analysis is correct but you wronged the math. The last step is: $T(n) = nT$
Right?

^ | v • Reply • Share ›



raa • 3 years ago

but what about complexity in the following case:
if number of nodes in left and right sub trees are not zero and not equal.

^ | v • Reply • Share ›



kartik → raa • 3 years ago

For general cases, we can use substitution method given in CLRS book
 $O(n)$.

^ | v • Reply • Share ›



Algoseekar • 3 years ago

WHATS THE k in time complexity

$$T(n) = T(k) + T(n - k - 1) + c$$

Please reply asap

^ | v • Reply • Share ›



GeeksforGeeks → Algoseekar • 3 years ago

k is the number of nodes on one side of root and $n-k-1$ on the other side

^ | v • Reply • Share ›



devraj • 3 years ago

it could be better if the reason is mention here that why different types of travel

^ | v • Reply • Share ›



Venki • 4 years ago

There is a typo in the description "Uses of Postorder
Preorder traversal ... " Change postorder to preorder. Level order code is miss

1 ^ | v • Reply • Share ›



GeeksforGeeks → Venki • 4 years ago

@Venki: Thanks for pointing this out. we have corrected the typo. We l
(<http://geeksforgeeks.org/?p=26...> for Level Order Traversal

^ | v • Reply • Share ›



raa • 4 years ago

You are the one - giving the clear details with space complexity also - nice pos

^ | v • Reply • Share ›



Subscribe



Add Disqus to your site

