

## Search an element in a sorted and pivoted array

### Question:

An element in a sorted array can be found in  $O(\log n)$  time via binary search. But suppose I rotate the sorted array at some pivot unknown to you beforehand. So for instance, 1 2 3 4 5 might become 3 4 5 1 2. Devise a way to find an element in the rotated array in  $O(\log n)$  time.



### Solution:

Thanks to Ajay Mishra for initial solution.

### Algorithm:

Find the pivot point, divide the array in two sub-arrays and call binary search.

The main idea for finding pivot is – for a sorted (in increasing order) and pivoted array, pivot element is the only element for which next element to it is smaller than it.

Using above criteria and binary search methodology we can get pivot element in  $O(\log n)$  time

```
Input arr[] = {3, 4, 5, 1, 2}
```

```
Element to Search = 1
```

- 1) Find out pivot point and divide the array in two sub-arrays. (pivot = 2) /\*Index of 5\*/

Google™ Custom Search




GeeksforGeeks



53,521 people like GeeksforGeeks.



"LOG KYA KAHENGE"



Facebook

Interview Experiences

Advanced Data Structures

Dynamic Programming

Greedy Algorithms

Backtracking

Pattern Searching

Divide & Conquer

Mathematical Algorithms

Recursion

Geometric Algorithms

- 2) Now call binary search for one of the two sub-arrays.
  - (a) **If** element is greater than 0th element then  
search in left array
  - (b) **Else** Search in right array  
(1 will go in else as  $1 < 0$ th element(3))
- 3) **If** element is found in selected sub-array then return index  
**Else** return -1.

### Implementation:

```
/* Program to search an element in a sorted and pivoted array*/
#include <stdio.h>

int findPivot(int[], int, int);
int binarySearch(int[], int, int, int);

/* Searches an element no in a pivoted sorted array arrp[]
of size arr_size */
int pivotedBinarySearch(int arr[], int arr_size, int no)
{
    int pivot = findPivot(arr, 0, arr_size-1);

    // If we didn't find a pivot, then array is not rotated at all
    if (pivot == -1)
        return binarySearch(arr, 0, arr_size-1, no);

    // If we found a pivot, then first compare with pivot and then
    // search in two subarrays around pivot
    if (arr[pivot] == no)
        return pivot;
    if (arr[0] <= no)
        return binarySearch(arr, 0, pivot-1, no);
    else
        return binarySearch(arr, pivot+1, arr_size-1, no);
}

/* Function to get pivot. For array 3, 4, 5, 6, 1, 2 it will
return 3. If array is not rotated at all, then it returns -1 */
int findPivot(int arr[], int low, int high)
{
    // base cases
    if (high < low) return -1;
    if (high == low) return low;

    int mid = (low + high)/2; /*low + (high - low)/2;*/
```



### Popular Posts

- All permutations of a given string
- Memory Layout of C Programs
- Understanding "extern" keyword in C
- Median of two sorted arrays
- Tree traversal without recursion and without stack!
- Structure Member Alignment, Padding and Data Packing
- Intersection point of two Linked Lists
- Lowest Common Ancestor in a BST.
- Check if a binary tree is BST or not
- Sorted Linked List to Balanced BST

```

    if (mid < high && arr[mid] > arr[mid + 1])
        return mid;
    if (mid > low && arr[mid] < arr[mid - 1])
        return (mid-1);
    if (arr[low] >= arr[mid])
        return findPivot(arr, low, mid-1);
    else
        return findPivot(arr, mid + 1, high);
}

/* Standard Binary Search function*/
int binarySearch(int arr[], int low, int high, int no)
{
    if (high < low)
        return -1;
    int mid = (low + high)/2;  /*low + (high - low)/2;*/
    if (no == arr[mid])
        return mid;
    if (no > arr[mid])
        return binarySearch(arr, (mid + 1), high, no);
    else
        return binarySearch(arr, low, (mid -1), no);
}

/* Driver program to check above functions */
int main()
{
    // Let us search 3 in below array
    int arr1[] = {5, 6, 7, 8, 9, 10, 1, 2, 3};
    int arr_size = sizeof(arr1)/sizeof(arr1[0]);
    int no = 3;
    printf("Index of the element is %d\n", pivotedBinarySearch(arr1, a

    // Let us search 3 in below array
    int arr2[] = {3, 4, 5, 1, 2};
    arr_size = sizeof(arr2)/sizeof(arr2[0]);
    printf("Index of the element is %d\n", pivotedBinarySearch(arr2, a

    // Let us search for 4 in above array
    no = 4;
    printf("Index of the element is %d\n", pivotedBinarySearch(arr2, a

    // Let us search 0 in below array
    int arr3[] = {1, 1, 1, 0, 1, 1, 1, 1, 1, 1};
    no = 0;
    arr size = sizeof(arr3)/sizeof(arr3[0]);

```

# Deploy Early. Deploy Often.

DevOps from  
Rackspace:

## Automation

**FIND OUT HOW ►**





```

printf("Index of the element is %d\n", pivotedBinarySearch(arr3, a

// Let us search 3 in below array
int arr4[] = {2, 3, 0, 2, 2, 2, 2, 2, 2, 2};
no = 3;
arr_size = sizeof(arr4)/sizeof(arr4[0]);
printf("Index of the element is %d\n", pivotedBinarySearch(arr4, a

// Let us search 2 in above array
no = 2;
printf("Index of the element is %d\n", pivotedBinarySearch(arr4, a

// Let us search 3 in below array
int arr5[] = {1, 2, 3, 4};
no = 3;
arr_size = sizeof(arr5)/sizeof(arr5[0]);
printf("Index of the element is %d\n", pivotedBinarySearch(arr5, a

return 0;
}

```

Output:

```

Index of the element is 8
Index of the element is 0
Index of the element is 1
Index of the element is 3
Index of the element is 1
Index of the element is 0
Index of the element is 2

```

Please note that the solution may not work for cases where the input array has duplicates.

**Time Complexity**  $O(\log n)$

Please write comments if you find any bug in above codes/algorithms, or find other ways to solve the same problem.

## Recent Comments

**Aman** Hi, Why arent we checking for conditions...

Write a C program to Delete a Tree. · 22 minutes ago

kzs please provide solution for the problem...

Backtracking | Set 2 (Rat in a Maze) · 25 minutes ago

**Sanjay Agarwal** bool

tree::Root\_to\_leaf\_path\_given\_sum(tree...

Root to leaf path sum equal to a given number · 50 minutes ago

**GOPI GOPINATH** @admin Highlight this sentence "We can easily...

Count trailing zeroes in factorial of a number · 52 minutes ago


**newCoder3006** If the array contains negative numbers also. We...

Find subarray with given sum · 1 hour ago

**newCoder3006** Code without using while loop. We can do it...

Find subarray with given sum · 1 hour ago

AdChoices



- ▶ [C++ Array](#)
- ▶ [JavaScript Array](#)
- ▶ [Java Array](#)
- AdChoices ▶
- ▶ [C++ Code](#)
- ▶ [An Array](#)
- ▶ [Jquery Array](#)
- AdChoices ▶
- ▶ [Array Element](#)
- ▶ [Search Array](#)
- ▶ [Int in Array](#)

## Related Tpoics:

- Remove minimum elements from either side such that  $2 \times \text{min}$  becomes more than max
- Divide and Conquer | Set 6 (Search in a Row-wise and Column-wise Sorted 2D Array)
- Bucket Sort
- Kth smallest element in a row-wise and column-wise sorted 2D array | Set 1
- Find the number of zeroes
- Find if there is a subarray with 0 sum
- Divide and Conquer | Set 5 (Strassen's Matrix Multiplication)
- Count all possible groups of size 2 or 3 that have sum as multiple of 3



7



Tweet

0



0

Writing code in comment? Please use [ideone.com](https://ideone.com) and share the link here.

@geeksforgeeks, **Some rights reserved**

**Contact Us!**

Powered by **WordPress** & **MooTools**, customized by geeksforgeeks team