

MRI Image Quality Metrics (IQMs)

RadQy Project

December 7, 2025

Abstract

This document summarizes commonly used MRI image quality metrics (IQMs) and their mathematical definitions for reproducibility and reporting.

Contents

Introduction	1
1 Per-Slice IQMs (Foreground / Background pixels)	2
1.1 Mean (MEAN)	2
1.2 Range (RNG)	2
1.3 Variance (VAR)	2
1.4 Coefficient of Variation (CV)	2
1.5 Contrast per Pixel (CPP)	2
1.6 Peak Signal-to-Noise Ratio (PSNR)	2
1.7 SNR1	3
1.8 SNR2	3
1.9 SNR3	3
1.10 SNR4	3
1.11 Contrast-to-Noise Ratio (CNR)	3
1.12 Patch Coefficient of Variation (CVP)	3
1.13 Coefficient of Joint Variation (CJV)	3
1.14 Entropy Focus Criterion (EFC)	4
1.15 Foreground-Background Energy Ratio (FBER)	4
1.16 Skewness (SKW)	4
1.17 Excess Kurtosis (KURT)	4
2 Participant-Level QC	4
2.1 Failure Count (FAIL_FRAC)	4
References	4

Introduction

This document summarizes commonly used MRI image quality metrics (IQMs) and their mathematical definitions for reproducibility and reporting.

1 Per-Slice IQMs (Foreground / Background pixels)

All metrics below accept foreground pixels **F** (from segmentation) and background pixels **B**. NaN/Inf inputs yield NaN. For BG-dependent metrics (SNR1, SNR2, SNR4, CNR, CJV, FBER), if background is missing or unusable (empty, zero variance, non-finite), we fall back to foreground homogeneity μ_F/σ_F to avoid artificial NaNs.

1.1 Mean (MEAN)

Foreground mean intensity:

$$\text{MEAN} = \mu_F = \frac{1}{N_F} \sum_i F_i$$

1.2 Range (RNG)

Foreground intensity range:

$$\text{RNG} = \max(F) - \min(F)$$

1.3 Variance (VAR)

Foreground variance:

$$\text{VAR} = \sigma_F^2 = \frac{1}{N_F} \sum_i (F_i - \mu_F)^2$$

1.4 Coefficient of Variation (CV)

Foreground coefficient of variation (percent):

$$\text{CV} = \frac{\sigma_F}{\mu_F} \times 100$$

1.5 Contrast per Pixel (CPP)

Laplacian-filtered contrast, mean response of a 3×3 Laplacian:

$$f_1 = \frac{1}{8} \begin{bmatrix} -1 & -1 & -1 \\ -1 & 8 & -1 \\ -1 & -1 & -1 \end{bmatrix}, \quad \text{CPP} = \text{mean}(f_1 * F)$$

where $*$ is 2D convolution (foreground is median-filtered only when used for PSNR below).

1.6 Peak Signal-to-Noise Ratio (PSNR)

$$\text{PSNR} = 10 \log_{10} \left(\frac{\max(F)^2}{\text{MSE}(F, \hat{F})} \right)$$

where $\hat{F}$ is either the background **B** (if provided) or a median-filtered version of **F**.

1.7 SNR1

Foreground/background std; fallback to foreground stability if background unusable [1], [2]:

$$\text{SNR1} = \begin{cases} \frac{\sigma_F}{\sigma_B}, & \sigma_B \text{ finite and } \sigma_B \neq 0 \\ \frac{\mu_F}{\sigma_F}, & \text{otherwise (fg homogeneity)} \end{cases}$$

1.8 SNR2

Foreground mean over background std; fallback to foreground stability if background unusable:

$$\text{SNR2} = \begin{cases} \frac{\mu_F}{\sigma_B}, & \sigma_B \text{ finite and } \sigma_B \neq 0 \\ \frac{\mu_F}{\sigma_F}, & \text{otherwise} \end{cases}$$

1.9 SNR3

Foreground standard deviation divided by centered-foreground standard deviation (stability check):

$$\text{SNR3} = \frac{\sigma_F}{\sigma_{F-\mu_F}}$$

1.10 SNR4

Foreground mean over background mean; fallback to foreground stability if background unusable:

$$\text{SNR4} = \begin{cases} \frac{\mu_F}{\mu_B}, & \mu_B \text{ finite and } \mu_B \neq 0 \\ \frac{\mu_F}{\sigma_F}, & \text{otherwise} \end{cases}$$

1.11 Contrast-to-Noise Ratio (CNR)

Foreground/background mean difference over background std; fallback to foreground stability if background unusable:

$$\text{CNR} = \begin{cases} \frac{\mu_F - \mu_B}{\sigma_B}, & \sigma_B \text{ finite and } \sigma_B \neq 0 \\ \frac{\mu_F}{\sigma_F}, & \text{otherwise} \end{cases}$$

1.12 Patch Coefficient of Variation (CVP)

Foreground patch coefficient of variation:

$$\text{CVP} = \frac{\sigma_F}{\mu_F}$$

1.13 Coefficient of Joint Variation (CJV)

Joint variation between foreground and background; fallback to foreground stability if background unusable:

$$\text{CJV} = \begin{cases} \frac{\sigma_F + \sigma_B}{|\mu_F - \mu_B|}, & \text{finite and } |\mu_F - \mu_B| \neq 0 \\ \frac{\mu_F}{\sigma_F}, & \text{otherwise} \end{cases}$$

1.14 Entropy Focus Criterion (EFC)

Normalized Shannon entropy of foreground:

$$p_i = \frac{F_i}{\sqrt{\sum_j F_j^2}}, \quad \text{EFC} = -\frac{1}{\log N_F} \sum_i p_i \log p_i$$

higher values suggest more ghosting/noise.

1.15 Foreground-Background Energy Ratio (FBER)

Median energy ratio; fallback to foreground stability if background unusable:

$$\text{FBER} = \begin{cases} \frac{\text{median}(F^2)}{\text{median}(B^2)}, & \text{finite and median}(B^2) \neq 0 \\ \frac{\mu_F}{\sigma_F}, & \text{otherwise} \end{cases}$$

1.16 Skewness (SKW)

Foreground skewness (third standardized moment):

$$\text{SKW} = \frac{\frac{1}{N_F} \sum_i (F_i - \mu_F)^3}{\sigma_F^3}$$

1.17 Excess Kurtosis (KURT)

Foreground excess kurtosis (fourth standardized moment minus 3):

$$\text{KURT} = \frac{\frac{1}{N_F} \sum_i (F_i - \mu_F)^4}{\sigma_F^4} - 3$$

2 Participant-Level QC

2.1 Failure Count (FAIL_FRAC)

Counts total non-finite IQM evaluations (NaN/Inf) across all slices/metrics for a participant. Higher counts flag poor FG/BG segmentation or corrupted slices:

$$\text{FAIL_FRAC} = \sum_{s \in \text{slices}} \sum_{m \in \text{IQMs}} \mathbf{1}\{\text{IQM}_{m,s} \text{ is non-finite}\}$$

References

- [1] Amir Reza Sadri et al. “MRQy—An open-source tool for quality control of MR imaging data”. In: *Medical physics* 47.12 (2020), pp. 6029–6038.
- [2] Rafsanjany Kushol et al. “DSMRI: domain shift analyzer for multi-center MRI datasets”. In: *Diagnostics* 13.18 (2023), p. 2947.