

MRI Foreground/Background Detection

Amir R. Sadri
ars329@case.edu
December 9, 2025

Abstract

This note outlines how we derive foreground and background masks for MRI volumes in RadQy. Each section documents one detection method, its assumptions, and the clean-up steps needed so FG/BG pixels are reproducible across datasets. salami ch

Contents

1	Introduction	2
2	Image Processing Segmenters	2
2.1	OtsuHull (OtsuHull.py)	2
2.2	Adaptive Border Segmentation (AdaptiveBorderSeg.py)	2
2.3	Hybrid Otsu + Convex Hull (HybridOtsuHullSeg.py)	3
3	Deep Learning Segmenters	3
3.1	U-Net (placeholder)	3
4	Notes for Integration	3
	References	3

1 Introduction

This document lists the foreground/background (FG/BG) segmentation methods in `backend/seg/mri`. Each section mirrors a Python module and notes its inputs, thresholds, morphology, and fallbacks so downstream IQMs get consistent masks.

2 Image Processing Segmenters

Classical pipelines based on intensity statistics and morphology.

2.1 OtsuHull (`OtsuHull.py`)

Legacy variant mirroring the original hybrid Otsu pipeline with more defensive fallbacks [1]. This subsection is listed first because it matches the earliest implementation shipped with RadQy.

Algorithm 1: OtsuHull foreground/background estimation

1. Input slice I ; cast to uint16.
2. Histogram-equalize I to get H .
3. Otsu on I and H to obtain masks m_1, m_2 and FG fractions w_1, w_2 .
4. Hybrid recombination: $S = w_1 \cdot I + w_2 \cdot H$ (normalize to image range).
5. Otsu on S to get final mask M .
6. Cleanup: convex hull of M (fallback to hole filling if hull fails).
7. Outputs: $fg = M, bg = 1 - M$.

Notes on the weights and masks: m_1 is the Otsu mask on the raw slice I , m_2 is the Otsu mask on the hist-equalized slice H . The weights $w_1 = |m_1|/|I|$ and $w_2 = |m_2|/|I|$ measure how much of each slice is classified as foreground; they scale the raw and equalized images when forming $S = w_1 \cdot I + w_2 \cdot H$ so that the cleaner mask (smaller foreground fraction) influences the recombined image more.

2.2 Adaptive Border Segmentation (`AdaptiveBorderSeg.py`)

Single-slice segmenter that estimates background from the image border and keeps the largest non-background component.

Algorithm 2: AdaptiveBorder foreground/background estimation

1. Normalize input slice to uint8 via 1st/99th percentile scaling.
2. Extract border ring (default 12 px each side); compute μ, σ on non-zero border pixels (fallback: full image if border empty).
3. Mark background where $I < \mu - 1\sigma$.
4. Morphology: binary closing then opening with 5×5 kernel; fill holes.
5. Foreground = inverse of background; keep largest connected component.
6. Safety: if FG area $< 5\%$, set FG to all-ones (entire slice).

7. Outputs: (fg, bg) with $bg = 1 - fg$.

2.3 Hybrid Otsu + Convex Hull (HybridOtsuHullSeg.py)

Modern hybrid approach combining Otsu on raw and histogram-equalized images with convex hull cleanup.

Algorithm 3: Hybrid Otsu + Convex Hull

1. Robust-scale input slice to $[0, 1]$ via 1st/99th percentiles; cast to uint8 for thresholding.
2. Compute Otsu masks on raw (x) and hist-equalized (h) images to get FG fractions w_1, w_2 .
3. Recombine: $S = w_1 \cdot x + w_2 \cdot h$.
4. Otsu on S to obtain mask M .
5. Cleanup: apply convex hull to M (fallback: hole filling if hull unavailable).
6. Outputs: (fg, bg) with $fg = M$, $bg = 1 - fg$.

3 Deep Learning Segmenters

Learned models for FG/BG inference.

3.1 U-Net (placeholder)

Planned slot for the learned U-Net FG/BG mask generator.

Algorithm 4: U-Net inference pipeline (placeholder)

1. Preprocess: normalize/standardize input slice to network expectations.
2. Forward pass through U-Net to obtain probability map P .
3. Threshold P (e.g., at 0.5) to get binary mask M .
4. Post-process: optional hole filling, small-component removal, and convex hull if needed.
5. Outputs: (fg, bg) with $fg = M$, $bg = 1 - fg$.

4 Notes for Integration

All segmenters operate per 2D slice and return uint8 masks in $\{0, 1\}$. Background is always defined as the complement of foreground to ensure downstream IQMs receive matching shapes and disjoint FG/BG sets.

References

- [1] Amir Reza Sadri et al. “MRQy: An open-source tool for the quality control of structural MRI images”. In: *Journal of Imaging* 6.1 (2020). Placeholder entry; replace with canonical citation if available, pp. 1–15.