


There were issues affecting this run of Lighthouse:

- Chrome extensions negatively affected this page's load performance. Try auditing the page in incognito mode or from a Chrome profile without extensions.
- There may be stored data affecting loading performance in this location: IndexedDB. Audit this page in an incognito window to prevent those resources from affecting your scores.
- The page loaded too slowly to finish within the time limit. Results may be incomplete.



Performance

Values are estimated and may vary. The [performance score is calculated](#) directly from these metrics. [See calculator.](#)



▲ 0–49 ■ 50–89 ● 90–100

METRICS

Expand view


▲ First Contentful Paint
9.1 s

▲ Largest Contentful Paint
14.1 s

● Total Blocking Time
0 ms

● Cumulative Layout Shift
0

▲ Speed Index
9.1 s



Show audits relevant to: All FCP LCP TBT CLS

INSIGHTS

▲ Render-blocking requests — Est savings of 150 ms

Requests are blocking the page's initial render, which may delay LCP. [Deferring or inlining](#) can move these network requests out of the critical path. FCP LCP Unscored

☒ Show 3rd-party resources (2)

URL	Transfer Size	Duration
Unpkg Cdn	0.0 KiB	850 ms
...dist/aos.css (unpkg.com)	0.0 KiB	850 ms
Cloudflare CDN Cdn	0.0 KiB	840 ms
...css/all.min.css (cdnjs.cloudflare.com)	0.0 KiB	840 ms

URL	Transfer Size	Duration
vitabletech.in 1st Party	0.0 KiB	320 ms
/css/main.css (vitabletech.in)	0.0 KiB	320 ms

▲ Font display — Est savings of 110 ms

Consider setting [font-display](#) to swap or optional to ensure text is consistently visible. swap can be further optimized to mitigate layout shifts with [font metric overrides](#). FCP Unscored

URL	Est Savings
Cloudflare CDN Cdn	
...webfonts/fa-brands-400.woff2 (cdnjs.cloudflare.com)	110 ms
...webfonts/fa-solid-900.woff2 (cdnjs.cloudflare.com)	110 ms
Google Fonts Cdn	
...v48/KFO7CnqEu....woff2 (fonts.gstatic.com)	80 ms


▲ Network dependency tree

Warnings: More than 4 `preconnect` connections were found. These should be used sparingly and only to the most important origins.

[Avoid chaining critical requests](#) by reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load. LCP Unscored

Maximum critical path latency: **453 ms**

Initial Navigation



Preconnected origins

[preconnect](#) hints help the browser establish a connection earlier in the page load, saving time when the first request for that origin is made. The following are the origins that the page preconnected to.

Origin	Source
https://cdnjs.cloudflare.com/	
https://fonts.googleapis.com/	
Unused preconnect. Only use `preconnect` for origins that the page is likely to request.	
https://i.ytimg.com/	div.md:w-1/2.mb-10.md:mb-0
https://cdnjs.cloudflare.com/	link
https://fonts.googleapis.com/	link
Unused preconnect. Only use `preconnect` for origins that the page is likely to request.	

Origin

Source

https://i.ytimg.com/

ul.space-y-2

Preconnect candidates

Add [preconnect](#) hints to your most important origins, but try to use no more than 4.

No additional origins are good candidates for preconnecting

■ Use efficient cache lifetimes — Est savings of 10 KiB

^

A long cache lifetime can speed up repeat visits to your page. [Learn more about caching.](#)

FCP

LCP

Unscored

☒ Show 3rd-party resources (3)

Request	Cache TTL	Transfer Size
vitabletech.in 1st Party		11 KiB
...8fc8ed1d8752/main.js (vitabletech.in)	4h	11 KiB
...cloudflare-static/rocket-loader.min.js (vitabletech.in)	1d 23h 59m 11s	0 KiB
YouTube Video		3 KiB
...LfzYfziR4yQ/default.jpg?sqp=-oaymwEkC...&rs=AO4CLAZF... (i.ytimg.com)	2h	3 KiB
Google/DoubleClick Ads Ad		0 KiB
/instream/ad_status.js (static.doubleclick.net)	15m	0 KiB
Cloudflare Utility		0 KiB

Request	Cache TTL	Transfer Size
/beacon.min.js/v833ccba... (static.cloudflareinsights.com)	1d	0 KiB

LCP breakdown

Each [subpart has specific improvement strategies](#). Ideally, most of the LCP time should be spent on loading the resources, not within delays. LCP Unscored

Subpart	Duration
Time to first byte	170 ms
Element render delay	170 ms

p.text-lg.md:text-xl.mb-8.opacity-90

3rd parties

3rd party code can significantly impact load performance. [Reduce and defer loading of 3rd party code](#) to prioritize your page's content. Unscored

3rd party	Transfer size	Main thread time
nngceckbapebfimlniiahkandclblb	0 KiB	47 ms
chrome-extension://nngceckbapebfimlniiahkandclblb/content/bootstrap-autofill-overlay.js	0 KiB	42 ms
chrome-extension://nngceckbapebfimlniiahkandclblb/content/content-message-handler.js	0 KiB	2 ms
chrome-extension://nngceckbapebfimlniiahkandclblb/content/fido2-content-script.js	0 KiB	1 ms

3rd party	Transfer size	Main thread time
chrome-extension://nngceckbapebfimlniiiahkandclblb/content/fido2-page-script.js	0 KiB	1 ms
chrome-extension://nngceckbapebfimlniiiahkandclblb/content/contextMenuHandler.js	0 KiB	0 ms
chrome-extension://nngceckbapebfimlniiiahkandclblb/content/trigger-autofill-script-injection.js	0 KiB	0 ms
gighmmpiobklfepjocnamgkkgbiglidom	0 KiB	33 ms
chrome-extension://gighmmpiobklfepjocnamgkkgbiglidom/vendor/@eyeo/webext-ad-filtering-solution/content.js	0 KiB	12 ms
chrome-extension://gighmmpiobklfepjocnamgkkgbiglidom/globals-front.js	0 KiB	9 ms
chrome-extension://gighmmpiobklfepjocnamgkkgbiglidom/vendor/@eyeo/webext-ad-filtering-solution/content-main.js	0 KiB	6 ms
chrome-extension://gighmmpiobklfepjocnamgkkgbiglidom/polyfill.js	0 KiB	3 ms
chrome-extension://gighmmpiobklfepjocnamgkkgbiglidom/adblock-picreplacement.js	0 KiB	1 ms
chrome-extension://gighmmpiobklfepjocnamgkkgbiglidom/adblock-functions.js	0 KiB	1 ms
chrome-extension://gighmmpiobklfepjocnamgkkgbiglidom/cookie-banner-detection.preload.js	0 KiB	1 ms
chrome-extension://gighmmpiobklfepjocnamgkkgbiglidom/premium.preload.js	0 KiB	0 ms
chrome-extension://gighmmpiobklfepjocnamgkkgbiglidom/contentscript-loader.js	0 KiB	0 ms
chrome-extension://gighmmpiobklfepjocnamgkkgbiglidom/ext/content.js	0 KiB	0 ms
chrome-extension://gighmmpiobklfepjocnamgkkgbiglidom/ext/common.js	0 KiB	0 ms
chrome-extension://gighmmpiobklfepjocnamgkkgbiglidom/adblock-uiscrpts-rightclick_hook.js	0 KiB	0 ms
bnjjngeaknajbdcgpfkgnonkmififhfo	0 KiB	20 ms

3rd party	Transfer size	Main thread time
chrome-extension://bnjjngeaknajbdcgpfkgnonkmififhfo/src/content-script.js	0 KiB	20 ms
Cloudflare CDN Cdn	941 KiB	9 ms
...r128/three.min.js (cdnjs.cloudflare.com)	589 KiB	9 ms
...webfonts/fa-solid-900.woff2 (cdnjs.cloudflare.com)	147 KiB	0 ms
...webfonts/fa-brands-400.woff2 (cdnjs.cloudflare.com)	105 KiB	0 ms
...css/all.min.css (cdnjs.cloudflare.com)	100 KiB	0 ms
nmigaijibiabddkkmjhlehchpmgbokfj	0 KiB	5 ms
chrome-extension://nmigaijibiabddkkmjhlehchpmgbokfj/js/libs/jquery.min.js	0 KiB	4 ms
chrome-extension://nmigaijibiabddkkmjhlehchpmgbokfj/js/content.js	0 KiB	1 ms
mpiodijhokgodhhofbcjdecpfjipkle	0 KiB	5 ms
chrome-extension://mpiodijhokgodhhofbcjdecpfjipkle/lib/single-file-frames.bundle.js	0 KiB	2 ms
chrome-extension://mpiodijhokgodhhofbcjdecpfjipkle/lib/single-file-bootstrap.bundle.js	0 KiB	2 ms
chrome-extension://mpiodijhokgodhhofbcjdecpfjipkle/lib/single-file-hooks-frames.js	0 KiB	1 ms
Cloudflare Utility	32 KiB	1 ms
/beacon.min.js/v833ccba... (static.cloudflareinsights.com)	32 KiB	1 ms
Unpkg Cdn	39 KiB	1 ms
...dist/aos.js (unpkg.com)	14 KiB	1 ms
...dist/aos.css (unpkg.com)	25 KiB	0 ms

These insights are also available in the Chrome DevTools Performance Panel - [record a trace](#) to view more detailed information.

DIAGNOSTICS

▲ Reduce unused JavaScript — Est savings of 668 KiB

Reduce unused JavaScript and defer loading scripts until they are required to decrease bytes consumed by network activity. [Learn how to reduce unused JavaScript.](#) FCP LCP Unscored

☒ Show 3rd-party resources (1)

URL	Transfer Size	Est Savings
Unattributable	968.0 KiB	599.0 KiB
chrome-extension://nngceckbapebfimlniiahkandclblb/content/bootstrap-autofill-overlay.js	530.5 KiB	330.9 KiB
chrome-extension://bnjjngeaknajbdcgpfkgnonkmifihfo/src/content-script.js	155.0 KiB	96.0 KiB
chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/vendor/@eyeo/webext-ad-filtering-solution/content-main.js	37.2 KiB	33.2 KiB
chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/vendor/@eyeo/webext-ad-filtering-solution/content-main.js	37.2 KiB	33.2 KiB
chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/globals-front.js	66.2 KiB	32.7 KiB
chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/globals-front.js	66.2 KiB	32.7 KiB
chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/vendor/@eyeo/webext-ad-filtering-solution/content.js	37.9 KiB	20.4 KiB

URL	Transfer Size	Est Savings
chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/vendor/@eyeo/webext-ad-filtering-solution/content.js	37.9 KiB	20.0 KiB
Cloudflare CDN Cdn	118.1 KiB	68.5 KiB
...r128/three.min.js (cdnjs.cloudflare.com)	118.1 KiB	68.5 KiB

Image elements do not have explicit `width` and `height`

Set an explicit width and height on image elements to reduce layout shifts and improve CLS. [Learn how to set image dimensions](#) CLS Unscored

URL
img
img
img
img
img

Minify JavaScript — Est savings of 337 KiB

Minifying JavaScript files can reduce payload sizes and script parse time. [Learn how to minify JavaScript](#). FCP LCP Unscored

URL	Transfer Size	Est Savings
chrome-extension://nngceckbapebfimnlndiihahkandclblb/content/bootstrap-autofill-overlay.js	530.5 KiB	187.7 KiB
chrome-extension://bnjjngeaknajbdcgpfkgnonkmififhfo/src/content-script.js	155.0 KiB	33.3 KiB
chrome-extension://gighmmpiobklfepjocnamgkkgbiglidom/globals-front.js	66.2 KiB	29.3 KiB
chrome-extension://gighmmpiobklfepjocnamgkkgbiglidom/globals-front.js	66.2 KiB	29.3 KiB
chrome-extension://gighmmpiobklfepjocnamgkkgbiglidom/polyfill.js	10.6 KiB	5.7 KiB
chrome-extension://gighmmpiobklfepjocnamgkkgbiglidom/polyfill.js	10.6 KiB	5.7 KiB
chrome-extension://gighmmpiobklfepjocnamgkkgbiglidom/polyfill.js	10.6 KiB	5.7 KiB
chrome-extension://gighmmpiobklfepjocnamgkkgbiglidom/vendor/@eyeo/webext-ad-filtering-solution/content-main.js	37.2 KiB	5.7 KiB
chrome-extension://gighmmpiobklfepjocnamgkkgbiglidom/vendor/@eyeo/webext-ad-filtering-solution/content-main.js	37.2 KiB	5.7 KiB
chrome-extension://gighmmpiobklfepjocnamgkkgbiglidom/cookie-banner-detection.preload.js	10.0 KiB	5.3 KiB
chrome-extension://nngceckbapebfimnlndiihahkandclblb/content/fido2-content-script.js	12.4 KiB	5.3 KiB
chrome-extension://nngceckbapebfimnlndiihahkandclblb/content/fido2-page-script.js	9.8 KiB	4.0 KiB

URL	Transfer Size	Est Savings
chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/adblock-picreplacement.js	9.1 KiB	3.8 KiB
chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/adblock-picreplacement.js	9.1 KiB	3.8 KiB
chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/adblock-functions.js	6.9 KiB	3.2 KiB
chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/adblock-functions.js	6.9 KiB	3.2 KiB

■ Avoid enormous network payloads — Total size was 2,882 KiB

Large network payloads cost users real money and are highly correlated with long load times. [Learn how to reduce payload sizes.](#) Unscored

☒ Show 3rd-party resources (9)

URL	Transfer Size
YouTube Video	1,561.2 KiB
...en_GB/base.js (www.youtube.com)	444.1 KiB
...en_GB/base.js (www.youtube.com)	444.1 KiB
...rs=AGKMywGsD.../m=r78Drb (www.youtube.com)	196.1 KiB
...rs=AGKMywGsD.../m=r78Drb (www.youtube.com)	196.0 KiB
...rs=AGKMywGsD.../m=root,base (www.youtube.com)	140.4 KiB

URL	Transfer Size
...rs=AGKMywGsD.../m=root,base (www.youtube.com)	140.4 KiB
Cloudflare CDN Cdn	372.0 KiB
...webfonts/fa-solid-900.woff2 (cdnjs.cloudflare.com)	147.3 KiB
...r128/three.min.js (cdnjs.cloudflare.com)	118.7 KiB
...webfonts/fa-brands-400.woff2 (cdnjs.cloudflare.com)	106.1 KiB
vitabletech.in 1st Party	284.9 KiB
/icons-vitabletech/favicon.svg (vitabletech.in)	284.9 KiB

Reduce JavaScript execution time — 3.2 s

Consider reducing the time spent parsing, compiling, and executing JS. You may find delivering smaller JS payloads helps with this. [Learn how to reduce Javascript execution time.](#) TBT Unscored

☒ Show 3rd-party resources (1)

URL	Total CPU Time	Script Evaluation	Script Parse
vitabletech.in 1st Party	6,439 ms	2,266 ms	240 ms
/js/3d-hero.js (vitabletech.in)	4,789 ms	1,864 ms	1 ms
https://vitabletech.in	1,170 ms	94 ms	137 ms

URL	Total CPU Time	Script Evaluation	Script Parse
...cloudflare-static/rocket-loader.min.js (vitabletech.in)	314 ms	244 ms	8 ms
/js/custom_script.js (vitabletech.in)	167 ms	63 ms	95 ms
Unattributable	2,634 ms	255 ms	329 ms
Unattributable	2,028 ms	10 ms	0 ms
chrome-extension://nngceckbapebfimnlndiihahkandclblb/content/bootstrap-autofill-overlay.js	364 ms	116 ms	240 ms
chrome-extension://bnjjngeaknajbdcgpfkgnonkmifihfo/src/content-script.js	242 ms	129 ms	89 ms
Cloudflare CDN Cdn	76 ms	17 ms	58 ms
...r128/three.min.js (cdnjs.cloudflare.com)	76 ms	17 ms	58 ms

Minimize main-thread work — 9.3 s ^

Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. [Learn how to minimize main-thread work](#) TBT Unscored

Category	Time Spent
Other	3,892 ms

Category	Time Spent
Script Evaluation	2,664 ms
Rendering	1,099 ms
Style & Layout	790 ms
Script Parsing & Compilation	665 ms
Garbage Collection	181 ms
Parse HTML & CSS	54 ms

Avoid non-composited animations — 3 animated elements found

Animations which are not composited can be janky and increase CLS. [Learn how to avoid non-composited animations](#)

CLSUnscored

Element	Name
a.flex.flex-col.items-center.hover:text-primary.active:scale-90.transition-all.duration-300.touch...	
Unsupported CSS Property: color	color
span.text-[10px].font-semibold.mt-1.transition-colors.nav-text	
Unsupported CSS Property: color	color
Unsupported CSS Property: color	color
div.relative.w-12.h-8.flex.items-center.justify-center.rounded-full.transition-colors.icon-contain...	

Element

Unsupported CSS Property: color

Name

color

Avoid long main-thread tasks

— 13 long tasks found

Lists the longest tasks on the main thread, useful for identifying worst contributors to input delay. [Learn how to avoid long main-thread tasks](#)

TBT

Unscored

Show 3rd-party resources (1)

URL	Start Time	Duration
Unattributable		710 ms
chrome-extension://nngceckbapebfimnlndiihahkandclblb/content/bootstrap-autofill-overlay.js	1,269 ms	159 ms
chrome-extension://nngceckbapebfimnlndiihahkandclblb/content/bootstrap-autofill-overlay.js	1,896 ms	158 ms
Unattributable	2,139 ms	120 ms
Unattributable	1,068 ms	97 ms
chrome-extension://bnjjngeaknajbdcgpfkgnonkmififhfo/src/content-script.js	1,455 ms	63 ms
Unattributable	1,696 ms	61 ms
chrome-extension://bnjjngeaknajbdcgpfkgnonkmififhfo/src/content-script.js	2,054 ms	52 ms
vitaletech.in 1st Party		415 ms

about:blank

16/45

URL	Start Time	Duration
https://vitabletech.in	1,165 ms	104 ms
https://vitabletech.in	1,802 ms	94 ms
/js/custom_script.js (vitabletech.in)	3,021 ms	85 ms
/js/custom_script.js (vitabletech.in)	1,518 ms	80 ms
https://vitabletech.in	5,027 ms	52 ms
Unpkg Cdn		60 ms
...dist/aos.js (unpkg.com)	1,598 ms	60 ms

More information about the performance of your application. These numbers don't [directly affect](#) the Performance score.

PASSED AUDITS (15)

Hide

● Layout shift culprits

Layout shifts occur when elements move absent any user interaction. [Investigate the causes of layout shifts](#), such as elements being added, removed, or their fonts changing as the page loads. CLS Unscored

● Document request latency

Your first network request is the most important. [Reduce its latency](#) by avoiding redirects, ensuring a fast server response, and enabling text compression. FCP LCP Unscored

✓

- ✔ Avoids redirects
- ✔ Server responds quickly (observed 166 ms)
- ✔ Applies text compression

● Optimize DOM size ^

A large DOM can increase the duration of style calculations and layout reflows, impacting page responsiveness. A large DOM will also increase memory usage. [Learn how to avoid an excessive DOM size.](#) Unscored

Statistic	Element	Value
Total elements		763
DOM depth	i.fas.fa-check.text-green-600.text-xs	10
Most children	body.font-sans.text-gray-800.bg-gray-50.overflow-x-hidden	34

● Duplicated JavaScript ^

Remove large, [duplicate JavaScript modules](#) from bundles to reduce unnecessary bytes consumed by network activity. FCP LCP Unscored

● Forced reflow ^

A forced reflow occurs when JavaScript queries geometric properties (such as `offsetWidth`) after styles have been invalidated by a change to the DOM state. This can result in poor performance. Learn more about [forced reflows](#) and possible mitigations. Unscored

● Improve image delivery ^

Reducing the download time of images can improve the perceived load time of the page and LCP. [Learn more about optimizing image size](#) FCP LCP Unscored

INP breakdown
Start investigating how to improve INP by looking at the longest subpart. Unscored
LCP request discovery
Optimize LCP by making the LCP image discoverable from the HTML immediately, and avoiding lazy-loading Unscored
Legacy JavaScript
Polyfills and transforms enable older browsers to use new JavaScript features. However, many aren't necessary for modern browsers. Consider modifying your JavaScript build process to not transpile Baseline features, unless you know you must support older browsers. Learn why most sites can deploy ES6+ code without transpiling FCP LCP Unscored
Modern HTTP
HTTP/2 and HTTP/3 offer many benefits over HTTP/1.1, such as multiplexing. Learn more about using modern HTTP. FCP LCP Unscored
Optimize viewport for mobile
Tap interactions may be delayed by up to 300 ms if the viewport is not optimized for mobile. Unscored meta
Minify CSS
Minifying CSS files can reduce network payload sizes. Learn how to minify CSS. FCP LCP Unscored

Reduce unused CSS
Reduce unused rules from stylesheets and defer CSS not used for above-the-fold content to decrease bytes consumed by network activity. Learn how to reduce unused CSS. FCP LCP Unscored
User Timing marks and measures
Consider instrumenting your app with the User Timing API to measure your app's real-world performance during key user experiences. Learn more about User Timing marks. Unscored
Page didn't prevent back/forward cache restoration
Many navigations are performed by going back to a previous page, or forwards again. The back/forward cache (bfcache) can speed up these return navigations. Learn more about the bfcache Unscored



Accessibility

These checks highlight opportunities to [improve the accessibility of your web app](#). Automatic detection can only detect a subset of issues and does not guarantee the accessibility of your web app, so [manual testing](#) is also encouraged.

NAMES AND LABELS

Buttons do not have an accessible name
When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for

users who rely on screen readers. [Learn how to make buttons more accessible.](#)

Failing Elements

button#mobile-menu-button.text-gray-700.hover:text-primary.focus:outline-none

▲ Links do not have a discernible name



Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the navigation experience for screen reader users. [Learn how to make links accessible.](#)

Failing Elements

a.absolute.inset-0.z-10

a.absolute.inset-0.z-10

a.absolute.inset-0.z-10

a.absolute.inset-0.z-10

a.absolute.inset-0.z-10

a.absolute.inset-0.z-10

a.absolute.inset-0.z-10

a.absolute.inset-0.z-10

a.absolute.inset-0.z-10

Failing Elements

a.absolute.inset-0.z-10

a.absolute.inset-0.z-10

a.absolute.inset-0.z-10

a.text-gray-300.hover:text-white.transition-colors.text-xl

a.text-gray-300.hover:text-white.transition-colors.text-xl

a.text-gray-300.hover:text-white.transition-colors.text-xl

a.text-gray-300.hover:text-white.transition-colors.text-xl

a.text-gray-300.hover:text-white.transition-colors.text-xl

These are opportunities to improve the semantics of the controls in your application. This may enhance the experience for users of assistive technology, like a screen reader.

BEST PRACTICES



`[user-scalable="no"]` is used in the `<meta name="viewport">` element or the `[maximum-scale]` attribute is less than 5.



Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. [Learn more about the viewport meta tag.](#)

Failing Elements

meta

▲ Document does not have a main landmark.

One main landmark helps screen reader users navigate a web page. [Learn more about landmarks.](#)

Failing Elements

html

○ Identical links have the same purpose.

Links with the same destination should have the same description, to help users understand the link's purpose and decide whether to follow it. [Learn more about identical links.](#) Unscored

Failing Elements

a.hover:text-white.transition-colors

a.hover:text-white.transition-colors

These items highlight common accessibility best practices.

CONTRAST

▲ Background and foreground colors do not have a sufficient contrast ratio.

Low-contrast text is difficult or impossible for many users to read. [Learn how to provide sufficient color contrast.](#)

Failing Elements

button.text-xs.text-gray-500.hover:text-white.transition-colors.underline.cursor-pointer

footer.bg-secondary-dark.text-white.py-12

These are opportunities to improve the legibility of your content.

ADDITIONAL ITEMS TO MANUALLY CHECK (10)

Hide

☐ Interactive controls are keyboard focusable



Custom interactive controls are keyboard focusable and display a focus indicator. [Learn how to make custom controls focusable.](#) Unscored

☐ Interactive elements indicate their purpose and state



Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. [Learn how to decorate interactive elements with affordance hints.](#) Unscored

☐ The page has a logical tab order



Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. [Learn more about logical tab ordering.](#) Unscored

☐ Visual order on the page follows DOM order



DOM order matches the visual order, improving navigation for assistive technology. [Learn more about DOM and visual ordering.](#) Unscored

☐ User focus is not accidentally trapped in a region	^
A user can tab into and out of any control or region without accidentally trapping their focus. Learn how to avoid focus traps. Unscored	
☐ The user's focus is directed to new content added to the page	^
If new content, such as a dialog, is added to the page, the user's focus is directed to it. Learn how to direct focus to new content. Unscored	
☐ HTML5 landmark elements are used to improve navigation	^
Landmark elements (<main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technology. Learn more about landmark elements. Unscored	
☐ Offscreen content is hidden from assistive technology	^
Offscreen content is hidden with display: none or aria-hidden=true. Learn how to properly hide offscreen content. Unscored	
☐ Custom controls have associated labels	^
Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. Learn more about custom controls and labels. Unscored	
☐ Custom controls have ARIA roles	^
Custom interactive controls have appropriate ARIA roles. Learn how to add roles to custom controls. Unscored	

These items address areas which an automated testing tool cannot cover. Learn more in our guide on [conducting an accessibility review](#).

PASSED AUDITS (10)

Hide

 [aria-hidden="true"] is not present on the document <body>	^
Assistive technologies, like screen readers, work inconsistently when aria-hidden="true" is set on the document <body>. Learn how aria-hidden affects the document body.	
 Image elements have [alt] attributes	^
Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. Learn more about the alt attribute.	
 Document has a <title> element	^
The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. Learn more about document titles.	
 <frame> or <iframe> elements have a title	^
Screen reader users rely on frame titles to describe the contents of frames. Learn more about frame titles.	
 <html> element has a [lang] attribute	^
If a page doesn't specify a lang attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. Learn more about the lang attribute.	
 <html> element has a valid value for its [lang] attribute	^
Specifying a valid BCP 47 language helps screen readers announce text properly. Learn how to use the lang attribute.	

Lists contain only `<li>` elements and script supporting elements (`<script>` and `<template>`).

Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. [Learn more about proper list structure.](#)

List items (`<li>`) are contained within `<ul>`, `<ol>` or `<menu>` parent elements

Screen readers require list items (`<li>`) to be contained within a parent `<ul>`, `<ol>` or `<menu>` to be announced properly. [Learn more about proper list structure.](#)

Touch targets have sufficient size and spacing.

Touch targets with sufficient size and spacing help users who may have difficulty targeting small controls to activate the targets. [Learn more about touch targets.](#)

Heading elements appear in a sequentially-descending order

Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. [Learn more about heading order.](#)

NOT APPLICABLE (44)

Hide

`[accesskey]` values are unique

Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. [Learn more about access keys.](#) Unscored

`[aria-*) attributes match their roles`

Each ARIA role supports a specific subset of `aria-*)` attributes. Mismatching these invalidates the `aria-*)` attributes. [Learn how to match ARIA attributes to their roles.](#) Unscored

- ☐ [button](#), [link](#), and [menuitem](#) elements have accessible names ^

When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to make command elements more accessible.](#) Unscored

- ☐ ARIA attributes are used as specified for the element's role ^

Some ARIA attributes are only allowed on an element under certain conditions. [Learn more about conditional ARIA attributes.](#) Unscored

- ☐ Deprecated ARIA roles were not used ^

Deprecated ARIA roles may not be processed correctly by assistive technology. [Learn more about deprecated ARIA roles.](#) Unscored

- ☐ Elements with `role="dialog"` or `role="alertdialog"` have accessible names. ^

ARIA dialog elements without accessible names may prevent screen readers users from discerning the purpose of these elements. [Learn how to make ARIA dialog elements more accessible.](#) Unscored

- ☐ `[aria-hidden="true"]` elements do not contain focusable descendents ^

Focusable descendents within an `[aria-hidden="true"]` element prevent those interactive elements from being available to users of assistive technologies like screen readers. [Learn how aria-hidden affects focusable elements.](#) Unscored

- ☐ ARIA input fields have accessible names ^

When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn more about input field labels.](#) Unscored

☐ ARIA `meter` elements have accessible names

When a meter element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to name meter elements.](#) Unscored

☐ ARIA `progressbar` elements have accessible names

When a progressbar element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. [Learn how to label progressbar elements.](#) Unscored

☐ Elements use only permitted ARIA attributes

Using ARIA attributes in roles where they are prohibited can mean that important information is not communicated to users of assistive technologies. [Learn more about prohibited ARIA roles.](#) Unscored

☐ `[role]`s have all required `[aria-*)` attributes

Some ARIA roles have required attributes that describe the state of the element to screen readers. [Learn more about roles and required attributes.](#) Unscored

☐ Elements with an ARIA `[role]` that require children to contain a specific `[role]` have all required children.

Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. [Learn more about roles and required children elements.](#) Unscored

☐ `[role]`s are contained by their required parent element

Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. [Learn more about ARIA roles and required parent element.](#) Unscored

☐ `[role]` values are valid

ARIA roles must have valid values in order to perform their intended accessibility functions. Learn more about valid ARIA roles. Unscored	
☐ Elements with the <code>role=text</code> attribute do not have focusable descendents.	^
Adding <code>role=text</code> around a text node split by markup enables VoiceOver to treat it as one phrase, but the element's focusable descendents will not be announced. Learn more about the <code>role=text</code> attribute. Unscored	
☐ ARIA toggle fields have accessible names	^
When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more about toggle fields. Unscored	
☐ ARIA <code>tooltip</code> elements have accessible names	^
When a tooltip element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn how to name tooltip elements. Unscored	
☐ ARIA <code>treeitem</code> elements have accessible names	^
When a <code>treeitem</code> element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more about labeling <code>treeitem</code> elements. Unscored	
☐ <code>[aria-*)</code> attributes have valid values	^
Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. Learn more about valid values for ARIA attributes. Unscored	
☐ <code>[aria-*)</code> attributes are valid and not misspelled	^
Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. Learn more about valid ARIA attributes. Unscored	

The page contains a heading, skip link, or landmark region ^ Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. Learn more about bypass blocks. Unscored
<dl>'s contain only properly-ordered <dt> and <dd> groups, <script>, <template> or <div> elements. ^ When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. Learn how to structure definition lists correctly. Unscored
Definition list items are wrapped in <dl> elements ^ Definition list items (<dt> and <dd>) must be wrapped in a parent <dl> element to ensure that screen readers can properly announce them. Learn how to structure definition lists correctly. Unscored
ARIA IDs are unique ^ The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. Learn how to fix duplicate ARIA IDs. Unscored
No form fields have multiple labels ^ Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. Learn how to use form labels. Unscored
<html> element has an [xml:lang] attribute with the same base language as the [lang] attribute. ^ If the webpage does not specify a consistent language, then the screen reader might not announce the page's text correctly. Learn more about the lang attribute. Unscored
Input buttons have discernible text. ^

Adding discernable and accessible text to input buttons may help screen reader users understand the purpose of the input button. [Learn more about input buttons.](#) Unscored

☐ `<input type="image">` elements have `[alt]` text ^

When an image is being used as an `<input>` button, providing alternative text can help screen reader users understand the purpose of the button. [Learn about input image alt text.](#) Unscored

☐ Form elements have associated labels ^

Labels ensure that form controls are announced properly by assistive technologies, like screen readers. [Learn more about form element labels.](#) Unscored

☐ Links are distinguishable without relying on color. ^

Low-contrast text is difficult or impossible for many users to read. Link text that is discernible improves the experience for users with low vision. [Learn how to make links distinguishable.](#) Unscored

☐ The document does not use `<meta http-equiv="refresh">` ^

Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. [Learn more about the refresh meta tag.](#) Unscored

☐ `<object>` elements have alternate text ^

Screen readers cannot translate non-text content. Adding alternate text to `<object>` elements helps screen readers convey meaning to users. [Learn more about alt text for object elements.](#) Unscored

☐ Select elements have associated label elements. ^

Form elements without effective labels can create frustrating experiences for screen reader users. [Learn more about the select element.](#) Unscored

Skip links are focusable. ^	Including a skip link can help users skip to the main content to save time. Learn more about skip links. Unscored
No element has a <code>[tabindex]</code> value greater than 0 ^	A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. Learn more about the tabindex attribute. Unscored
Cells in a <code><table></code> element that use the <code>[headers]</code> attribute refer to table cells within the same table. ^	Screen readers have features to make navigating tables easier. Ensuring <code><td></code> cells using the <code>[headers]</code> attribute only refer to other cells in the same table may improve the experience for screen reader users. Learn more about the headers attribute. Unscored
<code><th></code> elements and elements with <code>[role="columnheader"/"rowheader"]</code> have data cells they describe. ^	Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. Learn more about table headers. Unscored
<code>[lang]</code> attributes have a valid value ^	Specifying a valid BCP 47 language on elements helps ensure that text is pronounced correctly by a screen reader. Learn how to use the lang attribute. Unscored
<code><video></code> elements contain a <code><track></code> element with <code>[kind="captions"]</code> ^	When a video provides a caption it is easier for deaf and hearing impaired users to access its information. Learn more about video captions. Unscored

- ☐ Tables have different content in the summary attribute and `<caption>`.



The summary attribute should describe the table structure, while `<caption>` should have the onscreen title. Accurate table mark-up helps users of screen readers. [Learn more about summary and caption.](#) Unscored

- ☐ All heading elements contain content.



A heading with no content or inaccessible text prevent screen reader users from accessing information on the page's structure. [Learn more about headings.](#) Unscored

- ☐ Uses ARIA roles only on compatible elements



Many HTML elements can only be assigned certain ARIA roles. Using ARIA roles where they are not allowed can interfere with the accessibility of the web page. [Learn more about ARIA roles.](#) Unscored

- ☐ Image elements do not have `[alt]` attributes that are redundant text.



Informative elements should aim for short, descriptive alternative text. Alternative text that is exactly the same as the text adjacent to the link or image is potentially confusing for screen reader users, because the text will be read twice. [Learn more about the alt attribute.](#) Unscored

77

Best Practices

GENERAL

▲ Uses third-party cookies — 40 cookies found

Third-party cookies may be blocked in some contexts. [Learn more about preparing for third-party cookie restrictions.](#)

Name	URL
Cloudflare CDN Cdn	
edgesessions_enabled	...css/all.min.css (cdnjs.cloudflare.com)
_ga	...css/all.min.css (cdnjs.cloudflare.com)
kndctr_8AD56F28618A50850A495FB6_AdobeOr g_identity	...css/all.min.css (cdnjs.cloudflare.com)
_ga_SQCRB0TXZW	...css/all.min.css (cdnjs.cloudflare.com)
YouTube Video	
LOGIN_INFO	/embed/LfzYfziR4yQ? si=_6MLE993NS6wTLjw (www.youtube.com)
__Secure-3PAPISID	/embed/LfzYfziR4yQ? si=_6MLE993NS6wTLjw (www.youtube.com)
__Secure-3PSID	/embed/LfzYfziR4yQ? si=_6MLE993NS6wTLjw (www.youtube.com)
__Secure-3PSIDTS	/embed/LfzYfziR4yQ? si=_6MLE993NS6wTLjw (www.youtube.com)

Name	URL
__Secure-3PSIDCC	/embed/LfzYfziR4yQ?si=_6MLE993NS6wTLjw (www.youtube.com)
Google/DoubleClick Ads Ad	
DSID	/instream/ad_status.js (static.doubleclick.net)
IDE	/instream/ad_status.js (static.doubleclick.net)
Other Google APIs/SDKs Utility	
COMPASS	...th/lsQzGK8Ck....js (www.google.com)
COMPASS	...th/lsQzGK8Ck....js (www.google.com)
COMPASS	...th/lsQzGK8Ck....js (www.google.com)
__Secure-OSID	...th/lsQzGK8Ck....js (www.google.com)
__Secure-OSID	...th/lsQzGK8Ck....js (www.google.com)
__Secure-OSID	...th/lsQzGK8Ck....js (www.google.com)
__Secure-OSID	...th/lsQzGK8Ck....js (www.google.com)
__Secure-OSID	...th/lsQzGK8Ck....js (www.google.com)
__Secure-OSID	...th/lsQzGK8Ck....js (www.google.com)
__Secure-OSID	...th/lsQzGK8Ck....js (www.google.com)
__Secure-OSID	...th/lsQzGK8Ck....js (www.google.com)

Name	URL
__Secure-OSID	...th/lsQzGK8Ck....js (www.google.com)
__Secure-OSID	...th/lsQzGK8Ck....js (www.google.com)
__Host-3PLSID	...th/lsQzGK8Ck....js (www.google.com)
__Secure-OSID	...th/lsQzGK8Ck....js (www.google.com)
COMPASS	...th/lsQzGK8Ck....js (www.google.com)
__Secure-OSID	...th/lsQzGK8Ck....js (www.google.com)
LSOLH	...th/lsQzGK8Ck....js (www.google.com)
COMPASS	...th/lsQzGK8Ck....js (www.google.com)
_sp_id.6393	...th/lsQzGK8Ck....js (www.google.com)
COMPASS	...th/lsQzGK8Ck....js (www.google.com)
COMPASS	...th/lsQzGK8Ck....js (www.google.com)
__Secure-OSID	...th/lsQzGK8Ck....js (www.google.com)
COMPASS	...th/lsQzGK8Ck....js (www.google.com)
COMPASS	...th/lsQzGK8Ck....js (www.google.com)
__Secure-3PAPISID	...th/lsQzGK8Ck....js (www.google.com)

Name	URL
__Secure-3PSID	...th/lsQzGK8Ck....js (www.google.com)
NID	...th/lsQzGK8Ck....js (www.google.com)
__Secure-3PSIDTS	...th/lsQzGK8Ck....js (www.google.com)
__Secure-3PSIDCC	...th/lsQzGK8Ck....js (www.google.com)

▲ Issues were logged in the [Issues](#) panel in Chrome Devtools ^

Issues logged to the Issues panel in Chrome Devtools indicate unresolved problems. They can come from network request failures, insufficient security controls, and other browser concerns. Open up the Issues panel in Chrome DevTools for more details on each issue.

Issue type

Cookie

- ...css/all.min.css (cdnjs.cloudflare.com)
- ...dist/aos.css (unpkg.com)
- /embed/LfzYfziR4yQ?si=_6MLE993NS6wTLjw (www.youtube.com)
- ...5cabb421/www-player.css (www.youtube.com)
- ...br=1/rs=AGKMywHet... (www.youtube.com)
- ...rs=AGKMywGsD.../m=root,base (www.youtube.com)
- ...en_GB/base.js (www.youtube.com)
- /instream/ad_status.js (static.doubleclick.net)
- ...rs=AGKMywGsD.../m=r78Drb (www.youtube.com)

Issue type

/pagead/id (googleads.g.doubleclick.net)
...rs=AGKMywGsD.../m=RZekJ (www.youtube.com)
...lottie-light.vflset/lottie-light.js (www.youtube.com)
...dist/aos.js (unpkg.com)
...v1/log_event?alt=json (www.youtube.com)
...r128/three.min.js (cdnjs.cloudflare.com)
...th/lsQzGK8Ck...js (www.google.com)
/generate_204?uk557w (www.youtube.com)
/generate_204?DZb0Xw (www.youtube.com)

○ Detected JavaScript libraries

All front-end JavaScript libraries detected on the page. [Learn more about this JavaScript library detection diagnostic audit.](#) Unscored

Name	Version
three.js	r128

TRUST AND SAFETY

○ Ensure CSP is effective against XSS attacks

A strong Content Security Policy (CSP) significantly reduces the risk of cross-site scripting (XSS) attacks. [Learn how to use a CSP to prevent XSS](#) Unscored

Description	Directive	Severity
No CSP found in enforcement mode		High

Use a strong HSTS policy

Deployment of the HSTS header significantly reduces the risk of downgrading HTTP connections and eavesdropping attacks. A rollout in stages, starting with a low max-age is recommended. [Learn more about using a strong HSTS policy.](#) Unscored

Description	Directive	Severity
No HSTS header found		High

Ensure proper origin isolation with COOP

The Cross-Origin-Opener-Policy (COOP) can be used to isolate the top-level window from other documents such as pop-ups. [Learn more about deploying the COOP header.](#) Unscored

Description	Directive	Severity
No COOP header found		High

Mitigate clickjacking with XFO or CSP

The X-Frame-Options (XFO) header or the frame-ancestors directive in the Content-Security-Policy (CSP) header control where a page can be embedded. These can mitigate clickjacking attacks by blocking some or all sites from embedding the page. [Learn more about mitigating clickjacking.](#) Unscored

DescriptionSeverity

No frame control policy foundHigh

Mitigate DOM-based XSS with Trusted Types

The require-trusted-types-for directive in the Content-Security-Policy (CSP) header instructs user agents to control the data passed to DOM XSS sink functions. [Learn more about mitigating DOM-based XSS with Trusted Types.](#) Unscored

DescriptionSeverity

No `Content-Security-Policy` header with Trusted Types directive foundHigh

PASSED AUDITS (11)

Hide

Uses HTTPS

All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding [mixed content](#), where some resources are loaded over HTTP despite the initial request being served over HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. [Learn more about HTTPS.](#)

Avoids deprecated APIs

Deprecated APIs will eventually be removed from the browser. [Learn more about deprecated APIs.](#)

Allows users to paste into input fields

about:blank

41/45

Preventing input pasting is a bad practice for the UX, and weakens security by blocking password managers. Learn more about user-friendly input fields.	
● Avoids requesting the geolocation permission on page load	^
Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. Learn more about the geolocation permission.	
● Avoids requesting the notification permission on page load	^
Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. Learn more about responsibly getting permission for notifications.	
● Displays images with correct aspect ratio	^
Image display dimensions should match natural aspect ratio. Learn more about image aspect ratio.	
● Serves images with appropriate resolution	^
Image natural dimensions should be proportional to the display size and the pixel ratio to maximize image clarity. Learn how to provide responsive images.	
● Page has the HTML doctype	^
Specifying a doctype prevents the browser from switching to quirks-mode. Learn more about the doctype declaration.	
● Properly defines charset	^
A character encoding declaration is required. It can be done with a <meta> tag in the first 1024 bytes of the HTML or in the Content-Type HTTP response header. Learn more about declaring the character encoding.	

No browser errors logged to the console

Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns. [Learn more about this errors in console diagnostic audit](#)

Page has valid source maps

Source maps translate minified code to the original source code. This helps developers debug in production. In addition, Lighthouse is able to provide further insights. Consider deploying source maps to take advantage of these benefits. [Learn more about source maps.](#) Unscored

URL	Map URL
chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/polyfill.js	chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/polyfill.js.map
Error: Failed fetching source map (null)	
chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/polyfill.js	chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/polyfill.js.map
Error: Failed fetching source map (null)	
chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/polyfill.js	chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/polyfill.js.map
Error: Failed fetching source map (null)	
chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/polyfill.js	chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/polyfill.js.map
Error: Failed fetching source map (null)	

URL	Map URL
chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/polyfill.js Error: Failed fetching source map (null)	chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/polyfill.js.map
chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/polyfill.js Error: Failed fetching source map (null)	chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/polyfill.js.map
chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/globals-front.js Error: Failed fetching source map (null)	chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/globals-front.js.map
chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/globals-front.js Error: Failed fetching source map (null)	chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/globals-front.js.map
chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/globals-front.js Error: Failed fetching source map (null)	chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/globals-front.js.map
chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/globals-front.js Error: Failed fetching source map (null)	chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/globals-front.js.map

URL	Map URL
chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/cookie-banner-detection.preload.js	chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/cookie-banner-detection.preload.js.map
Error: Failed fetching source map (null)	
chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/cookie-banner-detection.preload.js	chrome-extension://gighmmpiobklfepjocnamgkkbiglidom/cookie-banner-detection.preload.js.map
Error: Failed fetching source map (null)	

NOT APPLICABLE (1)

Hide

Redirects HTTP traffic to HTTPS

Make sure that you redirect all HTTP traffic to HTTPS in order to enable secure web features for all your users. [Learn more.](#) Unscored

Captured at Jun 7, 2026, 3:34 PM GMT+5:30

Emulated Moto G Power with Lighthouse 13.0.2

Single page session

Initial page load

Slow 4G throttling

Using Chromium 148.0.0.0 with devtools