

- 1-Provisioner to install 32mmP on Pole
- 2- Connect 2F service leads to existing OF-DC A4/B8.
- 3- Haul thru duct to where the Rugg., cable is left.
- 4-2F service leads to be connected to the Rugged cable using a GATOR.

Type	Lot No.	Address	Terminal
Aerial	1D	Alanbrooke Cres	F-ASE 251
Aerial	1E	Alanbrooke Cres	F-ASE 251

Points	Codes	Civil
1		Existing OFDC-B8(F-ASE 251) is located on pole
2		GATOR will be installed by Provisioner
2-3	D01 x 2 D03 x 6.6	ISB.Trench 2m in Grass MT 6.6m in Concrete and lay 2 x Ruggedized 733 x 54
3-4	D03 x 2.8 D01 x 1.9	MT 2.8m in Concrete Trench 1.9m in Garden and lay 1 x Ruggedized
4		Leave a drop off for # 1D(REQ) Alanbrooke Cres
3-5	733 x 1.7	Clip 1 x Ruggedized on fence for 1.7m
5		Leave a drop off for # 1E Alanbrooke Cres

Existing OFDC-B8
F-AES 251

If duct is unusable, dig & fix will apply

Existing OFDC-B8
F-AES 252

1D
REQ

1E

1C

1A

1B

