

SHOW RUNNING-CONFIG — TODOS LOS ROUTERS

ROUTER ESTE

```
version 15.1
no service timestamps log datetime msec
no service timestamps debug datetime msec
service password-encryption
!
hostname ESTE
!
no ip cef
ipv6 unicast-routing
!
no ipv6 cef
!
username Manager secret 5 $1$mERr$9xcyzgMubYEUu5jrby8ds.
!
ip ssh version 2
no ip domain-lookup
ip domain-name red.local
!
spanning-tree mode pvst
!
interface GigabitEthernet0/0
description LAN 1
no ip address
duplex auto
speed auto
ipv6 address FE80::1:1 link-local
ipv6 address 2003:BEBA:506:1::1/64
ipv6 nd other-config-flag
ipv6 nd managed-config-flag
ipv6 dhcp server LAN_1
!
interface GigabitEthernet0/1
description LAN 2
no ip address
duplex auto
speed auto
ipv6 address FE80::2:1 link-local
ipv6 address 2003:BEBA:506:2::1/64
ipv6 nd other-config-flag
ipv6 nd managed-config-flag
```

```

    ipv6 dhcp server LAN_2
!
interface Serial0/0/0
  description Conexion con SUCURSAL-4
  no ip address
  ipv6 address FE80::101:2 link-local
  ipv6 address 2003:BEBA:506:101::2/64
  ipv6 rip ITLA_RIP enable
!
interface Serial0/0/1
  description Conexion con OESTE
  no ip address
  ipv6 address FE80::102:1 link-local
  ipv6 address 2003:BEBA:506:102::1/64
  ipv6 rip ITLA_RIP enable
  clock rate 2000000
!
interface Serial0/1/0
  description Conexion con NORESTE
  no ip address
  ipv6 address FE80::103:1 link-local
  ipv6 address 2003:BEBA:506:103::1/64
  ipv6 rip ITLA_RIP enable
  clock rate 2000000
!
ipv6 router rip ITLA_RIP
  redistribute connected
!
line con 0
  exec-timeout 5 0
  password 7 0822455D0A165546
  login
!
line vty 0 4
  login local
  transport input ssh
!
end

```

ROUTER NORESTE

```

version 15.1
service password-encryption
hostname NORESTE
!
no ip cef
ipv6 unicast-routing
no ipv6 cef

```

```
!  
username Manager secret 5 $1$mERr$9xcyzgMubYEUu5jrby8ds.  
!  
ip ssh version 2  
no ip domain-lookup  
ip domain-name red.local  
!  
interface GigabitEthernet0/0  
  description LAN 4  
  no ip address  
  ipv6 address FE80::4:1 link-local  
  ipv6 address 2003:BEBA:506:4::1/64  
  ipv6 dhcp server LAN_4  
!  
interface Serial0/0/0  
  description Hacia SUR  
  no ip address  
  ipv6 address FE80::104:1 link-local  
  ipv6 address 2003:BEBA:506:104::1/64  
  ipv6 rip ITLA_RIP enable  
  clock rate 2000000  
!  
interface Serial0/0/1  
  description Hacia SEDE  
  no ip address  
  ipv6 address FE80::105:1 link-local  
  ipv6 address 2003:BEBA:506:105::1/64  
  ipv6 rip ITLA_RIP enable  
  clock rate 64000  
!  
interface Serial0/1/0  
  description Hacia ESTE  
  no ip address  
  ipv6 address FE80::103:2 link-local  
  ipv6 address 2003:BEBA:506:103::2/64  
  ipv6 rip ITLA_RIP enable  
!  
ipv6 router rip ITLA_RIP  
  redistribute connected  
!  
line vty 0 4  
  login local  
  transport input ssh  
!  
end
```

ROUTER OESTE

```
version 15.1
service password-encryption
hostname OESTE
!
no ip cef
ipv6 unicast-routing
no ipv6 cef
!
ipv6 dhcp pool LAN_3
  address prefix 2003:BEBA:506:3::/64 lifetime 172800 86400
  dns-server 2002:FEA:CAC0::2
  domain-name globals.com
!
username Manager secret 5 $1$mERr$9xcyzgMubYEUu5jrby8ds.
!
ip ssh version 2
no ip domain-lookup
ip domain-name red.local
!
interface GigabitEthernet0/0
  description LAN 3
  no ip address
  ipv6 address FE80::3:1 link-local
  ipv6 address 2003:BEBA:506:3::1/64
  ipv6 rip ITLA_RIP enable
  ipv6 dhcp server LAN_3
!
interface Serial0/0/1
  description Conexion con ESTE
  no ip address
  ipv6 address FE80::102:2 link-local
  ipv6 address 2003:BEBA:506:102::2/64
  ipv6 rip ITLA_RIP enable
!
ipv6 router rip ITLA_RIP
!
line vty 0 4
  login local
  transport input ssh
!
end
```

ROUTER SEDE

```
version 15.1
service password-encryption
hostname SEDE
!
ip cef
ipv6 unicast-routing
no ipv6 cef
!
username Manager privilege 15 secret 5 $1$mERr$9xcyzgMubYEUu5jrby8ds.
!
ip ssh version 2
ip domain-name red.local
!
interface GigabitEthernet0/0
description LAN
no ip address
ipv6 address FE80::6:1 link-local
ipv6 address 2003:BEBA:506:6::1/64
ipv6 dhcp server LAN_6
!
interface GigabitEthernet0/1
description LAN
no ip address
ipv6 address FE80::7:1 link-local
ipv6 address 2003:BEBA:506:7::1/64
ipv6 dhcp server LAN_7
!
interface Serial0/0/0
description Conexion con SUCURSAL_1
no ip address
ipv6 address FE80::106:1 link-local
ipv6 address 2003:BEBA:506:106::1/64
ipv6 rip ITLA_RIP enable
clock rate 2000000
!
interface Serial0/0/1
description Hacia NORESTE
no ip address
ipv6 address FE80::105:2 link-local
ipv6 address 2003:BEBA:506:105::2/64
ipv6 rip ITLA_RIP enable
!
interface Serial0/1/0
description Hacia SUCURSAL_3
no ip address
ipv6 address FE80::108:1 link-local
ipv6 address 2003:BEBA:506:108::1/64
ipv6 rip ITLA_RIP enable
```

```

    clock rate 2000000
    !
interface Serial0/1/1
    description Hacia SUCURSAL_2
    no ip address
    ipv6 address FE80::107:1 link-local
    ipv6 address 2003:BEBA:506:107::1/64
    ipv6 rip ITLA_RIP enable
    clock rate 2000000
    !
ipv6 router rip ITLA_RIP
    redistribute connected
    !
line vty 0 4
    login local
    transport input ssh
    !
end

```

ROUTER SUR

```

version 15.1
service password-encryption
hostname SUR
!
no ip cef
ipv6 unicast-routing
no ipv6 cef
!
username Manager secret 5 $1$mERr$9xcyzgMubYEUu5jrby8ds.
!
ip ssh version 2
no ip domain-lookup
ip domain-name red.local
!
interface GigabitEthernet0/0
    description LAN 5
    no ip address
    ipv6 address FE80::5:1 link-local
    ipv6 address 2003:BEBA:506:5::1/64
    ipv6 rip ITLA_RIP enable
    ipv6 dhcp server LAN_5
    !
interface Serial0/0/0
    description Conexion con NOROESTE
    no ip address
    ipv6 address FE80::104:2 link-local
    ipv6 address 2003:BEBA:506:104::2/64

```

```
    ipv6 rip ITLA_RIP enable
!
ipv6 router rip ITLA_RIP
!
line vty 0 4
    login local
    transport input ssh
!
end
```

ROUTER SUCURSAL_1

```
version 15.1
service password-encryption
hostname SUCURSAL_1
!
no ip cef
ipv6 unicast-routing
no ipv6 cef
!
username Manager secret 5 $1$mERr$9xcyzgMubYEUu5jrby8ds.
!
ip ssh version 2
no ip domain-lookup
ip domain-name red.local
!
interface GigabitEthernet0/0
    description LAN_SUC1_H1
    no ip address
    ipv6 address FE80::13:1 link-local
    ipv6 address 2003:BEBA:506:13::1/64
    ipv6 rip ITLA_RIP enable
    ipv6 dhcp server LAN_13
!
interface GigabitEthernet0/1
    description LAN_SUC1_H2
    no ip address
    ipv6 address FE80::12:1 link-local
    ipv6 address 2003:BEBA:506:12::1/64
    ipv6 rip ITLA_RIP enable
    ipv6 dhcp server LAN_12
!
interface Serial0/0/0
    description Conexion con SEDE
    no ip address
    ipv6 address FE80::106:2 link-local
    ipv6 address 2003:BEBA:506:106::2/64
    ipv6 rip ITLA_RIP enable
```

```
!  
ipv6 router rip ITLA_RIP  
!  
line vty 0 4  
  login local  
  transport input ssh  
!  
end
```

ROUTER SUCURSAL_2

```
version 15.1  
service password-encryption  
hostname SUCURSAL_2  
!  
no ip cef  
ipv6 unicast-routing  
no ipv6 cef  
!  
username Manager secret 5 $1$mERr$9xcyzgMubYEUu5jrby8ds.  
!  
ip ssh version 2  
no ip domain-lookup  
ip domain-name red.local  
!  
interface GigabitEthernet0/0  
  description LAN  
  no ip address  
  ipv6 address FE80::8:1 link-local  
  ipv6 address 2003:BEBA:506:8::1/64  
  ipv6 rip ITLA_RIP enable  
  ipv6 dhcp server LAN_8  
!  
interface GigabitEthernet0/1  
  description LAN  
  no ip address  
  ipv6 address FE80::9:1 link-local  
  ipv6 address 2003:BEBA:506:9::1/64  
  ipv6 rip ITLA_RIP enable  
  ipv6 dhcp server LAN_9  
!  
interface Serial0/1/1  
  no ip address  
  ipv6 address FE80::107:2 link-local  
  ipv6 address 2003:BEBA:506:107::2/64  
  ipv6 rip ITLA_RIP enable  
!  
ipv6 router rip ITLA_RIP
```



```
!  
line vty 0 4  
    login local  
    transport input ssh  
!  
end
```

ROUTER SUCURSAL_3

```
version 15.1  
service password-encryption  
hostname SUCURSAL_3  
!  
no ip cef  
ipv6 unicast-routing  
no ipv6 cef  
!  
ipv6 dhcp pool POOL_LAN  
    dns-server 2002:FEA:CAC0::2  
!  
username Manager secret 5 $1$mERr$9xcyzgMubYEUu5jrby8ds.  
!  
ip ssh version 2  
no ip domain-lookup  
ip domain-name red.local  
!  
interface GigabitEthernet0/0  
    description LAN 10  
    no ip address  
    ipv6 address FE80::10:1 link-local  
    ipv6 address 2003:BEBA:506:10::1/64  
    ipv6 rip ITLA_RIP enable  
    ipv6 dhcp server LAN_11  
!  
interface GigabitEthernet0/1  
    description Conexion con LAN 11  
    no ip address  
    ipv6 address FE80::11:1 link-local  
    ipv6 address 2003:BEBA:506:11::1/64  
    ipv6 rip ITLA_RIP enable  
    ipv6 dhcp server POOL_LAN  
!  
interface Serial0/1/0  
    no ip address  
    ipv6 address FE80::108:2 link-local  
    ipv6 address 2003:BEBA:506:108::2/64  
    ipv6 rip ITLA_RIP enable  
!
```

```
ipv6 router rip ITLA_RIP
!
line vty 0 4
  login local
  transport input ssh
!
end
```

ROUTER SUCURSAL_4

```
version 15.1
service password-encryption
hostname SUCURSAL4
!
no ip cef
ipv6 unicast-routing
no ipv6 cef
!
username Manager secret 5 $1$mERr$9xcyzgMubYEUu5jrby8ds.
!
ip ssh version 2
no ip domain-lookup
ip domain-name red.local
!
interface GigabitEthernet0/0
  description LAN 14
  no ip address
  ipv6 address FE80::14:1 link-local
  ipv6 address 2003:BEBA:506:14::1/64
  ipv6 rip ITLA_RIP enable
  ipv6 dhcp server LAN_14
!
interface GigabitEthernet0/1
  description LAN 15
  no ip address
  ipv6 address FE80::15:1 link-local
  ipv6 address 2003:BEBA:506:15::1/64
  ipv6 rip ITLA_RIP enable
  ipv6 dhcp server LAN_15
!
interface Serial0/0/0
  description Conexion hacia ESTE
  no ip address
  ipv6 address FE80::101:1 link-local
  ipv6 address 2003:BEBA:506:101::1/64
  ipv6 rip ITLA_RIP enable
  clock rate 2000000
!
```

```
ipv6 router rip ITLA_RIP
!  
line vty 0 4  
  login local  
  transport input ssh  
!  
end
```