Final Assessment Test (FAT) - APRIL/MAY 2023

Programme	B.Tech	Samast	
is compact time	FLUID MECHANICS AND	Semester	Winter Semester 2022-23
	MACHINES	Course Code	BMEE204L
_	Prof. Vinayagamurthy G 3 Hours	Slot	D2+TD2
		Class Nbr	CH2022235002422
		Max. Marks	

Section A (10 X 10 Marks) Answer any 10 questions

- 91. If the velocity profile of a fluid over a plate is parabolic with the vertex 30 cm from the plate. [10] where the velocity is 60 cm/sec. Calculate the velocity gradient and shear stress at the distance of 5.15.30 cm from the plate, if the viscosity of the fluid is 7.5 poise. [Hint: Assume the parabolic distribution for velocity profile $u = c y^2 + by + a$]. Also draw a schematic sketch of the velocity profile above the flat plate.
- 02. (a) Find out the differential reading 'h' of an inverted U-tube manometer containing oil of specific gravity 0.7 as the manometric fluid when connected across pipes A and B as shown in Figure below, conveying liquids of specific gravities 1.2 and 1.0 are immiscible with manometric fluid. Pipes A and B are located at the same level and assume pressures at A and B to be equal. [7 Marks]




Figure 1

- (b) Discuss the stability of a submerged body and a floating body whose center of gravity is above the center of buoyancy. [3 Marks]
- 03. (a) A fluid flow field is given by $V=x^2y \ i+y^2z \ j-(2xyz+yz^2) \ k$. Prove that it is a case of possible steady incompressible fluid flow. Calculate the velocity and acceleration at the point (2,1,3). [7]
 - (b) Differentiate between steady and unsteady flow with appropriate examples. [3 Marks]
- 04. A Venturimeter of inlet diameter 300 mm and throat diameter 150 mm is fixed in a vertical pipe line. A liquid of specific gravity 0.8 is flowing upward through the pipe line. A differential manometer containing mercury gives a reading of 100 mm when connected at inlet and throat. The elevation difference between the inlet and throat is 500 mm. If the value of C_d = 0.98, then determine the (i) rate of flow of liquid in liters per second and (ii) differential pressure between the inlet and throat in N/m²

- bend being 600 mm and 300 mm respectively. Find the Magnitude and direction of force exerted by water on the bend if the intensity of pressure at inlet to bend is 8.829 N.cm² and rate of flow of water is 600 litres 8.
 - of water is 600 lines.

 On Three pipes of 400 mm, 200 mm and 300 mm diameters have lengths of 400 m, 200 m and 300 m respectively. They are connected in series to make a compound pipe. The ends of this compound pipe are connected with tanks whose difference of water levels is 16m. If coefficient of friction for these pipes is same and equal to 0.005, determine the discharge through the compound pipe neglecting first the minor losses and then including them.
 - 07. The pressure drop. Δp along a straight pipe of diameter D has been experimentally studied, and it is observed that for laminar flow of a given fluid and pipe, the pressure drop varies directly with the distance, l, between pressure taps. Assume that Δp is a function of D and l, the velocity, l, and the fluid viscosity, μ. Use dimensional analysis to deduce how the pressure drop varies with pipe diameter.
 - 08. (a) A jet plane which weights 29.43 kN and having a wing area of 20 m³ flies at a velocity of 1100 km/hr, when the entire plane delivers 7357.5 kW power. It is to be noted that 65% of the power is used to overcome the drag resistance of the wing. Calculate the coefficients of lift and drag for the wing. Assume the density of the atmospheric air is 1.15 kg/m³. [7 Marks]
 - (b) Differentiate streamlined body from a bluff body in the view of aerodynamics. Draw the flow pattern and mark the stagnation and separation points for any four bluff bodies with its Drag coefficient. [3 Marks]
 - 09. Define a centrifugal pump. Explain the working of a single stage centrifugal pump with neat sketches.
- →10. Draw the schematic view of a Kaplan turbine and explain it construction and working.
 - 11. (a) Consider steady flow of water through an axisymmetric garden hose nozzle (refer Figure below). Along the centerline of the nozzle, the water speed increases from u_{entrance} to u_{exit} as sketched. Measurements reveal that the centerline water speed increases parabolically through the nozzle. Write an equation for centerline speed u(x), based on the parameters given below, from x=0 to x -L. [5 Marks]




Figure 2

- (b) What do you mean by Boundary layer separation. Also discuss any three methods to avoid boundary layer separation. [5 Marks]
- 12. (a) Water at 10 C (ρ=999.7 kg/m3 and μ=1.307 ×10-3 kg/m·s) is flowing steadily in a 0.12 cm diameter, 15 m long pipe at an average velocity of 0.9 m/s. Determine (i) the pressure drop. (ii) the head loss, and (iii) the pumping power requirement to overcome this pressure drop. /5 Marks/
 - (b) What are various kinds of Similitude? Discuss the importance of Dimensional analysis with appropriate examples. [5 Marks]

[16]

[10]

[10]

2 [10]

⇔⇔⇔

2