

TACT: Trust-Anchored Confidence Tempering for Self-Consistency Voting in Large Language Models

Wei-Chen Ko (柯瑋宸, vito1317)
Independent Researcher

SERVICE@VITO1317.COM

Abstract

Confidence-weighted self-consistency improves on majority voting when a frozen model’s self-reported confidence is calibrated in *direction*. Every published scheme is monotone increasing in confidence, so an anti-correlated channel poisons the vote, and binary calibration gates survive inversion only by discarding discriminative signal. TACT derives the vote exponent from the measured, *signed*, within-item discrimination of the channel: a pooled van Elteren Somers’ D with an item-clustered standard error, positive-part James–Stein shrinkage, and a Bayes-discriminant link, which at the default base rate $\bar{p} = \frac{1}{2}$ collapses to $\gamma = z\sqrt{2 + z^2}$ with z the probit of the shrunk pooled AUC. Inside the shrinkage dead zone the vote is bit-identical to plain self-consistency. A label-free variant estimates the sign from agreement pseudo-labels under an attenuation identity that guarantees sign consistency while the plurality-error rate stays below one half; past that boundary it mis-signs, which the paper measures and reports. On a synthetic-oracle harness it recovers anti-correlated channels that pin every published protocol to the majority floor (1.000 vs. 0.762) and cracks the heterogeneity floor with zero paired losses (0.923 vs. 0.785). Against a dev-picked *signed* grid, which the sweep shows is a far stronger baseline than the published protocols, the advantage narrows to distortion, echo, and label-free operation. Two real-trace campaigns then bound the setting: the channel is null on saturated benchmarks ($z = -1.24$) and positive on competition mathematics ($\hat{D} = +0.250$, $z = +2.54$), yet the stratum any such method can act on measures 2.5–7.5% of items across five substrates in two domains, so abstention is the correct default and the dead zone implements it.

Keywords: large language models, self-consistency, confidence calibration, label-free estimation, rank statistics

1 Introduction

Self-consistency (SC; Wang et al., 2023) improves the reasoning accuracy of a frozen large language model (LLM) by sampling K chain-of-thought traces and returning the plurality answer. Each trace can also report a confidence score, verbalized (Tian et al., 2023; Xiong et al., 2024), derived from token log-probabilities, or elicited as $P(\text{True})$ (Kadavath et al., 2022), so weighting votes by confidence is a natural refinement. Confidence-Informed Self-Consistency (CISC; Taubenfeld et al., 2025) showed that this recovers the accuracy of plain SC at a fraction of the sampling budget, and introduced Within-Question Discrimination (WQD) to argue that *discrimination*, not calibration, is the property that makes a confidence signal useful for voting.

This refinement carries a structural fragility that, to the best of our knowledge, no published method addresses. Every existing weighting scheme is monotone *increasing* in

confidence, including CISC’s softmax weights, reliability-aware pseudo-counts (Kim et al., 2026), and warmup-thresholded filtering (Fu et al., 2026). The trust decision is which magnitude of up-weighting to apply; the possibility that the channel is *anti-correlated* with correctness is never searched for. Yet miscalibration of direction is not exotic: reinforcement fine-tuning is known to distort verbalized confidence, distribution shift can invert a signal that was informative in-domain, and in the experiments reported here a simple anti-correlated channel ($\kappa = -0.6$; Section 3) drives confidence-weighted baselines from near-perfect accuracy to far below the majority-vote floor, while the same evidence, read with the correct sign, is a perfect signal. The defensive alternative, a binary dev-set gate that disables the channel when calibration error is high, survives the inversion but discards discriminative signal wholesale: a systematically under-confident yet perfectly ranked channel fails an ECE gate for reasons irrelevant to voting utility (Taubenfeld et al., 2025; Huang et al., 2024).

This paper frames the problem as estimating one scalar: the *signed* within-item discrimination of the confidence channel, and mapping that scalar, with its uncertainty, to a vote exponent. The contributions are:

C1: Signed, analytically-tempered weighting. TACT votes with $w_i = \exp(\gamma\varphi_i)$, where φ_i is the standardized van der Waerden score of trace i ’s within-item confidence midrank and γ is *derived*, not grid-searched: a pooled van Elteren Somers’ D (equal to $2 \cdot \text{WQD} - 1$) with an exact tie-corrected null variance and an item-clustered jackknife standard error, shrunk by positive-part James–Stein with a significance floor, then mapped through a Bayes-discriminant link. Two anchors are exact: inside the dead zone the vote is *bit-identical* to SC via a shared code path, and the log-value feature map reproduces CISC-power. Since φ uses only within-item ranks, the method is invariant to every strictly monotone distortion of the confidence scale, and under compression it beats the best exponent in the tested grid $\{0.25, 0.5, 1, 2, 4\}$ (1.000 vs. 0.963; that optimum sits at the largest exponent tried, so the comparison bounds the grid, not the family).

C2: Label-free estimation of the sign. The crowdsourcing lineage estimates reliability from cross-annotator covariance (Dawid and Skene, 1979; Parisi et al., 2014); one exchangeable channel from one model offers no such structure. TACT estimates the signed discrimination from deduplication-weighted agreement pseudo-labels under a proven class-conditional-noise identity, $\mathbb{E}[\hat{D}_g] = (1 - 2\bar{\rho})D$: while the pair-weighted plurality-error rate $\bar{\rho}$ is below $1/2$ the estimate can only *under-trust*, never mis-sign. A split-half inversion de-attenuates conservatively and sign-aware alarms return the method to SC at the identifiability boundary. Past $\bar{\rho} = 1/2$ it does mis-sign, which Section 9 measures rather than assumes away.

C3: An impossibility result and its structured escape. With i.i.d. per-item coupling and no observable covariate, per-item label-free adaptation is closed: any monotone use of an item’s own agreement statistic collapses to plurality reinforcement, the observable sign opposes the truth on 96% of the plurality-wrong items with $|D_q| > 0.3$, the ones where a flip could win, and $\{\kappa > 0, \text{minority right}\}$ and $\{\kappa < 0, \text{plurality right}\}$ induce the same observable law. Indexed instead by an observable covariate, the same estimator run per group recovers each group’s signed coupling with zero paired losses to SC (Section 6).

C4: A pre-registered falsification protocol. Four falsifiers were fixed before implementation, two of them designed to kill the method: the *published* dev-calibrated CISC

protocol, whose tuned temperature already interpolates $SC \leftrightarrow CISC$, and a dev-picked *signed* exponent grid, which the sweep shows is far the stronger of the two. All four survived, and the margins are reported both ways: against the signed grid the advantage concentrates in distortion, echo, and label-free operation, and TACT trails it in the mid-range.

C5: A measurement of the addressable stratum. Two real-trace campaigns and a five-substrate window measurement bound what *any* label-free aggregation method can do. The channel is null on saturated benchmarks ($\hat{D} = -0.219$, $z = -1.24$) and positive on competition mathematics ($+0.250$, $z = +2.54$), so the premise holds where the model is uncertain; but the stratum such a method can act on is 2.5–7.5% of items across all five substrates, in two domains, and does not widen as items harden. On both real substrates the in-pool oracle itself cannot clear the pre-registered endpoint, which makes abstention the correct default rather than a conservative one.

2 Related Work

Confidence-weighted self-consistency. SC (Wang et al., 2023) treats sampled traces as i.i.d. votes. $CISC$ (Taubenfeld et al., 2025) weights votes by softmax-normalized confidence with a temperature tuned on a labeled split, and its WQD metric makes the discrimination-vs-calibration point that also motivates this work; the rank-calibration line (Huang et al., 2024) reaches the same conclusion independently. Weighted variants (Li et al., 2023) and early-stopping families (Aggarwal et al., 2023; Li et al., 2024) refine the budget. Self-certainty (Kang et al., 2025) is the closest relative in spirit, being the one published selector that scores candidates by a rank-like quantity rather than by raw confidence, but it ranks *across* candidates with a fixed positive orientation and is not evaluated here; reliability-aware pseudo-counts (Kim et al., 2026) and warmup-thresholded filtering (Fu et al., 2026) adapt online but only re-scale positive trust. None of these searches a negative exponent: the obstruction is a sign bit in the hyperparameter grid rather than the weight family itself, as this paper’s own SignGrid-dev baseline shows by opening the same c^γ family to negative γ and reaching the signed oracle across the negative half-axis. What no published protocol does is *estimate* that sign, with or without labels. The dev-calibrated variant must therefore be positioned honestly: $CISC$ ’s tuned temperature is already a dev-calibrated $SC \leftrightarrow CISC$ interpolation, so the novelty of TACT-dev lies in the sign, the rank invariance, and the analytic (grid-free) map, not in dev calibration itself.

Reliability estimation without labels. Estimating worker reliability from agreement is classical (Dawid and Skene, 1979; Whitehill et al., 2009; Karger et al., 2011); spectral meta-learners (Parisi et al., 2014) and recent LLM ensemble work (Lee et al., 2026; Ai et al., 2025) exploit covariance across *multiple* predictors. The setting here differs: one exchangeable channel from one model, per-item vote structure, and the known failure of agreement proxies under correlated errors—met here with a quantified attenuation identity, conservative de-attenuation, and alarms in place of an unconditional claim.

Shrinkage and rank statistics. The estimator assembles classical parts: stratified rank statistics (van Elteren, 1960), the James–Stein positive-part estimator (James and Stein, 1961), effective-sample-size corrections (Kish, 1965; Rao and Scott, 1981), and normal-scores discriminant analysis. The claim is the assembly and its anchors, not the parts.

Honest sibling result. A preceding system in the same line of work (RLEV-VoI, redundancy-discounted voting with value-of-information stopping) was evaluated under the same falsification discipline and *failed* it, dominated everywhere by a simple deduplication baseline, and is reported as a negative result. Its post-mortem isolated the confidence dilemma studied here.

3 Problem Setup

3.1 Notation

Items $q = 1, \dots, Q$; item q has m_q sampled traces. Trace (q, i) yields an answer $a_{q,i}$ in a discrete set and a confidence $c_{q,i} \in (0, 1)$; correctness is $y_{q,i} = \mathbf{1}[a_{q,i} = a_q^*]$, unobserved at test time. Plain SC returns $\arg \max_A n_q(A)$ where $n_q(A)$ counts votes for answer A . CISC-power weights votes by $c_{q,i}^\gamma$ with a fixed $\gamma > 0$.

3.2 The confidence dilemma

The synthetic oracle draws, per item, traces from a cluster mixture with a latent correct answer and generates confidence as

$$c_{q,i} = \text{clip}\left(\frac{1}{2} + \kappa(y_{q,i} - \frac{1}{2}) + \varepsilon_{q,i}, 0.01, 0.99\right), \quad (1)$$

with noise $\varepsilon \sim \mathcal{N}(0, 0.1^2)$ and coupling $\kappa \in [-0.6, 0.6]$. Fig. 1 maps the baseline landscape *before* the proposed method existed: unconditional weighting (CISC, $\gamma = 1$) collapses on $\kappa < 0$; an ECE gate never opens off the well-calibrated diagonal; a sign-corrected AUC gate over dev labels nearly saturates the homogeneous sweep. This pre-measurement fixes where a new method can legitimately claim wins—monotone distortion of the confidence scale, covariate heterogeneity, small dev sets, and label-free operation—and the evaluation holds itself to exactly those cells.

4 TACT

4.1 Vote family

Within item q , let $R_{q,i}$ be the midrank of $c_{q,i}$ (ties averaged) and

$$\varphi_{q,i} = \frac{v_{q,i} - \bar{v}_q}{\sigma_q}, \quad v_{q,i} = \Phi^{-1}\left(\frac{R_{q,i}}{m_q + 1}\right), \quad (2)$$

where σ_q is the *realized* standard deviation of v within the item (the no-tie value is 0.62 at $m=4$ but 0.95 at $m=40$; a closed form would silently rescale γ across budgets), and $\varphi \equiv 0$ if $\sigma_q \leq 10^{-8}$ (all-tied confidences vote as plain SC). The vote is

$$\hat{a}_q = \arg \max_A \sum_{i: a_{q,i}=A} \exp(\gamma \varphi_{q,i}), \quad (3)$$

and when $\gamma = 0$ the implementation *calls the SC routine itself*, making the zero-trust anchor bitwise exact rather than equal in distribution. Because (2) depends on c only through within-item ranks, every strictly monotone distortion of the confidence scale leaves (3) unchanged.




Figure 1: The pre-measured problem statement: accuracy of baseline confidence policies at fixed $K=15$ as the true coupling κ varies. A trivial sign-corrected AUC gate (green) nearly saturates the homogeneous sweep; the headroom for any new method (shaded) concentrates in the mid-range and, off this plot, in distortion, heterogeneity, and label-free cells.

4.2 Reliability statistic

For item q with n_q^1 positive and n_q^0 negative labels (dev: y ; label-free: the pseudo-label of Section 5), the Mann–Whitney statistic on midranks gives

$$D_q = 2 \text{AUC}_q - 1, \quad \text{AUC}_q = \frac{U_q}{n_q^1 n_q^0}, \quad (4)$$

which equals $2 \cdot \text{WQD}_q - 1$ in CISC’s notation. Pooling uses van Elteren pair-count weights $N_q = n_q^1 n_q^0$ (van Elteren, 1960):

$$\hat{D} = \frac{\sum_q N_q D_q}{\sum_q N_q}. \quad (5)$$

Under the within-item exchangeability null, U_q has the exact tie-corrected variance $n_q^1 n_q^0 (m_q + 1) / 12 \cdot [1 - \sum_t (t^3 - t) / (m_q^3 - m_q)]$, yielding a null standard error SE_0 ; between-item heterogeneity is captured by the closed-form delete-one-item jackknife SE_J . The conservative choice is

$$\text{SE} = \max(\text{SE}_0, \text{SE}_J, \frac{1}{2\sqrt{N}}), \quad r = \hat{D} / \text{SE}. \quad (6)$$

Because D is a pairwise functional, $\mathbb{E}[\hat{D}]$ does not depend on m_q : an exponent estimated at $m=40$ transfers to deployment at $m=8$.

4.3 Tempering map

Shrinkage. Positive-part James–Stein with a significance floor ν :

$$\tilde{D} = \text{sign}(\hat{D}) \max(0, |\hat{D}| - \nu^2 \text{SE}^2 / |\hat{D}|), \quad (7)$$

with dead zone $\{|r| \leq \nu\}$; $\nu_{\text{dev}} = 1.28$, $\nu_{\text{LF}} = 2.33$. With $\nu = 1$, (7) is exactly the empirical-Bayes posterior mean under a $\mathcal{N}(0, \tau^2)$ prior with plug-in $\hat{\tau}^2 = \max(0, \hat{D}^2 - \text{SE}^2)$ (James and Stein, 1961). The map is odd, continuous, never exceeds $|\hat{D}|$, and is monotone in $\hat{D}$ and anti-monotone in SE.

Link. Model $\varphi | y \sim \mathcal{N}(\mu_y, s^2)$ within item with the *mixture* standardized to unit variance, which is what (2) enforces, so $s^2 = 1/(1 + \bar{p}(1 - \bar{p})u^2)$ where $u = \sqrt{2} \Phi^{-1}(\frac{1+\tilde{D}}{2})$ and $\bar{p}$ is the base rate of correct traces. The Bayes-optimal per-trace log-weight coefficient is then

$$\gamma^* = \frac{u}{s} = u \sqrt{1 + \bar{p}(1 - \bar{p})u^2}, \quad (8)$$

capped at γ_{max} (4 dev, 2 label-free). The uncorrected link $\gamma = u$ under-weights strong channels by up to $\sim 50\%$ at $D = 0.9$. The link assumes φ is within-item normal, which (2) supplies only asymptotically: at $m_q=4$ the score takes four values before standardization. The scale consequence is handled by using the realized σ_q , but the distributional one is not, and it bites hardest in the small-budget setting this paper advertises ($m=40$ estimates transferring to $m=8$). Where $\hat{D}$ saturates the cap binds and the link’s shape is irrelevant; small m is where it has to hold and where it is least justified.

4.4 tact in one expression

Two simplifications collapse the pipeline. Factoring $\hat{D}$ out of (7) makes the shrinkage a multiplicative gain in the pooled z -statistic $\zeta = \hat{D}/\text{SE}$ alone, and substituting $u = \sqrt{2}z$ with $z = \Phi^{-1}(\frac{1+\tilde{D}}{2})$ into (8) removes the nested radical. TACT is then

$$\boxed{\begin{aligned} \hat{a}_q &= \arg \max_A \sum_{i: a_{q,i}=A} \exp(\gamma \varphi_{q,i}), \\ \gamma &= \left[z \sqrt{2 + 4\bar{p}(1 - \bar{p})z^2} \right]_{-\gamma_{\text{max}}}^{\gamma_{\text{max}}}, \end{aligned}} \quad (9)$$

$$z = \Phi^{-1}\left(\frac{1}{2}[1 + \hat{D}(1 - \nu^2/\zeta^2)_+]\right), \quad \zeta = \frac{\hat{D}}{\text{SE}}, \quad (10)$$

with $\hat{D}$ from (5) and φ from (2). At the default $\bar{p} = \frac{1}{2}$ the exponent is exactly

$$\gamma = z \sqrt{2 + z^2}, \quad z = \Phi^{-1}\left(\frac{1+\tilde{D}}{2}\right), \quad (11)$$

one probit and one square root, where $\tilde{D}$ is the shrunk *pooled* statistic of (7) and not the per-item AUC_q of (5). Nothing in it is fitted to outcomes: ν is a significance level and γ_{max} a clip, both fixed before any data is seen. The clip is not cosmetic, though. Where $\hat{D}$ saturates it binds, and the vote then sees γ_{max} rather than the derived magnitude (Section 8). The dead zone is now visible as a single condition, $|\zeta| \leq \nu$, on which γ

Algorithm 1 TACT: derive the exponent, then vote

Require: labeled dev pools $\mathcal{D}$, test pools $\mathcal{T}$, budget K , floor ν , cap $\gamma_{\max}$
Ensure: one scalar γ ; an answer $\hat{a}_q$ for each $q \in \mathcal{T}$

```

1:  $\mathcal{S} \leftarrow \emptyset$ ,  $H \leftarrow \emptyset$ 
2: for  $q \in \mathcal{D}$  do
3:    $y_i \leftarrow \mathbf{1}[a_{q,i} = a_q^*]$ ,  $i \leq K$ ;  $H \leftarrow H \cup \{y\}$ 
4:   if  $0 < \sum_i y_i < K$  then ▷ informative items only
5:      $R \leftarrow$  within-item midranks of  $c_{q,1:K}$ 
6:      $D_q \leftarrow 2U_q / (n_q^1 n_q^0) - 1$ ,  $U_q$  from  $R$ 
7:      $\mathcal{S} \leftarrow \mathcal{S} \cup \{(D_q, N_q, \text{Var}_0(D_q))\}$ 
8:    $\hat{D} \leftarrow \sum_q N_q D_q / \sum_q N_q$  ▷ van Elteren
9:    $\text{SE} \leftarrow \max\{\text{SE}_0, \text{SE}_J, 1/(2\sqrt{N})\}$ 
10:   $\bar{p} \leftarrow \text{clip}(\text{mean}(H), 0.05, 0.95)$ 
11:   $\zeta \leftarrow \hat{D}/\text{SE}$ 
12:  if  $|\zeta| \leq \nu$  then ▷ dead zone
13:     $\gamma \leftarrow 0$ 
14:  else
15:     $\tilde{D} \leftarrow \hat{D}(1 - \nu^2/\zeta^2)$  ▷ positive-part JS
16:     $z \leftarrow \Phi^{-1}((1 + \tilde{D})/2)$ 
17:     $\gamma \leftarrow \text{clip}(z\sqrt{2 + 4\bar{p}(1 - \bar{p})z^2}, \pm\gamma_{\max})$ 
18: for  $q \in \mathcal{T}$  do
19:   if  $\gamma = 0$  then
20:      $\hat{a}_q \leftarrow \text{SC}(a_{q,1:K})$  ▷ same routine, bit-identical
21:   else
22:      $\varphi \leftarrow$  standardized van der Waerden scores of  $c_{q,1:K}$ 
23:      $\hat{a}_q \leftarrow \arg \max_A \sum_{i: a_{q,i}=A} e^{\gamma\varphi_i}$ 
24: return  $\gamma, \{\hat{a}_q\}$ 
    
```

is identically zero and (9) is bitwise SC by Proposition 1. Equations (9)–(11) are verified equivalent to the shipped implementation over randomised inputs including every boundary (`tests/test_formula.py`).

Algorithm 1 states the labeled path end to end. Both loops cost $O(K \log K)$ per item, dominated by the within-item ranking, and the estimate is a single scalar: nothing item-specific crosses from dev to test, which is what makes the dead zone a global abstention rather than a per-item one.

4.5 Anchor properties

Proposition 1 (Exact sc reduction) *At $\gamma = 0$, (3) equals plain SC as a function on every trace pool, including tie-breaks. Under $D = 0$, $P(\gamma = 0) \rightarrow 2\Phi(\nu) - 1$ (80% dev, 98% label-free), and γ is continuous through the dead-zone boundary, so a false positive applies an infinitesimal exponent.*

Proposition 2 (Exact CISC reduction) *With the feature map $\varphi_{q,i}^{\log} = \log c_{q,i} - \overline{\log c_q}$, the weights equal $\lambda_q c_{q,i}^\gamma$, with a per-item constant $\lambda_q > 0$ (distinct from the coupling κ of (1)); hence the argmax, the ties, and the normalized vote shares coincide with CISC-power(γ) on every pool.*

Proposition 3 (Regularity) *The composite $g(\hat{D}, \text{SE})$ is continuous, odd, nondecreasing in $\hat{D}$, nonincreasing in SE in magnitude, with $g(D, 0^+) = \gamma^*(D)$.*

Proofs are elementary and pinned by unit tests in the released code (102 tests; the permutation-verified null variance, the EB identity in (7), and the link derivation (8) are each tested numerically).

5 Label-Free Estimation

5.1 Pipeline

(i) *Dedup*: single-linkage duplicate groups on the lexical-similarity channel at 0.95; each trace gets weight $1/|\text{group}|$ for plurality determination and pair weighting. (ii) *Pseudo-label*: $g_{q,i} = \mathbf{1}[a_{q,i} = M_q]$ with M_q the dedup-weighted plurality. (iii) *Margin gate*: keep the top 60% of items by dedup-weighted margin. (iv) Compute (5) with $\text{lab} = g$, giving $(\hat{D}_g, \text{SE}_g, r_g)$.

Two orderings in Algorithm 2 are load-bearing. The significance gate on line 17 tests the *raw* z_g , whose sign is unbiased by Proposition 4, while the tempering on line 19 uses the de-attenuated pair; testing the inflated statistic instead would let the de-attenuation manufacture significance. And $\bar{p}$ is left unset on the label-free path, so the mixture correction of (8) is not applied there: the base rate is exactly what no label-free estimator knows.

5.2 Sign consistency and its boundary

Proposition 4 (Attenuation identity) *Let $\bar{p}$ be the pair-weighted probability that an item’s plurality is wrong. If the plurality-error event is independent of φ given y (class-conditional noise), then $\mathbb{E}[\hat{D}_g] = (1 - 2\bar{p})D$. In particular $\text{sign } \mathbb{E}[\hat{D}_g] = \text{sign } D$ whenever $\bar{p} < 1/2$: the label-free estimate can only under-trust, never mis-sign.*

The identity fails when the flip is *caused* by confidence, that is, under a confident echo. There the observable law under {majority right, $D < 0$ } and {majority wrong via confident echo, $D > 0$ } is identical (the two-root ambiguity of Parisi et al. (2014) restated for a single channel), so any label-free guarantee is necessarily conditional; it is stated as such rather than papered over.

5.3 De-attenuation and alarms

Split-half agreement over $R=20$ random half-splits estimates $\alpha = p^2 + (1 - p)^2/k$ under a one-coin model with k effective wrong alternatives (inverse-Simpson), inverted as $p = [1 + \sqrt{1 - (k+1)(1 - k\alpha)}]/(k+1)$; $\hat{D}_g$ is divided by the *upper* 95% bootstrap bound of $2p - 1$ (floored at 0.2), which can only under-inflate. Four alarms force $\gamma = 0$: duplicate collapse (median Kish ratio < 0.5), sign-aware margin-decoupling, root ambiguity in the split-half

Algorithm 2 TACT-LF: recovering the sign without labels

Require: pools $\mathcal{P}$, budget K , dedup threshold $\theta=0.95$, margin quantile $\beta=0.40$, floor ν_{LF} , cap γ_{max} , splits $J=20$, attenuation floor 0.20, minGated; $\hat{\eta}$ below is the estimated attenuation $1 - 2\bar{\rho}$, not $\bar{\rho}$

Ensure: γ , equal to 0 whenever any alarm fires

```

1: for  $q \in \mathcal{P}$  do
2:    $w_i \leftarrow 1/|\text{group}(i)|$  from single linkage at  $\text{dup} \geq \theta$ 
3:    $M_q \leftarrow \arg \max_A \sum_{i:a_{q,i}=A} w_i$  ▷ dedup-weighted plurality
4:    $\text{mgn}_q \leftarrow$  top-two dedup-weighted share gap
5:    $G \leftarrow \{q : \text{mgn}_q \geq Q_\beta(\text{mgn}), \geq 2 \text{ distinct answers}\}$ 
6:    $E_1 \leftarrow [\text{median}_q(\text{Kish ratio}) < 0.5]$  ▷ duplicate collapse
7:    $E_4 \leftarrow [|G| < \text{minGated}]$ 
8:    $g_{q,i} \leftarrow \mathbf{1}[a_{q,i} = M_q]$  for  $q \in G$ 
9:    $(\hat{D}_g, \text{SE}_g, z_g) \leftarrow$  pooled statistic over  $G$  using  $g$ 
10:   $s \leftarrow \text{sign}(\hat{D}_g)$  ▷ estimated trust direction
11:   $E_2 \leftarrow [\psi(s) > 0.05]$  ▷ sign-aware margin decoupling
12:   $\alpha \leftarrow$  mean two-half plurality agreement over  $J$  splits
13:   $k \leftarrow$  inverse-Simpson size of the non-plurality mass
14:   $p \leftarrow [1 + \sqrt{1 - (k+1)(1 - k\alpha)}]/(k+1)$ 
15:   $E_3 \leftarrow [\text{discriminant} < 0.02]$  ▷ root ambiguity
16:   $\hat{\eta} \leftarrow \text{clip}(\text{UCB}_{95}(2p - 1), 0.20, 1)$ 
17:  if  $E_1 \vee E_2 \vee E_3 \vee E_4$  or  $|z_g| \leq \nu_{\text{LF}}$  then
18:    return 0 ▷ refuse; the vote stays SC
19: return Temper( $\hat{D}_g/\hat{\eta}$ ,  $\text{SE}_g/\hat{\eta}$ ) with  $\bar{p}$  unset
    
```

quadratic, and insufficient gated items. The margin-decoupling alarm must condition on the estimated trust direction: a sign-naïve version (“plurality has the highest mean φ ”) false-alarms on every benign anti-correlated channel—a defect encountered, diagnosed, and fixed during development, and pinned by the released tests. Finally the significance gate acts on the *raw* z (unbiased sign under Proposition 4) and temper on the de-attenuated value. A semi-label-free mode takes only the sign from ~ 50 dev labels, routing it into the pipeline and disabling only the proxy-sign alarm; this purchases immunity to the ambiguity above at negligible labeling cost.

6 Heterogeneity: Impossibility and Escape

6.1 Per-item adaptation is closed under i.i.d. coupling

Suppose $\kappa_q \stackrel{\text{iid}}{\sim} \mathcal{N}(0, 0.6^2)$ with no observable covariate.

Proposition 5 (Self-reinforcement) *Any per-item rule $\gamma_q = h(\hat{D}_q^g)$ with h monotone increasing and odd reinforces the plurality on both branches: $\hat{D}_q^g > 0$ up-weights confident traces, which agree with the plurality; $\hat{D}_q^g < 0$ up-weights unconfident traces, which are again the plurality side.*

Remark 6 *Measured in this harness, such a rule agrees with SC on 97.5% of items and its residual flips are net-harmful (1 right vs. 9 wrong per 400 items).*

Remark 7 (Winner’s curse) *This is a measurement in the present harness rather than a theorem: on plurality-wrong items with $|D_q| > 0.3$, the items where a flip could win, the agreement statistic’s sign matches the true sign only 4% of the time.*

Proposition 8 (Two-world unidentifiability) *Let $w_1 = \{\kappa > 0, \text{ minority correct}\}$ and $w_2 = \{\kappa < 0, \text{ plurality correct}\}$. Computed against either truth, $D^{w_1} = -D^{w_2}$, so the statistic TACT uses cannot order the two worlds. When the item has exactly two answer clusters the laws of (a, c) coincide outright and no label-free method can separate them. With three or more populated clusters they do not coincide: under w_1 only the correct minority carries elevated confidence, whereas under w_2 every non-plurality cluster does, so the conditional law of c on a third cluster separates them (verified numerically; the two laws agree on the top two clusters and differ with KS $p < 10^{-15}$ on the third). The impossibility is therefore conditional on the pool being effectively binary, which is the regime the confident-echo cell occupies: 88% of its items have no third cluster at $K=15$. TACT does not exploit the residual signal, and no published method does either; doing so is left open.*

Consequently the per-item oracle (0.973 in this harness) is unreachable, and the honest behaviour is to fall back to the global estimate, which TACT’s dead zone does: in the i.i.d. cell every variant returns bitwise SC (zero discordant pairs).

6.2 TACT-group

Real heterogeneity is typically indexed by an observable covariate (domain, question type). With κ indexed by a group label, running the estimator per group keeps every group inside the operating regime of Sections 4–5; groups with fewer than 30 dev (or 60 unlabeled) items fall back to the global estimate, which Propositions 5–8 show is the only defensible default.

7 Experimental Setup

Harness. A cluster-mixture oracle generates, per item, up to $K_{\max}=20$ cached traces with answers, confidences (1), and two similarity channels; all methods replay identical pools (paired comparisons, exact McNemar tests). Voting budget $K=15$; 400 items per cell on the sweep, 600 for the group study; dev splits of 200 (primary) and 50 (small-dev).

Regimes. The κ sweep $\{-0.6, \dots, +0.6\}$; three strictly monotone confidence distortions (compression toward 0.5, over-confident sigmoid, fourth power), rank-preserving by construction, so discrimination is intact while calibration is destroyed; i.i.d. heterogeneity ($\kappa_q \sim \mathcal{N}(0, 0.6^2)$); covariate-structured heterogeneity (three groups at $+0.6/0/-0.6$); and a confident-echo poison (a wrong cluster echoes verbatim with confidence 0.95).

Baselines. SC; CISC-power with $\gamma \in \{0.25, \dots, 4\}$; *CISC-devT*, the published dev-calibrated protocol (positive grid picked on dev); a binary ECE gate; *SignGrid-dev*, the strongest trivial baseline (signed exponent grid picked on dev); and the test-set oracle over signed fixed exponents as the upper envelope. The group study adds the naive self-referential per-item method as a negative control and the per-item link oracle as the ceiling.




Figure 2: Main result on the confidence-usage frontier. TACT-dev and the fully label-free TACT-LF track the signed oracle across the sweep; CISC-devT and the ECE gate sit at the SC floor for all $\kappa < 0$.

Pre-registered falsifiers. The decision rule is stated here because the protocol is offered as a contribution. Each falsifier is an exact paired McNemar test on the 400 items of a cell, at $\alpha = 0.05$ one-sided, with the seed-level bootstrap of Section 8.6 as the second gate: a falsifier fires when the single-cell test is significant *and* the across-seed interval excludes zero. Single-cell tests at this size are underpowered against a strong baseline, which is the reason for the second gate; the earlier fixed $\tau = 0.02$ tolerance is retained only as a reporting convenience in the tables. F1: TACT-dev below the best fixed- γ CISC at $\kappa = +0.6$ by more than τ . F2: either variant below SC by more than τ anywhere on the sweep. F3: the label-free variant fails to beat the ECE gate on sweep average. F4: CISC-devT or SignGrid-dev within τ of TACT-dev everywhere, including the distortion, heterogeneity, and small-dev cells. F4 is the falsifier this matters most for: on a single cell the TACT-minus-SignGrid comparison never reaches significance anywhere on the sweep (smallest $p = 0.08$ at $\kappa = +0.1$), and it is the ten-seed bootstrap that resolves the mid-range gap as systematic. A protocol that had reported only the single-seed tests would have called the mid-range a tie.

8 Results

8.1 Signed recovery, with and without labels

Table 1 and Fig. 2 give the sweep. Three observations. First, the published protocols never leave the floor on $\kappa < 0$: CISC-devT’s grid is positive-only and the ECE gate never opens (dev ECE ranges 0.10–0.80 across the sweep while the signal’s discrimination is perfect at the extremes). Second, the label-free variant matches the 200-label variant nearly point-

Table 1: Coupling sweep (accuracy at $K=15$; 400 paired items per cell; dev $n=200$). Published protocols sit at the SC floor on the entire negative half-axis.

κ	SC	ECE	devT	SignGrid	tact-dev	tact-LF	oracle
-0.6	.762	.762	.762	1.000	1.000	1.000	1.000
-0.4	.805	.805	.805	1.000	1.000	1.000	1.000
-0.2	.750	.750	.750	.985	.975	.975	.985
-0.1	.750	.750	.750	.915	.900	.890	.915
0.0	.745	.745	.760	.760	.745	.745	.772
+0.1	.777	.777	.932	.932	.907	.907	.932
+0.2	.760	.760	.985	.985	.978	.978	.985
+0.4	.785	.785	1.000	1.000	1.000	1.000	1.000
+0.6	.780	.780	1.000	1.000	1.000	1.000	1.000

Table 2: Adversarial regimes (accuracy at $K=15$). “Oracle” is the test-set best over *raw-value* weight policies; rank invariance beats that entire family under compression.

Regime	SC	devT	SignGrid	tact-dev	tact-LF	
Monotone compress	.775	.963	.963	1.000	1.000	
Monotone overconf	.775	1.000	1.000	1.000	1.000	†alarm fires and the method
Monotone power	.775	1.000	1.000	1.000	1.000	
Hetero (i.i.d.)	.765	.765	.765	.765	.765	
Confident echo	.190	.190	.568	.615	.190†	

refuses to leave SC: the conditional guarantee of Prop. 4 working as stated.

for-point—at $\kappa=-0.6$ the raw agreement statistic is $\hat{D}_g = -0.81$ with $z = -17.6$, and the CCN identity’s sign guarantee holds as predicted, yielding 1.000 with zero labels. Third, at $\kappa = 0$ the dead zone returns $\gamma = 0$ exactly, so the paired accuracy difference to SC is identically zero—“non-inferior” is replaced by “identical.”

Where the derived exponent actually operates. The four cells that carry the headline 1.000 ($\kappa = \pm 0.4, \pm 0.6$) are cells where $\hat{D}$ saturates, so the link returns an untempered γ^* between -8.4 and $+12.1$ across the seven saturated cells and the cap $\gamma_{\max} = 4$ is what the vote actually sees; the derived magnitude is not doing the work there, the sign is. Conversely, at $\kappa = \pm 0.1, \pm 0.2$, where the derived value lands strictly inside the cap ($|\gamma|$ from 1.10 to 2.91), TACT-dev trails the dev-picked signed grid on all four cells (0.900 vs. 0.915; 0.907 vs. 0.932; 0.975 vs. 0.985; 0.978 vs. 0.985). Read together: against the *published* protocols the advantage is large and comes from representing the sign at all, whereas against a signed grid the analytic map is not better at choosing a magnitude on these cells. Its advantage over the grid is elsewhere, in the three cells named in C4, and the one place the interpolation itself pays is confident echo, where $\gamma = -1.198$ falls between grid points and beats the grid optimum $\gamma = -1$ (0.615 vs. 0.568).




Figure 3: Adversarial regimes. Dotted line: the oracle over raw-value weights. Left group of bars: rank invariance beats that family under compression; right: the labeled variant counters the confident echo while the label-free variant alarms and refuses.

8.2 Rank invariance where raw values fail

Under monotone compression (Table 2, Fig. 3) all confidences huddle near 0.5, so every c^γ -family weight is nearly uniform: even the *oracle* over raw-value policies reaches only 0.963. TACT’s rank scores are untouched by the distortion and both variants reach 1.000. Under the confident echo, dev labels reveal the inversion (high confidence $\Rightarrow$ wrong) and TACT-dev counters with $\gamma = -1.20$, the best result in the field (0.615; $3.2\times$ the SC floor); label-free, the duplicate-collapse alarm fires and the method correctly refuses—by Proposition 8 no label-free method could do better than a coin flip on the sign here, since 88% of the cell’s items are effectively binary and the escape the proposition identifies is unavailable on them; pretending otherwise would be the real failure.

8.3 Heterogeneity

Table 3 and Fig. 4 give the group study. In the covariate-structured cell, per-group TACT recovers each group’s signed coupling (dev $\{+4.0, 0.0, -4.0\}$, label-free $\{+2.0, 0.0, -2.0\}$, the $\kappa=0$ group correctly dead-zoned—and cracks the floor that provably binds every global policy: the label-free variant reaches 0.923, within 0.023 of the per-item link oracle, with *zero* paired losses to SC over 600 items ($+83/-0$, $p = 2.1 \times 10^{-25}$). In the i.i.d. cell every method sits at the floor with zero discordant pairs, the naive self-referential control included: it cannot beat the plurality it is derived from. That control is the empirical face of Propositions 5–8, and the grouped cell is where it shows: given the same covariate the per-group estimator exploits, it reaches 0.787 against the 0.785 floor, two items in 600. The two arms land within seed noise of each other here (0.923 and 0.927 on one seed;

Table 3: Heterogeneity study (600 paired items; $K=15$).

Method	Grouped	i.i.d.
SC (floor)	.785	.752
TACT global (dev)	.785	.752
TACT-group (dev)	.927	.752
tact-group (label-free)	.923	.752
Naive per-item (neg. control)	.787	.752
Per-item link oracle (ceiling)	.947	.973




Figure 4: Structured vs. i.i.d. heterogeneity. Left: with an observable covariate, per-group TACT (label-free) approaches the per-item oracle from the 0.785 floor with zero losses to SC. Right: the provably closed i.i.d. cell—every method at the floor, the negative control included.

0.929 ± 0.015 each over five). A natural explanation would be the arms' different exponent caps; the ablation rules it out. Sweeping the cap over $\{1, 2, 3, 4, 6, 8\}$ moves neither arm at all (spread 0.0000 for both), so the cap is not load-bearing in this cell and the difference is sampling variation.

Table 4: What the test suite verifies. Every proposition in the paper has an executable counterpart; the counter-tests fail deliberately on rejected alternatives so a regression cannot silently reinstate them.

Claim	Evidence
Prop. 1 (exact SC)	identical incl. ties, 200 pools; dead-zone rate $>70\%$ under $D=0$
Prop. 2 (exact CISC)	identical vote shares, 100 pools
Prop. 4 (attenuation)	$\rho \in \{.1, .25, .4\}$, abs. .06
Props. 5–8	97.5% SC agreement; 4% sign match; the two-world boundary is pinned both ways (binary pools indistinguishable, a populated third cluster separates them at KS $p < 10^{-10}$)
Rank invariance	3 distortions $\times$ 100 pools
Estimator internals	permutation null variance (3,000 draws, 10% tol.), JS-EB identity to 10^{-12} , link (8) to rel. 10^{-9} , permutation-invariance regression
Rejected alternatives	Kish ESS and the SAFE-under-VoI guarantee each have a test asserting their <i>failure</i>

8.4 Small dev sets and falsifiers

With dev $n=50$ the conclusions are unchanged (1.000 at $|\kappa|=0.6$; 0.978 at -0.2): the SE-aware shrinkage degrades smoothly rather than catastrophically. All four falsifiers survived: F1 (1.000 vs. 1.000), F2 (bit-identical at $\kappa=0$; nowhere more than the pre-registered 0.02 accuracy tolerance below SC), F3 (sweep means 0.944 vs. 0.768), and F4 (both grid baselines trail by 0.037 and 0.047 on the distortion and echo cells, and neither can operate without labels). On the single seed the paired tests against SignGrid-dev are not significant anywhere ($\kappa = -0.2$: 3/7 discordant, exact $p = 0.34$; $\kappa = +0.1$: 8/18, $p = 0.08$), and the ten-seed intervals of Section 8.6 are what establish the mid-range deficit. Against SignGrid-dev the honest margin is narrow on the homogeneous sweep—TACT even trails by 0.007–0.025 in the mid-range, the deliberate cost of shrinkage—and the net advantage concentrates exactly where pre-registered: distortion (+0.037), echo (+0.047), and label-free operation, which no grid can perform.

8.5 Verification of the implementation

Because every claim in Sections 4–6 is a mathematical property rather than an empirical trend, the released code pins each one with an executable test; the suite is 102 tests covering TACT and the follow-on work. Table 4 maps propositions to the tests that would fail if they stopped holding.

Two entries deserve comment. The permutation-invariance test was added after a defect in which the memoisation key made the *test* pass while the estimator itself was order-dependent by up to 0.10; it now calls the internal routine directly. And the last two rows

are counter-tests that assert *failure* of rejected alternatives — the Kish effective-sample-size formulation and the claim that the shipped default honours the SAFE stopping guarantee — so that neither can be silently reinstated by a later change.

8.6 A harness artifact, and dispersion across seeds

Two corrections to the synthetic results, both found by re-running what had been single-seed measurements.

Tie-breaking was rewarding SC for free. The generator assigned the correct answer the code 0 on every item, and `argmax` breaks ties toward the lowest index, so on any item whose vote was tied plain SC chose correctly by construction: 67.7% on near-tied items against 50.4% for a random tie-break, with 31.8% of items tied at $K=15$. Every method that perturbs the weights off integers forfeits that subsidy, so the artifact inflated the baseline and penalised the proposed method. It also produced a spurious falsifier: at $\kappa = 0$, TACT-dev averaged 0.797 against SC at 0.818 across ten seeds, tripping F2, while the exponents responsible were $|\gamma| \leq 0.05$. The items were near-ties whose tie-break had moved, not items the exponent had reweighted. Answer codes are now permuted per item. With the artifact removed the two coincide exactly where the dead zone should hold: $\kappa = 0$ gives 0.745 for both methods and heterogeneous- κ gives 0.765 for both (ten-seed means 0.758 and 0.768, zero discordant pairs in every seed): the dead zone behaves as Proposition 1 states. All synthetic numbers in this paper are post-fix.

Dispersion. Ten seeds per cell, 400 paired items each, bootstrap over seeds. The extremes are stable to the third decimal (1.000 ± 0.001 at $|\kappa| \geq 0.4$). The mid-range deficit against SignGrid-dev is small but real rather than noise: -0.013 $[-0.017, -0.009]$ at $\kappa = -0.2$, -0.016 $[-0.024, -0.009]$ at -0.1 , -0.012 $[-0.018, -0.005]$ at $+0.1$, -0.013 $[-0.019, -0.008]$ at $+0.2$, all $p < 0.001$. So is the advantage where the paper claims it: $+0.032$ $[+0.027, +0.037]$ on monotone compression and $+0.048$ $[+0.037, +0.059]$ on confident echo. The one cell that changes sign under the fix is heterogeneous- κ , now $+0.011$ $[0.000, +0.031]$ rather than a loss. Reporting a single seed would have hidden both the artifact and the fact that the mid-range gap is systematic.

8.7 Real-trace validation

Validation on real traces used Claude Haiku 4.5 as the frozen model: 100 items, 50 from GSM8K (Cobbe et al., 2021) and 50 from CommonsenseQA, with 12 independent chain-of-thought traces and a verbalized confidence per item (1,200 traces total), evaluated at $K=12$ with a 40/60 dev/test split. Four findings.

(a) *The calibration–discrimination distinction reverses on real data, and TACT reads it correctly.* The channel is *extremely well calibrated* in the usual sense: ECE = 0.016, far inside the 0.10 gate, so a binary ECE gate *opens* and hands the channel to CISC. Yet the measured within-item discrimination is $\hat{D} = -0.219$ with SE = 0.176 ($z = -1.24$): no usable signal, and what little there is points the *wrong way* (math -0.515 , commonsense -0.173 ; both groups negative). This is the exact mirror image of the synthetic case in which ECE wrongly *closed* the gate on a discriminative channel (Section 3): on real traces ECE wrongly *opens* it on a non-discriminative one. Calibration is uninformative about voting utility in both directions, and a signed discrimination statistic is what distinguishes them.

(b) *The dead zone fires, and costs exactly nothing.* With $|z| < \nu$, TACT-dev, TACT-LF and TACT-group all return $\gamma = 0$ and are bit-identical to SC on every test item (+0/−0 discordant pairs, $p = 1$). All methods score 0.917. This is the pre-registered null-direction prediction of Section 9 confirmed on real data: where the channel carries no signal, the method is free.

(c) *Saturation is the binding constraint, not the estimator.* Trace-level accuracy is 0.958 on GSM8K and 0.847 on CommonsenseQA, so only 12 of 100 items contain both a correct and an incorrect trace, the only items a within-item rank statistic can use. The estimator is not underpowered by design; the benchmark simply does not present the model with enough genuine uncertainty. Exposing non-null coupling on a strong model requires harder item pools, not more traces per item.

(d) *Verbalized confidence is tie-heavy.* Two values (0.99, 0.95) account for 49% of all reports, activating the tie-safe degeneration path of (2) on many items.

(e) *The abstention is a measurement, and a fragile one here.* A rule that never acts reproduces (b) exactly, so the campaign on its own separates a working safety mechanism from an absent signal not at all. Three replays of the same cached pools separate a little more. *Stability:* bootstrapping the items, the dev gate opens in 50.4% of resamples—with $|z| = 1.24$ against $\nu = 1.28$ the reported abstention is a 3% margin, not a reading of the evidence—while the label-free gate opens in 16.2%—though finding (f) will show that figure describes the significance gate alone. *Specificity:* permuting confidences within items, which preserves the real marginals, ties, pool composition and difficulty and destroys only the coupling, puts the false-open rate at 18.4% against a nominal 20% (1.6% against 2% label-free), with the null z at mean -0.002 and SD 0.954. The dead zone’s null behaviour is therefore calibrated on the real substrate and not only on the generator it was derived from, which is the one piece of evidence here that the mechanism is doing work. *Cost:* overriding the gate, the derived $\gamma = -0.40$ would have scored 0.933 (+1/−0) and a gold-label oracle reaches 0.950 at $\gamma = -1.25$, a ceiling of two items. Neither approaches significance, so the substrate is null in the way that matters; but the sign the estimator derived is the sign the oracle wanted, and (b) should be read as *costs nothing measurable at this n* rather than as a demonstration that abstaining was right.

(f) *What the gate could have detected here.* Finding (e) measures specificity; sensitivity needs a channel of known strength, so one is planted into these same pools—real answers, difficulty and duplication untouched, only the confidence vector replaced, conditioned on the real correctness pattern. Planting only the estimator’s own location-shift model would prove nothing (the invariance-group pitfall of Section 9), so four families are swept: the Gaussian location shift; the same shift under Laplace noise, violating the link’s normality assumption while preserving D ; a rank-concentrated channel that forces the top-confidence slot onto a correct trace; and a variance-only channel, informative but unsigned. Four results, 40 seeds per cell. *One:* the gate’s operating characteristic is a function of the realized $|\hat{D}|$ and not of the family—half-power near $|\hat{D}| = 0.247$ (Gaussian) and 0.208 (Laplace), full power by ≈ 0.49 on both, and the derived exponent captures the entire oracle gain from $|\hat{D}| \approx 0.83$ upward on both—so detection is a property of the rank functional rather than of the generator, and the link survives the normality violation. The measured channel of (a), $|\hat{D}| = 0.219$, sits at the half-power floor: finding (e)’s coin flip restated as an operating characteristic. *Two:* conditional on the gate opening, the sign is never wrong, in any cell

of any family. *Three:* the scope boundaries are real. The rank-concentrated channel yields $|\hat{D}| \leq 0.183$ at full strength—a pooled pair statistic barely sees information carried by a single rank position—and leaves the derived gain near zero where a gold-label exponent takes $+0.039$; the unsigned channel is invisible by construction and the gate correctly holds its nominal false-open rate on it. *Four, a defect:* the label-free arm never acts in any cell, even on a saturating channel with the item floor lowered to one, because with 85 of 100 items unanimous the margin gate’s 40%-quantile cut equals 1.0, and no item satisfies margin ≥ 1.0 with two distinct answers. Its abstention in (b) was therefore structural rather than a reading of the channel, and on saturated substrates the quantile gate needs an absolute cut.

Scope of this first campaign: one model, two benchmarks, $K=12$. It confirms the null-direction prediction and the calibration–discrimination argument, and it is not evidence that TACT improves accuracy, since the channel carried no signal to exploit. Finding (c) predicts what to do about that, and Section 8.8 does it.

8.8 Confirmatory campaign on harder items

Finding (c) predicts that a channel measured as null on saturated benchmarks should become measurable on items the model finds genuinely uncertain. A pre-registered follow-up tests that prediction: 119 MATH level-5 problems (Hendrycks et al., 2021; Lightman et al., 2024), 16 traces each from the same frozen model, a 30-item sign set and an 89-item evaluation set drawn from the registered list before any trace was collected, and five hypotheses (H1–H5) fixed in advance.

The channel is real. On the evaluation set the pooled statistic is $\hat{D} = +0.250$ with $SE = 0.098$, so $z = +2.54$ and H1 passes. This is the first real-trace evidence that verbalized confidence carries positive within-item discrimination; the same measurement on GSM8K/CommonsenseQA gave -0.219 ($z = -1.24$).

The endpoint was unpassable for any method. The realized substrate saturated again: per-trace accuracy 0.819, SC 0.888, a decisive stratum of 10 of 89 items, and the correct answer present in the pool on only 4 of those. The in-pool *oracle* therefore tops out at $+4/-0$, exact one-sided $p = 0.0625$. H2 fails, but it fails for every conceivable aggregation method including a perfect one, so the failure is a property of the substrate rather than of the estimator.

Abstention behaved as designed. TACT returned $\gamma = 0$, with alarms E4 and E2 firing on the label-free path and the sign set holding too few informative items to supply a semi-label-free sign. The vote is therefore bit-identical to SC at 0.888 (H3, H4 pass). The cost of acting anyway is visible in the same table: best-single-confidence, the trivial baseline that always trusts the channel, loses 4.5 points at 0.843.

One caveat from this campaign transfers beyond TACT. Measured difficulty depended on the collection protocol: a 30-problem-per-call probe put level-5 plurality accuracy at 0.40, while the 15-problem-per-call confirmatory run yielded 0.888 on the same stratum. Batch size belongs in the experimental record whenever traces are collected in batches.

Table 5: Confirmatory campaign, MATH level-5 evaluation set (89 items, $K=16$). Every method replays the same cached pools. The duplication channel is inert because no reasoning text was collected, so dedup-SC coincides with SC by construction.

Method	Accuracy	net vs. SC
SC / dedup-SC / CISC-linear	0.888	—
TACT-LF	0.888	+0/ − 0
TACT-semi-LF	0.888	+0/ − 0
best-single-confidence	0.843	+1/ − 5
in-pool oracle (ceiling)	0.933	+4/ − 0

8.9 How wide is the addressable stratum?

Both campaigns failed their endpoint for the same reason, which suggests measuring that reason directly. Define the *window* as the fraction of items where the plurality is wrong *and* the correct answer is present in the pool: the ceiling for any label-free aggregation method, since nothing outside it can be changed.

The window was measured on five substrates spanning two domains (Table 6). For code generation, where an executable test suite supplies per-sample ground truth and the window might reasonably be expected to widen, 40 LeetCode Medium/Hard problems (Xia et al., 2025) were solved 8 times each and graded against the benchmark’s hidden suites, with the baseline taken as the largest behavioural cluster over probe inputs (never expected outputs). The window is $3/40 = 7.5\%$ (CI_{95} 2.6–19.9%): wider than label-free QA, but the same order, and the composition is the same shape at 30 saturated, 7 capability wall and 3 rescuable, i.e. 75/17.5/7.5%. Nor does budget open it. The seven capability-wall problems produced zero correct solutions in 224 further attempts (per-problem 95% upper bound on the pass rate 0.088), and extrapolating oracle@ N shows the window saturating by $N=32$.

One precaution belongs with these numbers, because omitting it would have inverted them. The grading harness was validated against the benchmark’s own reference solutions before any candidate was scored: 178 of 180 pass under the sandbox’s resource limits. The check is not a formality: a sandbox whose resource limits the host rejects outright fails 100% of executions, and that condition presents as a candidate failure rather than as an error. Studies that grade by execution should report their reference-solution pass rate for the same reason a calibration curve is reported: without it, a broken harness and a capability wall look identical.

8.10 A third axis: reasoning budget

Difficulty is not the only way to lower per-sample accuracy. Constraining the reasoning budget lowers it while leaving the correct answer inside the model’s competence, which is the combination the decisive stratum needs and that difficulty does not supply: as items harden they pass from saturated to capability-limited without pausing in between. A paired run tests this on the same 119 items, same model, same K , with the model instructed to answer without writing any working.

Table 6: The addressable stratum across substrates, on one definition throughout: *decisive* is the fraction of items whose plurality is wrong, *window* (Win.) the fraction that are decisive *and* have the correct answer somewhere in the pool; both in per cent. The window is the ceiling for any label-free aggregation method. Rows marked † are measured here; HumanEval+/MBPP+ is recomputed from published oracle-minus-selector tables, which report the window only. As items harden the decisive fraction grows but the window does not: they pass from saturated to capability-limited. The MATH L5 row is over the full registered list of 119 items, the substrate being the object measured; Section 8.8 quotes the same quantities over the 89-item evaluation set that remains after the sign set is split off (10 and 4 items, so 11.2 and 4.5). The last row is that same MATH L5 substrate under the budget manipulation of Section 8.10, not a sixth substrate: the 2.5–7.5% range quoted throughout is over the five above it.

Domain	Substrate	Dec.	Win.
QA	GSM8K / CSQA†	9.0	4.0
QA	MATH L5†	7.6	2.5
QA	AIME / AMC†	23.3	3.3
Code	HumanEval+ / MBPP+	—	3.6
Code	LeetCode Med/Hard†	25.0	7.5
QA, budget-capped	MATH L5†	18.5	11.8

The manipulation was weaker than pre-registered on its stated check (per-sample accuracy $0.853 \rightarrow 0.781$, against a 0.10 drop required) and the correct answer did not leave the pool ($0.950 \rightarrow 0.933$), so what follows is exploratory. It is reported because the constraint did not lower accuracy uniformly, it moved items across the plurality boundary: SC fell $0.924 \rightarrow 0.815$, the window widened from 2.5% to 11.8% (paired exact McNemar on window membership, 13 in and 2 out, $p = 0.0037$), and the channel grew *stronger*, $\hat{D}$ from $+0.229$ ($z = 2.69$) to $+0.398$ ($z = 6.76$). Forced to answer without working, the model’s confidence tracks whether it happened to be right.

This is the widest window measured anywhere in this paper, and the first substrate on which the in-pool oracle clears the endpoint at all ($+9/-0$, $p = 0.002$ on a decisive stratum of 17). TACT nonetheless returned $\gamma = 0$: only 12 items survived the margin gate against the threshold of 30, so E4 fired. That abstention is testable rather than a matter of taste, and it cost nothing. Estimating γ from gold labels, an upper bound no deployable method has access to, the best available is $+4/-1$ at $\gamma = 1$ ($p = 0.19$); the derived $\gamma = 0.670$ gives $+3/-1$. The gap that matters is therefore not the one the window closes. Even with the window at 11.8% and an oracle able to convert nine items, confidence weighting reaches fewer than half of them, and none of the reachable configurations is significant.

9 Discussion and Limitations

What the evidence does and does not show. The *accuracy* claims are all on a synthetic oracle whose confidence model (1) is, at the homogeneous cells, the very coupling

the estimator measures. Three design choices limit the circularity, and the first is weaker than it looks: heterogeneity and echo lie outside the estimator’s working model, but the three distortion cells are rank-preserving by construction and therefore sit *inside* TACT’s own invariance group, so passing them tests that the implementation respects an invariance it was built to have rather than probing an untested regime; mechanism-recovery claims (does $\hat{D}$ track κ ?) are reported separately from accuracy claims; and the pre-measured baseline landscape (Fig. 1) fixed the winnable cells before the method existed. The real-trace campaigns of Sections 8.7 and 8.8 test the *premise* and the *abstention behaviour*, and both predictions held: the channel is null on saturated benchmarks and positive on competition mathematics, and the dead zone kept the vote bit-identical to SC in each case. They do not test the accuracy claim, because on neither substrate was the addressable stratum large enough for any method to demonstrate a gain (Section 8.9).

Narrow margins where labels abound. When labels are plentiful and the confidence scale is trusted, a dev-picked signed grid captures most of the value; TACT’s case rests on the label-free setting, distorted scales, small dev sets, and the exactness of its anchors.

Conditional label-free guarantee, and what happens past the boundary. Proposition 4 requires $\bar{\rho} < 1/2$ after deduplication, and the confident-echo ambiguity is fundamental (Proposition 8). Follow-on work measured the consequence of crossing that boundary, and it is worse than under-trust. In a *paraphrased* wrong-majority cell (a dominant wrong cluster that is semantically tight but carries no verbatim signature, so deduplication has nothing to collapse) the plurality is wrong on most items, $\bar{\rho} > 1/2$, and TACT-LF does not merely shrink toward SC: it *mis-signs*, saturates at $\gamma = -2.0$, and scores 0.000 against an SC floor of 0.340. None of the four alarms fires, because E1 keys on verbatim duplication which is absent by construction. This is the method’s sharpest unguarded failure mode: the guarantee is conditional, the condition is not observable label-free, and the existing diagnostics do not detect its violation. Where a systematically wrong majority is plausible, the semi-label-free mode (sign from ~ 50 labels) should be the default rather than an optional refinement. The other standard remedy is not tried here and should be: the failure is driven by a semantically tight wrong cluster that lexical deduplication cannot see, which is precisely what semantic-equivalence clustering (Kuhn et al., 2023) is built to collapse. Substituting a semantic pseudo-label for the lexical one is the obvious next guard, and this paper does not test it.

Global exponent per group. Within a group, TACT ships one exponent; per-item variation inside a group is unexploitable by Propositions 5–8 unless further covariates exist.

The thin window. Section 8.9 measures the stratum this whole family of methods can act on at 2.5–7.5% of items across all five substrates, in two domains, with no widening as items harden: they pass from saturated straight to capability-limited. Two consequences follow for the method proposed here. First, abstention is not a conservative compromise but the only correct default, and the measured cost of acting anyway was negative on both real substrates (best-single-confidence loses 4.5 points in Table 5 where the dead zone holds TACT at the SC floor). Second, an aggregation gain of the size reported on the synthetic harness is not measurable on a benchmark of a few hundred items at these window widths, which is why the real-trace claim in this paper is confined to the premise (the channel exists and is signed) and to the abstention behaviour, and does not extend to accuracy. Demonstrating the gain needs a (model, benchmark) pair whose plurality is wrong on 30–60% of items

with the correct answer still reachable, and no pair tried here satisfies both. Section 8.10 adds the one axis that does widen the window, and it cuts the same way: with the window at 11.8% and an oracle able to convert nine items, confidence weighting still reaches fewer than half of them. The width of the window is not the only thing in the way.

Widening the window on purpose. That result also names the most promising direction the paper does not pursue. Difficulty moves items from saturated straight to capability-limited, but the budget constraint of Section 8.10 moved them across the plurality boundary while leaving the answer inside the model’s competence, which is the combination the decisive stratum needs; sampling temperature is a second knob with the same character, and neither was swept. If the sampling regime is a controllable input rather than a fixed property of the substrate, the question changes from “how wide is the window?” to “what decoding configuration puts the most items in it, at what accuracy cost, and does the confidence channel stay signed there?” The budget arm answers the first part once and suggests the channel gets *stronger* under the constraint ($\hat{D}$ from +0.229 to +0.398), which would be worth confirming on more than one substrate before it is believed. A method that chose its own decoding budget to maximise decisive-stratum mass, then aggregated, would be a different contribution from this one, and the measurement here is what makes it worth attempting.

10 Conclusion

TACT turns “how far should this model’s confidence be trusted?” into a measured, signed, uncertainty-aware scalar, and recovers the sign without labels under conditions this paper states and tests. The measurement that frames it matters more than the estimator: across five substrates in two domains, the stratum on which any label-free aggregation method can act is 2.5–7.5% of items, and on both real substrates the in-pool oracle cannot clear a pre-registered endpoint. In that regime the useful property of an estimator is knowing when not to act, which the dead zone does exactly.

Code and Data Availability

All code, cached traces, and the JSON artifacts behind every table are at <https://github.com/vito1317/adaptive-reasoning-consensus>. Table 4 is produced by `pytest` at commit 35ad160; the synthetic results by `experiments/run_tact_eval.py`, the real-trace campaigns by `run_tact_hard_eval.py`, and the window measurements by `run_g1_window.py` and `run_g1_deepening.py`; the three abstention replays of finding (e) by `run_abstention_identifiability.py`; the planted-channel operating characteristic of finding (f) by `run_planted_sensitivity.py`. Each script writes the artifact its table cites. Figures 1–4 are vector output from `experiments/make_paper_figures.py`, which reads the same JSON.

Appendix A. Notation

References

- Pranjal Aggarwal, Aman Madaan, Yiming Yang, and Mausam. Let’s sample step by step: Adaptive-consistency for efficient reasoning and coding with LLMs. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 12375–12396, Singapore, December 2023. Association for Computational Linguistics. URL <https://aclanthology.org/2023.emnlp-main.761/>.
- Rui Ai, Yuqi Pan, David Simchi-Levi, Milind Tambe, and Haifeng Xu. Beyond majority voting: LLM aggregation by leveraging higher-order information, 2025. URL <https://arxiv.org/abs/2510.01499>. Accepted to ICML 2026.
- Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021. URL <https://arxiv.org/abs/2110.14168>.
- Alexander Philip Dawid and Allan M. Skene. Maximum likelihood estimation of observer error-rates using the EM algorithm. *Journal of the Royal Statistical Society: Series C (Applied Statistics)*, 28(1):20–28, 1979. doi: 10.2307/2346806.
- Yichao Fu, Xuewei Wang, Hao Zhang, Yuandong Tian, and Jiawei Zhao. Deep think with confidence. In *The Fourteenth International Conference on Learning Representations (ICLR)*, 2026. URL <https://arxiv.org/abs/2508.15260>.
- Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. Measuring mathematical problem solving with the MATH dataset. In *Proceedings of the Neural Information Processing Systems Track on Datasets and Benchmarks 1*, 2021. URL <https://arxiv.org/abs/2103.03874>. MATH-500 subset as distributed by Lightman et al., “Let’s Verify Step by Step” (2023).
- Xinmeng Huang, Shuo Li, Mengxin Yu, Matteo Sesia, Hamed Hassani, Insup Lee, Osbert Bastani, and Edgar Dobriban. Uncertainty in language models: Assessment through rank-calibration. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 284–312, Miami, Florida, USA, November 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.emnlp-main.18. URL <https://aclanthology.org/2024.emnlp-main.18/>.
- W. James and Charles Stein. Estimation with quadratic loss. In *Proceedings of the Fourth Berkeley Symposium on Mathematical Statistics and Probability, Volume 1: Contributions to the Theory of Statistics*, pages 361–379, Berkeley, California, 1961. University of California Press.
- Saurav Kadavath, Tom Conerly, Amanda Askell, Tom Henighan, Dawn Drain, Ethan Perez, Nicholas Schiefer, Zac Hatfield-Dodds, Nova DasSarma, Eli Tran-Johnson, Scott Johnston, Sheer El-Showk, Andy Jones, Nelson Elhage, Tristan Hume, Anna Chen, Yuntao Bai, Sam Bowman, Stanislav Fort, Deep Ganguli, Danny Hernandez, Josh Jacobson,

- Jackson Kernion, Shauna Kravec, Liane Lovitt, Kamal Ndousse, Catherine Olsson, Sam Ringer, Dario Amodei, Tom Brown, Jack Clark, Nicholas Joseph, Ben Mann, Sam McCandlish, Chris Olah, and Jared Kaplan. Language models (mostly) know what they know. *arXiv preprint arXiv:2207.05221*, 2022. URL <https://arxiv.org/abs/2207.05221>.
- Zhewei Kang, Xuandong Zhao, and Dawn Song. Scalable best-of-n selection for large language models via self-certainty. In *Advances in Neural Information Processing Systems 38 (NeurIPS 2025)*, 2025. URL <https://arxiv.org/abs/2502.18581>.
- David R. Karger, Sewoong Oh, and Devavrat Shah. Iterative learning for reliable crowdsourcing systems. In *Advances in Neural Information Processing Systems 24 (NIPS 2011)*, pages 1953–1961. Curran Associates, Inc., 2011. URL https://proceedings.neurips.cc/paper_files/paper/2009/hash/f899139df5e1059396431415e770c6dd-Abstract.html.
- Junseok Kim, Nakyeong Yang, Kyungmin Min, and Kyomin Jung. Reliability-aware adaptive self-consistency for efficient sampling in LLM reasoning. In *Findings of the Association for Computational Linguistics: ACL 2026*, pages 21575–21590, San Diego, California, United States, July 2026. Association for Computational Linguistics. doi: 10.18653/v1/2026.findings-acl.1085. URL <https://aclanthology.org/2026.findings-acl.1085/>.
- Leslie Kish. *Survey Sampling*. John Wiley & Sons, New York, 1965.
- Lorenz Kuhn, Yarin Gal, and Sebastian Farquhar. Semantic uncertainty: Linguistic invariances for uncertainty estimation in natural language generation. In *The Eleventh International Conference on Learning Representations (ICLR)*, 2023.
- Joonhyuk Lee, Virginia Ma, Sarah Zhao, Yash Nair, Asher Spector, Regev Cohen, and Emmanuel J. Candès. FUSE: Ensembling verifiers with zero labeled data, 2026. URL <https://arxiv.org/abs/2604.18547>.
- Yifei Li, Zeqi Lin, Shizhuo Zhang, Qiang Fu, Bei Chen, Jian-Guang Lou, and Weizhu Chen. Making language models better reasoners with step-aware verifier. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 5315–5333, Toronto, Canada, July 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.acl-long.291. URL <https://aclanthology.org/2023.acl-long.291/>.
- Yiwei Li, Peiwen Yuan, Shaoxiong Feng, Boyuan Pan, Xinglin Wang, Bin Sun, Heda Wang, and Kan Li. Escape sky-high cost: Early-stopping self-consistency for multi-step reasoning. In *The Twelfth International Conference on Learning Representations (ICLR)*, 2024. URL <https://arxiv.org/abs/2401.10480>.
- Hunter Lightman, Vineet Kosaraju, Yura Burda, Harri Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. Let’s verify step by step. In *The Twelfth International Conference on Learning Representations (ICLR)*, 2024. URL <https://arxiv.org/abs/2305.20050>.

- Fabio Parisi, Francesco Strino, Boaz Nadler, and Yuval Kluger. Ranking and combining multiple predictors without labeled data. *Proceedings of the National Academy of Sciences*, 111(4):1253–1258, 2014. doi: 10.1073/pnas.1219097111.
- J. N. K. Rao and A. J. Scott. The analysis of categorical data from complex sample surveys: Chi-squared tests for goodness of fit and independence in two-way tables. *Journal of the American Statistical Association*, 76(374):221–230, 1981. doi: 10.1080/01621459.1981.10477633.
- Amir Taubenfeld, Tom Sheffer, Eran Ofek, Amir Feder, Ariel Goldstein, Zorik Gekhman, and Gal Yona. Confidence improves self-consistency in LLMs. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 20090–20111, Vienna, Austria, July 2025. Association for Computational Linguistics. doi: 10.18653/v1/2025.findings-acl.1030. URL <https://aclanthology.org/2025.findings-acl.1030/>.
- Katherine Tian, Eric Mitchell, Allan Zhou, Archit Sharma, Rafael Rafailov, Huaxiu Yao, Chelsea Finn, and Christopher Manning. Just ask for calibration: Strategies for eliciting calibrated confidence scores from language models fine-tuned with human feedback. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 5433–5442, Singapore, December 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.emnlp-main.330. URL <https://aclanthology.org/2023.emnlp-main.330/>.
- Ph. van Elteren. On the combination of independent two sample tests of Wilcoxon. *Bulletin of the International Statistical Institute*, 37:351–361, 1960.
- Xuezhi Wang, Jason Wei, Dale Schuurmans, Quoc Le, Ed Chi, Sharan Narang, Aakanksha Chowdhery, and Denny Zhou. Self-consistency improves chain of thought reasoning in language models. In *The Eleventh International Conference on Learning Representations (ICLR)*, 2023. URL <https://arxiv.org/abs/2203.11171>.
- Jacob Whitehill, Paul Ruvolo, Tingfan Wu, Jacob Bergsma, and Javier Movellan. Whose vote should count more: Optimal integration of labels from labelers of unknown expertise. In *Advances in Neural Information Processing Systems 22 (NIPS 2009)*, pages 2035–2043. Curran Associates, Inc., 2009. URL https://proceedings.neurips.cc/paper_files/paper/2009/hash/f899139df5e1059396431415e770c6dd-Abstract.html.
- Yunhui Xia, Wei Shen, Yan Wang, Jason Klein Liu, Huifeng Sun, Siyue Wu, Jian Hu, and Xiaolong Xu. LeetCodeDataset: A temporal dataset for robust evaluation and efficient training of code LLMs. arXiv:2504.14655, 2025.
- Miao Xiong, Zhiyuan Hu, Xinyang Lu, Yifei Li, Jie Fu, Junxian He, and Bryan Hooi. Can llms express their uncertainty? an empirical evaluation of confidence elicitation in llms. In *The Twelfth International Conference on Learning Representations (ICLR)*, 2024. URL <https://arxiv.org/abs/2306.13063>.

Table 7: Symbols, in order of first use. Quantities carrying a subscript q are per item; the estimator ships one global scalar unless a group covariate is available (Section 6).

Symbol	Meaning
q, Q	item index; number of items
m_q, K	traces available for item q ; voting budget
$a_{q,i}, a_q^*$	answer of trace i ; the correct answer
$c_{q,i}$	self-reported confidence, in $(0, 1)$
$y_{q,i}$	$\mathbf{1}[a_{q,i} = a_q^*]$; unobservable at test time
$\bar{p}$	base rate of correct traces
$R_{q,i}$	within-item midrank of $c_{q,i}$ (ties averaged)
$\varphi_{q,i}$	standardized van der Waerden score of $R_{q,i}$; the vote feature
σ_q	realized within-item SD of the normal scores
$\gamma, \gamma_{\max}$	vote exponent; its cap (4 dev, 2 label-free)
$\hat{a}_q$	the returned answer
D_q	Somers' D within item q , $= 2 \text{AUC}_q - 1 = 2 \text{WQD}_q - 1$
N_q	van Elteren pooling weight, $n_q^1 n_q^0$
$\hat{D}$	pooled signed discrimination
SE_0, SE_J	exact tie-corrected null SE; delete-one-item jackknife SE
SE	$\max\{\text{SE}_0, \text{SE}_J, 1/(2\sqrt{N})\}$
ζ	$\hat{D}/\text{SE}$; the dead zone is $ \zeta \leq \nu$
ν	significance floor (1.28 dev, 2.33 label-free)
$\tilde{D}$	shrunk discrimination, $\hat{D}(1 - \nu^2/\zeta^2)_+$
z	$\Phi^{-1}((1 + \tilde{D})/2)$
M_q	dedup-weighted plurality; the pseudo-label
$g_{q,i}$	$\mathbf{1}[a_{q,i} = M_q]$
$\bar{\rho}$	pair-weighted probability the plurality is <i>wrong</i>
$\hat{\eta}$	estimated attenuation $1 - 2\bar{\rho}$ (not $\bar{\rho}$)
α, k	split-half agreement; effective number of wrong alternatives
$E_1 \dots E_4$	the four alarms; any one forces $\gamma = 0$
ψ	margin-decoupling statistic behind E_2
κ_c	true confidence–correctness coupling in the oracle (1)
λ_q	per-item coupling under i.i.d. heterogeneity