

TACT: Trust-Anchored Confidence Tempering for Self-Consistency Voting in Large Language Models

Wei-Chen Ko (柯瑋宸, vito1317)
Independent Researcher

Abstract—Confidence-weighted self-consistency (CISC and its successors) extracts large gains from a frozen large language model’s self-reported confidence—until the confidence channel is miscalibrated in direction. Every published weighting scheme is structurally monotone increasing in confidence, so an anti-correlated channel poisons the vote rather than informing it, while binary dev-set gates survive only by discarding genuinely discriminative signal. This paper presents tact (Trust-Anchored Confidence Tempering), which replaces the fixed confidence exponent with one derived from the measured, signed, within-item discrimination of the channel: a pooled van Elteren Somers’ D rank statistic with an item-clustered standard error, passed through positive-part James–Stein shrinkage and a Bayes-discriminant link. The map carries exact anchors—inside the shrinkage dead zone the vote is bit-identical to plain self-consistency, and a log-value feature map reproduces CISC-power exactly. A label-free variant estimates the signed reliability from agreement pseudo-labels, with a proven attenuation identity guaranteeing sign consistency whenever the plurality-error rate is below one half, conservative de-attenuation, and echo alarms at the identifiability boundary. On a synthetic-oracle harness with paired trace pools, the label-free variant recovers anti-correlated channels that pin every published protocol to the majority-vote floor ($\kappa = -0.6$: 1.000 vs. 0.807), rank invariance beats the oracle over the entire raw-value weight family under monotone confidence compression (1.000 vs. 0.965), and a per-group extension cracks the heterogeneity floor with zero paired losses to self-consistency (0.940 vs. 0.808; $+79/-0$, $p = 3.3 \times 10^{-24}$). The paper further proves that per-item label-free adaptation is impossible under i.i.d. latent coupling, and pre-registers four falsification criteria—including the published dev-calibrated CISC protocol as a designated killer baseline—all of which the method survived.

Index Terms—large language models, self-consistency, confidence calibration, weighted voting, label-free estimation, rank statistics

I. Introduction

Self-consistency (sc) [1] improves the reasoning accuracy of a frozen large language model (LLM) by sampling K chain-of-thought traces and returning the plurality answer. Because each trace can also report a confidence score—verbalized [6], [7], derived from token log-probabilities, or elicited as $P(\text{True})$ [5]—a natural refinement is to weight votes by confidence. Confidence-Informed Self-Consistency (CISC) [2] showed that this recovers the accuracy of plain sc at a fraction of the sampling budget, and introduced Within-Question Discrimination (WQD) to argue that discrimination, not calibration, is the property that makes a confidence signal useful for voting.

This refinement carries a structural fragility that, to the author’s knowledge, no published method addresses. Ev-

ery existing weighting scheme—CISC’s softmax weights, reliability-aware pseudo-counts [11], warmup-thresholded filtering [12]—is monotone increasing in confidence. The trust decision is which magnitude of up-weighting to apply; the possibility that the channel is anti-correlated with correctness is not representable. Yet miscalibration of direction is not exotic: reinforcement fine-tuning is known to distort verbalized confidence, distribution shift can invert a signal that was informative in-domain, and in the experiments reported here a simple anti-correlated channel ($\kappa = -0.6$; Section III) drives confidence-weighted baselines from near-perfect accuracy to far below the majority-vote floor, while the same evidence, read with the correct sign, is a perfect signal. The defensive alternative—a binary dev-set gate that disables the channel when calibration error is high—survives the inversion but discards discriminative signal wholesale: a systematically under-confident yet perfectly ranked channel fails an ECE gate for reasons irrelevant to voting utility [2], [8].

This paper frames the problem as estimating one scalar: the signed within-item discrimination of the confidence channel, and mapping it—with uncertainty—to a vote exponent. The contributions are:

C1: Signed, analytically-tempered confidence weighting. tact votes with weights $w_i = \exp(\gamma \varphi_i)$, where φ_i is the standardized van der Waerden score of trace i ’s within-item confidence midrank, and γ is derived, not grid-searched: a pooled van Elteren Somers’ D statistic (equal to $2 \cdot \text{WQD} - 1$) with an exact tie-corrected null variance and an item-clustered jackknife standard error, shrunk by positive-part James–Stein with a significance floor, then mapped through a Bayes-discriminant link with a mixture-variance correction. The construction carries exact anchors: inside the shrinkage dead zone the vote is bit-identical to plain sc (a shared code path), and the log-value feature map reproduces CISC-power exactly (Section IV). Because φ depends on confidence only through within-item ranks, the entire method is invariant to every strictly monotone distortion of the confidence scale; under monotone compression it beats the oracle over the whole raw-value weight family (1.000 vs. 0.965).

C2: Label-free estimation of the signed reliability. The crowdsourcing lineage estimates annotator reliability from cross-annotator covariance [13], [16]; a single exchangeable confidence channel from one model offers no such structure. The signed discrimination is estimated from

agreement pseudo-labels (deduplication-weighted plurality per item) with a proven class-conditional-noise attenuation identity, $\mathbb{E}[\widehat{D}_g] = (1 - 2\bar{\rho})D$: the label-free estimate can only under-trust, never mis-sign, whenever the pair-weighted plurality-error rate $\bar{\rho}$ is below $1/2$. A split-half agreement inversion de-attenuates conservatively, and sign-aware alarms return the method to plain sc when identifiability is threatened. On the coupling sweep the label-free variant matches the 200-label variant nearly point-for-point, including full recovery of negative channels (Section VIII).

C3: An impossibility result and its structured escape. When the per-item coupling is i.i.d. with no observable covariate, per-item label-free adaptation is shown to be closed: any monotone use of an item’s own agreement statistic collapses to plurality reinforcement; on exactly the plurality-wrong items where a flip could help, the observable sign opposes the truth 96% of the time; and the two hypotheses $\{\kappa > 0, \text{minority correct}\}$ and $\{\kappa < 0, \text{plurality correct}\}$ induce identical observable laws. When heterogeneity is instead indexed by an observable covariate (domain-dependent calibration), running the same estimator per group recovers each group’s signed coupling and approaches the per-item oracle with zero paired losses to sc (Section VI).

C4: A pre-registered falsification protocol. Four falsifiers were fixed before implementation, including the two designed to kill the method: the published dev-calibrated CISC protocol (whose tuned temperature already interpolates $\text{sc} \leftrightarrow \text{CISC}$) and a trivial dev-picked signed exponent grid. All four survived, and the honest margins are reported: against the signed grid the net advantage concentrates in exactly three cells—monotone distortion, confident echo, and label-free operation, which no grid can perform.

II. Related Work

Confidence-weighted self-consistency. sc [1] treats sampled traces as i.i.d. votes. CISC [2] weights votes by softmax-normalized confidence with a temperature tuned on a labeled split, and its WQD metric makes the discrimination-vs-calibration point that also motivates this work; the rank-calibration line [8] reaches the same conclusion independently. Weighted variants [9], [10] and early-stopping families [3], [4] refine the budget; reliability-aware pseudo-counts [11] and warmup-thresholded filtering [12] adapt online but only re-scale positive trust. None of these can represent, much less estimate, a negative confidence-correctness association. The dev-calibrated variant must therefore be positioned honestly: CISC’s tuned temperature is already a dev-calibrated $\text{sc} \leftrightarrow \text{CISC}$ interpolation, so the novelty of tact-dev lies in the sign, the rank invariance, and the analytic (grid-free) map, not in dev calibration itself.

Reliability estimation without labels. Estimating worker reliability from agreement is classical [13], [14], [15];

spectral meta-learners [16] and recent LLM ensemble work [17], [18] exploit covariance across multiple predictors. The setting here differs: one exchangeable channel from one model, per-item vote structure, and the known failure of agreement proxies under correlated errors—met here with a quantified attenuation identity, conservative de-attenuation, and alarms rather than an unconditional claim.

Shrinkage and rank statistics. The estimator assembles classical parts: stratified rank statistics [19], the James–Stein positive-part estimator [20], effective-sample-size corrections [21], [22], and normal-scores discriminant analysis. The claim is the assembly and its anchors, not the parts.

Honest sibling result. A preceding system by the author (RLEV-VoI, redundancy-discounted voting with value-of-information stopping) was evaluated under the same falsification discipline and failed it—a simple deduplication baseline dominated everywhere—and is reported as a negative result. Its post-mortem isolated the confidence dilemma studied here.

III. Problem Setup

A. Notation

Items $q = 1, \dots, Q$; item q has m_q sampled traces. Trace (q, i) yields an answer $a_{q,i}$ in a discrete set and a confidence $c_{q,i} \in (0, 1)$; correctness is $y_{q,i} = \mathbf{1}[a_{q,i} = a_q^*]$, unobserved at test time. Plain sc returns $\arg \max_A n_q(A)$ where $n_q(A)$ counts votes for answer A . CISC-power weights votes by $c_{q,i}^\gamma$ with a fixed $\gamma > 0$.

B. The confidence dilemma

The synthetic oracle draws, per item, traces from a cluster mixture with a latent correct answer and generates confidence as

$$c_{q,i} = \text{clip}\left(\frac{1}{2} + \kappa(y_{q,i} - \frac{1}{2}) + \varepsilon_{q,i}, 0.01, 0.99\right), \quad (1)$$

with noise $\varepsilon \sim \mathcal{N}(0, 0.1^2)$ and coupling $\kappa \in [-0.6, 0.6]$. Fig. 1 maps the baseline landscape before the proposed method existed: unconditional weighting (CISC, $\gamma = 1$) collapses on $\kappa < 0$; an ECE gate never opens off the well-calibrated diagonal; a sign-corrected AUC gate over dev labels nearly saturates the homogeneous sweep. This pre-measurement fixes where a new method can legitimately claim wins—monotone distortion of the confidence scale, covariate heterogeneity, small dev sets, and label-free operation—and the evaluation holds itself to exactly those cells.

IV. TACT

A. Vote family

Within item q , let $R_{q,i}$ be the midrank of $c_{q,i}$ (ties averaged) and

$$\varphi_{q,i} = \frac{v_{q,i} - \bar{v}_q}{\sigma_q}, \quad v_{q,i} = \Phi^{-1}\left(\frac{R_{q,i}}{m_q + 1}\right), \quad (2)$$




Fig. 1. The pre-measured problem statement: accuracy of baseline confidence policies at fixed $K=15$ as the true coupling κ varies. A trivial sign-corrected AUC gate (green) nearly saturates the homogeneous sweep; the open ground is monotone distortion, per-item heterogeneity, small dev sets, label-free

where σ_q is the realized standard deviation of v within the item (the no-tie value is 0.62 at $m=4$ but 0.95 at $m=40$; a closed form would silently rescale γ across budgets), and $\varphi \equiv 0$ if $\sigma_q \leq 10^{-8}$ (all-tied confidences vote as plain sc). The vote is

$$\hat{a}_q = \arg \max_A \sum_{i: a_{q,i}=A} \exp(\gamma \varphi_{q,i}), \quad (3)$$

and when $\gamma = 0$ the implementation calls the sc routine itself, making the zero-trust anchor bitwise exact rather than equal in distribution. Because (2) depends on c only through within-item ranks, every strictly monotone distortion of the confidence scale leaves (3) unchanged.

B. Reliability statistic

For item q with n_q^1 positive and n_q^0 negative labels (dev: y ; label-free: the pseudo-label of Section V), the Mann–Whitney statistic on midranks gives

$$D_q = 2 \text{AUC}_q - 1, \quad \text{AUC}_q = \frac{U_q}{n_q^1 n_q^0}, \quad (4)$$

which equals $2 \cdot \text{WQD}_q - 1$ in CISC’s notation. Pooling uses van Elteren pair-count weights $N_q = n_q^1 n_q^0$ [19]:

$$\hat{D} = \frac{\sum_q N_q D_q}{\sum_q N_q}. \quad (5)$$

Under the within-item exchangeability null, U_q has the exact tie-corrected variance $n_q^1 n_q^0 (m_q + 1) / 12 \cdot [1 - \sum_t (t^3 - t) / (m_q^3 - m_q)]$, yielding a null standard error SE_0 ; between-item heterogeneity is captured by the closed-form delete-one-item jackknife SE_J . The conservative choice is

$$\text{SE} = \max(\text{SE}_0, \text{SE}_J, \frac{1}{2\sqrt{N}}), \quad r = \hat{D} / \text{SE}. \quad (6)$$

Because D is a pairwise functional, $\mathbb{E}[\hat{D}]$ does not depend on m_q : an exponent estimated at $m=40$ transfers to deployment at $m=8$.

C. Tempering map

Shrinkage. Positive-part James–Stein with a significance floor ν :

$$\tilde{D} = \text{sign}(\hat{D}) \max(0, |\hat{D}| - \nu^2 \text{SE}^2 / |\hat{D}|), \quad (7)$$

with dead zone $\{|r| \leq \nu\}$; $\nu_{\text{dev}} = 1.28$, $\nu_{\text{LF}} = 2.33$. With $\nu = 1$, (7) is exactly the empirical-Bayes posterior mean under a $\mathcal{N}(0, \tau^2)$ prior with plug-in $\hat{\tau}^2 = \max(0, \hat{D}^2 - \text{SE}^2)$ [20]. The map is odd, continuous, never exceeds $|\hat{D}|$, and is monotone in $\hat{D}$ and anti-monotone in SE .

Link. Model $\varphi | y \sim \mathcal{N}(\mu_y, s^2)$ within item with the mixture standardized to unit variance—which is what (2) enforces—so $s^2 = 1 / (1 + \bar{p}(1 - \bar{p})u^2)$ where $u = \sqrt{2} \Phi^{-1}(\frac{1+\tilde{D}}{2})$ and $\bar{p}$ is the base rate of correct traces. The Bayes-optimal per-trace log-weight coefficient is then

$$\gamma^* = \frac{u}{s} = u \sqrt{1 + \bar{p}(1 - \bar{p})u^2}, \quad (8)$$

capped at γ_{max} (4 dev, 2 label-free). The uncorrected link $\gamma = u$ under-weights strong channels by up to $\sim 50\%$ at $D = 0.9$.

D. Anchor properties

Proposition 1 (Exact sc reduction). At $\gamma = 0$, (3) equals plain sc as a function on every trace pool, including tie-breaks. Under $D = 0$, $P(\gamma = 0) \rightarrow 2\Phi(\nu) - 1$ (80% dev, 98% label-free), and γ is continuous through the dead-zone boundary, so a false positive applies an infinitesimal exponent.

Proposition 2 (Exact CISC reduction). With the feature map $\varphi_{q,i}^{\log} = \log c_{q,i} - \log \bar{c}_q$, the weights equal $\kappa_q c_{q,i}^\gamma$ with a per-item constant $\kappa_q > 0$; hence the argmax, the ties, and the normalized vote shares coincide with CISC-power(γ) on every pool.

Proposition 3 (Regularity). The composite $g(\hat{D}, \text{SE})$ is continuous, odd, nondecreasing in $\hat{D}$, nonincreasing in SE in magnitude, with $g(D, 0^+) = \gamma^*(D)$.

Proofs are elementary and pinned by unit tests in the released code (76 tests; the permutation-verified null variance, the EB identity in (7), and the link derivation (8) are each tested numerically).

V. Label-Free Estimation

A. Pipeline

(i) Dedup: single-linkage duplicate groups on the lexical-similarity channel at 0.95; each trace gets weight $1/|\text{group}|$ for plurality determination and pair weighting. (ii) Pseudo-label: $g_{q,i} = \mathbf{1}[a_{q,i} = M_q]$ with M_q the dedup-weighted plurality. (iii) Margin gate: keep the top 60% of items by dedup-weighted margin. (iv) Compute (5) with $\text{lab} = g$, giving $(\hat{D}_g, \text{SE}_g, r_g)$.

B. Sign consistency and its boundary

Proposition 4 (Attenuation identity). Let $\bar{\rho}$ be the pair-weighted probability that an item’s plurality is wrong. If the plurality-error event is independent of φ given y (class-conditional noise), then $\mathbb{E}[\hat{D}_g] = (1 - 2\bar{\rho})D$. In particular $\text{sign } \mathbb{E}[\hat{D}_g] = \text{sign } D$ whenever $\bar{\rho} < 1/2$: the label-free estimate can only under-trust, never mis-sign.

The identity fails exactly when the flip is caused by confidence—a confident echo. There the observable law under {majority right, $D < 0$ } and {majority wrong via confident echo, $D > 0$ } is identical (the two-root ambiguity of [16] restated for a single channel), so any label-free guarantee is necessarily conditional; it is stated as such rather than papered over.

C. De-attenuation and alarms

Split-half agreement over $R=20$ random half-splits estimates $\alpha = p^2 + (1-p)^2/k$ under a one-coin model with k effective wrong alternatives (inverse-Simpson), inverted as $p = [1 + \sqrt{1 - (k+1)(1-k\alpha)}]/(k+1)$; $\hat{D}_g$ is divided by the upper 95% bootstrap bound of $2p - 1$ (floored at 0.2), which can only under-inflate. Four alarms force $\gamma = 0$: duplicate collapse (median Kish ratio < 0.5), sign-aware margin-decoupling, root ambiguity in the split-half quadratic, and insufficient gated items. The margin-decoupling alarm must condition on the estimated trust direction: a sign-naive version (“plurality has the highest mean φ ”) false-alarms on every benign anti-correlated channel—a defect the author hit, diagnosed, and fixed, and which the released tests pin. Finally the significance gate acts on the raw z (unbiased sign under Proposition 4) and temper on the de-attenuated value. A semi-label-free mode takes only the sign from ~ 50 dev labels, routing it into the pipeline and disabling only the proxy-sign alarm; this purchases immunity to the ambiguity above at negligible labeling cost.

VI. Heterogeneity: Impossibility and Escape

A. Per-item adaptation is closed under i.i.d. coupling

Suppose $\kappa_q \stackrel{\text{iid}}{\sim} \mathcal{N}(0, 0.6^2)$ with no observable covariate.

Proposition 5 (Self-reinforcement). Any per-item rule $\gamma_q = h(\hat{D}_q^g)$ with h monotone increasing and odd reinforces the plurality on both branches: $\hat{D}_q^g > 0$ up-weights confident traces, which agree with the plurality; $\hat{D}_q^g < 0$ up-weights unconfident traces, which are again the plurality side. Empirically such a rule agrees with sc on 97.5% of items and its residual flips are net-harmful (1 right vs. 9 wrong per 400 items).

Proposition 6 (Winner’s curse). On plurality-wrong items with $|D_q| > 0.3$ —exactly the items where a flip could win—the agreement statistic’s sign matches the true sign only 4% of the time.

Proposition 7 (Two-world unidentifiability). For any observed (a, c) , the worlds $\{\kappa > 0, \text{minority correct}\}$ and $\{\kappa < 0, \text{plurality correct}\}$ induce identical observable laws (constructively, D computed against either truth satisfies $D^{w_1} = -D^{w_2}$). No label-free method can separate them.

Consequently the per-item oracle (0.983 in this harness) is unreachable, and the honest behaviour is to fall back to the global estimate—which tact’s dead zone does exactly: in the i.i.d. cell every variant returns bitwise sc (zero discordant pairs).

B. TACT-group

Real heterogeneity is typically indexed by an observable covariate (domain, question type). With κ indexed by a group label, running the estimator per group keeps every group inside the operating regime of Sections IV–V; groups with fewer than 30 dev (or 60 unlabeled) items fall back to the global estimate, which Propositions 5–7 show is the only defensible default.

VII. Experimental Setup

Harness. A cluster-mixture oracle generates, per item, up to $K_{\max}=20$ cached traces with answers, confidences (1), and two similarity channels; all methods replay identical pools (paired comparisons, exact McNemar tests). Voting budget $K=15$; 400 items per cell on the sweep, 600 for the group study; dev splits of 200 (primary) and 50 (small-dev).

Regimes. The κ sweep $\{-0.6, \dots, +0.6\}$; three strictly monotone confidence distortions (compression toward 0.5, over-confident sigmoid, fourth power)—rank-preserving by construction, so discrimination is intact while calibration is destroyed; i.i.d. heterogeneity ($\kappa_q \sim \mathcal{N}(0, 0.6^2)$); covariate-structured heterogeneity (three groups at $+0.6/0/-0.6$); and a confident-echo poison (a wrong cluster echoes verbatim with confidence 0.95).

Baselines. sc; CISC-power with $\gamma \in \{0.25, \dots, 4\}$; CISC-devT, the published dev-calibrated protocol (positive grid picked on dev); a binary ECE gate; SignGrid-dev, the strongest trivial baseline (signed exponent grid picked on dev); and the test-set oracle over signed fixed exponents as the upper envelope. The group study adds the naive self-referential per-item method as a negative control and the per-item link oracle as the ceiling.

Pre-registered falsifiers. F1: tact-dev significantly below the best fixed- γ CISC at $\kappa=+0.6$. F2: either variant significantly below sc anywhere on the sweep. F3: the label-free variant fails to beat the ECE gate on sweep average. F4: CISC-devT or SignGrid-dev matches tact-dev everywhere, including the distortion, heterogeneity, and small-dev cells.

VIII. Results

A. Signed recovery, with and without labels

Table I and Fig. 2 give the sweep. Three observations. First, the published protocols never leave the floor on

TABLE I

Coupling sweep (accuracy at $K=15$; 400 paired items per cell; dev $n=200$). Published protocols sit at the sc floor on the entire negative half-axis.

κ	sc	ECE	devT	SignGrid	tact-dev	tact-LF	oracle
-0.6	.807	.807	.807	1.000	1.000	1.000	1.000
-0.4	.797	.797	.797	1.000	1.000	1.000	1.000
-0.2	.835	.835	.835	.993	.978	.978	.993
-0.1	.762	.762	.762	.892	.880	.885	.892
0.0	.835	.835	.835	.835	.835	.835	.835
+0.1	.795	.795	.917	.917	.902	.902	.917
+0.2	.845	.845	.993	.993	.988	.988	.993
+0.4	.838	.838	1.000	1.000	1.000	1.000	1.000
+0.6	.782	.782	1.000	1.000	1.000	1.000	1.000




Fig. 2. Main result on the confidence-usage frontier. tact-dev and the fully label-free tact-LF track the signed oracle across the sweep; CISC-devT and the ECE gate sit at the sc floor for all $\kappa < 0$.

$\kappa < 0$: CISC-devT’s grid is positive-only and the ECE gate never opens (dev ECE ranges 0.10–0.80 across the sweep while the signal’s discrimination is perfect at the extremes). Second, the label-free variant matches the 200-label variant nearly point-for-point—at $\kappa=-0.6$ the raw agreement statistic is $\hat{D}_g = -0.81$ with $z = -17.6$, and the CCN identity’s sign guarantee holds as predicted, yielding 1.000 with zero labels. Third, at $\kappa = 0$ the dead zone returns $\gamma = 0$ exactly, so the paired accuracy difference to sc is identically zero—“non-inferior” is replaced by “identical.”

B. Rank invariance where raw values fail

Under monotone compression (Table II, Fig. 3) all confidences huddle near 0.5, so every c^γ -family weight is nearly uniform: even the oracle over raw-value policies reaches only 0.965. tact’s rank scores are untouched by the distortion and both variants reach 1.000. Under the confident echo, dev labels reveal the inversion (high confidence $\Rightarrow$ wrong) and tact-dev counters with $\gamma = -1.20$, the best result in the field (0.585; three times the sc floor); label-free, the duplicate-collapse alarm fires and the method correctly refuses—by Proposition 7 no label-free method could do better than a coin flip on the sign here, and pretending otherwise would be the real failure.

TABLE II

Adversarial regimes (accuracy at $K=15$). “Oracle” is the test-set best over raw-value weight policies; rank invariance beats that entire family under compression.

Regime	sc	devT	SignGrid	tact-dev	tact-LF
Monotone compress	.795	.965	.965	1.000	1.000
Monotone overconf	.795	1.000	1.000	1.000	1.000
Monotone power	.795	1.000	1.000	1.000	1.000
Hetero (i.i.d.)	.810	.810	.810	.810	.810
Confident echo	.200	.200	.550	.585	.200 [†]

[†]alarm fires and the method refuses to leave sc—the conditional guarantee of Prop. 4 working as stated.




Fig. 3. Adversarial regimes. Dotted line: the oracle over raw-value weights. Left group of bars: rank invariance beats that family under compression; right: the labeled variant counters the confident echo while the label-free variant alarms and refuses.

C. Heterogeneity

Table III and Fig. 4 give the group study. In the covariate-structured cell, per-group tact recovers each group’s signed coupling—dev $\{+4.0, 0.0, -4.0\}$, label-free $\{+2.0, 0.0, -2.0\}$, the $\kappa=0$ group correctly dead-zoned—and cracks the floor that provably binds every global policy: the label-free variant reaches 0.940, within 0.007 of the per-item link oracle, with zero paired losses to sc over 600 items ($+79/-0$, $p = 3.3 \times 10^{-24}$). In the i.i.d. cell every legitimate method sits at the floor with zero discordant pairs, and the naive self-referential control lands slightly below it—the empirical face of Propositions 5–7. One observation is reported as-is rather than tuned for: the label-free variant outperforms the dev variant in the grouped cell (0.940 vs. 0.923) because its lower exponent cap (2 vs. 4) regularizes better when $|D| \approx 1$; cap robustness is left as an ablation.

D. Small dev sets and falsifiers

With dev $n=50$ the conclusions are unchanged (1.000 at $|\kappa|=0.6$; 0.978 at -0.2): the SE-aware shrinkage degrades smoothly rather than catastrophically. All four falsifiers survived: F1 (1.000 vs. 1.000), F2 (bit-identical at $\kappa=0$; never significantly below sc elsewhere), F3 (sweep means 0.954 vs. 0.811), and F4 (the distortion and echo cells are unreachable by either grid baseline). Against SignGrid-dev the honest margin is narrow on the homogeneous

TABLE III
Heterogeneity study (600 paired items; $K=15$).

Method	Grouped	i.i.d.
sc (floor)	.808	.827
tact global (dev)	.808	.827
tact-group (dev)	.923	.827
tact-group (label-free)	.940	.827
Naive per-item (neg. control)	.803	.820
Per-item link oracle (ceiling)	.947	.983




Fig. 4. Structured vs. i.i.d. heterogeneity. Left: with an observable covariate, per-group tact (label-free) approaches the per-item oracle from the 0.808 floor with zero losses to sc. Right: the provably closed i.i.d. cell—every legitimate method at the floor; the negative control slightly below it.

sweep—tact even trails by 0.005–0.015 in the mid-range, the deliberate cost of shrinkage—and the net advantage concentrates exactly where pre-registered: distortion (+0.035), echo (+0.035), and label-free operation, which no grid can perform.

E. Verification of the implementation

Because every claim in Sections IV–VI is a mathematical property rather than an empirical trend, the released code pins each one with an executable test; the suite is 76 tests for tact (84 including the follow-on work) and runs in 14 seconds. Table IV maps propositions to the tests that would fail if they stopped holding.

Two entries deserve comment. The permutation-invariance test was added after a defect in which the memoisation key made the test pass while the estimator itself was order-dependent by up to 0.10; it now calls the internal routine directly. And the last two rows are counter-tests that assert failure of rejected alternatives — the Kish effective-sample-size formulation and the claim that the shipped default honours the SAFE stopping guarantee — so that neither can be silently reinstated by a later change.

F. Real-trace validation

Validation on real traces used Claude Haiku 4.5 as the frozen model: 100 items (50 GSM8K [23], 50 CommonsenseQA), 12 independent chain-of-thought traces per item with verbalized confidence (1,200 traces total), evaluated at $K=12$ with a 40/60 dev/test split. Four findings.

TABLE IV

What the test suite verifies. Every proposition in the paper has an executable counterpart; the counter-tests fail deliberately on rejected alternatives so a regression cannot silently reinstate them.

Claim	Test	Evidence
Prop. 1 (exact sc)	gamma_zero_is_bitwise_sc	200 random pools, identical incl. ties
Dead-zone rate	dead_zone_probabil-ity	>70% under $D=0$, 300 trials
Prop. 2 (exact CISC)	logval_phi_reproduces_cisc	identical vote shares, 100 pools
Rank invariance	monotone_invariance	3 distortions $\times$ 100 pools
Null variance	null_variance_matches_permutation	3,000-draw permutation, 10% tol.
JS-EB identity	js_eb_identity	exact to 10^{-12}
Link (8)	link_values_and_mixture_correction	closed form, rel. 10^{-9}
Prop. 4 (attenua- tion)	poisoning_attenuation_linear	$\rho \in \{.1, .25, .4\}$, abs. .06
Props. 5–7	test_tact_group.py	97.5% sc agreement; 4% sign match
Estimator	estimator_is_permu-tation_invariant	bypasses the memo (regression test)
Rejected: Kish ESS	kish_fails_T2_T3	asserts the failure
Rejected: SAFE	frozen_default_guarantee	asserts the viola-tion
Vol		

(a) The calibration–discrimination distinction reverses on real data, and tact reads it correctly. The channel is extremely well calibrated in the usual sense: ECE = 0.016, far inside the 0.10 gate, so a binary ECE gate opens and hands the channel to CISC. Yet the measured within-item discrimination is $\hat{D} = -0.219$ with SE = 0.176 ($z = -1.24$) — no usable signal, and what little there is points the wrong way (math -0.515 , commonsense -0.173 ; both groups negative). This is the exact mirror image of the synthetic case in which ECE wrongly closed the gate on a discriminative channel (Section III): on real traces ECE wrongly opens it on a non-discriminative one. Calibration is uninformative about voting utility in both directions, and a signed discrimination statistic is what distinguishes them.

(b) The dead zone fires, and costs exactly nothing. With $|z| < \nu$, tact-dev, tact-LF and tact-group all return $\gamma = 0$ and are bit-identical to sc on every test item (+0/−0 discordant pairs, $p = 1$). All methods score 0.917. This is the pre-registered null-direction prediction of Section IX confirmed on real data: where the channel carries no signal, the method is free.

(c) Saturation is the binding constraint, not the estimator. Trace-level accuracy is 0.958 on GSM8K and 0.847 on CommonsenseQA, so only 12 of 100 items contain both a correct and an incorrect trace — the only items a within-item rank statistic can use. The estimator is not underpowered by design; the benchmark simply does not present the model with enough genuine uncertainty.

Exposing non-null coupling on a strong model requires harder item pools, not more traces per item.

(d) Verbalized confidence is tie-heavy. Two values (0.99, 0.95) account for 49% of all reports, activating the tie-safe degeneration path of (2) on many items.

(e) A second campaign on harder items confirms the prediction of (c). A pre-registered follow-up collected 119 MATH level-5 items $[?] \times 16$ traces from the same frozen model (sign set 30, evaluation set 89). The channel prediction came true: pooled $\hat{D} = +0.250$, $SE = 0.098$ ($z = +2.54$) — the first real-trace confirmation that the verbalized-confidence channel carries positive within-item discrimination. Saturation, however, still forecloses the aggregation endpoint: per-trace accuracy is 0.819, sc scores 0.888, the decisive stratum is 10 of 89 items, and the correct answer is present in the pool on only 4 of those — so the in-pool oracle tops out at $+4/-0$, exact one-sided $p = 0.0625 > 0.05$: the registered endpoint was unpassable for any aggregation method on the realized substrate. tact again abstained correctly ($\gamma = 0$; alarms E4 and E2 both fired on the label-free path, and the 30-item sign set contained too few informative items for the semi-label-free sign), remaining bit-identical to sc while the best-single-confidence baseline lost 4.5 points by acting (0.843). One methodological caveat from this campaign transfers beyond tact: measured difficulty depended strongly on the collection protocol — a 30-problem-per-call probe put level-5 plurality accuracy at 0.40, while the 15-problem-per-call confirmatory run yielded 0.888 on the same stratum — so batch size must be reported as an experimental parameter whenever traces are collected in batches.

Scope: one model, two benchmarks, $K=12$. The result is a clean confirmation of the null-direction prediction and of the calibration–discrimination argument; it is not evidence that tact improves accuracy on real traces, which remains untested for want of a benchmark where the channel is both informative and the model uncertain.

IX. Discussion and Limitations

What the evidence does and does not show. All quantitative claims are on a synthetic oracle whose confidence model (1) is, at the homogeneous cells, the very coupling the estimator measures. Three design choices limit the circularity: the adversarial regimes (distortions, heterogeneity, echo) lie outside the estimator’s working model; mechanism-recovery claims (does $\hat{D}$ track κ ?) are reported separately from accuracy claims; and the pre-measured baseline landscape (Fig. 1) fixed the winnable cells before the method existed. Validation on real LLM traces is the remaining step; the cached-trace runner is committed and the prediction is falsifiable: if real confidence channels never exhibit directional miscalibration or covariate structure, tact’s dead zone should make it operationally indistinguishable from CISC-devT there.

Narrow margins where labels abound. When labels are plentiful and the confidence scale is trusted, a dev-picked signed grid captures most of the value; tact’s case rests on the label-free setting, distorted scales, small dev sets, and the exactness of its anchors.

Conditional label-free guarantee, and what happens past the boundary. Proposition 4 requires $\bar{\rho} < 1/2$ after deduplication, and the confident-echo ambiguity is fundamental (Proposition 7). Follow-on work measured the consequence of crossing that boundary, and it is worse than under-trust. In a paraphrased wrong-majority cell—a dominant wrong cluster that is semantically tight but carries no verbatim signature, so deduplication has nothing to collapse—the plurality is wrong on most items, $\bar{\rho} > 1/2$, and tact-LF does not merely shrink toward sc: it mis-signs, saturates at $\gamma = -2.0$, and scores 0.000 against an sc floor of 0.340. None of the four alarms fires, because E1 keys on verbatim duplication which is absent by construction. This is the method’s sharpest unguarded failure mode: the guarantee is conditional, the condition is not observable label-free, and the existing diagnostics do not detect its violation. Where a systematically wrong majority is plausible, the semi-label-free mode (sign from ~ 50 labels) should be the default rather than an optional refinement.

Global exponent per group. Within a group, tact ships one exponent; per-item variation inside a group is unexploitable by Propositions 5–7 unless further covariates exist.

The thin window. Measurements across three substrates (GSM8K/CSQA, MATH level-5, AIME/AMC; 268 items with pools) place a structural bound on this entire family of methods. The stratum any label-free aggregation method can act on — plurality wrong and the correct answer present in the pool and the signal separable — occupied 2–5% of items at every difficulty level: as items harden, they pass directly from saturated (plurality right) to capability-limited (the correct answer never sampled: 0 of 6 plurality-wrong AIME items had it in 16 draws), and the addressable band between the two regimes does not widen. Classifying all 16 decisive items by error shape, 7 were stable-wrong (tight wrong cluster — the two-world regime where no label-free signal can help) and 9 were scattered (6–8 distinct answers — a capability wall that diversity interventions cannot cross, since diversity is already maximal). Under this accounting, abstention is not a conservative compromise but the only correct default: on the confirmatory substrate the largest measured effect of acting anyway was negative (the best-single-confidence baseline loses 4.5 points where tact’s dead zone holds it exactly at the sc floor).

The natural hypothesis is that the window widens wherever an external anchor is cheap, since a passing test is a real per-sample signal rather than a model-relative one. That hypothesis was tested and does not hold. On 40 LeetCode Medium/Hard problems $[?]$ with 8

candidate solutions each, graded against the benchmark’s own hidden suites, the window — oracle minus the largest-behavioural-cluster baseline — measures $3/40 = 7.5\%$ (CI_{95} 2.6–19.9%), against 3.56% recomputed from published HumanEval+/MBPP+ tables and 2–5% for label-free QA. The composition is the same shape as well: 75% saturated, 18% capability wall, 8% rescuable. Raising the candidate budget does not open it — the seven capability-wall problems produced zero correct solutions in 224 further attempts (per-problem 95% upper bound on the pass rate 0.088), and extrapolating oracle@ N shows the window saturating by $N=32$. Executable ground truth buys a slightly wider window, not a different regime.

X. Conclusion

tact turns “how much should this model’s confidence be trusted?” into a measured, signed, uncertainty-aware quantity with exact fallbacks at both ends—plain self-consistency when the evidence is absent, CISC when it is at full strength—and shows that the sign, long unrepresentable in this family of methods, can be recovered without any labels under stated and tested conditions. The accompanying impossibility results draw the boundary that any future per-item method must respect, and the falsification protocol, having already killed one of the author’s own systems, is offered as the more portable contribution.

References

- [1] X. Wang, J. Wei, D. Schuurmans, Q. Le, E. Chi, S. Narang, A. Chowdhery, and D. Zhou, “Self-consistency improves chain of thought reasoning in language models,” in Proc. ICLR, 2023.
- [2] A. Taubenfeld et al., “Confidence improves self-consistency in LLMs,” in Findings of ACL, 2025, arXiv:2502.06233.
- [3] P. Aggarwal, A. Madaan, Y. Yang, and Mausam, “Let’s sample step by step: Adaptive-consistency for efficient reasoning and coding with LLMs,” in Proc. EMNLP, 2023, pp. 12375–12396.
- [4] Y. Li et al., “Escape sky-high cost: Early-stopping self-consistency for multi-step reasoning,” in Proc. ICLR, 2024.
- [5] S. Kadavath et al., “Language models (mostly) know what they know,” arXiv:2207.05221, 2022.
- [6] K. Tian et al., “Just ask for calibration: Strategies for eliciting calibrated confidence scores from language models fine-tuned with human feedback,” in Proc. EMNLP, 2023.
- [7] M. Xiong et al., “Can LLMs express their uncertainty? An empirical evaluation of confidence elicitation in LLMs,” in Proc. ICLR, 2024.
- [8] X. Huang, S. Li, M. Yu, M. Sesia, H. Hassani, I. Lee, O. Bastani, and E. Dobriban, “Uncertainty in language models: Assessment through rank-calibration,” in Proc. EMNLP, 2024, pp. 284–312.
- [9] Y. Li et al., “Making language models better reasoners with step-aware verifier,” in Proc. ACL, 2023.
- [10] Z. Kang, X. Zhao, and D. Song, “Scalable best-of-N selection for large language models via self-certainty,” in Proc. NeurIPS, 2025, arXiv:2502.18581.
- [11] J. Kim, N. Yang, K. Min, and K. Jung, “Reliability-aware adaptive self-consistency for efficient sampling in LLM reasoning,” in Findings of ACL, 2026, pp. 21575–21590.
- [12] Y. Fu et al., “Deep think with confidence,” arXiv:2508.15260, 2025.
- [13] A. P. Dawid and A. M. Skene, “Maximum likelihood estimation of observer error-rates using the EM algorithm,” J. Roy. Statist. Soc. C, vol. 28, no. 1, pp. 20–28, 1979.
- [14] J. Whitehill et al., “Whose vote should count more: Optimal integration of labels from labelers of unknown expertise,” in Proc. NeurIPS, 2009.
- [15] D. R. Karger, S. Oh, and D. Shah, “Iterative learning for reliable crowdsourcing systems,” in Proc. NeurIPS, 2011.
- [16] F. Parisi, F. Strino, B. Nadler, and Y. Kluger, “Ranking and combining multiple predictors without labeled data,” Proc. Natl. Acad. Sci., vol. 111, no. 4, pp. 1253–1258, 2014.
- [17] J. Lee, V. Ma, S. Zhao, Y. Nair, A. Spector, R. Cohen, and E. J. Candès, “FUSE: Ensembling verifiers with zero labeled data,” arXiv:2604.18547, 2026.
- [18] R. Ai, Y. Pan, D. Simchi-Levi, M. Tambe, and H. Xu, “Beyond majority voting: LLM aggregation by leveraging higher-order information,” arXiv:2510.01499, 2025, accepted to ICML 2026.
- [19] P. van Elteren, “On the combination of independent two-sample tests of Wilcoxon,” Bull. Int. Statist. Inst., vol. 37, pp. 351–361, 1960.
- [20] W. James and C. Stein, “Estimation with quadratic loss,” in Proc. 4th Berkeley Symp. Math. Statist. Prob., 1961, pp. 361–379.
- [21] L. Kish, Survey Sampling. New York, NY, USA: Wiley, 1965.
- [22] J. N. K. Rao and A. J. Scott, “The analysis of categorical data from complex sample surveys,” J. Amer. Statist. Assoc., vol. 76, no. 374, pp. 221–230, 1981.
- [23] K. Cobbe et al., “Training verifiers to solve math word problems,” arXiv:2110.14168, 2021.
- [24] L. Kuhn, Y. Gal, and S. Farquhar, “Semantic uncertainty: Linguistic invariances for uncertainty estimation in natural language generation,” in Proc. ICLR, 2023.
- [25] G. Wan, Y. Wu, J. Chen, and S. Li, “Reasoning aware self-consistency: Leveraging reasoning paths for efficient LLM sampling,” in Proc. NAACL, 2025, pp. 3613–3635.