

Lab06VitorAugustoCosta267117

```
library(DBI)
library(RSQLite)
library(dplyr)

path <- getwd()
fname <- file.path(path, "disco.db")

conn <- dbConnect(RSQLite::SQLite(), fname)

tabelas <- dbListTables(conn)
print("Tabelas disponíveis no banco de dados:")
```

```
[1] "Tabelas disponíveis no banco de dados:"
```

```
print(tabelas)
```

```
[1] "albums"           "artists"           "customers"          "employees"
[5] "genres"           "invoice_items"      "invoices"            "media_types"
[9] "playlist_track"   "playlists"          "sqlite_sequence"     "sqlite_stat1"
[13] "tracks"
```

```
colunas_customers <- dbListFields(conn, "customers")
print("Colunas da tabela customers:")
```

```
[1] "Colunas da tabela customers:"
```

```
print(colunas_customers)
```

```
[1] "CustomerId" "FirstName" "LastName" "Company" "Address"
[6] "City" "State" "Country" "PostalCode" "Phone"
[11] "Fax" "Email" "SupportRepId"
```

```
query_total_clientes <- "
  SELECT COUNT(*) AS total_clientes
  FROM customers;
"
total_clientes <- dbGetQuery(conn, query_total_clientes) %>% as_tibble()
print(total_clientes)
```

```
# A tibble: 1 x 1
  total_clientes
      <int>
1             59
```

```
query_total_paises <- "
  SELECT COUNT(DISTINCT Country) AS total_paises
  FROM customers;
"
total_paises <- dbGetQuery(conn, query_total_paises) %>% as_tibble()
print(total_paises)
```

```
# A tibble: 1 x 1
  total_paises
      <int>
1            24
```

```
query_clientes_por_pais <- "
  SELECT Country, COUNT(*) AS qtd_clientes
  FROM customers
  GROUP BY Country
  ORDER BY qtd_clientes DESC;"
clientes_por_pais <- dbGetQuery(conn, query_clientes_por_pais) %>% as_tibble()
print(clientes_por_pais)
```

```
# A tibble: 24 x 2
  Country      qtd_clientes
  <chr>         <int>
1 USA             13
2 Canada           8
3 France           5
4 Brazil           5
5 Germany          4
6 United Kingdom   3
7 Portugal         2
8 India            2
9 Czech Republic   2
10 Sweden           1
# i 14 more rows
```

```
query_top5_paises <- "
  SELECT Country, COUNT(*) AS qtd_clientes
  FROM customers
  GROUP BY Country
  ORDER BY qtd_clientes DESC
  LIMIT 5;
"
top5_paises <- dbGetQuery(conn, query_top5_paises) %>% as_tibble()
print(top5_paises)
```

```
# A tibble: 5 x 2
  Country qtd_clientes
  <chr>         <int>
1 USA             13
2 Canada           8
3 France           5
4 Brazil           5
5 Germany          4
```

```
query_paises_6_letras <- "
  SELECT DISTINCT Country
  FROM customers
  WHERE Country GLOB '???????';
"
paises_6_letras <- dbGetQuery(conn, query_paises_6_letras) %>% as_tibble()
print(paises_6_letras)
```

```
# A tibble: 6 x 1
  Country
  <chr>
1 Brazil
2 Canada
3 Norway
4 France
5 Poland
6 Sweden
```

```
query_musicas_br <- "
  SELECT DISTINCT t.Name AS Nome_Musica
  FROM customers c
  INNER JOIN invoices i ON c.CustomerId = i.CustomerId
  INNER JOIN invoice_items ii ON i.InvoiceId = ii.InvoiceId
  INNER JOIN tracks t ON ii.TrackId = t.TrackId
  WHERE c.Country = 'Brazil';
"
musicas_brasil <- dbGetQuery(conn, query_musicas_br) %>% as_tibble()
print("Amostra das músicas compradas por brasileiros:")
```

```
[1] "Amostra das músicas compradas por brasileiros:"
```

```
print(head(musicas_brasil, 10))
```

```
# A tibble: 10 x 1
  Nome_Musica
  <chr>
1 Experiment In Terra
2 Take the Celestra
3 Shout It Out Loud
4 Calling Dr. Love
5 Strutter
6 Cold Gin
7 Think About You
8 Rocket Queen
9 Don't Cry (Original)
10 Back off Bitch
```

```
dbDisconnect(conn)
```

horario

```
Sys.setenv(TZ = "America/Sao_Paulo")  
Sys.time()
```

```
[1] "2026-09-21 21:05:29 -03"
```