

RegressionCV

mod regression_cv

Definition for RegressionCV.

class RegressionCV

Bases: [BaseAutoCV](#), [RegressorMixin](#), [ExplainerMixin](#)

Defines an auto regression tree, based on the bayesian optimization base class.

Source code in `src/tree_machine/regression_cv.py`



114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164

▼ Details

165166167168169170171172173174175176177178179180181182183184185186187188189190191192193194195196197198199

attr **scorer** property

```
scorer
```

Returns correct scorer to use when scoring with RegressionCV.

meth **__init__**

```
__init__(metric, cv, n_trials, timeout, config)
```

Constructor for RegressionCV.

Parameters:

Name	Type	Description	Default
<code>metric</code>	<code>AcceptableRegression</code>	Loss metric to use as base for the estimation process.	<i>required</i>
<code>cv</code>	<code>BaseCrossValidator</code>	Splitter object to use when estimating the model.	<i>required</i>
<code>n_trials</code>	<code>NonNegativeInt</code>	Number of optimization trials to use when finding a model.	<i>required</i>
<code>timeout</code>	<code>NonNegativeInt</code>	Timeout in seconds to stop the optimization.	<i>required</i>
<code>config</code>	<code>RegressionCVConfig</code>	Configuration to use when fitting the model.	<i>required</i>

Source code in `src/tree_machine/regression_cv.py`

```
123 @validate_call(config={"arbitrary_types_allowed": True})
124 def __init__(
125     self,
126     metric: AcceptableRegression,
127     cv: BaseCrossValidator,
128     n_trials: NonNegativeInt,
129     timeout: NonNegativeInt,
130     config: RegressionCVConfig,
131 ) -> None:
132     """
133     Constructor for RegressionCV.
134
135     Args:
136         metric: Loss metric to use as base for the estimation process.
137         cv: Splitter object to use when estimating the model.
138         n_trials: Number of optimization trials to use when finding a model.
139         timeout: Timeout in seconds to stop the optimization.
140         config: Configuration to use when fitting the model.
141     """
142     super().__init__(metric, cv, n_trials, timeout)
143     self.config = config
```

meth `explain`

```
explain(X, **explainer_params)
```

Explains the inputs.

Source code in `src/tree_machine/regression_cv.py`

```
145 def explain(self, X: Inputs, **explainer_params) -> dict[str,  
146         NumpyArray[np.float64]]:  
147     """  
148     Explains the inputs.  
149     """  
150  
151     check_is_fitted(self, "model_", msg="Model is not fitted.")  
152  
153     if getattr(self, "explainer_", None) is None:  
154         self.explainer_ = TreeExplainer(self.model_, **explainer_params)  
155  
156     return {  
157         "mean_value": self.explainer_.expected_value,  
158         "shap_values": self.explainer_.shap_values(self._validate_X(X)),  
    }
```

meth `fit`

```
fit(X, y, **fit_params)
```

Fits RegressionCV.

Parameters:

Name	Type	Description	Default
<code>X</code>	<code>Inputs</code>	input data to use in fitting trees.	<i>required</i>
<code>y</code>	<code>GroundTruth</code>	actual targets for fitting.	<i>required</i>

Source code in `src/tree_machine/regression_cv.py`

```
160 def fit(self, X: Inputs, y: GroundTruth, **fit_params) -> "RegressionCV":
161     """
162     Fits RegressionCV.
163
164     Args:
165         X: input data to use in fitting trees.
166         y: actual targets for fitting.
167     """
168     self.feature_names_ = list(X.columns) if isinstance(X, pd.DataFrame) else
169     []
170     constraints = self.config.get_kwargs(self.feature_names_)
171
172     if self.metric == "quantile" and "quantile_alpha" not in constraints:
173         raise ValueError(
174             "Model set for quantile metric requires a 'quantile_alpha' to be
175 set."
176         )
177
178     self.model_ = self.optimize(
179         estimator_type=XGBRegressor,
180         X=self._validate_X(X),
181         y=self._validate_y(y),
182         parameters=self.config.parameters,
183         return_train_score=self.config.return_train_score,
184         **constraints,
185     )
186     self.feature_importances_ = self.model_.feature_importances_
187
188     return self
```

meth predict

```
predict(X)
```

Returns model predictions.


Source code in `src/tree_machine/regression_cv.py`

```
188 def predict(self, X: Inputs) -> Predictions:
189     """
190     Returns model predictions.
191     """
192     check_is_fitted(self, "model_", msg="Model is not fitted.")
193     return self.model_.predict(self._validate_X(X))
```

meth predict_proba

```
predict_proba(X)
```

Returns model probability predictions.

” Source code in `src/tree_machine/regression_cv.py` 

```
195 def predict_proba(self, X: Inputs) -> Predictions:
196     """
197     Returns model probability predictions.
198     """
199     raise NotImplementedError("Not implemented for RegressionCV.")
```

class RegressionCVConfig

Available config to use when fitting a regression model.

 **dictionary containing monotonicity direction allowed for each** 

variable. 0 means no monotonicity, 1 means increasing and -1 means decreasing monotonicity.

interactions: list of lists containing permitted relationships in data. n_jobs: Number of jobs to use when fitting the model. parameters: dictionary with distribution bounds for each hyperparameter to search on during optimization. return_train_score: whether to return the train score when fitting the model. quantile_alpha: Quantile alpha to use when fitting the model, if fitting a quantile model.

” Source code in `src/tree_machine/regression_cv.py`



35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81

▼ Details

```
@dataclass(frozen=True, config={"arbitrary_types_allowed": True})
class RegressionCVConfig:
    """
    Available config to use when fitting a regression model.

    monotone_constraints: dictionary containing monotonicity direction allowed
    for each
        variable. 0 means no monotonicity, 1 means increasing and -1 means
    decreasing
        monotonicity.
    interactions: list of lists containing permitted relationships in data.
    n_jobs: Number of jobs to use when fitting the model.
    parameters: dictionary with distribution bounds for each hyperparameter to
    search
        on during optimization.
    return_train_score: whether to return the train score when fitting the model.
    quantile_alpha: Quantile alpha to use when fitting the model, if fitting a
    quantile
        model.
    """

    monotone_constraints: dict[str, int]
    interactions: list[list[str]]
    n_jobs: int
    parameters: OptimizerParams
    return_train_score: bool
    quantile_alpha: float | None = None

    def get_kwargs(self, feature_names: list[str]) -> dict:
        """
        Returns parsed and validated constraint configuration for a RegressionCV
    model.

    Args:
        feature_names: list of feature names. If empty, will return empty
        constraints dictionaries and lists.
        """
        kwargs = {
            "monotone_constraints": {
                feature_names.index(key): value
                for key, value in self.monotone_constraints.items()
            },
            "interaction_constraints": [
                [feature_names.index(key) for key in lt] for lt in
            self.interactions
            ],
            "n_jobs": self.n_jobs,
        }

        if self.quantile_alpha is not None:
            kwargs["quantile_alpha"] = self.quantile_alpha

        return kwargs
```

meth `get_kwargs`

```
get_kwargs(feature_names)
```

Returns parsed and validated constraint configuration for a RegressionCV model.

Parameters:

Name	Type	Description	Default
<code>feature_names</code>	<code>list[str]</code>	list of feature names. If empty, will return empty constraints dictionaries and lists.	<i>required</i>

” Source code in `src/tree_machine/regression_cv.py`

```
59 def get_kwargs(self, feature_names: list[str]) -> dict:
60     """
61     Returns parsed and validated constraint configuration for a RegressionCV
62     model.
63
64     Args:
65         feature_names: list of feature names. If empty, will return empty
66         constraints dictionaries and lists.
67     """
68     kwargs = {
69         "monotone_constraints": {
70             feature_names.index(key): value
71             for key, value in self.monotone_constraints.items()
72         },
73         "interaction_constraints": [
74             [feature_names.index(key) for key in lt] for lt in
75 self.interactions
76         ],
77         "n_jobs": self.n_jobs,
78     }
79
80     if self.quantile_alpha is not None:
81         kwargs["quantile_alpha"] = self.quantile_alpha
82
83     return kwargs
```

func `balanced_quantile`

```
balanced_quantile(alpha)
```

Returns a Balanced regression CV config.

” Source code in `src/tree_machine/regression_cv.py`

```
102 def balanced_quantile(alpha: float) -> RegressionCVConfig:
103     """Returns a Balanced regression CV config."""
104     return RegressionCVConfig(
105         monotone_constraints={},
106         interactions=[],
107         n_jobs=multiprocessing.cpu_count() - 1,
108         parameters=BalancedParams(),
109         return_train_score=True,
110         quantile_alpha=alpha,
111     )
```