

# ClassifierCV

**mod** classifier\_cv

Definition for ClassifierCV.

**class** ClassifierCV

Bases: BaseAutoCV, ClassifierMixin, ExplainerMixIn

Defines an auto classification tree, based on the bayesian optimization base class.

” Source code in `src/tree_machine/classifier_cv.py`



92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142

▼ Details

14314414514614714814915015115215315415515615715815916016116216316416516616716816917017117217317417517617

**attr** **scorer** property

```
scorer
```

Returns correct scorer to use when scoring with RegressionCV.

**meth** **\_\_init\_\_**

```
__init__(metric, cv, n_trials, timeout, config)
```

Constructor for ClassifierCV.

**Parameters:**

| Name                  | Type                              | Description  | Default         |
|-----------------------|-----------------------------------|--|-----------------|
| <code>metric</code>   | <code>AcceptableClassifier</code> | Loss metric to use as base for estimation process.         | <i>required</i> |
| <code>cv</code>       | <code>BaseCrossValidator</code>   | Splitter object to use when estimating the model.          | <i>required</i> |
| <code>n_trials</code> | <code>NonNegativeInt</code>       | Number of optimization trials to use when finding a model. | <i>required</i> |
| <code>timeout</code>  | <code>NonNegativeInt</code>       | Timeout in seconds to stop the optimization.               | <i>required</i> |
| <code>config</code>   | <code>ClassifierCVConfig</code>   | Configuration to use when fitting the model.               | <i>required</i> |

Source code in `src/tree_machine/classifier_cv.py`

```
101 @validate_call(config={"arbitrary_types_allowed": True})
102 def __init__(
103     self,
104     metric: AcceptableClassifier,
105     cv: BaseCrossValidator,
106     n_trials: NonNegativeInt,
107     timeout: NonNegativeInt,
108     config: ClassifierCVConfig,
109 ) -> None:
110     """
111     Constructor for ClassifierCV.
112
113     Args:
114         metric: Loss metric to use as base for estimation process.
115         cv: Splitter object to use when estimating the model.
116         n_trials: Number of optimization trials to use when finding a model.
117         timeout: Timeout in seconds to stop the optimization.
118         config: Configuration to use when fitting the model.
119     """
120     super().__init__(metric, cv, n_trials, timeout)
121     self.config = config
```

**meth** `explain`

```
explain(X, **explainer_params)
```

Explains the inputs.

Source code in `src/tree_machine/classifier_cv.py`

```
123 def explain(self, X: Inputs, **explainer_params) -> dict[str,  
124     NumpyArray[np.float64]]:  
125     """  
126     Explains the inputs.  
127     """  
128     check_is_fitted(self, "model_", msg="Model is not fitted.")  
129  
130     if getattr(self, "explainer_", None) is None:  
131         self.explainer_ = TreeExplainer(self.model_, **explainer_params)  
132  
133     shap_values = self.explainer_.shap_values(self._validate_X(X))  
134     shape = shap_values.shape  
135  
136     return {  
137         "mean_value": self.explainer_.expected_value,  
138         "shap_values": shap_values.reshape(shape[0], shape[1], -1),  
    }
```

meth `fit`

```
fit(X, y, **fit_params)
```

Fits ClassifierCV.

Parameters:

| Name           | Type                     | Description                         | Default         |
|----------------|--------------------------|-------------------------------------|-----------------|
| <code>X</code> | <code>Inputs</code>      | input data to use in fitting trees. | <i>required</i> |
| <code>y</code> | <code>GroundTruth</code> | actual targets for fitting.         | <i>required</i> |

Source code in `src/tree_machine/classifier_cv.py`

```
140 def fit(self, X: Inputs, y: GroundTruth, **fit_params) -> "ClassifierCV":
141     """
142     Fits ClassifierCV.
143
144     Args:
145         X: input data to use in fitting trees.
146         y: actual targets for fitting.
147     """
148     self.feature_names_ = list(X.columns) if isinstance(X, pd.DataFrame) else
149     []
150     constraints = self.config.get_kwargs(self.feature_names_)
151
152     self.model_ = self.optimize(
153         estimator_type=XGBClassifier,
154         X=self._validate_X(X),
155         y=self._validate_y(y),
156         parameters=self.config.parameters,
157         return_train_score=self.config.return_train_score,
158         **constraints,
159     )
160     self.feature_importances_ = self.model_.feature_importances_
161
162     return self
```

meth `predict`

```
predict(X)
```

Returns model predictions.

Source code in `src/tree_machine/classifier_cv.py`

```
163 def predict(self, X: Inputs) -> Predictions:
164     """
165     Returns model predictions.
166     """
167     check_is_fitted(self, "model_", msg="Model is not fitted.")
168     return self.model_.predict(self._validate_X(X))
```

meth `predict_proba`

```
predict_proba(X)
```

Returns model probability predictions.

” Source code in `src/tree_machine/classifier_cv.py`

```
170 def predict_proba(self, X: Inputs) -> Predictions:
171     """
172     Returns model probability predictions.
173     """
174     check_is_fitted(self, "model_", msg="Model is not fitted.")
175     return self.model_.predict_proba(self._validate_X(X))
```

### `class` ClassifierCVConfig

Available config to use when fitting a classification model.

 dictionary containing monotonicity direction allowed for each

variable. 0 means no monotonicity, 1 means increasing and -1 means decreasing monotonicity.

interactions: list of lists containing permitted relationships in data. parameters: dictionary with distribution bounds for each hyperparameter to search on during optimization. n\_jobs: Number of jobs to use when fitting the model. sampler: `imblearn` sampler to use when fitting models.



Source code in `src/tree_machine/classifier_cv.py`

```
34 @dataclass(frozen=True, config={"arbitrary_types_allowed": True})
35 class ClassifierCVConfig:
36     """
37     Available config to use when fitting a classification model.
38
39     monotone_constraints: dictionary containing monotonicity direction allowed
40     for each
41     variable. 0 means no monotonicity, 1 means increasing and -1 means
42     decreasing
43     monotonicity.
44     interactions: list of lists containing permitted relationships in data.
45     parameters: dictionary with distribution bounds for each hyperparameter to
46     search
47     on during optimization.
48     n_jobs: Number of jobs to use when fitting the model.
49     sampler: `imblearn` sampler to use when fitting models.
50     """
51
52     monotone_constraints: dict[str, int]
53     interactions: list[list[str]]
54     n_jobs: int
55     parameters: OptimizerParams
56     return_train_score: bool
57
58     def get_kwargs(self, feature_names: list[str]) -> dict:
59         """
60         Returns parsed and validated constraint configuration for a
61         ClassifierCV model.
62
63         Args:
64             feature_names: list of feature names. If empty, will return empty
65             constraints dictionaries and lists.
66         """
67         return {
68             "monotone_constraints": {
69                 feature_names.index(key): value
70                 for key, value in self.monotone_constraints.items()
71             },
72             "interaction_constraints": [
73                 [feature_names.index(key) for key in lt] for lt in
74                 self.interactions
75             ],
76             "n_jobs": self.n_jobs,
77         }
```

meth `get_kwargs`

`get_kwargs(feature_names)`

Returns parsed and validated constraint configuration for a ClassifierCV model.

**Parameters:**

| Name                       | Type                   | Description  | Default         |
|----------------------------|------------------------|--|-----------------|
| <code>feature_names</code> | <code>list[str]</code> | list of feature names. If empty, will return empty constraints dictionaries and lists. | <i>required</i> |

” Source code in `src/tree_machine/classifier_cv.py`

```
55 def get_kwargs(self, feature_names: list[str]) -> dict:
56     """
57     Returns parsed and validated constraint configuration for a ClassifierCV
58     model.
59
60     Args:
61         feature_names: list of feature names. If empty, will return empty
62         constraints dictionaries and lists.
63     """
64     return {
65         "monotone_constraints": {
66             feature_names.index(key): value
67             for key, value in self.monotone_constraints.items()
68         },
69         "interaction_constraints": [
70             [feature_names.index(key) for key in lt] for lt in
71 self.interactions
72         ],
73         "n_jobs": self.n_jobs,
74     }
```