

Part 1

[slide 4]

Check the list of docker images:

```
$ docker images
```

REPOSITORY	TAG	IMAGE ID	CREATED	SIZE
------------	-----	----------	---------	------

Get our first docker image (**syntax** `docker pull IMAGE`):

```
$ docker pull python:alpine
```

Check the list of docker images:

```
$ docker images
```

REPOSITORY	TAG	IMAGE ID	CREATED	SIZE
python	alpine	8eb1c554687d	3 weeks ago	90.4MB

[slide 5]

Run the our first container:

```
$ docker run python:alpine
```

Nothing happened, since there's no pre-configured command to run.

Let's indicate a command then (**syntax** `docker run IMAGE CMD`):

```
$ docker run python:alpine python --version
Python 3.6.5
```

Hello world!

Python:

```
$ python -c 'print("hello world!")'
hello world!
```

Python in Docker:

```
$ docker run python:alpine python -c 'print("hello world!")'
hello world!
```

Alternative:

```
$ echo "hello world!"
hello world!
$ docker run python:alpine echo "hello world!"
hello world!
```

Listing containers running

Let's check the list of containers running:

```
$ docker ps
```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	PORTS
--------------	-------	---------	---------	--------	-------

Well, nothing as expected.

Let's run a container for some time then.

```
$ man sleep
$ docker run python:alpine sleep 10
```

In the next 10 seconds, run in another terminal:

```
$ docker ps
```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	PORTS
6e6be0c8f31c	python:alpine	"sleep 10"	Less than a second ago	Up 1 second	

[slide 5]

Let's create simple container

Our first Dockerfile:

```
FROM python:alpine
```

```
CMD python -c 'print("hello world!")'
```

Let's now build the docker image with a repository and tag, as in `python:alpine` (syntax `docker build -f FILE -t IMAGE DIR`):

```
$ docker build -f Dockerfile -t vitorenesduarte/tutorial:hello .
```

And check that the new image is in the list of images:

```
$ docker images
```

REPOSITORY	TAG	IMAGE ID	CREATED	SIZE
vitorenesduarte/tutorial	hello	49aa76850e83	About a minute ago	90.4MB
python	alpine	8eb1c554687d	3 weeks ago	90.4MB

Let's run our app:

```
$ docker run vitorenesduarte/tutorial:hello
hello world!
```

But this is not how we write apps, right?

Let's then create a file named `hello.py` with:

```
print("hello world!")
```

Verify it is okay:

```
$ python hello.py
hello world!
```

And modify Dockerfile to:

```
FROM python:alpine
```

```
COPY hello.py /
```

```
CMD python hello.py
```

Let's build the image again:

```
$ docker build -t vitorenesduarte/tutorial:hello .
```

Note how we didn't indicate which file to use. Docker tries to find a file named `Dockerfile` in the directory passed as argument.

Verify `hello.py` was indeed copied to the docker image:

```
$ docker run vitorenesduarte/tutorial:hello ls | grep hello
hello.py
```

Let's run it again:

```
docker run vitorenesduarte/tutorial:hello
hello world!
```

[slide 7]