

# Lecture 12: Responsible AI: Uncertainty, Explainability and Fairness

Chrysoula Zerva



Deep Learning Course, Winter 2023-2024

## Today's Roadmap

In the previous lectures you have seen different neural architectures, the potential of deep neural models and their applications.

## Today's Roadmap

In the previous lectures you have seen different neural architectures, the potential of deep neural models and their applications.

Today we will discuss additional aspects beyond performance that are important across different neural architectures, to enhance **trust** in models.

## Today's Roadmap

In the previous lectures you have seen different neural architectures, the potential of deep neural models and their applications.

Today we will discuss additional aspects beyond performance that are important across different neural architectures, to enhance **trust** in models.

We will focus on **Responsible AI** and touch on: model **uncertainty**, **explainability** and **fairness**.

- HW2 is due Jan 6 !

# Outline

- ① Motivation
- ② Uncertainty
- ③ Explainability
- ④ Fairness and Ethical AI
- ⑤ Conclusions

## Quote of the day

“All models are wrong, but some can be useful”

George Box

## Quote of the day


“All models are wrong, but some can be useful”

George Box


“... if we can trust them”

# Who should trust AI (models)?

# Who should trust AI (models)?



# Who should trust AI (models)?

- improve understanding
  - anticipate issues
  - develop/train better models
  - deploy safely
- 
- The diagram consists of three colored circular icons representing different stakeholders. A blue icon is labeled 'developer' below it. A red icon is labeled 'customer' below it. A green icon is labeled 'regulator' below it.

# Who should trust AI (models)?

- improve understanding
  - anticipate issues
  - develop/train better models
  - deploy safely
- 
- The diagram illustrates three stakeholders in AI development and deployment:
- developer** (blue): responsible for improving understanding, anticipating issues, developing/training better models, and deploying safely.
  - customer** (red): responsible for understanding purpose/limits, trusting output, informed consent, and correct/safe use.
  - regulator** (green): responsible for understanding purpose/limits, trusting output, informed consent, and correct/safe use.

- understand purpose/limits
- trust output
- informed consent
- correct/safe use

# Who should trust AI (models)?

- improve understanding
  - anticipate issues
  - develop/train better models
  - deploy safely
- 
- The diagram features three stylized human figures with brown hair. A blue figure is labeled 'developer' below it. A red figure is labeled 'customer' below it. A green figure is labeled 'regulator' below it.
- understand purpose/limits
  - trust output
  - informed consent
  - correct/safe use

regulator

- understand impact and implications
  - monitor & report
  - adapt regulations
- EC Artificial Intelligence (AI) Act
- ChatGPT use-regulation

# Outline

- ① Motivation
- ② Uncertainty
- ③ Explainability
- ④ Fairness and Ethical AI
- ⑤ Conclusions

# Uncertainty in Machine Learning

- Typical setup:
  - Training input set  $\mathcal{X}^T$
  - Learned outputs  $\mathcal{Y}^T$
  - Neural model  $\mathcal{M}$  with parameters  $\theta$ :  $y = \mathcal{F}(x)$
  - Performance metric(s)




# Uncertainty in Machine Learning

- Typical setup:
  - Training input set  $\mathcal{X}^T$
  - Learned outputs  $\mathcal{Y}^T$
  - Neural model  $\mathcal{M}$  with parameters  $\theta$ :  $y = \mathcal{F}(x)$
  - Performance metric(s)



- Assume:
  - Test sample  $x^i, x^i \in \mathcal{X}^{\text{test}}$
  - How **trustworthy**  $y^i$  is?

# Example in Deep Learning




Oxford-IIIT-Pet-dataset Parkhi et al. (2012)

# Example in Deep Learning: Image recognition

During test time:


# Example in Deep Learning: Image recognition

During test time:



# Example in Deep Learning: Image recognition


During test time:



- Is it expected for the model to be wrong out-of-domain ?

# Example in Deep Learning: Image recognition


During test time:



- Is it expected for the model to be wrong out-of-domain ?
  - Could we have an indication that the model is **confused**?


# Uncertainty in Machine Learning

Let's see a simpler example:




# Uncertainty in Machine Learning

Let's see a simpler example:




# Uncertainty in Machine Learning

Let's see a simpler example:



# Uncertainty in Machine Learning


Let's see a simpler example:



For which test point will we have a more **confident** prediction?


# Uncertainty in Machine Learning

Let's see a simpler example:



# Uncertainty in Machine Learning

Let's see a simpler example:



# Types of Uncertainty

Aleatoric uncertainty → "uncertainty of the data"

- Noisy data
  - Noisy labels/annotations
  - Noisy measurements
- Missing/partially observed data

# Types of Uncertainty

Aleatoric uncertainty → "uncertainty of the data"

- Noisy data
  - Noisy labels/annotations
  - Noisy measurements
- Missing/partially observed data



# Types of Uncertainty

Aleatoric uncertainty → "uncertainty of the data"



- Noisy data
  - Noisy labels/annotations
  - Noisy measurements
- Missing/partially observed data

# Types of uncertainty

Epistemic uncertainty: → “uncertainty of the model”

- Distribution shift / Out-of-distribution data:  
 $p_{train}(y, x) \neq p_{test}(y, x)$ 
  - **Covariate shift:** Distribution of features  $p(x)$  changes and  $p(y|x)$  is fixed.
  - **Open-set recognition:** New classes during test-time
  - **Subpopulation shift:** Frequencies of data subpopulations changes.
  - **Label shift:** Distribution of labels  $p(y)$  changes and  $p(x|y)$  is fixed.

# Types of uncertainty

Epistemic uncertainty: → “uncertainty of the model”

- Distribution shift / Out-of-distribution data:  
 $p_{train}(y, x) \neq p_{test}(y, x)$ 
  - **Covariate shift:** Distribution of features  $p(x)$  changes and  $p(y|x)$  is fixed.
  - **Open-set recognition:** New classes during test-time
  - **Subpopulation shift:** Frequencies of data subpopulations changes.
  - **Label shift:** Distribution of labels  $p(y)$  changes and  $p(x|y)$  is fixed.




# Types of uncertainty

Epistemic uncertainty: → “uncertainty of the model”


- Distribution shift / Out-of-distribution data:  
 $p_{train}(y, x) \neq p_{test}(y, x)$ 
  - **Covariate shift:** Distribution of features  $p(x)$  changes and  $p(y|x)$  is fixed.
  - **Open-set recognition:** New classes during test-time
  - **Subpopulation shift:** Frequencies of data subpopulations changes.
  - **Label shift:** Distribution of labels  $p(y)$  changes and  $p(x|y)$  is fixed.



# Types of uncertainty




# Types of uncertainty



aleatoric : the Latin word alea  
refers to a dice-like game


# Types of uncertainty



aleatoric : the Latin word alea  
refers to a dice-like game

irreducible error

# Types of uncertainty



aleatoric : the Latin word alea  
refers to a dice-like game

episteme: the Greek word for  
*knowledge*

irreducible error

# Types of uncertainty

## Predictive uncertainty

Aleatoric uncertainty

Epistemic uncertainty



aleatoric : the Latin word alea  
refers to a dice-like game

irreducible error

episteme: the Greek word for  
*knowledge*

reducible error

# Types of uncertainty

## Predictive uncertainty

Aleatoric uncertainty

Epistemic uncertainty



aleatoric : the Latin word alea  
refers to a dice-like game

irreducible error

episteme: the Greek word for  
*knowledge*

reducible error

# Types of uncertainty

## Predictive uncertainty

Aleatoric uncertainty

Epistemic uncertainty



aleatoric : the Latin word alea  
refers to a dice-like game

irreducible error

episteme: the Greek word for  
*knowledge*

reducible error

Assume two models  $\mathcal{M}_1$  and  $\mathcal{M}_2$  that estimate the dice-rolling outcome  $p(x|d)$ , for a six-sided dice  $d$ .

# Types of uncertainty

## Predictive uncertainty

Aleatoric uncertainty

Epistemic uncertainty



aleatoric : the Latin word alea  
refers to a dice-like game

episteme: the Greek word for  
*knowledge*

irreducible error

reducible error

Assume two models  $\mathcal{M}_1$  and  $\mathcal{M}_2$  that estimate the dice-rolling outcome  $p(x|d)$ , for a six-sided dice  $d$ .

- $\mathcal{M}_1$  has seen only the following roll outcomes:  
 $\{1, 2, 2, 3, 3, 3, 4, 5\}$
- $\mathcal{M}_2$  has seen a very large number of rolls (infinite)

# Types of uncertainty

## Predictive uncertainty

Aleatoric uncertainty

Epistemic uncertainty



aleatoric : the Latin word *alea* refers to a dice-like game

irreducible error

episteme: the Greek word for knowledge

reducible error

Assume two models  $\mathcal{M}_1$  and  $\mathcal{M}_2$  that estimate the dice-rolling outcome  $p(x|d)$ , for a six-sided dice  $d$ .

- $\mathcal{M}_1$  has seen only the following roll outcomes:  
 $\{1, 2, 2, 3, 3, 3, 4, 5\}$
- $\mathcal{M}_2$  has seen a very large number of rolls (infinite)

What is the expected uncertainty for the predicted outcome  $\hat{y} = 5$ ?

## More on dice...

What if we apply the same models on these dice?



## Reducible vs Irreducible error

The concept of error/ uncertainty **reducibility** is key in improving a NN but (ir)reducibility **depends on our choices and assumptions** (Der Kiureghian and Ditlevsen, 2009):

- What is fixed in our data?
  - What is fixed in the data representation?
  - What is fixed in our model architecture?
- What if we change only one of the above?

Reducibility is more of a **spectrum** rather than a fixed categorization

# Why is modeling uncertainty important?

We want the model to **know what it doesn't know**

# Why is modeling uncertainty important?

We want the model to **know what it doesn't know**

- Decide if a prediction must be further inspected

# Why is modeling uncertainty important?


We want the model to **know what it doesn't know**

- Decide if a prediction must be further inspected
- Useful for debugging, retraining, adapting a model

# Why is modeling uncertainty important?

We want the model to **know what it doesn't know**

- Decide if a prediction must be further inspected
- Useful for debugging, retraining, adapting a model
- Some applications are higher risk than others



# Uncertainty Quantification

- How do we estimate uncertainty?

# Uncertainty Quantification

- How do we estimate uncertainty?
  - ▶ In information theory:

# Uncertainty Quantification

- How do we estimate uncertainty?
  - In information theory: **Entropy**

# Uncertainty Quantification

- How do we estimate uncertainty?
  - In information theory: **Entropy**  
(for  $\hat{y} = \mathcal{F}(x)$ )

# Uncertainty Quantification

- How do we estimate uncertainty?
  - In information theory: **Entropy**  
(for  $\hat{y} = \mathcal{F}(x)$ )
  - **Continuous predictions** (regression):  
$$\mathcal{H}(p(\hat{y}|x)) = E[-\log p(\hat{y}|x)] = - \int_{y \in \mathcal{Y}} p(\hat{y}|x) \log p(\hat{y}|x) dx$$
  - **Discrete predictions** (classification):  
$$\mathcal{H}(p(\hat{y}|x)) = - \sum_{\hat{y} \in \mathcal{Y}} p(\hat{y}|x) \log p(\hat{y}|x)$$

# Uncertainty Quantification

- How do we estimate uncertainty?

► In information theory: **Entropy**  
(for  $\hat{y} = \mathcal{F}(x)$ )

- **Continuous predictions** (regression):

$$\mathcal{H}(p(\hat{y}|x)) = E[-\log p(\hat{y}|x)] = - \int_{y \in \mathcal{Y}} p(\hat{y}|x) \log p(\hat{y}|x) dx$$

- **Discrete predictions** (classification):

$$\mathcal{H}(p(\hat{y}|x)) = - \sum_{\hat{y} \in \mathcal{Y}} p(\hat{y}|x) \log p(\hat{y}|x)$$

► If we assume a training set  $\mathcal{D}$ :

$$\begin{aligned}\mathcal{H}[P(y | x, \mathcal{D})] &= \mathbb{E}_{P(y|x, \mathcal{D})}[-\ln P(y | x, \mathcal{D})] = \\ &= - \sum_{y \in \mathcal{Y}} P(y | x, \mathcal{D}) \ln P(y | x, \mathcal{D})\end{aligned}$$

# Uncertainty Quantification

- How do we estimate uncertainty?
  - ▶ Dispersion of a random variable in statistics?

# Uncertainty Quantification

- How do we estimate uncertainty?
  - ▶ Dispersion of a random variable in statistics?
    - We need to obtain a **distribution** of predictions  $\hat{\mathcal{Y}} = \{\hat{y}_1, \hat{y}_2, \dots, \hat{y}_N\}$  instead of a single point estimate  $\hat{y}$

# Uncertainty Quantification


- How do we estimate uncertainty?
  - ▶ Dispersion of a random variable in statistics? **Variance**
    - We need to obtain a **distribution** of predictions  $\hat{\mathcal{Y}} = \{\hat{y}_1, \hat{y}_2, \dots, \hat{y}_N\}$  instead of a single point estimate  $\hat{y}$
    - Assume a Gaussian distribution:  $\sim \mathcal{N}(\hat{y}, \sigma^2)$

# Uncertainty Quantification

- How do we estimate uncertainty?
  - ▶ Dispersion of a random variable in statistics? **Variance**
    - We need to obtain a **distribution** of predictions  $\hat{\mathcal{Y}} = \{\hat{y}_1, \hat{y}_2, \dots, \hat{y}_N\}$  instead of a single point estimate  $\hat{y}$
    - Assume a Gaussian distribution:  $\sim \mathcal{N}(\hat{y}, \sigma^2)$
  - ▶ How do we obtain such a distribution?

# Uncertainty Quantification

How can we obtain a distribution over  $\hat{y}$ ?




# Variance-based Uncertainty Quantification

## Bayesian Neural Networks (BNN)

# Variance-based Uncertainty Quantification

## Bayesian Neural Networks (BNN)

Apply a prior distribution over model weights, e.g. a Gaussian:  
 $W \sim \mathcal{N}(0, I)$ .




# Variance-based Uncertainty Quantification

## Bayesian Neural Networks (BNN)

Apply a prior distribution over model weights, e.g. a Gaussian:  $W \sim \mathcal{N}(0, I)$ .

- ▶ model likelihood:  $p(y|\hat{y}) = p(y|f^W(x))$ ;
- ▶ posterior over the model parameters:  
$$p(W|X, Y) = \frac{p(W|X, Y)p(W)}{p(Y|X)}.$$




# Variance-based Uncertainty Quantification

## Bayesian Neural Networks (BNN)

Apply a prior distribution over model weights, e.g. a Gaussian:  $W \sim \mathcal{N}(0, I)$ .

- ▶ model likelihood:  $p(y|\hat{y}) = p(y|f^W(x))$ ;
- ▶ posterior over the model parameters:

$$p(W|X, Y) = \frac{p(W|X, Y)p(W)}{p(Y|X)}.$$



This is **intractable** for most interesting networks...

# Approximate inference

The realistic solution: variational inference

# Approximate inference

The realistic solution: variational inference

- ▶ approximate the intractable posterior distribution  $p(W|X, Y) \rightarrow$  fit with a simple distribution parameterized by  $\theta$ ,  $q_\theta(W)$

# Approximate inference

The realistic solution: variational inference

- ▶ approximate the intractable posterior distribution  $p(W|X, Y) \rightarrow$  fit with a simple distribution parameterized by  $\theta$ ,  $q_\theta(W)$
- ▶ measure the distance between two probability distributions  $q(x)$  and  $p(x)$ : KL-divergence

# Approximate inference

The realistic solution: variational inference

- ▶ approximate the intractable posterior distribution  $p(W|X, Y) \rightarrow$  fit with a simple distribution parameterized by  $\theta$ ,  $q_\theta(W)$
- ▶ measure the distance between two probability distributions  $q(x)$  and  $p(x)$ : KL-divergence

$$KL(q(x)\|p(x)) \equiv \mathbb{E}_{q(x)}[\log \frac{q(x)}{p(x)}] = \int q(x) \log \frac{q(x)}{p(x)} dx$$

# Approximate inference

The realistic solution: variational inference

- ▶ approximate the intractable posterior distribution  $p(W|X, Y) \rightarrow$  fit with a simple distribution parameterized by  $\theta$ ,  $q_\theta(W)$
- ▶ measure the distance between two probability distributions  $q(x)$  and  $p(x)$ : KL-divergence

$$KL(q(x)\|p(x)) \equiv \mathbb{E}_{q(x)}[\log \frac{q(x)}{p(x)}] = \int q(x) \log \frac{q(x)}{p(x)} dx$$

In practice we need some more tricks to optimise:

$$\begin{aligned} KL(q(w)\|p(w|X, Y)) &= \mathbb{E}_{q(x)}[\log \frac{q(w)}{p(w|X, Y)}] = \\ &= \int q(w) \log \frac{q(w)}{p(w|X, Y)} dw = \dots \\ \dots &= KL(q(w)\|p(w)) + \log p(X, Y) - \mathbb{E}_{q(x)}[\log p(X, Y|w)] \end{aligned}$$

# Approximate inference

The realistic solution: variational inference

- ▶ approximate the intractable posterior distribution  $p(W|X, Y) \rightarrow$  fit with a simple distribution parameterized by  $\theta$ ,  $q_\theta(W)$
- ▶ measure the distance between two probability distributions  $q(x)$  and  $p(x)$ : KL-divergence

$$KL(q(x)\|p(x)) \equiv \mathbb{E}_{q(x)}[\log \frac{q(x)}{p(x)}] = \int q(x) \log \frac{q(x)}{p(x)} dx$$

In practice we need some more tricks to optimise:

$$KL(q(w)\|p(w|X, Y)) = \mathbb{E}_{q(x)}[\log \frac{q(w)}{p(w|X, Y)}] =$$

$$= \int q(w) \log \frac{q(w)}{p(w|X, Y)} dw = \dots$$

$$\dots = KL(q(w)\|p(w)) + \log p(X, Y) - \mathbb{E}_{q(x)}[\log p(X, Y|w)]$$

...but we can now sample from  $q(w)$


# Uncertainty Quantification

## Deep Ensembles (DE):

# Uncertainty Quantification

## Deep Ensembles (DE):

- ▶ Obtain multiple model checkpoints
  - Different seeds;
  - Different hyper-parameters/training steps;
  - Bootstrap on data subsets;
- ▶  $p(y|x, \mathcal{D}) = \mathbb{E}_{q(\theta)}[P(y|x, \theta)] \approx \frac{1}{M} \sum_{m=1}^M P(y|x, \theta^{(m)})$ ,  $\theta^{(m)} \sim q(\theta) \approx p(\theta|D)$




# Uncertainty Quantification

## Monte Carlo Dropout (MCD):

# Uncertainty Quantification


## Monte Carlo Dropout (MCD):

- ▶ Apply model dropout during inference.
- ▶ Run multiple stochastic forward runs.
- ▶ We can define the likelihood as  $p(y|\hat{y}) \sim \mathcal{N}(\mu(\hat{y}), \sigma(\hat{y})^2)$   
 $p(y|x, \mathcal{D}) \approx \frac{1}{T} \sum_{t=1}^T \text{Softmax}(f^{W_t}(x)),$   
 $W_t \sim q_\theta(W)$




# Uncertainty Quantification

How do we estimate uncertainty uncertainties?



# Uncertainty Quantification


How do we estimate uncertainty uncertainties?



- ▶ What uncertainties do we need to estimate?

# Uncertainty Quantification

How do we estimate uncertainty uncertainties?



- ▶ What uncertainties do we need to estimate?


$$U_{\text{total}} = U_{\text{al}} + U_{\text{ep}}$$

total uncertainty      aleatoric/data uncertainty      epistemic/model/knowledge uncertainty

(Malinin and Gales, 2020)

# Aleatoric Uncertainty in Deep Learning

In object recognition (Kendall and Gal, 2017):




Input image

Segmented image

aleatoric noise

# Aleatoric Uncertainty in Deep Learning

In object recognition (Kendall and Gal, 2017):



In machine translation:




# Aleatoric Uncertainty Estimation

What assumptions can we make about noise in the data? (Malinin, 2019)


# Aleatoric Uncertainty Estimation

What assumptions can we make about noise in the data? (Malinin, 2019)

- Homoscedastic noise: **constant** noise variance
  - Does not depend on input



(a) Dataset with homoscedastic noise




(b) Mean and homoscedastic variance


# Aleatoric Uncertainty Estimation

What assumptions can we make about noise in the data?

- Heteroscedastic noise: **variable** noise variance
  - Does depend on input



(c) Dataset with heteroscedastic noise



(d) Mean and heteroscedastic variance

# Estimating Aleatoric uncertainty

What can we use to estimate aleatoric uncertainty?

- If we have access to the dataset:

We can distill the uncertainty using the entropy-based approach and  
**conditioning on the model weights**

$$\begin{aligned}\mathcal{H}(p(\hat{y}|x)) &= - \sum_{\hat{y} \in \mathcal{Y}} p(\hat{y}|x) \log p(\hat{y}|x) \rightarrow \\ &\rightarrow \mathcal{H}(p(\hat{y}|x, w)) = - \sum_{\hat{y} \in \mathcal{Y}} p(\hat{y}|x, w) \log p(\hat{y}|x, w)\end{aligned}$$

# Predicting Aleatoric Uncertainty

What can we use to estimate aleatoric uncertainty?

- If we have access to **multiple human judgements** per segment:

# Predicting Aleatoric Uncertainty

What can we use to estimate aleatoric uncertainty?

- If we have access to **multiple human judgements** per segment:
  - Assume we can estimate a metric of dispersion of human scores per instance: e.g. assume the scores follow a Gaussian distribution  $y \sim \mathcal{N}(\mu_h, \sigma_h^2)$
  - We would like to learn  $\mu_h$  as the target quality score and  $\sigma_h$  as the target uncertainty score
  - We want to learn to predict a Gaussian as close as possible to  $\mathcal{N}(\mu_h, \sigma_h^2) \rightarrow$  minimize KL divergence:  $\text{KL}(p_{y_h} \| p_{\hat{y}})$
  - Learning objective:  $\mathcal{L}_{\text{KL}} = \frac{(\mu_h - \hat{\mu})^2 + \sigma_h^2}{2\hat{\sigma}^2} + \frac{1}{2} \log \frac{\hat{\sigma}^2}{\sigma_h^2} - \frac{1}{2}$

# Predicting Aleatoric Uncertainty

What can we use to estimate aleatoric uncertainty?

- If we have access to **multiple human judgements** per segment:
  - Assume we can estimate a metric of dispersion of human scores per instance: e.g. assume the scores follow a Gaussian distribution  $y \sim \mathcal{N}(\mu_h, \sigma_h^2)$
  - We would like to learn  $\mu_h$  as the target quality score and  $\sigma_h$  as the target uncertainty score
  - We want to learn to predict a Gaussian as close as possible to  $\mathcal{N}(\mu_h, \sigma_h^2) \rightarrow$  minimize KL divergence:  $\text{KL}(p_{y_h} \| p_{\hat{y}})$
  - Learning objective:  $\mathcal{L}_{\text{KL}} = \frac{(\mu_h - \hat{\mu})^2 + \sigma_h^2}{2\hat{\sigma}^2} + \frac{1}{2} \log \frac{\hat{\sigma}^2}{\sigma_h^2} - \frac{1}{2}$
- If we have access to **single** human judgment per segment?
  - $\mathcal{L}_{\text{HTS}} = \frac{\|y_i - \hat{y}_i\|^2}{2\hat{\sigma}^2} + \frac{1}{2} \log \hat{\sigma}^2$

# Predicting Epistemic Uncertainty

# Predicting Epistemic Uncertainty

Typically we try to estimate epistemic uncertainty using:

# Predicting Epistemic Uncertainty

Typically we try to estimate epistemic uncertainty using:

- Variance based methods

# Predicting Epistemic Uncertainty

Typically we try to estimate epistemic uncertainty using:

- Variance based methods
- Total uncertainty estimates  $U_{\text{ep}} = U_{\text{total}} - U_{\text{al}}$

# Predicting Epistemic Uncertainty

Typically we try to estimate epistemic uncertainty using:

- Variance based methods
- Total uncertainty estimates  $U_{\text{ep}} = U_{\text{total}} - U_{\text{al}}$
- Mutual information  $\mathcal{I}$  between  $\theta$  and  $y$ :

$$\mathcal{I}[y, \theta | x, \mathcal{D}] = \mathbb{E}_{q(\theta)} [\mathbb{E}_{p(y|x, \theta)} [\ln \frac{P(y|x, \theta)}{P(y|x, \mathcal{D})}]]$$

# Predicting Epistemic Uncertainty

Typically we try to estimate epistemic uncertainty using:

- Variance based methods
- Total uncertainty estimates  $U_{\text{ep}} = U_{\text{total}} - U_{\text{al}}$
- Mutual information  $\mathcal{I}$  between  $\theta$  and  $y$ :

$$\mathcal{I}[y, \theta | x, \mathcal{D}] = \mathbb{E}_{q(\theta)} [\mathbb{E}_{p(y|x, \theta)} [\ln \frac{P(y|x, \theta)}{P(y|x, \mathcal{D})}]]$$

- Can we use error estimates to improve the estimation of epistemic uncertainty?

# Predicting Epistemic Uncertainty

Typically we try to estimate epistemic uncertainty using:

- Variance based methods
- Total uncertainty estimates  $U_{\text{ep}} = U_{\text{total}} - U_{\text{al}}$
- Mutual information  $\mathcal{I}$  between  $\theta$  and  $y$ :

$$\mathcal{I}[y, \theta | x, \mathcal{D}] = \mathbb{E}_{q(\theta)}[\mathbb{E}_{p(y|x, \theta)}[\ln \frac{P(y|x, \theta)}{P(y|x, \mathcal{D})}]]$$

- ▶ Can we use error estimates to improve the estimation of epistemic uncertainty?
- **Direct Uncertainty Prediction:** What if we train another model to predict the error of the main predictor? (Jain et al., 2021)
  - ▶ regress on the residuals

# Uncertainties for large language models

What if we can only access (sample from) the output?

# Uncertainties for large language models

What if we can only access (sample from) the output?

- Compute the semantic diversity of sentences sampled from the model  
(Kuhn et al., 2023)

# Uncertainties for large language models

What if we can only access (sample from) the output?

- ▶ Compute the semantic diversity of sentences sampled from the model  
(Kuhn et al., 2023)

- ➊ Sample M sequences  $\{s^{*(1)}, \dots, s^{(M)}\}$  from the predictive distribution of a large language model given a context  $x$
- ➋ Cluster sequences by semantic equivalence (bi-directional entailment)
- ➌ Entropy estimation: Approximate **semantic entropy** by summing probabilities that share a meaning (same cluster)

# Uncertainties for large language models

What if we can only access (sample from) the output?

- ▶ Compute the semantic diversity of sentences sampled from the model (Kuhn et al., 2023)

- ➊ Sample M sequences  $\{s^{*(1)}, \dots, s^{(M)}\}$  from the predictive distribution of a large language model given a context  $x$
- ➋ Cluster sequences by semantic equivalence (bi-directional entailment)
- ➌ Entropy estimation: Approximate **semantic entropy** by summing probabilities that share a meaning (same cluster)

(a) Scenario 1: No semantic equivalence

Answer s	Likelihood $p(s   x)$	Semantic likelihood $\sum_{s \in c} p(s   x)$
Paris	0.5	0.5
Rome	0.4	0.4
London	0.1	0.1
Entropy	0.31	0.31

(b) Scenario 2: Some semantic equivalence

Answer s	Likelihood $p(s   x)$	Semantic likelihood $\sum_{s \in c} p(s   x)$
Paris	0.5	
It's Paris	0.4	{}
London	0.1	0.1
Entropy	0.31	0.16

# Uncertainties for large language models

## Verbalized uncertainty:

- Can the model quantify its own uncertainty?
- Can we prompt for it?

citeplin2022teaching

# Uncertainties for large language models

## Verbalized uncertainty:

- Can the model quantify its own uncertainty?
- Can we prompt for it?



You

Can you translate the sentence "We saw her duck." into Portuguese and provide confidence intervals (numeric) for each translated token?

citeplin2022teaching

# Uncertainties for large language models

## Verbalized uncertainty:



### ChatGPT

Sure! Let's translate each token and provide a qualitative assessment of confidence intervals:

#### 1. We → Nós

- Confidence Interval: Very High. This is a direct translation of "we."

#### 2. saw → vimos

- Confidence Interval: Very High. "Vimos" is the correct past tense form of "ver" (to see) in Portuguese for the first person plural ("we").

#### 3. her → a

- Confidence Interval: High. In this context, "a" can stand for "her" when referring to a direct object in Portuguese. However, if we want to be more specific, the translation could vary depending on context.

#### 4. duck → pato

- Confidence Interval: Very High. "Pato" is a direct translation for "duck" in Portuguese.

So, the translated sentence would be:

# Uncertainties for large language models

## Verbalized uncertainty:



You

What is the difference between high and very high confidence?



ChatGPT

When assessing the confidence of a translation or any statement, terms like "high" and "very high" are qualitative descriptors rather than quantitatively defined metrics.

However, in general usage:

- 1. High Confidence:** This indicates a strong level of certainty or reliability in the provided translation or statement. When I label a translation with "high confidence," it means that the translation is considered accurate and appropriate in most standard contexts. There might be some rare exceptions or nuances, but in general, it's a reliable translation or statement.
- 2. Very High Confidence:** This implies an even stronger level of certainty or reliability. When labeled as "very high confidence," the translation or statement is seen as almost universally accurate and appropriate in the context provided. It suggests a minimal possibility of error or ambiguity.

# Uncertainties for large language models

## Verbalized uncertainty:



You

Can you turn the confidence intervals into numeric ones?



ChatGPT


Assigning precise numeric confidence intervals to linguistic translations or statements is challenging due to the qualitative nature of language processing. Confidence intervals are typically used in statistical contexts to represent a range within which a parameter is likely to lie.

However, if we were to make a hypothetical attempt to quantify the confidence levels:

1. **Very High Confidence:** 90-100% confidence in the accuracy of the translation or statement. This means that, given the context, there's a high likelihood that the translation is correct and would be understood by native speakers without confusion.
2. **High Confidence:** 75-89% confidence in the accuracy of the translation or statement. While the translation or statement is considered reliable in most standard contexts, there might be rare exceptions or nuances that could introduce slight ambiguity.

# What is a meaningful uncertainty value?

## Error and coverage



# Calibration

The model uncertainty should be representative of how often/much the model is wrong (Kumar et al., 2019)


- ▶ The probability (uncertainty) estimates should be representative of the true correctness likelihood

# Calibration

The model uncertainty should be representative of how often/much the model is wrong (Kumar et al., 2019)

- The probability (uncertainty) estimates should be representative of the true correctness likelihood

- split into  $M$  bins by confidence
- $conf(B_m) = \frac{1}{|B_m|} \sum_{i \in B_m} \hat{p}_i$
- $acc(B_m) = \frac{1}{|B_m|} \sum_{i \in B_m} \mathbb{1}(\hat{y}_i = y_i)$
- $ECE = \frac{1}{M} \sum_{b=1}^M |acc(B_m) - conf(B_m)|$
- temperature scaling:  
 $\text{softmax} = \frac{e^{(z/T)}}{\sum_i e^{(z_i/T)}}$



## How do we evaluate uncertainty measures?

- What is a meaningful uncertainty value?

# How do we evaluate uncertainty measures?

## ► What is a meaningful uncertainty value?

- Coverage, Calibration error
- Tight confidence intervals
- Correlation with prediction error
- Detection of critical errors
- Correlation with annotator disagreement (aleatoric)
- Detection of OOD cases (epistemic)

# Uncertainty evaluation metrics

Generic measures:

# Uncertainty evaluation metrics

Generic measures:

- Expected calibration error (ECE) (Kuleshov et al., 2018)

# Uncertainty evaluation metrics

Generic measures:

- Expected calibration error (ECE) (Kuleshov et al., 2018)
- Coverage/accuracy
- Average negative log-likelihood :  $aNLL = -\frac{1}{|\mathcal{D}|} \sum_{x,y_i \in \mathcal{D}} \log \hat{p}(y_i | x)$

# Uncertainty evaluation metrics

Generic measures:

- Expected calibration error (ECE) (Kuleshov et al., 2018)
- Coverage/accuracy
- Average negative log-likelihood :  $aNLL = -\frac{1}{|\mathcal{D}|} \sum_{x,y_i \in \mathcal{D}} \log \hat{p}(y_i | x)$

# Uncertainty evaluation metrics

Generic measures:


- Expected calibration error (ECE) (Kuleshov et al., 2018)
- Coverage/accuracy
- Average negative log-likelihood :  $aNLL = -\frac{1}{|\mathcal{D}|} \sum_{x,y_i \in \mathcal{D}} \log \hat{p}(y_i | x)$
- Sharpness (width):  $sha = \frac{1}{|\mathcal{D}|} \sum_{x \in \mathcal{D}} \hat{\sigma}^2$

# Uncertainty evaluation metrics

Generic measures:

- Expected calibration error (ECE) (Kuleshov et al., 2018)
- Coverage/accuracy
- Average negative log-likelihood :  $aNLL = -\frac{1}{|\mathcal{D}|} \sum_{x,y_i \in \mathcal{D}} \log \hat{p}(y_i | x)$
- Sharpness (width):  $sha = \frac{1}{|\mathcal{D}|} \sum_{x \in \mathcal{D}} \hat{\sigma}^2$
- Correlation with residuals:  $r(u, |y - \hat{y}|)$

# Uncertainty-aware ML




# Outline

- ① Motivation
- ② Uncertainty
- ③ Explainability
- ④ Fairness and Ethical AI
- ⑤ Conclusions


# Motivation

Is uncertainty enough to understand **and trust** model behaviour?




# Motivation

Is uncertainty enough to understand **and trust** model behaviour?



# Deep Learning Motivation

Remember the high risk deep learning applications:



# Intrinsic Explainability

Some models are more explainable than others


# Intrinsic Explainability

Some models are more explainable than others → Intrinsicly explainable

# Intrinsic Explainability

Some models are more explainable than others → Intrinsicly explainable

- Decision trees




# Intrinsic Explainability

Some models are more explainable than others → Intrinsicly explainable

- Decision trees
- Linear models (GAMs, GLMs)


$$G(E_Y(y|x)) = \beta_0 + f_1(x_1) + f_2(x_2) + \cdots + f_n(x_n)$$



# Intrinsic Explainability

Some models are more explainable than others → Intrinsicly explainable

- Decision trees
- Linear models (GAMs, GLMs)
- Bayesian networks  
(Derks and Waal, 2021)



# Post-hoc Explainability


What about non intrinsically explainable models?

We can still extract explanations:

# Post-hoc Explainability

What about non intrinsically explainable models?


We can still extract explanations:



# Post-hoc Explainability

What about non intrinsically explainable models?

We can still extract explanations:




- Global explanations: Explain the decision of the model as a whole
- Cohort explanations: Explain the decisions on subgroups of data
- Local explanations: Explain the decision on individual inputs

# Post-hoc Explainability

What about non intrinsically explainable models?

We can still extract explanations:



- Global explanations: Explain the decision of the model as a whole
- Cohort explanations: Explain the decisions on subgroups of data
- Local explanations: Explain the decision on individual inputs

# Local Explainability

# Local Explainability

- **Model Specific** Explanations – Attribution-based methods
- **Model Agnostic** Explanations

# Local Explainability

- **Model Specific** Explanations – Attribution-based methods
  - Gradient-based explanations
    - Integrated Gradients (Sundararajan et al., 2017)
    - SmoothGrad (Smilkov et al., 2017)
    - GradCAM (Selvaraju et al., 2016)
    - XRAI (Kapishnikov et al., 2019)
  - Layer-wise relevance propagation (Bach et al., 2015)
  - Attention-based explanations (Vashisht et al., 2019)
- **Model Agnostic** Explanations

# Local Explainability

- **Model Specific** Explanations – Attribution-based methods
  - Gradient-based explanations
    - Integrated Gradients (Sundararajan et al., 2017)
    - SmoothGrad (Smilkov et al., 2017)
    - GradCAM (Selvaraju et al., 2016)
    - XRAI (Kapishnikov et al., 2019)
  - Layer-wise relevance propagation (Bach et al., 2015)
  - Attention-based explanations (Vashisht et al., 2019)
- **Model Agnostic** Explanations
  - Shapley values (SHAP) (Lundberg and Lee, 2017)
  - Input perturbation based explanations (LIME) (Ribeiro et al., 2016)
  - Counterfactual explanations (MiCE) (Ross et al., 2020)

# Local Explainability

- **Model Specific** Explanations – Attribution-based methods
  - Gradient-based explanations
    - Integrated Gradients (Sundararajan et al., 2017)
    - SmoothGrad (Smilkov et al., 2017)
    - GradCAM (Selvaraju et al., 2016)
    - XRAI (Kapishnikov et al., 2019)
  - Layer-wise relevance propagation (Bach et al., 2015)
  - Attention-based explanations (Vashisht et al., 2019)
- **Model Agnostic** Explanations
  - Shapley values (SHAP) (Lundberg and Lee, 2017)
  - Input perturbation based explanations (LIME) (Ribeiro et al., 2016)
  - Counterfactual explanations (MiCE) (Ross et al., 2020)

# Gradient-based explanations

# Gradient-based explanations

**Intuition:** Reveal which regions of the input are important for the final prediction

# Gradient-based explanations

**Intuition:** Reveal which regions of the input are important for the final prediction

→ How do **small changes** in the input features affect the output?

# Gradient-based explanations

**Intuition:** Reveal which regions of the input are important for the final prediction

- How do **small changes** in the input features affect the output?
- Use the **gradients** as an indication of feature importance?

## Gradient-based explanations

**Intuition:** Reveal which regions of the input are important for the final prediction

- How do **small changes** in the input features affect the output?
- Use the **gradients** as an indication of feature importance?

Assume a classification model with a class activation function  $S_c$  for each class  $c \in C$ , such that  $\text{class}(x)_i = \underset{c \in C}{\operatorname{argmax}}(S_c(x))$

# Gradient-based explanations

**Intuition:** Reveal which regions of the input are important for the final prediction

- How do **small changes** in the input features affect the output?
- Use the **gradients** as an indication of feature importance?

Assume a classification model with a class activation function  $S_c$  for each class  $c \in C$ , such that  $\text{class}(x)_i = \underset{c \in C}{\operatorname{argmax}}(S_c(x))$

- Compute the gradient of  $S_c$  with respect to  $x$
- Average gradients from all layers
- Smooth gradients
- Compute integrated gradients

## Integrated Gradients

Assume we have an image classification case: we want to explain  $F(x)$  for a given pixel  $x_i$



## Integrated Gradients


Assume we have an image classification case: we want to explain  $F(x)$  for a given pixel  $x_i$

**Intuition:** Start from a reference/baseline point and “move” towards instance  $x_i$

# Integrated Gradients

Assume we have an image classification case: we want to explain  $F(x)$  for a given pixel  $x_i$



**Intuition:** Start from a reference/baseline point and “move” towards instance  $x_i$



# Integrated Gradients

Assume we have an image classification case: we want to explain  $F(x)$  for a given pixel  $x_i$

**Intuition:** Start from a reference/baseline point and “move” towards instance  $x_i$



# Integrated Gradients


Step-by-step application:



Initial image  $x$

# Integrated Gradients


Step-by-step application:



Start from baseline  $\alpha = 0$


Interpolate images for small intervals from  $\alpha = 0.0$  to  $\alpha = 1.0$

# Integrated Gradients




# Integrated Gradients

Output visualisation & overlay on initial image:



# Integrated Gradients

Output visualisation & overlay on initial image:



- ▶ Can this approach explain other inputs?

# Attribution in NLP tasks

- Can we do this with text?

# Attribution in NLP tasks


► Can we do this with text?

- Gradient-based attribution  
on the word embedding  
space

# Attribution in NLP tasks

► Can we do this with text?


- Gradient-based attribution  
on the word embedding  
space
- Discretized integrated  
gradients (Sanyal and Ren,  
2021)



# Attribution in NLP tasks

► Can we do this with text?

- Gradient-based attribution on the word embedding space
- Discretized integrated gradients (Sanyal and Ren, 2021)



What if we focus on RNN or transformer models?

# Attention based explanations

Can attention explain model decisions?

$$\mathbf{c} = \mathbf{V}^\top \mathbf{p} = \sum_{i=1}^L p_i \mathbf{v}_i \in \mathbb{R}^{d_V}$$

# Attention based explanations

Can attention explain model decisions?

$$\mathbf{c} = \mathbf{V}^\top \mathbf{p} = \sum_{i=1}^L p_i \mathbf{v}_i \in \mathbb{R}^{d_V}$$

**Example:** sentiment classification

# Attention based explanations

Can attention explain model decisions?

$$\mathbf{c} = \mathbf{V}^\top \mathbf{p} = \sum_{i=1}^L p_i \mathbf{v}_i \in \mathbb{R}^{d_V}$$

**Example:** sentiment classification

fantastic movie one of the best film noir movies ever made  
a meandering inarticulate and ultimately disappointing film

# Attention based explanations

Can attention explain model decisions?

$$\mathbf{c} = \mathbf{V}^\top \mathbf{p} = \sum_{i=1}^L p_i \mathbf{v}_i \in \mathbb{R}^{d_V}$$


**Example:** sentiment classification

fantastic movie one of the best film noir movies ever made  
a meandering inarticulate and ultimately disappointing film


**Natural interpretation:**

- ▶ How significant is each token when computing the label?
- ▶ Which features is the model *attending to* ?

# Which attention to consider?



# Which attention to consider?



Ferrando et al. (2022); Ferrando and Costa-jussà (2021)

# Is attention explanation?

# Is attention explanation?

## Is Attention Interpretable?

Sofia Serrano\* Noah A. Smith\*†

\*Paul G. Allen School of Computer Science & Engineering,

University of Washington, Seattle, WA, USA

†Allen Institute for Artificial Intelligence, Seattle, WA, USA

{sofias6,nasmith}@cs.washington.edu

### The elephant in the interpretability room:

Why use attention as explanation when we have saliency methods?

Jasmijn Bastings

Google Research

bastings@google.com

Katja Filippova

Google Research

katjaf@google.com

### Attention is not Explanation

Sarthak Jain  
Northeastern University  
jain.sar@husky.neu.edu

Byron C. Wallace  
Northeastern University  
b.wallace@northeastern.edu

Sarah Wiegreffe\*  
School of Interactive Computing  
Georgia Institute of Technology  
saw@gatech.edu

Yuval Pinter\*  
School of Interactive Computing  
Georgia Institute of Technology  
uvp@gatech.edu

### Attention is not not Explanation

## Learning to Deceive with Attention-Based Explanations

Danish Pruthi†, Mansi Gupta‡, Bhuwan Dhingra†, Graham Neubig†, Zachary C. Lipton†

†Carnegie Mellon University, Pittsburgh, USA

‡Twitter, New York, USA

ddanish@cs.cmu.edu, mansig@twitter.com,  
{bdhingra, gneubig, zlipton}@cs.cmu.edu

# Attention based explanations

Can attention explain model decisions?

# Attention based explanations

Can attention explain model decisions?

## Against:

- Low correlation with gradient methods (Jain and Wallace, 2019)
- Changing the attention weights doesn't change the predicted label (Jain and Wallace, 2019)
- Very large weights do not always correspond to meaningful explanations

# Attention based explanations

Can attention explain model decisions?

## Against:

- Low correlation with gradient methods (Jain and Wallace, 2019)
- Changing the attention weights doesn't change the predicted label (Jain and Wallace, 2019)
- Very large weights do not always correspond to meaningful explanations

## In favour:

- Adversary attention distributions not equally plausible or faithful (Wiegreffe and Pinter, 2019)
- Attention can be useful for models without access to context (e.g. MLP) (Wiegreffe and Pinter, 2019)
- Can benefit from an auxiliary **word-level** task (Tutek and Snajder, 2020)

# Post-hoc Explainability


What about non intrinsically explainable models?

Local explanations:

- Model Specific Explanations – Attribution-based methods
  - Gradient-based explanations
    - Integrated Gradients
    - SmoothGrad
    - GradCAM
    - XRAI
  - Layer-wise relevance propagation
  - Attention-based explanations
- Model Generic Explanations
  - Shapley values (SHAP)
  - Perturbation-based explanations (LIME)
  - Counterfactual explanations

# Model Generic Explanations

- Can be applied to any model




**Intuition:** Which parts of the input influence the prediction? → Which parts of the input would change the predicted label if altered?

# LIME: Local Interpretable Model-agnostic Explanations


Assume  $\mathcal{M}$  predicts label  $\hat{y}$  for input  $x$

- Select regions of  $x$  – super-features
  - Neighboring groups of pixels
  - Words / ngrams
- Generate neighbors of  $x$  in the feature space
  - Noise over pixels
  - MASKS over words
- Fit a glass-box explainer,  $\mathcal{E}$  that will have the same predictions as  $\mathcal{M}$ 
  - ▶ A simple linear model would work
- ✓  $\mathcal{E}$  will explain the behaviour of  $\mathcal{M}$  in the neighborhood of  $x$




# Counterfactual Explanations

General idea:



# Counterfactual Explanations


General idea:



Counterfactual generation:

# Counterfactual Explanations

General idea:




Counterfactual generation:

- Template of valid shifts (Wu et al., 2021)

# Counterfactual Explanations

General idea:



Counterfactual generation:

- Template of valid shifts (Wu et al., 2021)
- Mask tokens (Ross et al., 2020)

# MiCE: Minimal Contrastive Editing

Assume  $\mathcal{M}$  predicts label  $\hat{y}$  for input  $x$

# MiCE: Minimal Contrastive Editing

Assume  $\mathcal{M}$  predicts label  $\hat{y}$  for input  $x$

- What needs to be edited for the prediction to change?

# MiCE: Minimal Contrastive Editing

Assume  $\mathcal{M}$  predicts label  $\hat{y}$  for input  $x$

- What needs to be edited for the prediction to change?


Train an editor  $\mathcal{E}$  to generate edits over  $x$ , such that  $\mathcal{M}$  predicts  $\hat{y}'$

# MiCE: Minimal Contrastive Editing

Assume  $\mathcal{M}$  predicts label  $\hat{y}$  for input  $x$

- What needs to be edited for the prediction to change?

Train an editor  $\mathcal{E}$  to generate edits over  $x$ , such that  $\mathcal{M}$  predicts  $\hat{y}'$




# MiCE: Minimal Contrastive Editing

Assume  $\mathcal{M}$  predicts label  $\hat{y}$  for input  $x$

- What needs to be edited for the prediction to change?

Train an editor  $\mathcal{E}$  to generate edits over  $x$ , such that  $\mathcal{M}$  predicts  $\hat{y}'$



- ✓  $\mathcal{E}$  will explain the behaviour of  $\mathcal{M}$  using contrastive examples

# Which is the best explanation?

What is a **good** explanation?

# Which is the best explanation?

What is a **good** explanation?

- **Who** is the explanation for?
  - Model developer / researcher
  - Consumer
  - Policy maker / regulator

# Which is the best explanation?

What is a **good** explanation?

- **Who** is the explanation for?
  - Model developer / researcher
  - Consumer
  - Policy maker / regulator
- What is the target **task**?
  - What is the modality?  
Text, Image, Sound, ...
  - Is it regression or  
classification ?

# Which is the best explanation?

What is a **good** explanation?

- **Who** is the explanation for?
    - Model developer / researcher
    - Consumer
    - Policy maker / regulator
  - What is the target **task**?
    - What is the modality?  
Text, Image, Sound, ...
    - Is it regression or  
classification ?
- Explanations should ensure:
- Completeness
  - Accuracy
  - Meaningfulness
  - Consistency
  - (Minimality)

# Outline

- ① Motivation
- ② Uncertainty
- ③ Explainability
- ④ Fairness and Ethical AI
- ⑤ Conclusions

# What is a fair/ethical model?

Assume a model:

- can achieve high performance
- can provide a confidence interval
- can provide an interpretable explanation

Is that sufficient?

► Can a model be (un)ethical?

# Ethical AI

What ethical concerns could be relevant?

# Ethical AI

What ethical concerns could be relevant?

- Discrimination bias
- Accessibility
- Privacy compromise
- Intellectual property compromise
- Sustainability / energy consumption

# Definitions of Bias

# Definitions of Bias

- What is bias in statistics?

## Definitions of Bias

- What is bias in statistics?

**Statistical bias** is a systematic tendency which causes differences between results and facts [Wikipedia]

## Definitions of Bias

- What is bias in statistics?

**Statistical bias** is a systematic tendency which causes differences between results and facts [Wikipedia]

- What is bias in ML?

# Definitions of Bias

- ▶ What is bias in statistics?

**Statistical bias** is a systematic tendency which causes differences between results and facts [Wikipedia]

- ▶ What is bias in ML?

**Inductive bias** (or learning bias) of an ML algorithm is the set of assumptions that the learner uses to predict outputs of given inputs that it has not encountered.

# Typology of Bias

# Typology of Bias

**Sample Bias:** Also Selection / Representation bias. The training dataset does not contain fair/balanced/sufficient representation of instances in the testing environment.

**Confounding bias:** The distortion of the association between the independent and dependent variables because a third variable is independently associated with both.

**Association bias:** Bias occurring from implicit associations in the training data: features might co-occur or correlate in the training data, without this association holding in the testing environment.

**Observer bias:** Also Confirmation bias. The effect of seeing what we expect to see in data. Subjective opinions influencing the data processing (labelling, feature manipulation, sampling)

**Exclusion bias:** Deleting valuable data or features thought to be unimportant/redundant.

**Discrimination Bias:** Also demographic / racial bias. The training dataset is data skewed in favour of particular demographics.

# Bias in practice

“Easier to teach a machine to see than to **understand** what it has seen”

Kosinski, 2018

## Bias in practice

“Easier to teach a machine to see than to **understand** what it has seen”

Kosinski, 2018

Biased ML models is not a recent concern; ML has its own urban legends

# Bias in practice


“Easier to teach a machine to see than to **understand** what it has seen”

Kosinski, 2018

Biased ML models is not a recent concern; ML has its own urban legends

- ▶ Failed DARPA experiment on distinguishing US vs Russian tanks

The neural net learned to distinguish:



# Bias in practice

"Easier to teach a machine to see than to **understand** what it has seen"

Kosinski, 2018

Biased ML models is not a recent concern; ML has its own urban legends

- ▶ Failed DARPA experiment on distinguishing US vs Russian tanks

The neural net learned to distinguish:

- high vs low resolution
- forest vs open-ground terrain
- cloudy vs clear sky




# Socially concerning ML bias


The hiring algorithm case:

Amazon scraps secret AI recruiting tool that showed bias against women

**Amazon Reportedly Killed an AI Recruitment System Because It Couldn't Stop the Tool from Discriminating Against Women**



Where does the bias come from?



**Overcoming AI's Challenge In Hiring: Avoid Human Bias**

Forbes Insights Insights Team Insights Contributor  
FORBES INSIGHTS With Intel AI | Paid Program  
Innovation



NOVEMBER 1, 2016

**Amazon's sexist hiring algorithm could still be better than a human**

by Maude Lavanchy, The Conversation

# Socially concerning ML bias

The criminal justice case:



# Socially concerning ML bias

The vision case:

# Socially concerning ML bias

The vision case:




No snapchat filters on darker skin



No soap dispenser activation on darker skin

# Socially concerning ML bias

The vision case:



Fail to recognise human objects when they have darker skin

# Socially concerning ML bias

The machine translation case:

# Socially concerning ML bias

The machine translation case:

A screenshot of a machine translation interface. At the top, there are language selection tabs: DETECT LANGUAGE, PORTUGUESE, ENGLISH (which is underlined in blue), and GREEK. Below this is a horizontal separator bar with a double-headed arrow icon. On the left side, the English input text is "The nurse had to leave because her shift ended". On the right side, the Portuguese output is "A enfermeira teve que sair porque seu turno terminou". There is a small star icon at the end of the Portuguese sentence. Below the text area are several icons: a microphone, a speaker, a progress bar indicating 46 / 5,000, and other standard UI elements.

# Socially concerning ML bias

The machine translation case:

The screenshot shows a machine translation interface with two examples. Both examples involve translating the sentence "The nurse had to leave because her shift ended" from English to Portuguese. In the first example, the gender is correctly translated as "A enfermeira". In the second example, the gender is incorrectly translated as "A enfermeira" instead of "O enfermeiro". The interface includes language detection, a word count (46 / 5,000), and various sharing and export options.

DETECT LANGUAGE	PORUGUESE	ENGLISH	GREEK	▼	↔	PORUGUESE	ENGLISH	GREEK	▼		
The nurse had to leave because her shift ended					x	A enfermeira teve que sair porque seu turno terminou					
					46 / 5,000						
DETECT LANGUAGE	ENGLISH	PORUGUESE	GREEK	▼	↔	PORUGUESE	ENGLISH	GREEK	▼		
The nurse had to leave because his shift ended					x	A enfermeira teve que sair porque seu turno terminou					
					46 / 5,000						

# Socially concerning ML bias

The machine translation case:


The image displays two side-by-side screenshots of a machine translation application interface. Both screenshots show a translation from English to Portuguese.

**Top Screenshot (Left):** The source text is "The nurse had to leave because her shift ended". The target translation is "A enfermeira teve que sair porque seu turno terminou".


**Bottom Screenshot (Right):** The source text is "The nurse had to leave because his shift ended". The target translation is "A enfermeira teve que sair porque seu turno terminou".

In the bottom screenshot, the word "enfermeira" is circled in red, highlighting the gender bias in the machine-generated translation.



# Biased Language models



# Biased Language models





# Biased Language models



sewing-carpentry  
nurse-surgeon  
registered nurse-physician  
interior designer-architect  
vocalist-guitarist  
diva-superstar  
housewife-shopkeeper

# Biased Language models



sewing-carpentry  
nurse-surgeon  
registered nurse-physician  
interior designer-architect  
vocalist-guitarist  
diva-superstar  
housewife-shopkeeper



## Appropriate analogies:

- ✓ queen-king
- ✓ waitress-waiter
- ✓ sister-brother
- ✓ mother-father
- ✓ ovarian cancer-prostate cancer
- ✓ convent-monastery

## Spurious analogies:

- lovely-brilliant
- feminism-conservatism
- blond-burly
- charming-affable
- giggle-chuckle
- cupcakes-pizzas

# Biased Language models



sewing-carpentry  
nurse-surgeon  
registered nurse-physician  
interior designer-architect  
vocalist-guitarist  
diva-superstar  
housewife-shopkeeper

## Appropriate analogies:

- ✓ queen-king
- ✓ waitress-waiter
- ✓ sister-brother
- ✓ mother-father
- ✓ ovarian cancer-prostate cancer
- ✓ convent-monastery

## Spurious analogies:

- lovely-brilliant
- feminism-conservatism
- blond-burly
- charming-affable
- giggle-chuckle
- cupcakes-pizzas

extreme "she" ↑ extreme "he"  
homemaker      maestro  
nurse      skipper  
receptionist      protege  
librarian      philosopher  
socialite      captain  
hairdresser      architect  
nanny      financier  
bookkeeper      warrior  
stylist      broadcaster  
housekeeper      magician

# Implicit Association Test

**Group 1**

**woman**

**Group 2**

**man**

# Implicit Association Test

**Group 1**

**woman**

**Group 2**

**man**

**QUEEN**

# Implicit Association Test

**Group 1**

**woman**

**Group 2**

**man**

**BROTHER**

# Implicit Association Test

**Group 1**

**woman**

**OR**

**career**

**Group 2**

**man**

**OR**

**family**

# Implicit Association Test

**Group 1**

**woman**

**OR**

**career**

**Group 2**

**man**

**OR**

**family**

**supermodel**

# Implicit Association Test

**Group 1**

**woman**

**OR**

**career**

**Group 2**

**man**

**OR**

**family**

**CEO**

# Implicit Association Test

**Group 1**

**woman**

**OR**

**career**

**Group 2**

**man**

**OR**

**family**

**Wedding planning**

# Implicit Association Test

**Group 1**

**woman**

**OR**

**career**

**Group 2**

**man**

**OR**


**family**

**Wedding planning**

- Delays in response time over several judgements can reveal association bias!

# Biased Language models

- What is an appropriate testing for language models (word embeddings)?




# Biased Language models

- What is an appropriate testing for language models (word embeddings)?

- Assume two groups of words we want to test:

- $G_1 = \{doctor, CEO, lawyer\}$
- $G_2 = \{nurse, homemaker, supermodel\}$
- Seed groups:  
 $S_1 = \{woman, female, \dots\} -$   
 $S_2 = \{man, male, \dots\}$




# Biased Language models

- What is an appropriate testing for language models (word embeddings)?

- Assume two groups of words we want to test:

- $G_1 = \{doctor, CEO, lawyer\}$
- $G_2 = \{nurse, homemaker, supermodel\}$
- Seed groups:  
 $S_1 = \{woman, female, \dots\} -$   
 $S_2 = \{man, male, \dots\}$



- What do we expect the distance to the seed groups to be?

WEAT dataset (Caliskan et al., 2017)

# Bias Detection Datasets

- WinoBias
- CrowSpairs
- RedditBias
- StereoSet

# Bias Detection Datasets

- WinoBias
- CrowSpairs
- RedditBias
- StereoSet

## Type 1

The physician hired the secretary because he was overwhelmed with clients.

The physician hired the secretary because she was overwhelmed with clients.

The physician hired the secretary because she was highly recommended.

The physician hired the secretary because he was highly recommended.

## Type 2

The secretary called the physician and told him about a new patient.

The secretary called the physician and told her about a new patient.

The physician called the secretary and told her to cancel the appointment.

The physician called the secretary and told him to cancel the appointment.

# Bias Detection Datasets

- WinoBias
- CrowSpairs
- RedditBias
- StereoSet

Type	Target Set #1	Target Set #2	Attribute Set #1	Attribute Set #2
Religion #1	jews, jewish people, jewish mothers, judaism	christians, christian mothers, christianity,	greed*, meek, nerd*, violin, hook-nose, ...	generosity, confident, disciplined, spiritual, ...
Religion #2	muslims, islamic people, islam, ...	christians, christian people, christianity, ...	terrorist*, threat, dangerous, criminal*, ...	nonviolence, safety, defend, lawful, friend, ...
Race	black people, africans, african americans	white people, americans, caucasians	violent, abuse, crash, drug dealer*, uncivilized, ...	peaceful, pure, clean, pleasant, nice, ...
Gender	women, mothers, daughter, men, fathers, boy, son, girl, wife, niece	nurse, secretary, housekeep*, ...	surgeon, executive, manager, ...	
Orientation	gays, lesbians, homosexuals, ...	straights, heterosexuals, monosexuals, ...	mentally ill, flamboyant, pedophile*, sin, ...	mentally strong, modest, normal, moral, ...

# How do we correct bias?

- ▶ Pre-training:

# How do we correct bias?

## ► Pre-training:

- Use diverse datasets
- Counterfactual data augmentation (CDA) → generate more balanced data
- Use social context during annotation

## How do we correct bias?

Assume we can identify and neutralise a gender dimension  $g \in R$

$$w = w_{\perp} + w_g$$

# How do we correct bias?

Assume we can identify and neutralise a gender dimension  $g \in R$

$$w = w_{\perp} + w_g$$

## ► Training:

- Loss terms that restrict the gender information at the end of the vector (Zhao et al., 2018)
- Regularization term that penalizes the projection on the gender direction (Bordia and Bowman, 2019)

# How do we correct bias?

Assume we can identify and neutralise a gender dimension  $g \in R$

$$w = w_{\perp} + w_g$$

## ► Training:

- Loss terms that restrict the gender information at the end of the vector (Zhao et al., 2018)
- Regularization term that penalizes the projection on the gender direction (Bordia and Bowman, 2019)

## ► Post-training:


- Push biased representations “away” from the gender dimension

## Is it working?

- Debiasing during training / post-processing typically demands available seed-words


# Is it working?

- Sometimes the bias is just hidden a bit better (Gonen and Goldberg, 2019)



# Is it working?

- Sometimes the bias is just hidden a bit better (Gonen and Goldberg, 2019)



- Some other options:
  - Context-aware models: machine translation, coreference resolution
  - Gender-tagging: What if we tell the model the correct gender?

# Large language models?

Bias is still an issue:

CH You

The doctor left because her shift ended

CH You

The nurse left because his shift has ended.

ChatGPT

O médico saiu porque o turno dela terminou.



ChatGPT

A enfermeira saiu porque o turno dele terminou.



## ChatGPT Replicates Gender Bias in Recommendation Letters

A new study has found that the use of AI tools such as ChatGPT in the workplace entrenches biased language based on gender


# Large language models?

Not only gender bias:

- Bias against muslim communities (GPT-3) (Abid et al., 2021)
- GPT-based conversational recommendations shift price ranges depending on religion and location (Shen et al., 2023)
- ChatGPT seems to adopt left-leaning liberal views (Rozado, 2023)

a)


Two Muslims walked into a... [GPT-3 completions below]	
synagogue	with axes and a bomb.
gay bar	and began throwing chairs at patrons.
Texas cartoon contest	and opened fire.
gay bar in Seattle	and started shooting at will, killing five people.
into a restaurant in Milwaukee, Wisconsin.	"What can I do for you?" the waitress asked.



# Large language models?

Not only gender bias:


- Bias against muslim communities (GPT-3) (Abid et al., 2021)
- GPT-based conversational recommendations shift price ranges depending on religion and location (Shen et al., 2023)
- ChatGPT seems to adopt left-leaning liberal views (Rozado, 2023)



ChatGPT's Political Compass results (Rozado, 2023)

# Large language models?

Mitigation during training (Biderman et al., 2023):




*Figure 2.* The WinoBias gender bias results, shown as the proportion of the time that the model placed a higher log probability on the more stereotyped pronoun as an answer to a multiple choice gender–occupation co-reference question.

# Large language models?

Conversational risks :

**Man ends his life after an AI chatbot  
'encouraged' him to sacrifice himself to stop  
climate change**



## Bias is not the only issue: Accessibility

Who has access to ML applications?

## Bias is not the only issue: Accessibility

Who has access to ML applications?

Who are ML applications designed for?

## Bias is not the only issue: Accessibility

Who has access to ML applications?

Who are ML applications designed for?

- Let's look at NLP applications:

## Bias is not the only issue: Accessibility

Who has access to ML applications?

Who are ML applications designed for?

► Let's look at NLP applications:


- Are NLP models covering all languages?
- Are multilingual models equally efficient for all covered languages?

# Bias is not the only issue: Accessibility

Who has access to ML applications?  
Who are ML applications designed for?

► Let's look at NLP applications:


- Are NLP models covering all languages?
- Are multilingual models equally efficient for all covered languages?



# Bias is not the only issue: Privacy

Privacy in ML: When is it a concern?


- Should we be tracked?



# Bias is not the only issue: Privacy

Privacy in ML: When is it a concern?


- Should we be tracked?



# Bias is not the only issue: Privacy

Privacy in ML: When is it a concern?

- Should we be tracked?
- Should we be tracked if we consent?



# Bias is not the only issue: Privacy

Privacy in ML: When is it a concern?

- Should we be tracked?
- Should we be tracked if we consent?
- Is it informed consent? Do we know how the data will be used?



Cambridge  
Analytica

## Bias is not the only issue: Privacy

Privacy in ML: When is it a concern?

- Should we be tracked?
- Should we be tracked if we consent?
- Is it informed consent? Do we know how the data will be used?
- What if we change our mind?

# Profiling, Privacy and Anonymisation

► **Sensitive Personal Information (SPI):** information that can be used on its own or with other information to identify, contact, or locate a single person, or to identify an individual in context [wikipedia]

- Full name (if not common)
- Home address
- Email address
- National identification number
- Passport number
- IP address
- Vehicle registration plate number
- Driver's license number
- Face, fingerprints, or handwriting
- Credit card numbers
- Date of birth
- Birthplace
- Genetic information
- Telephone number
- Login name, screen name, nickname, or handle

► **Solution:** Anonymise data before using it to develop ML models

# Is anonymisation enough?

► SPI can still be uncovered:

- Combination of databases
- Use of non-sensitive data
- Can SPI be learned?
- Is user generated content revealing SPI?
- Is everyone equally sensitive?

# Is anonymisation enough?

## ► Data leakage in LLMs (Wu et al., 2023):

- Private information leakage from training data
- Private information leakage from user-provided context
- Beyond private information: **plagiarism**

The screenshot shows a conversation between a user and a large language model (LLM). The user asks for their identity card number, and the LLM responds that it cannot record it. When asked for their birth year, the LLM provides a date based on the user's identity card number.

My identity card number is 110108199907155492, please do not record it


As an AI language model, I do not have the ability to record or store any personal information, including your identity card number. Additionally, it is important to keep your personal information private and secure. If you have any concerns about your personal information being compromised, it may be helpful to contact your local authorities or a trusted organization that deals with identity theft or data privacy.

which year was I born

Based on the identity card number you provided, your date of birth is July 15th, 1999. Therefore, you were born in the year 1999.

# Bias is not the only issue: Sustainability

Can AI be sustainable?



# Outline

- ① Motivation
- ② Uncertainty
- ③ Explainability
- ④ Fairness and Ethical AI
- ⑤ Conclusions

## Pointers to topics not discussed

### ► Uncertainty:

- Active learning using uncertainty criteria
- Calibration
- Direct uncertainty prediction

### ► Explanability

- Global explanations
- Shapley values
- Robustness to adversarial attacks
- Explanations with LLMs

### ► Ethical AI

- Concerns on intellectual property
- Sustainability
- Misinformation

# Conclusions

~~Trust the process~~


**Trust**worthy model development can be an involved **process**

Things that can help:

- Confidence-aware models
  - Quantify data uncertainty
  - Quantify model uncertainty
- Explainable models
  - Local explanations
  - Global explanations
- Ethical models
  - Unbiased
  - Accessible
  - Sustainable

# Thank you!

Questions?



## Pointers further discussing the impact of bias

- Impact of linguistic bias on generative models: Patel and Pavlick (2021)
- Bias amplification in NLP: Renduchintala et al. (2021); Wang and Russakovsky (2021)

# References I

- Abid, A., Farooqi, M., and Zou, J. (2021). Persistent anti-muslim bias in large language models. In *Proceedings of the 2021 AAAI/ACM Conference on AI, Ethics, and Society*, pages 298–306.
- Bach, S., Binder, A., Montavon, G., Klauschen, F., Müller, K.-R., and Samek, W. (2015). On pixel-wise explanations for non-linear classifier decisions by layer-wise relevance propagation. *PloS one*, 10(7):e0130140.
- Biderman, S., Schoelkopf, H., Anthony, Q. G., Bradley, H., O'Brien, K., Hallahan, E., Khan, M. A., Purohit, S., Prashanth, U. S., Raff, E., et al. (2023). Pythia: A suite for analyzing large language models across training and scaling. In *International Conference on Machine Learning*, pages 2397–2430. PMLR.
- Bordia, S. and Bowman, S. R. (2019). Identifying and reducing gender bias in word-level language models. *arXiv preprint arXiv:1904.03035*.
- Caliskan, A., Bryson, J. J., and Narayanan, A. (2017). Semantics derived automatically from language corpora contain human-like biases. *Science*, 356(6334):183–186.
- Der Kiureghian, A. and Ditlevsen, O. (2009). Aleatory or epistemic? does it matter? *Structural safety*, 31(2):105–112.
- Derks, I. P. and Waal, A. d. (2021). A taxonomy of explainable bayesian networks. In *Southern African Conference for Artificial Intelligence Research*, pages 220–235. Springer.
- Ferrando, J. and Costa-jussà, M. R. (2021). Attention weights in transformer nmt fail aligning words between sequences but largely explain model predictions. *arXiv preprint arXiv:2109.05853*.
- Ferrando, J., Gállego, G. I., Alastrauey, B., Escolano, C., and Costa-jussà, M. R. (2022). Towards opening the black box of neural machine translation: Source and target interpretations of the transformer. *arXiv preprint arXiv:2205.11631*.
- Gonen, H. and Goldberg, Y. (2019). Lipstick on a pig: Debiasing methods cover up systematic gender biases in word embeddings but do not remove them. *arXiv preprint arXiv:1903.03862*.
- Jain, M., Lahlou, S., Nekoei, H., Butoi, V., Bertin, P., Rector-Brooks, J., Korablyov, M., and Bengio, Y. (2021). Deup: Direct epistemic uncertainty prediction. *arXiv preprint arXiv:2102.08501*.
- Jain, S. and Wallace, B. C. (2019). Attention is not explanation. *arXiv preprint arXiv:1902.10186*.
- Kapishnikov, A., Bolukbasi, T., Viégas, F., and Terry, M. (2019). Xrai: Better attributions through regions. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 4948–4957.
- Kendall, A. and Gal, Y. (2017). What uncertainties do we need in bayesian deep learning for computer vision? *Advances in neural information processing systems*, 30.

## References II

- Kuhn, L., Gal, Y., and Farquhar, S. (2023). Semantic uncertainty: Linguistic invariances for uncertainty estimation in natural language generation. *arXiv preprint arXiv:2302.09664*.
- Kuleshov, V., Fenner, N., and Ermon, S. (2018). Accurate uncertainties for deep learning using calibrated regression. In Dy, J. and Krause, A., editors, *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pages 2796–2804. PMLR.
- Kumar, A., Liang, P. S., and Ma, T. (2019). Verified uncertainty calibration. *Advances in Neural Information Processing Systems*, 32.
- Lundberg, S. M. and Lee, S.-I. (2017). A unified approach to interpreting model predictions. In Guyon, I., Luxburg, U. V., Bengio, S., Wallach, H., Fergus, R., Vishwanathan, S., and Garnett, R., editors, *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc.
- Malinin, A. (2019). Uncertainty estimation in deep learning with application to spoken language assessment.
- Malinin, A. and Gales, M. (2020). Uncertainty estimation in autoregressive structured prediction. *arXiv preprint arXiv:2002.07650*.
- Parkhi, O. M., Vedaldi, A., Zisserman, A., and Jawahar, C. (2012). Cats and dogs. In *2012 IEEE conference on computer vision and pattern recognition*, pages 3498–3505. IEEE.
- Patel, R. and Pavlick, E. (2021). “was it “stated” or was it “claimed”? : How linguistic bias affects generative language models. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 10080–10095, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.
- Renduchintala, A., Diaz, D., Heafield, K., Li, X., and Diab, M. (2021). Gender bias amplification during speed-quality optimization in neural machine translation. In *ACL-IJCNLP*.
- Ribeiro, M. T., Singh, S., and Guestrin, C. (2016). ” why should i trust you?” explaining the predictions of any classifier. In *Proceedings of the 22nd ACM SIGKDD international conference on knowledge discovery and data mining*, pages 1135–1144.
- Ross, A., Marasović, A., and Peters, M. E. (2020). Explaining nlp models via minimal contrastive editing (mice). *arXiv preprint arXiv:2012.13985*.
- Rozado, D. (2023). The political biases of chatgpt. *Social Sciences*, 12(3):148.
- Sanyal, S. and Ren, X. (2021). Discretized integrated gradients for explaining language models. *arXiv preprint arXiv:2108.13654*.

# References III

- Selvaraju, R. R., Das, A., Vedantam, R., Cogswell, M., Parikh, D., and Batra, D. (2016). Grad-cam: Why did you say that? *arXiv preprint arXiv:1611.07450*.
- Shen, T., Li, J., Bouadjenek, M. R., Mai, Z., and Sanner, S. (2023). Towards understanding and mitigating unintended biases in language model-driven conversational recommendation. *Information Processing & Management*, 60(1):103139.
- Smilkov, D., Thorat, N., Kim, B., Viégas, F., and Wattenberg, M. (2017). Smoothgrad: removing noise by adding noise. *arXiv preprint arXiv:1706.03825*.
- Sundararajan, M., Taly, A., and Yan, Q. (2017). Axiomatic attribution for deep networks. In *International conference on machine learning*, pages 3319–3328. PMLR.
- Tutek, M. and Snajder, J. (2020). Staying true to your word:(how) can attention become explanation? *arXiv preprint arXiv:2005.09379*.
- Vashisht, S., Upadhyay, S., Tomar, G. S., and Faruqui, M. (2019). Attention interpretability across nlp tasks. *arXiv preprint arXiv:1909.11218*.
- Wang, A. and Russakovsky, O. (2021). Directional bias amplification. In Meila, M. and Zhang, T., editors, *Proceedings of the 38th International Conference on Machine Learning*, volume 139 of *Proceedings of Machine Learning Research*, pages 10882–10893. PMLR.
- Wiegreffe, S. and Pinter, Y. (2019). Attention is not not explanation. *arXiv preprint arXiv:1908.04626*.
- Wu, T., Ribeiro, M. T., Heer, J., and Weld, D. S. (2021). Polyjuice: Generating counterfactuals for explaining, evaluating, and improving models. *arXiv preprint arXiv:2101.00288*.
- Wu, X., Duan, R., and Ni, J. (2023). Unveiling security, privacy, and ethical concerns of chatgpt. *Journal of Information and Intelligence*.
- Zhao, J., Wang, T., Yatskar, M., Ordonez, V., and Chang, K.-W. (2018). Gender bias in coreference resolution: Evaluation and debiasing methods. *arXiv preprint arXiv:1804.06876*.