

Course Progress

[Course](#) > [Readings/Videos](#) > [Reading 10: Abstraction Functions and Rep Invariants](#) > [Questions](#)

[◀ Previous](#) [Next ▶](#)

Questions

 [Bookmark this page](#)

encapsulating preconditions in ADTs

1/1 point (graded)

Consider this method:

```
/**
 * Find tweets written by a particular user.
 *
 * @param tweets a list of tweets with distinct timestamps, not modified by this method.
 * @param username Twitter username (a nonempty sequence of letters, digits, and underscore)
 * @return all and only the tweets in the list whose author is username,
 *         in the same order as in the input list.
 */
public static List<Tweet> writtenBy(List<Tweet> tweets, String username) { ... }
```

Which ADTs would you create to eliminate the preconditions of this method? Check all that apply.

☐ TweetsAndUsername

☒ TweetList

☒ Username

☐ UsernameCharacter

Explanation

`TweetList` would be able to represent the requirement that the tweets have distinct timestamps, and `Username` would be able to represent the constraint on valid usernames.

Submit

 Show Answer

 Answers are displayed within the problem

[< Previous](#)
[Next >](#)

[All Courses](#)

[Facebook](#)

[Why Support MIT Open Learning?](#)

[Help](#)

[Privacy Policy](#) [Terms of Service](#)

© Massachusetts Institute of Technology, 2024