

[Course](#)[Progress](#)[Dates](#)[Discussion](#)

 [Course](#) / [18. Devices and Interrupts](#) / [Lecture Videos \(46:07\)](#)

< Previous




Next >

# LE18.5

 Bookmark this page



 Calculator

LE18.5.1: Real-time Constraints

0.0/1.0 point (ungraded)  
Three devices, D1, D2, and D3, are serviced by interrupt handlers in an interrupt system that may choose to use either strong (preemptive) priorities or weak (nonpreemptive) priorities. Their service times and maximum request rates are shown in the table below.

Device	Service time	Maximum frequency	Deadline
D1	100us	1/(1000us)	300us
D2	150us	1/(300us)	240us
D3	250us	1/(1000us)	1050us

1. Assuming each device were interrupting at its maximum rate, what fraction of the CPU time would be used to service **D1**? What fraction of the CPU time would be left for background computing? Answer in percent. Enter your response as "N%".

Give PERCENTAGE of CPU used to service D1:

10%

Answer: 10%

Give PERCENTAGE of unused CPU:

15%

Answer: 15%

Explanation  
The service time for D1 is 100us and this occurs every 1000us so it uses 100/1000 = 10% of the CPU. D2 uses 150us every 300us so it uses 50% of the CPU. D3 uses 250us every 1000us, so it uses 25% of the CPU. So the unused CPU after processing D1, D2, and D3 is 100 - (10 + 50 + 25) = 15%.

2. Can the requirements given in the table above be met using a **weak** priority ordering among the interrupt requests? If so give priority ordering for D1, D2, D3 or select device(s) whose deadlines cannot be met. Select all that apply.

Weak priority ordering or list device(s) with possibly missed deadlines:

☐ D1 > D2

☐ D1 > D3

☐ D2 > D1

☐ D2 > D3

☐ D3 > D1

☐ D3 > D2

☒ D1 misses deadline  
✓

☒ D2 misses deadline  
✓

☐ D3 misses deadline

Explanation  
In a weak priority system a running process does not get preempted even if it has a lower priority than the new interrupt. In this system, if D1 or D3 are running when a D2 interrupt arrives, then D2 could miss deadline. This can occur because D2's deadline of 240us is less than the service time of D1 plus D2

its less than the service time of D3 plus D2. In addition, if D1 arrives while D3 is running, then D1 may miss its deadline.

3. Can the requirements given in the table above be met using a **strong** priority ordering among the interrupt requests? If so give priority ordering for D1, D2, D3 or select device(s) whose deadlines cannot be met. Select all that apply.

Strong priority ordering or list device(s) with missed deadlines:

☐ D1 > D2

☒ D1 > D3  
✓

☒ D2 > D1  
✓

☒ D2 > D3  
✓

☐ D3 > D1

☐ D3 > D2

☐ D1 misses deadline

☐ D2 misses deadline

☐ D3 misses deadline


Explanation  
In order to guarantee that the deadlines are all satisfied, D2 cannot be delayed by either D1 or D3 because its deadline is less than the service time of D1 or D3 plus its own service time. In addition, D1 cannot be delayed by D3 because its deadline is less than the service time of D3 plus that of D1. So the priority ordering is D2 > D1 > D3.

Submit

**i** Answers are displayed within the problem

LE18.5.2: Assigning Priorities

0.0/1.0 point (ungraded)  
The following timeline shows how a processor executes interrupt handlers in response to interrupt requests (shown as ↑ in the diagram) from devices A, B and C. Assume that the processor is idle before the first interrupt request arrives.



1. Does the processor implement a weak priority system or strong priority system? If there's not enough information to decide, select "Can't Tell".

Type of priority system (weak, strong, can't tell):

☐ Weak

Calculator

☒ Strong  
✓

☐ Can't Tell

Explanation  
Since C pre-empts A, that means that it is using a strong priority scheme.

2. Indicate the relative priorities of A, B and C, e.g., select "A > B" if A has a higher priority than B. Select "None" if you can't tell. Select all that apply.

Relative priorities of A, B and C:

☒ A > B  
✓

☐ A > C

☐ B > A

☐ B > C

☒ C > A  
✓

☒ C > B  
✓

☐ None

Explanation  
Since C pre-empts A, that means that C has a higher priority than A, or  $C > A$ . Since B does not pre-empt A, that means that the priority of  $A > B$ . This also implies that  $C > B$ .

Submit

**i** Answers are displayed within the problem

Discussion

Hide Discussion

Topic: 18. Devices and Interrupts / LE18.5

Add a Post

< Previous

Next >



# edX

- [About](#)
- [Affiliates](#)
- [edX for Business](#)
- [Open edX](#)
- [Careers](#)
- [News](#)

## Legal

- [Terms of Service & Honor Code](#)
- [Privacy Policy](#)
- [Accessibility Policy](#)
- [Trademark Policy](#)
- [Sitemap](#)
- [Cookie Policy](#)
- [Your Privacy Choices](#)

## Connect

- [Idea Hub](#)
- [Contact Us](#)
- [Help Center](#)
- [Security](#)
- [Media Kit](#)



© 2024 edX LLC. All rights reserved.  
[ICP 17044299 -2](#)