

[Course](#)

[Progress](#)

[Dates](#)

[Discussion](#)

 [Course](#) / [14. Caches and the Memory Hierarchy](#) / [Lecture Videos \(65:39\)](#)



 Previous



























Next 

LE14.1

 Bookmark this page



LE14.1.1 Average Memory Access Time

1/1 point (ungraded)
A particular cache design responds in 1 cycle on a cache hit, but takes an *additional* 20 clock cycles if there's a cache miss. If we want an average memory access time of 2 cycles or better, what is the minimal acceptable cache hit ratio?

minimum acceptable cache hit ratio:

0.95

✓

Submit

✓ Correct (1/1 point)

LE14.1.2 Multi-level cache AMAT

1/1 point (ungraded)
A hierarchical memory system consists of a two-level SRAM cache and a large DRAM main memory. The system first checks the L1 cache. If the access to L1 is a cache miss, the system then checks the L2 cache. If the access to L2 is a cache miss, an access is made to main memory.

For L1: the cache hit time is 1 ns, the hit ratio is 95%

For L2: the cache hit time is 4 ns, the hit ratio is 98%

For main memory: the access time is 40ns

What is the average memory access time in ns?

1.24

✓

Submit

✓ Correct (1/1 point)

Discussion

Hide Discussion

Topic: 14. Caches and the Memory Hierarchy / LE14.1

Add a Post

Show all posts ▼

by recent activity ▼

There are no posts in this topic yet.

✕

< Previous

Next >



edX

- [About](#)
- [Affiliates](#)
- [edX for Business](#)
- [Open edX](#)
- [Careers](#)
- [News](#)

Legal

- [Terms of Service & Honor Code](#)
- [Privacy Policy](#)
- [Accessibility Policy](#)
- [Trademark Policy](#)
- [Sitemap](#)
- [Cookie Policy](#)
- [Your Privacy Choices](#)

Connect

- [Idea Hub](#)
- [Contact Us](#)
- [Help Center](#)
- [Security](#)
- [Media Kit](#)



© 2024 edX LLC. All rights reserved.
深圳市恒宇博科技有限公司 [粤ICP备17044299号-2](#)