

Hacking Exposed 7

Network Security Secrets & Solutions

Chapter 6 Cybercrime and Advanced Persistent Threats

Cybercrime and Advanced Persistent Threats

- What is an APT?
 - Operation Aurora
 - Anonymous
 - RBN
- What APTs are not?
- Examples of popular APT tools and techniques
- Common APTs indicators (detection, forensics)

What is an APT?

Advanced Persistent Threat (APT)

- Advanced
 - Uses sophisticated methods, such as zero-day exploits, crafting custom exploits.
- Persistent
 - Attacker returns to target system over and over again
 - Attacker has a long-term goal
 - Attacker works to achieve goals without detection
- Threat: organized, funded, and motivated

APT Goals

- Non-APT Attacks
 - Non-APT attacks are against "targets of opportunity" — just find vulnerable systems
 - Non-APT attacks are brief: smash and grab
- APT
 - Used to steal large amounts of data from a corporation over a long period of time
 - **Long-term goals**

Crime v. Espionage

- Two types of APTs
 - Crime
 - Steal PII, financial information, or corporate data just to use it for fraud
 - Espionage – industry or state-sponsored
 - Gather intellectual property or trade secrets
 - To gain competitive advantage
- APT goal is to gain and maintain access to information

APT Attacks

- Don't destroy systems
- Don't interrupt normal operation
- Try to stay hidden and keep the stolen data flowing
- Most often starts from spear phishing
 - Trick a user into installing malware

Hiding APT Techniques

- Cut-outs
 - Attacks are routed through other compromised computers to conceal attacker's location
- Dropper delivery services
 - "Pay per install" or "Leased" campaigns

Other APT Techniques

- SQL injection to add malware to websites
- Infected USB stick "drops"
- Infected hardware or software
- Social engineering, impersonating users, etc
- Less often: compromised human insiders

APT Phases

- Targeting
 - Collect info about the target and test: vulnerability scanning, social engineering, spear-phishing
- Access/compromise
 - Gain access: ascertain host info, collect credentials for additional compromises, obfuscate intention by malware
- Reconnaissance
 - Enumerate networks and systems
- Lateral movement
 - Move through network to other hosts
- Data collection and exfiltration
 - Establish collection points and exfiltrate via proxy
- Administration and maintenance
 - Maintain access over time

Detecting APTs

- Email logs
- Lateral movement may leave artifacts from misuse of access credentials or identities
- Exfiltration may leave traces in
 - Firewall and IDS logs
 - Data Loss Prevention logs
 - Application history logs
 - Web server logs

Forensics

- Artifacts of APT may be found in
 - Live file systems (RAM)
 - Hard disk image

Historical APT Campaigns

Historical APT Attacks

- Aurora
- Nitro
- ShadyRAT
- Lurid
- Night Dragon
- Stuxnet
- DuQu

Operation Aurora

2009

Targets: U.S. Technology and Defense Industries

- Google
- Juniper
- Adobe
- At least 29 other companies lost data over a period as long as six months

Spear-Phishing and RAT

- Email with a link to a Taiwanese website with malicious JavaScript
 - Exploited Internet Explorer vulnerability
 - Undetected by antivirus
- Trojan Downloaders placed on victim computers
- Installed a Backdoor Trojan Remote Administration Tool (RAT)
 - Accessed through SSL

Lateral Movement

- Network reconnaissance
- Compromised Active Directory credentials
- Access to computers and network shares with valuable intellectual property

China?

- Spear-phishing and downloader linked to Taiwan
- Backdoor Command & Control servers were traced to two schools in China
- Google blamed China
- No proof that Chinese government or industry sponsored or supported the attacks

Other APT Campaigns

- "Night Dragon" in 2010
- "RSA Breach" in 2011
- "Shady RAT" spanned several years
 - All commonly attributed to China, but not proven
- Commonly attributed APTs' C&C: China, India, Pakistan, Malaysia, Korea, UAE, Russia, USA, Mexico, Brazil.

Anonymous

2011

Anonymous

- From 2011, a loosely affiliated group or collection of groups, to expose sensitive info to public or interrupt services (DOS)
- A variety of hacking techniques
 - SQL injection, cross-site scripting, web service vulnerability exploits, social engineering (targeted spear-phishing, imitating employees like help desk personnel)

Targets

- Government agencies at all levels
- Sony
- Bay Area Rapid Transit (BART)
- Mastercard & Visa
- Many, many more

Techniques

- SQL injection
- Cross-site scripting
- Web service vulnerability exploits
- Social engineering

Goals

- Demonstrate that people can strike back at powerful organizations
- Expose corruption
- Primary goal: expose information
 - Not to use it for competitive or financial gain

RBN

RBN (Russian Business Network)

- From St. Petersburg to international cybercrime
- Operates several botnets for spamming, phishing, malware distribution
 - Identity or financial theft
 - Very sophisticated malware tools to remain persistent
 - A platform for subscribers to conduct activities
- Hosts pornographic subscription websites
- Main goal is identity theft and financial theft

APT Tools and Techniques

Examples of Tools and Techniques used in APT Campaigns

- Gh0st attack
- Malicious email

Investigate a potential “victim” system:

- Indicators of compromise
- Memory capture
- File/process capture
- Lost Linux host

Ghost Attack

- GhostRAT used in the "Ghostnet" attacks 2008-2010
- Targeted the Dalai Lama (Tibetan Government-in-Exile in India, London and New York City) and other Tibetan enterprises

Feature	Description
Existing rootkit removal	Clears System Service Descriptor Tables (SSDT) of all existing hooks
File Manager	Complete file explorer capabilities for local and remote hosts
Screen control	Complete control of remote screen.
Process Explorer	Complete listing of all active processes and all open windows
Keystroke logger	Real-time and offline remote keystroke logging
Remote Terminal	Fully functional remote shell
Webcam eavesdropping	Live video feed of remote web camera, if available
Voice monitoring	Live remote listening using installed microphone, if available

Table 6-1 Ghost RAT Capabilities (Courtesy of Michael Spohn, Foundstone Professional Services)

Dial-up profile cracking

Listing of dial-up profiles, including cracked passwords.

Remote screen blanking

Blanks compromised host screen, making computer unusable

Remote input blocking

Disables compromised host mouse and keyboard

Session management

Remote shutdown and reboot of host

Remote file downloads

Ability to download binaries from the Internet to remote host

Custom Gh0st server creation

Configurable server settings placed into custom binary


Summary of Gh0st Attack

- Phishing email
- Backdoor placed when malicious link clicked
- Backdoor hides itself to survive a reboot
- Connection to C&C
- Check internal domain, create accounts, use Terminal Server to hop to other hosts (Event Logs)
- Add/modify some files (diff \System32)
- Look for documents and zip for exfiltration
- Create a 2nd backdoor using netcat
- Create user account and execute FTP (Windows Security Event Log)
- Schedule a new job to clean logs everyday

GhostNET Phishing

- Attack started with an email from a server on several blacklists for spamming
- Tools used to research source of email
 - Whois
 - Robtex
 - Phishtank

Robtex



What is Robtex used for?

Robtex is used for various kinds of research of IP numbers, Domain names, etc

Are you a normal IT guy doing data forensics, investigating competitors, tracking spammers or hackers or a virus, or just curious? No matter what, this should be the first place to go

What does Robtex do?

Robtex uses various sources to gather public information about IP numbers, domain names, host names, Autonomous systems, routes etc. It indexes the data in a big database and provide free access to the data.

We aim to make the fastest and most comprehensive free DNS lookup tool on the Internet.

Our database now contains billions of documents of internet data collected over more than a decade.

How to use Robtex?

Enter an IP address or hostname in the field above, and click "GO" to look up technical information. From the resulting page you can navigate between the different tabs

PhishTank is operated by [OpenDNS](#), a free service that makes your Internet safer, faster, and smarter. [Get started today!](#)



username Sign In

[Register](#) | [Forgot Password](#)

[Home](#) [Add A Phish](#) [Verify A Phish](#) [Phish Search](#) **Stats** [FAQ](#) [Developers](#) [Mailing Lists](#) [My Account](#)

Stats

Monthly Stats Archive:

Online, valid phishes	Total Submissions	Total Votes
6,594	1,550,580	6,112,989


Phishes Verified as Valid		Suspected Phishes Submitted	
Total:	950,446	Total:	1,550,581
Online:	6,594	Online:	6,850
Offline:	943,852	Offline:	1,543,697

Most Active Users (out of 57,301 total)

Top 10 Submitters

1	PhishReporter	510,356 phishes
2	cleanmx	205,903 phishes
3	antiphishing	105,503 phishes
4	spamfighter	55,210 phishes

Daily Phishes Verified
chart created Oct 5 2012 17:26 UTC



Daily Phishes Submitted
chart created Oct 5 2012 17:26 UTC



Indicators of Compromise

■ How to survive reboot:

- Using various “Run” Registry keys
- Creating a service
- Hooking into an existing service
- Using a scheduled task
- Disguising communications as valid traffic
- Overwriting the master boot record
- Overwriting the system’s BIOS

Order of Volatility

- Memory
- Page or swap file
- Running process information
- Network data such as listening ports or existing connections to other systems
- System Registry (if applicable)
- System or application log files
- Forensic image of disk(s)
- Backup media

Forensic Tools copied to CD-ROM

- AccessData FTK Imager
- Sysinternals Autoruns
- Sysinternals Process Explorer
- Sysinternals Process Monitor
- WinMerge
- Currports
- Sysinternals Vmmap

Memory Dump Analysis

- Crucial for APT analysis because many APT methods use process injection or obfuscation
- Analyzing RAM data guarantees that the data are **unencrypted**
- **FTK Imager:** select the Capture Memory option, select an external mass-storage device as the output folder

Pagefile/Swapfile Analysis

- Virtual memory on pagefile.sys
- Also Hiberfil.sys
- Preferable to collect a forensic disk image of a compromised or suspicious computer
- Memory snapshot analysis Tools:
 - HBGary FDPPro
 - Mandiant Memoryze
 - Volatility Framework - open source

STARDUST

By Comae **BETA**

Enterprise memory forensics for threat detection and hunting.

*Yes, you are at the right place to download **Dumplt**. Sign up to continue.*



soon



Get Started

Email

Password

Memory Analysis

- Using Volatility Framework Tool (open source) to analyze memory
 - Processes
 - Network connections
 - DLLS from suspicious process
 - Use strings on the DLL

File/Process Capture (1/2)

- **Master File Table (MFT)**: metadata (filename, timestamp, file size, etc.), timeline is important
- Network/process/registry: **netstat** to find connections and process PID
- **Host file**: check any changes
- **Currports**: look into a current open port and its DLL
- **Process Explorer**: lookup a process, its DLL references, and cmd.exe shell executions
- **Process Monitor**: lookup process-kernel interactions → understand how malware modifies a compromised system and provide indicators for detection tools
- **VMMMap**: show virtual/physical memory map, check DLL strings → malware strings to imply RAT
- **DNS Cache**: find other possible infection hosts
- **Registry Query**: **reg query** to check for suspicious Registry entries of Run keys

File/Process Capture (2/2)

- **Scheduled Tasks**: **at** to find scheduled tasks
- **Event Logs**: **psloglist** to retrieve System and Security Event logs → commands issued by attackers
- **Prefetch Directory**: last 128 unique programs executed
- Collecting interesting files: **ntuser.dat** (user profile), **index.dat** (requested URLs), **.rdp** files (remote desktop session info), **.bmc** files (bit map to clients), **antivirus log files** (virus alerts)
- Analyzing RDP files: servers accessed, login info, etc. in XML → attackers use RDP to connect to other servers
- Analyzing BMC files: cached bitmap image for performance → **BMC Viewer** to find attacker's access to applications, files, network, credentials
- Investigating System 32 Directory for anomalies: **diff** system32 directory with cache directory to find files changed since installation → **.dll, .bat, .rar, .txt**
- Antivirus logs: check configurations that exclude detection of certain PUP (Potentially Unwanted Program), e.g. netcat/nc
- Network: analyze traffic between compromised host to C&C server → other targeted hosts → signatures for IDS


Netstat -aon

```
C:\Windows\system32>netstat -aon | more
```

Active Connections

Proto	Local Address	Foreign Address	State	PID
TCP	0.0.0.0:80	0.0.0.0:0	LISTENING	4
TCP	0.0.0.0:135	0.0.0.0:0	LISTENING	704
TCP	0.0.0.0:445	0.0.0.0:0	LISTENING	4
TCP	0.0.0.0:554	0.0.0.0:0	LISTENING	3012
TCP	0.0.0.0:1025	0.0.0.0:0	LISTENING	400
TCP	0.0.0.0:1026	0.0.0.0:0	LISTENING	752
TCP	0.0.0.0:1027	0.0.0.0:0	LISTENING	928
TCP	0.0.0.0:1028	0.0.0.0:0	LISTENING	488
TCP	0.0.0.0:1029	0.0.0.0:0	LISTENING	496
TCP	0.0.0.0:1031	0.0.0.0:0	LISTENING	2064
TCP	0.0.0.0:2869	0.0.0.0:0	LISTENING	4
TCP	0.0.0.0:3389	0.0.0.0:0	LISTENING	1240
TCP	0.0.0.0:10243	0.0.0.0:0	LISTENING	4
TCP	192.168.198.164:139	0.0.0.0:0	LISTENING	4
TCP	[::]:80	[::]:0	LISTENING	4
TCP	[::]:135	[::]:0	LISTENING	704
TCP	[::]:445	[::]:0	LISTENING	4
TCP	[::]:554	[::]:0	LISTENING	3012
TCP	[::]:1025	[::]:0	LISTENING	400
TCP	[::]:1026	[::]:0	LISTENING	752
TCP	[::]:1027	[::]:0	LISTENING	928
TCP	[::]:1028	[::]:0	LISTENING	488
TCP	[::]:1029	[::]:0	LISTENING	496
TCP	[::]:1031	[::]:0	LISTENING	2064
TCP	[::]:2869	[::]:0	LISTENING	4
TCP	[::]:3389	[::]:0	LISTENING	1240
TCP	[::]:10243	[::]:0	LISTENING	4
UDP	0.0.0.0:68	*:*		752

CurrPorts




The screenshot shows the CurrPorts application window. The title bar is blue with the CurrPorts icon and text. The menu bar includes File, Edit, View, Options, and Help. The toolbar contains icons for closing, saving, refreshing, printing, and other functions. The main area is a table with columns: Process Name, Process ID, P... (Protocol), Loc... (Local Address), L... (Local Port), Remote Port, Re... (Remote Address), and Remote Ac... (Remote Action). The table lists several processes, including iexplore.exe, mysql-nt.exe, inetinfo.exe, emule.exe, Netscp.exe, WCESCOMM.EXE, and Apache.exe. The emule.exe process with ID 628 and protocol UDP is selected, highlighted in blue. The status bar at the bottom indicates '88 Opened Ports, 1 Selected'.

Process Name	Process ID	P...	Loc...	L...	Remote Port	Re...	Remote Ac...
iexplore.exe	2736	TCP	3131	0.0.0.0	59565		0.0.0.0
iexplore.exe	2736	TCP	3131	80.17...	80	http	216.69.23
mysql-nt.exe	636	TCP	3306	0.0.0.0	43047		0.0.0.0
inetinfo.exe	2012	UDP	3456	0.0.0.0			
emule.exe	628	TCP	4662	0.0.0.0	2272		0.0.0.0
emule.exe	628	TCP	4662	80.17...	3236		61.72.18.2
emule.exe	628	TCP	4662	80.17...	4070		81.57.75.1
emule.exe	628	TCP	4662	80.17...	64585		83.25.6.20
emule.exe	628	TCP	4662	80.17...	2776		194.100.9
emule.exe	628	UDP	4672	0.0.0.0			
Netscp.exe	2644	TCP	5180	127.0...	18661		0.0.0.0
WCESCOMM.EXE	2456	TCP	5679	0.0.0.0	51379		0.0.0.0
Apache.exe	524	TCP	7123	0.0.0.0	43100		0.0.0.0

88 Opened Ports, 1 Selected

Process Explorer



Process Explorer - Sysinternals: www.sysinternals.com [WIN-H33Q TEN3A3M\student]

File Options View Process Find Users Help

Process	PID	CPU	Private Bytes	Working Set	Description	Company Name
vmtoolsd.exe	3060	0.10	7,656 K	8,644 K	VMware Tools Core Service	VMware, Inc.
TPAutoConnSvc.exe	924	0.02	1,684 K	4,040 K	ThinPrint AutoConnect printe...	Cortado AG
TPAutoConnect.exe	2876	0.01	2,960 K	6,724 K	ThinPrint AutoConnect comp...	Cortado AG
svchost.exe	3784	0.03	33,576 K	32,524 K	Host Process for Windows S...	Microsoft Corporation
wmpnetwk.exe	3012	< 0.01	9,760 K	8,540 K	Windows Media Player Netw...	Microsoft Corporation
lsass.exe	496	< 0.01	3,224 K	6,172 K	Local Security Authority Proc...	Microsoft Corporation
lsmd.exe	504	0.02	1,664 K	3,876 K		
csrss.exe	412	0.06	5,056 K	20,400 K		
conhost.exe	2820		620 K	2,376 K	Console Window Host	Microsoft Corporation
conhost.exe	1628		932 K	6,580 K		
winlogon.exe	468		1,740 K	4,300 K		
explorer.exe	2704	0.10	64,728 K	65,432 K	Windows Explorer	Microsoft Corporation
AdobeARM.exe	2808		3,600 K	9,064 K	Adobe Reader and Acrobat ...	Adobe Systems Incorporated
DivXUpdate.exe	2832	0.12	6,448 K	13,096 K	DivX Update	
jusched.exe	2840		1,696 K	6,228 K	Java(TM) Update Scheduler	Sun Microsystems, Inc.
cmd.exe	1584		1,740 K	2,184 K		
notepad.exe	3820		996 K	7,592 K	Notepad	Microsoft Corporation
chrome.exe	816	0.05	39,840 K	54,236 K	Google Chrome	Google Inc.
chrome.exe	1732		35,404 K	51,348 K	Google Chrome	Google Inc.
chrome.exe	1352		34,600 K	33,384 K	Google Chrome	Google Inc.
chrome.exe	1828		9,480 K	12,740 K	Google Chrome	Google Inc.
procexp.exe	4012	1.03	8,596 K	17,788 K	Sysinternals Process Explorer	Sysinternals - www.sysinter...
soffice.exe	2884		728 K	1,860 K	OpenOffice.org 3.4.1	OpenOffice.org
soffice.bin	2896		13,168 K	8,648 K	OpenOffice.org 3.4.1	OpenOffice.org
vmtoolsd.exe	656	0.32	17,552 K	17,372 K	VMware Tools Core Service	VMware, Inc.
VMwareTray.exe	2892		2,488 K	4,304 K	VMware Tools tray application	VMware, Inc.

CPU Usage: 4.69% Commit Charge: 46.88% Processes: 56 Physical Usage: 58.09%

Other SysInternals Tools

- Process Monitor
 - View all kernel interactions that processes make as the system runs
 - Very useful to run during malware infection
- VMMap
 - Analyzes virtual memory and physical memory used by a process
 - Can extract strings from the processes

Process Monitor - Sysinternals: www.sysinternals.com

File Edit Event Filter Tools Options Help



Time of Day	Process Name	PID	Operation	Path	Result	Detail
11:16:17.3343304 PM	Explorer.EXE	1612	RegCloseKey	HKCR\CLSID\{20D04FE0-3AEA-1069...	SUCCESS	
11:16:17.3343304 PM	Explorer.EXE	1612	RegQueryKey	HKCU\Software\Classes	SUCCESS	Query: Name
11:16:17.3343304 PM	Explorer.EXE	1612	RegOpenKey	HKCU\Software\Classes\CLSID\{20D0...	NAME NOT FOUND	Desired Access: M...
11:16:17.3343304 PM	Explorer.EXE	1612	RegOpenKey	HKCR\CLSID\{20D04FE0-3AEA-1069...	SUCCESS	Desired Access: M...
11:16:17.3343304 PM	Explorer.EXE	1612	RegQueryKey	HKCR\CLSID\{20D04FE0-3AEA-1069...	SUCCESS	Query: Name
11:16:17.3343304 PM	Explorer.EXE	1612	RegOpenKey	HKCU\Software\Classes\CLSID\{20D0...	NAME NOT FOUND	Desired Access: M...
11:16:17.3343304 PM	Explorer.EXE	1612	RegQueryValue	HKCR\CLSID\{20D04FE0-3AEA-1069...	NAME NOT FOUND	Length: 144
11:16:17.3343304 PM	Explorer.EXE	1612	RegCloseKey	HKCR\CLSID\{7007ACC7-3202-11D1...	SUCCESS	
11:16:17.3343304 PM	Explorer.EXE	1612	RegOpenKey	HKCU\Software\Microsoft\Windows\C...	NAME NOT FOUND	Desired Access: Q...
11:16:17.3343304 PM	Explorer.EXE	1612	RegOpenKey	HKLM\Software\Microsoft\Windows\C...	SUCCESS	Desired Access: Q...
11:16:17.3343304 PM	Explorer.EXE	1612	RegQueryValue	HKLM\SOFTWARE\Microsoft\Window...	NAME NOT FOUND	Length: 144
11:16:17.3343304 PM	Explorer.EXE	1612	RegCloseKey	HKLM\SOFTWARE\Microsoft\Window...	SUCCESS	
11:16:17.3343304 PM	Explorer.EXE	1612	CreateFileMapp...	C:\WINDOWS\Resources\Themes\Lu...	SUCCESS	SyncType: SyncTy...
11:16:17.3343304 PM	Explorer.EXE	1612	QueryStandardl...	C:\WINDOWS\Resources\Themes\Lu...	SUCCESS	AllocationSize: 364...
11:16:17.3343304 PM	Explorer.EXE	1612	CreateFileMapp...	C:\WINDOWS\Resources\Themes\Lu...	SUCCESS	SyncType: SyncTy...
11:16:17.3343304 PM	Explorer.EXE	1612	CloseFile	C:\WINDOWS\Resources\Themes\Lu...	SUCCESS	
11:16:17.3343304 PM	Explorer.EXE	1612	QueryOpen	C:\WINDOWS\Resources\Themes\Lu...	SUCCESS	CreationTime: 8/23...
11:16:17.3343304 PM	Explorer.EXE	1612	CreateFile	C:\WINDOWS\Resources\Themes\Lu...	SUCCESS	Desired Access: G...
11:16:17.3343304 PM	Explorer.EXE	1612	ReadFile	C:\WINDOWS\system32\shell32.dll	SUCCESS	Offset: 1,774,592, ...
11:16:17.3350238 PM	Explorer.EXE	1612	ReadFile	C:\WINDOWS\system32\shell32.dll	SUCCESS	Offset: 1,758,208, ...
11:16:17.3367757 PM	Explorer.EXE	1612	RegCloseKey	HKLM\SOFTWARE\Microsoft\Window...	SUCCESS	
11:16:17.3367955 PM	Explorer.EXE	1612	RegOpenKey	HKLM\SOFTWARE\Microsoft\Window...	NAME NOT FOUND	Desired Access: Q...
11:16:17.3368296 PM	Explorer.EXE	1612	RegOpenKey	HKCU\Software\Microsoft\Windows\C...	NAME NOT FOUND	Desired Access: Q...
11:16:17.3368542 PM	Explorer.EXE	1612	RegOpenKey	HKLM\Software\Microsoft\Windows\C...	NAME NOT FOUND	Desired Access: Q...
11:16:17.3368793 PM	Explorer.EXE	1612	RegQueryKey	HKCU\Software\Classes	SUCCESS	Query: Name

Showing 27,200 of 40,157 events (67%)

Backed by virtual memory

File Edit View Options Help



Process: chrome.exe

PID: 1828

Committed: 105,320 K



Private Bytes: 9,852 K



Working Set: 13,196 K



Type	Size	Committed	Private	Total WS	
Total	150,564 K	105,320 K	9,852 K	13,196 K	
Image	90,908 K	90,908 K	2,500 K	8,152 K	
Mapped File	3,292 K	3,292 K		300 K	
Shareable	3,616 K	1,332 K		260 K	
Heap	4,864 K	660 K	596 K	596 K	
Managed Heap					
Stack	7,168 K	272 K	272 K	60 K	
Private Data	37,540 K	5,680 K	5,680 K	3,024 K	
Page Table	804 K	804 K	804 K	804 K	
Unusable	2,372 K	2,372 K			
Free	1,947,328 K				

Address	Type	Size	Committed	Private	Total WS	Private ...
36D00000	Private Data	4 K	4 K	4 K	4 K	4 K
3C700000	Private Data	4 K	4 K	4 K	4 K	4 K
3DA00000	Private Data	4 K	4 K	4 K	4 K	4 K
5CAC0000	Image (ASLR)	12,928 K	12,928 K	1,200 K	2,592 K	60 K
5ECF0000	Image (ASLR)	9,732 K	9,732 K		16 K	
5F680000	Image (ASLR)	39,368 K	39,368 K	908 K	2,516 K	152 K
647F0000	Image (ASLR)	940 K	940 K	128 K	76 K	16 K
72580000						

Timeline...

Heap Allocations...

Call Tree...

Trace...

DNS Cache

Administrator: cmd - Shortcut

```
C:\Windows\system32>ipconfig /displaydns | more
```

```
Windows IP Configuration
```

```
social.microsoft.com
```

```
-----  
Record Name . . . . . : social.microsoft.com  
Record Type . . . . . : 5  
Time To Live . . . . . : 18  
Data Length . . . . . : 4  
Section . . . . . : Answer  
CNAME Record . . . . . : lb.social.ms.akadns.net
```

```
spzajuzqbr
```

```
-----  
Name does not exist.
```

```
155.198.168.192.in-addr.arpa
```

```
-----  
Record Name . . . . . : 155.198.168.192.in-addr.arpa.  
Record Type . . . . . : 12  
Time To Live . . . . . : 86400  
Data Length . . . . . : 4  
Section . . . . . : Answer  
PTR Record . . . . . : ISATAP
```

Registry Query for Run and RunOnce Keys

```
C:\Windows\system32>reg query HKLM\system\currentcontrolset\services /s | more
HKEY_LOCAL_MACHINE\system\currentcontrolset\services\.NET CLR Data
HKEY_LOCAL_MACHINE\system\currentcontrolset\services\.NET CLR Data\Linkage
Export REG_SZ 2e,00,4e,00,45,00,54,00,20,00,43,00,4c,00,52,00,20,00,44
,00,61,00,74,00,61,00,00,00,00,00
HKEY_LOCAL_MACHINE\system\currentcontrolset\services\.NET CLR Data\Performance
IsMultiInstance REG_DWORD 0x1
CategoryOptions REG_DWORD 0x1
Open REG_SZ OpenPerformanceData
Collect REG_SZ CollectPerformanceData
Close REG_SZ ClosePerformanceData
Library REG_SZ netfxperf.dll
Counter Types REG_BINARY 360035003500330036000000360035003500330036000
000360035003500330036000000360035003500330036000000360035003500330036003
5003500330036000000000
```

Other Tests

- Scheduled Tasks
- Event Viewer
- Prefetch Directory
 - Records the last 128 "unique" programs executed on the system

Prefetch

```
C:\Windows\Prefetch>dir c:\windows\prefetch\v*.*
Volume in drive C has no label.
Volume Serial Number is B074-0434

Directory of c:\windows\prefetch

10/05/2012  10:56 AM                18,676 VMMAP.EXE-1427F6E8.pf
10/05/2012  10:42 AM                18,844 VMWARERESOLUTIONSET.EXE-BAE6FDC8.pf
10/04/2012  06:59 PM                32,234 VSSVC.EXE-04D079CC.pf
               3 File(s)              69,754 bytes
               0 Dir(s)  14,902,439,936 bytes free

C:\Windows\Prefetch>_
```

Collecting Interesting Files

- **ntuser.dat** Contains the user's profile data
- **index.dat** Contains an index of requested URLs
- **.rdp files** Contains information around any remote desktop session(s)
- **.bmc files** Contains cached images of the RDC client
- **Antivirus log files** Contains virus alerts

Antivirus Exclusions

- The antivirus may have been reconfigured to allow the malware
- Packing the file is a common technique to evade antivirus

Linux APT Attack

Target Scenario

- Linux running Apache Tomcat with weak credentials, copied from an example page
- Exploit it with Metasploit through Tomcat
- `cat /etc/passwd` reveals usernames

```
root@bt:/etc# cat /etc/passwd | more
root:x:0:0:root:/root:/bin/bash
root2:x:0:0:root:/root:/bin/bash
daemon:x:1:1:daemon:/usr/sbin:/bin/sh
bin:x:2:2:bin:/bin:/bin/sh
sys:x:3:3:sys:/dev:/bin/sh
sync:x:4:65534:sync:/bin:/bin/sync
games:x:5:60:games:/usr/games:/bin/sh
```

Escalating to root

- One way: find a user with an obvious password; like their last name
- Crack superuser password

Backdoor

- Attackers upload a PHP backdoor
- Create a SUID root shell for getting root back in case a password is changed
- With **Metaexploit Framework**, compromised host used as a pivot host (without tools installed)
- Run shells like **Meterpreter** in memory without disk writes: leave little on the host

Diagnose Linux APT Attack

- Apache Tomcat server with weak credentials
- To diagnose the host
 - Block access by firewall
 - Check root account history, check added/modified files, check logs for **sudo su** – commands
 - Check listening ports and connections with **netstat** and **lsof**
 - Check hidden files in RAM drives, drive slack space, /dev, hard-to-see file or directory like “**..**” (dot-dot-space), /tmp and /var/tmp

Bash History

- In each user's home directory
- .bash_history
- Remembers the previous 2000 lines by default in BackTrack 5 R2

```
root@bt:~# tail .bash_history
ps aux
watch "ps aux | grep telnet"
ls /etc/sbin/passwd
cd /
find . -name passwd
ls -l /usr/bin/passwd
ls -l
exit
telnet hills.ccsf.edu
exit
root@bt:~#
```

HISTFILESIZE

- Controlled by .bashrc in each user's home directory
 - HISTFILESIZE controls this
 - HISTSIZE is just a RAM buffer

```
GNU nano 2.2.2      File: .bashrc

# append to the history file, don't overwrite it
shopt -s histappend

# for setting history length see HISTSIZE and HISTFILESIZE in bash$
HISTSIZE=1000
HISTFILESIZE=2000
```


Tomcat configured to log access requests

- Shows PUT being used to upload suspicious files
- PUT entries, someone [FROM THE INTERNET] has deployed an application on the server

Commands to Check Network Connections

- To check network connections, use
netstat -anlp
lsof -i -P
 - Shows all open files (and listening services)
- **IMPORTANT:** A rootkit could cause these programs to lie

```
root@bt:~# netstat -anlp | more
```

```
Active Internet connections (servers and established)
```

Proto	Recv-Q	Send-Q	Local Address	Foreign Address	State	PID/Program name
tcp	0	0	127.0.0.1:7175	0.0.0.0:*	LISTEN	2282/postgres
tcp	0	0	127.0.0.1:27017	0.0.0.0:*	LISTEN	860/mongod
tcp	0	0	127.0.0.1:28017	0.0.0.0:*	LISTEN	860/mongod
tcp	0	0	0.0.0.0:22	0.0.0.0:*	LISTEN	2241/sshd
tcp	0	0	127.0.0.1:8118	0.0.0.0:*	LISTEN	2221/privoxy
tcp	0	0	127.0.0.1:631	0.0.0.0:*	LISTEN	1656/cupsd
tcp	0	0	0.0.0.0:3128	0.0.0.0:*	LISTEN	1780/squid
tcp	0	0	127.0.0.1:25	0.0.0.0:*	LISTEN	2162/exim4
tcp	0	0	127.0.0.1:9050	0.0.0.0:*	LISTEN	2251/tor
tcp	0	0	192.168.198.136:36763	65.171.167.131:80	ESTABLISHED	2536/clock-applet
tcp6	0	0	:::1:7175	:::*	LISTEN	2282/postgres
tcp6	0	0	:::22	:::*	LISTEN	2241/sshd
tcp6	0	0	:::1:631	:::*	LISTEN	1656/cupsd
tcp6	0	0	:::1:25	:::*	LISTEN	2162/exim4
udp	0	0	0.0.0.0:47630	0.0.0.0:*		1780/squid
udp	0	0	0.0.0.0:3130	0.0.0.0:*		1780/squid
udp	0	0	0.0.0.0:68	0.0.0.0:*		3355/dhclient
udp	0	0	0.0.0.0:68	0.0.0.0:*		1718/dhclient3
udp6	0	0	:::1:57450	:::1:57450	ESTABLISHED	2282/postgres

```
Active UNIX domain sockets (servers and established)
```

Proto	RefCnt	Flags	Type	State	I-Node	PID/Program name	Path
-------	--------	-------	------	-------	--------	------------------	------

```
root@bt:~# lsof -i -P
```

COMMAND	PID	USER	FD	TYPE	DEVICE	SIZE/OFF	NODE	NAME
mongod	860	mongodb	5u	IPv4	5128	0t0	TCP	localhost:27017 (LISTEN)
mongod	860	mongodb	7u	IPv4	5130	0t0	TCP	localhost:28017 (LISTEN)
cupsd	1656	root	5u	IPv6	6156	0t0	TCP	localhost:631 (LISTEN)
cupsd	1656	root	6u	IPv4	6157	0t0	TCP	localhost:631 (LISTEN)
dhclient3	1718	root	5u	IPv4	3894	0t0	UDP	*:68
squid	1780	proxy	6u	IPv4	6338	0t0	UDP	*:47630
squid	1780	proxy	14u	IPv4	6347	0t0	TCP	*:3128 (LISTEN)
squid	1780	proxy	15u	IPv4	6349	0t0	UDP	*:3130
exim4	2162	Debian-exim	3u	IPv4	6694	0t0	TCP	localhost:25 (LISTEN)
exim4	2162	Debian-exim	4u	IPv6	6695	0t0	TCP	localhost:25 (LISTEN)
privoxy	2221	privoxy	1u	IPv4	6846	0t0	TCP	localhost:8118 (LISTEN)
sshd	2241	root	3u	IPv4	6895	0t0	TCP	*:22 (LISTEN)
sshd	2241	root	4u	IPv6	6897	0t0	TCP	*:22 (LISTEN)
tor	2251	debian-tor	7u	IPv4	6923	0t0	TCP	localhost:9050 (LISTEN)
postgres	2282	postgres	3u	IPv6	7089	0t0	TCP	localhost:7175 (LISTEN)
postgres	2282	postgres	4u	IPv4	7090	0t0	TCP	localhost:7175 (LISTEN)
postgres	2282	postgres	6u	IPv6	7098	0t0	UDP	localhost:57450->localhost:57450
postgres	2291	postgres	6u	IPv6	7098	0t0	UDP	localhost:57450->localhost:57450
postgres	2292	postgres	6u	IPv6	7098	0t0	UDP	localhost:57450->localhost:57450
postgres	2293	postgres	6u	IPv6	7098	0t0	UDP	localhost:57450->localhost:57450
postgres	2294	postgres	6u	IPv6	7098	0t0	UDP	localhost:57450->localhost:57450
clock-app	2536	root	22r	IPv4	40296	0t0	TCP	192.168.198.135:51626->65.171.167.131:80

Where to Hide Files

- RAM drives
(disappear)
- Drive slack space
- /dev
- Directories named "..
" (dot-dot-space)
- /tmp and /var/tmp

```
root@bt:~/dotdot# mkdir ".. "  
root@bt:~/dotdot# ls -a  
.  
..  
root@bt:~/dotdot# ls -ab  
.  
..  
..\br/>root@bt:~/dotdot#
```

RAM Drives

- /dev/shm is already mounted by default
- You can make your own with
 - `mkdir -p /tmp/ram`
 - `sudo mount -t ramfs -o size=512M ramfs /tmp/ram/`
- To see Ram drives, use
 - `df -a`

Linux Mount

- `mount -t type device dir`
- the kernel attaches the filesystem found on **device** (which is of type **type**) at the directory **dir**

Mount RAMDISK

```
root@bt:~# mkdir -p /tmp/ram
```

```
root@bt:~# mount -t ramfs -o size=512M ramfs /tmp/ram
```

```
root@bt:~# df -a
```

Filesystem	1K-blocks	Used	Available	Use%	Mounted on
/dev/sda1	19737268	11982916	6751756	64%	/
proc	0	0	0	-	/proc
none	0	0	0	-	/sys
none	0	0	0	-	/sys/fs/fuse/connections
none	0	0	0	-	/sys/kernel/debug
none	0	0	0	-	/sys/kernel/security
none	368004	268	367736	1%	/dev
none	0	0	0	-	/dev/pts
none	383596	28	383568	1%	/dev/shm
none	383596	116	383480	1%	/var/run
none	383596	0	383596	0%	/var/lock
none	383596	0	383596	0%	/lib/init/rw
vmware-vmblock	0	0	0	-	/var/run/vmblock-fuse
ramfs	0	0	0	-	/tmp/ram

```
root@bt:~#
```


Strings command

- To get readable strings from a file
strings malware.exe > malfile
- To view results
nano malfile

```
GNU nano 2.2.2
Xns%
(ZjXs%
Xns%
Xns%
jX()
sfrayH0wwTJJldvr
BSJB
v2.0.50727
#Strings
#GUID
#Blob
Record.exe
Record
mscorlib
System
kernel32
Header
<Module>
Program
^G Get Help
^X Exit
```

Poison Ivy

<http://www.poisonivy-rat.com/>

Source code available

Very Common

- Poison Ivy is a RAT used very often in APT attacks
- Used in
 - Aurora, 2009
 - RSA attacks, 2011
 - Nitro, April-October 2011

New IE zero day exploit circulating, used to install Poison Ivy

Join thousands of others, and sign up for Naked Security's newsletter

you@example.com

Do it!

Don't show me this again ☐

by [Paul Roberts](#) on September 17, 2012 | [Comments \(17\)](#)

FILED UNDER: [Featured](#), [Internet Explorer](#), [Vulnerability](#)

The gang behind the recent Java zero day attacks apparently hasn't packed up for the season.

A researcher examining one of the servers used to launch attacks on vulnerable Java installations says he has found a new zero day exploit for Microsoft's Internet Explorer web browser.



→ ↺ 🏠 📄 www.poisonivy-rat.com



Poison Ivy

Remote Administration Tool

[Home](#) - [Downloads](#) - [Screenshots](#) - [Development](#) - [Customer Portal](#) - [Links](#) - [Contact](#)

Site/downloads up again

2008-11-20

I have received a tremendous amount of emails from people wanting me to continue the project even though it might take some time until the next release.

It's meant alot to me to see this kind of support for the project. That's why I've decided to bring back the site, but I will not promise anything...

I hope to get some time and motivation to finish the new version.

TDSS (TLD1-4)

TDSS

- A botnet with 5 million compromised hosts
- Sophisticated malware
 - Rootkit
 - Encrypted files and communications
 - Many C&C servers
 - Variants: TDL 1, 2, 3, 4
 - Derivatives: *Zero Access, Purple Haze...*

Malware as a Service

- TDSS botnet rented to criminals
 - DDoS attacks
 - Click fraud
 - To install Trojans

Common APT Indicators

APT Method of Attack

1. Spear-phishing email
2. User clicks link; opens an application and redirects to a hidden address
3. Hidden address is a Dropsite; detect browser vulnerabilities, and drops a Trojan downloader

APT Method of Attack

4. Downloader sends a base64-encoded instruction to a different dropsite, which installs a Trojan backdoor
5. Trojan backdoor installed in `c:\windows\system32` and registers in NETSVCS
6. Trojan backdoor uses a filename slightly different from Windows filenames
7. Uses SSL communication with C&C server

APT Method of Attack

8. Attacker interacts via cutouts with Trojan with SSL-encrypted traffic
9. Attacker lists Computername and User Accounts; uses pass-the-hash, gets local and Active Directory account information
10. Service privilege escalation to network reconnaissance
11. Offline password hash cracking

APT Method of Attack

- 12. Lateral movement by using RDP (Terminal Services), SC.exe (to create services), or NET commands (to connect to shares)
- 13. Installs additional backdoor Trojans, and egress point
- 14. Stolen files are packaged in ZIP or RAR packages, renamed as GIFs

Detecting APTs

- Audit changes to the file system
- SMS alerts on administrative logins
- Firewalls that monitor inbound RDP/VNC/CMD.EXE
- AV, HIPS, file system integrity checking
- NIDS, NIPS; Snort
- Security Information/Events Management (SIEM)