Hacking Exposed 7 Network Security Secrets & Solutions


Book - Table of Contents

- Part I Casing the Establishment
 - Footprinting
 - Scanning
 - Enumeration
- Part II Endpoint and Server Hacking
 - Hacking Windows
 - Hacking UNIX
 - Cybercrime and Advanced Persistent Threats
- Part III Infrastructure Hacking
 - Remote Connectivity and VoIP Hacking
 - Wireless Hacking
 - Hacking Hardware
- Part IV Application and Data Hacking
 - Web and Database Hacking
 - Mobile Hacking
 - Countermeasures Cookbook


Part I Casing The Establishment Case Study: How A Hacker Works

- IAAAS (It's All About Anonymity, Stupid)
 - The Onion Router (Tor), www.torproject.org
 - Layered cryptography with SOCKS proxy
 - Anonymous outgoing TCP connections
 - Tor GUI client (Vidalia) and Privoxy (web filtering proxy)
 - Google on browser for juicy targets
 - tor-resolve instead of host for IP addresses
 - proxychains to force connections through Tor
 - Nmap to scan services on targets
 - socat to relay persistently
 - nc (netcat) to send requests to servers (check server version)
 - Exploit vulnerabilities to pwn (own or compromise)


Hacking-Labs




Hack The Box




The Onion Router (TOR) - Overview



TOR



Vidalia




Vidalia is a discontinued cross-platform GUI for controlling Tor. It allows the user to start, stop or view the status of Tor

Privoxy

 Privoxy is a free web proxy for enhancing privacy, manipulating cookies and modifying web page data and HTTP headers before the page is rendered by the browser.
 E.g. filtering web pages and removing advertisements. Privoxy can be customized by users.

Tor-resolve




Proxychains



NMAP



NMAP



socat

This command opens a proxy listening on localhost:8080 and forwards all requests through Tor to the target 10.10.10.100:80

```
bt - # socat TCP4-LISTEN:8080,fork
SOCK84a:127.0.0.1:10.10.10.100:80,socksport=9050 &
```

Chapter 1 Footprinting

- What is footprinting & why
- Internet footprinting
 - 1. Determine the scope of your activities
 - 2. Get proper authorization
 - 3. Publicly available information
 - 4. WHOIS & DNS enumeration
 - 5. DNS interrogation
 - 6. Network reconnaissance

What Is Footprinting?

- Footprint: profile of the target organization
- Why? It gives you a picture of what the hacker sees.
- Sun Tzu The Art of War: Know yourself and your enemy!
- What to footprint/profile?
 - Internet: domain names, network blocks and subnets, IP addresses, TCP/UDP services, CPU arch, access control, IDS, system enumeration, DNS hostnames
 - Intranet: network protocols, internal domain names, network blocks, IP addresses, TCP/UDP services, CPU arch, access control, IDS, system enumeration
 - Remote access: phone numbers, remote system type, authentication mechanisms, VPN
 - Extranet: domain names, connection source and destination, type of connection, access control

Internet Footprinting

- Step 1: Determine the scope of your activities
 - Entire organization or subsidiaries?
 - Determine all, so as to secure them
- Step 2: Get proper authorization
 - Layers 8 and 9: politics and funding
 - Get-out-of-jail-free card
- Step 3: Publicly available information
 - Nothing short of amazing!


Publicly Available Information Company Web Pages

- Unexpected: security configuration, asset inventory spreadsheet, etc.
- HTML source code (offline faster)
 - Things buried in comment tags: <, !, --</p>
 - Website mirroring tools for offline viewing: Wget (Linux), Teleport Pro (Windows)
- Enumerate hidden files and directories recursively
 - OWASP's DirBuster
 - Easy to be detected: proxy through privoxy
- Remote access to internal resources via browser
 - Proxy to internal servers (e.g. Microsoft Exchange server)
- Look for other sites beyond the main
 - www1, www2, web, test, etc.
 - VPN sites

Publicly Available Information Related Organizations Location Details

- Related organizations
 - Look for references and links to other organizations
 - Outsourced web development
 - Partners might not be security-minded
 - Social engineering attack
- Location details needed for
 - Dumpster-diving, surveillance, social engineering, unauthorized access, etc.
 - Images
 - Google Earth, Google Maps Street View (Wi-Fi MAC addresses), Google Locations and Skyhook (MAC → location: "How I Met Your Girlfriend" BlackHat 2010 demo)

Google tracking Wi-Fi



Publicly Available Information Employee Information (1/2)

- Names -> e-mail addresses, usernames
- Phone numbers

 physical address, social engineering
 - Phonenumber.com, 411.com, yellowpages.com
- Other personal details
 - Blackbookonline.info, peoplesearch.com
 - Home phone number, address, social security number, credit history, criminal record, etc.
 - Social/information/professional networking, career, family ancestry, photo management sites
 - Facebook.com, Myspace.com, Reunion.com, Classmates.com, Twitter.com, Linkedin.com, Plaxo.com, Monster.com, Careerbuilder.com, Dice.com, Ancestry.com, Flickr.com, Photobucket.com
- Business directory services: JigSaw.com
 - Used by sales teams
 - Paid-for services with incentive award points to new or update entries

Publicly Available Information Employee Information (2/2)

- Job posting and resumes
 - "Checkpoint firewalls and Snort IDS" tells much!
 - Google "company resume firewall" to get resumes from current and past employees
 - Search on job sites (monster.com, careerbuilder.com)
 - Watch disgruntled and ex- employees: revenge!
- Employee's home computers
 - Remote access to the target
 - Keystroke logger: free ride to the target!
 - Impersonate a trusted user!

Publicly Available Information Current Events


- Mergers, acquisitions, scandals, layoffs, rapid hiring, reorganization, outsourcing, temporary contractors
- Merger or acquisition
 - Blending of organizations' networks
 - · Less or disabled security
- Human factor
 - Low morale → update resumes
 - Unauthorized guests
- SEC (Security and Exchange Commission) reports
 - Periodical reporting: 10-Q (quarter) and 10-K (annual)
 - Sec.gov → organizational charts
- Business info and stock trading sites
 - Yahoo!Finance message boards

Publicly Available Information Privacy or Security Policies Archived Information

- Privacy or security policies
 - Technical details indicating the types of security mechanisms in place
- Archived information
 - Archived copies > current copies
 - Archive.org & cached results at Google

Publicly Available Information Search Engines and Data Relationships

- Google.com, bing.com, yahoo.com, dogpile.com, ask.com
- Search strings used by hackers Google Hacking Database (GHDB) at hackersforcharity.org/ghdb/
- Search Google's cache for vulnerabilities, errors, configuration issues, etc. – Athena (snakeoillabs.com), SiteDigger (foundstone.com), Wikto (sensepost.com/research/wikto)
- Analyze metadata in web files for info leaks FOCA (informatica64.com/foca.aspx)
- Mining and linking relevant pieces of info on a subject Maltego (paterva.com)
- Public Database Security Countermeasures:
 - ➤ Site Security Handbook: RFC 2196
 - Periodically review and remove public but sensitive data!







Sicuro https://www.amazon.com/Google-Hacking-Penetration-Testers-Third/dp/0128029641/ref=pd_lpo_sbs_14_t_0/143-4724252-3204714?_er


Kindle Monthly Deals Up to 80% off top titles > Browse now

Google Hacking for Penetration Testers, Third Edition 3rd Edition

by Johnny Long (Author), Bill Gardner * (Author), Justin Brown (Author)



22 customer reviews



ISBN-13: 978-0128029640 ISBN-10: 0128029641 Why is ISBN important? *

Have one to sell?

Sell on Amazon

Add to List















College student? Get FREE shipping and exclusive deals LEARN MORE

Add

Turn on 1-Cl

40 used & n

See All Buy

Google is the most popular search engine ever created, but Google's search capabilities are so powerful, they













24 New from \$52.43 16 Used from \$48.30






allinurl:tsweb/default.htm


- Microsoft Windows servers with Remote Desktop Web Connection exposed
- Google Hacking Database (GHDB), found at hackersforcharity.org/ghdb/

Step 4: WHOIS and DNS Enumeration

- Domain names, IP addresses, port numbers
 - Centrally managed by ICANN (Internet Corporation for Assigned Names and Numbers)
 - Hierarchically stored in WHOIS/DNS servers
- Three R of WHOIS: registry, registrar, registrant
- To lookup keyhole.com, start from whois.iana.org
 - Find the registry and registrar for .com (verisign-grs.com) and then keyhole.com (markmonitor.com)
 - Find the registrant details of keyhole.com (for later spoofing)
 - Web whois or command-line whois
 - Automatic tools (allwhois, uwhois) and GUI tools (superscan, netscan tools pro)
- To lookup 61.0.0.2, start from arin.net
 - Find apnic.net, then find National Backbone of India
 - But keep in mind the IP address might be spoofed/masqueraded

Internet Infrastructure







Your IPv4 address is 78.13.211.54

SEARCH Wh

all requests subj

NUMBER RESOURCES


PARTICIPATE

POLICIES

FEES & INVOICES

KNOWLEDGE

ABO



Username and password are case sensitive.

username:

new user?

password:

assistance

log in 👩

About ARIN Online



Announcements

Friday, 2 March 2018

IANA Issues /21 to ARIN, 7 Waiting List Requests Fulfilled

Tue, 27 Feb 2018

Extension of ACSP

Consultation: ASO Review

Consultation 2018

Mon, 26 Feb 2018

2018 ARIN Leadership

Announcement Archives



ARIN is a member of the Number Resource Organization.

09 Feb 2018

NRO EC and ASO AC Joint Response to the 2017 Independent ASO Review Recommendations

25 Jan 2018 ASO Review Consultation

NRO Archives

2018



Request Resources

Waiting List for Unmet Requests

Draft Policies & Proposals

Internet Governance

Resource Revocation, Returns, and Reinstatement





REGISTRATION OPEN




Public Database Security Countermeasures

Administrative contacts, registered net blocks authoritative name servers

- Keep administrative contacts up-to-date
- Anonymize administrative contacts
- Authenticate updates rigidly to avoid domain hijacking
 - AOL in 1998: redirected traffic

DNS - Start Of Authority (SOA) record

Typical Name Resolution Scenario



DNS record types

DS	43	RFC 4034₺	signer	The record used to identify the DNSSEC signing key of a delegated zone
HINFO	13	RFC 8482₺	Host Information	Providing Minimal-Sized Responses to DNS Queries That Have QTYPE=ANY
HIP	55	RFC 8005@	Host Identity Protocol	Method of separating the end-point identifier and locator roles of IP addresses.
IPSECKEY	45	RFC 4025₺	IPsec Key	Key record that can be used with IPsec
KEY	25	RFC 2535 & [3] and RFC 2930 & [4]	Key record	Used only for SIG(0) (RFC 2931 2) and TKEY (RFC 2930 2). [5] RFC 3445 2 eliminated their use for application keys and limited their use to DNSSEC. [6] RFC 3755 2 designates DNSKEY as the replacement within DNSSEC. [7] RFC 4025 2 designates IPSECKEY as the replacement for use with IPsec. [8]
KX	36	RFC 2230㎡	Key Exchanger record	Used with some cryptographic systems (not including DNSSEC) to identify a key management agent for the associated domain-name. Note that this has nothing to do with DNS Security. It is Informational status, rather than being on the IETF standards-track. It has always had limited deployment, but is still in use.
LOC	29	RFC 1876₺	Location record	Specifies a geographical location associated with a domain name
MX	15	RFC 1035 & [1] and RFC 7505 &	Mail exchange record	Maps a domain name to a list of message transfer agents for that domain
			NT!	

Step 5: DNS Interrogation

- Obtain revealing info about the organization by querying DNS servers (domain name <-> IP addresses)
- DNS zone transfer by untrusted users
 - Due to misconfiguration
 - From primary server to secondary server
 - Private DNS info: internal hostnames and IP addresses
 - dnsrecon
- nslookup
 - mapping and getting all resource records (A, RP, MX, HINFO, etc.)
 - HINFO: host info
 - Search with grep, sed, awk, perl
 - Scripts: dnsenum, dnsmap, fierce, host

DNS Security Countermeasures

- Restrict zone transfer to only authorized servers
 - named.conf in BIND
- Configure a firewall to deny unauthorized inbound connections to TCP port 53 (thwart zone transfer) DNS - Domain Name System.
- Configure not to provide internal DNS info
- Discourage the use of HINFO records

Step 6: Network Reconnaissance

- Network topology and access path diagram
- traceroute, tracert, visualroute, McAfee's NeoTrace, Foundstone's Trout
 - Find the exact path (IP nodes routers, firewall, etc.)
 - Leverage TTL and ICMP
- Thwarting Network Reconnaissance Countermeasures
 - Intrusion detection: snort, bro
 - Configure border routers to limit ICMP and UDP traffic to specific systems

Summary

- Footprinting: tedious works to be done regularly
- Automate tasks by shell, Python, Perl scripts
- Minimize info leaks
- Implement monitoring

Homework #1

- 1. (20 points) Select a web site.
 - 1) Use "Wget" or "Teleport Pro" to mirror the site. Look for comments within comment tags. Give screen dumps and explain what you found.
 - 2) Use "DirBuster" with a proxy feature through "privoxy" to enumerate hidden files and directories. Screen dump and explain the hidden files and directories you found.
- 2. (20 points) Lookup "How I met your girlfriend" in the BlackHat 2010 demo to explain, in 0.5 page, how this was done.
- 3. (20 points) Select a person. Use on-line sites for phone book, social network, information, job, photo management, business directory, jigsaw.com, etc. to summarize, with screen dumps and explanations, what information you can get. If your target is not in US nor native English speaker, you might need to use on-line sites different from the textbook.
- 4. (20 points) Google "XYZ resume firewall" and "XYZ resume intrusion detection" where "XYZ" is the name of your target company. Screen dump "useful" results and explain what you got.
- 5. (20 points) Lookup Archive.org and Google cached results, and select a target web site. Compare the differences between an archived and cached copy with its current on-line web site. Give screen dump and explain the differences.
- 6. (20 points) Find Google Hacking Database at hackersforcharity.org/ghdb/. Summarize what it has and select 3 strings to search. Screen dump and explain what you got.
- 7. (20 points) Select a web site. Start from whois.iana.org to find its registry, registrar, and registrant. Also select an IP address. Start from arin.net to find who owns the IP address. Show your screen dump and explain.
- 8. (20 points) Select a domain name. Use nslookup to dump its DNS records. Show your screen dump and explain.
- 9. (20 points) Select a domain name. Use traceroute or similar tools to find the access path to that domain. Show your screen dump and explain.
- 10. (bonus: 40 points) Follow the case study right before chapter 1. Select one target and run through all tools (Tor, Vidalia, Privoxy, tor-resolve, proxychains, Nmap, socat, nc). Screen dump 38 the process and explain what you got in your screen.