



# Foundations of Databases A.Y. 2021-2022 Homework 2 – Conceptual and Logical Design

# Master Degree in Computer Engineering Master Degree in Cybersecurity Master Degree in ICT for Internet and Multimedia

Deadline: November 26, 2021

Team acronym	TA	AGMS
Last Name	First Name	Student Number
Arslan	Tunahan	2023640
Basso	Marco	2005796
Cimarosto	Pietro	2027173
Collado	Martin	2039907
Esposito	Vittorio	2005795
Giuliani	Amedeo	2005797
Quiroz	Giannina	2041427
Zanini	Samuele	2019038

## **Conceptual Design**

#### Variations to the Requirement Analysis

An employee must necessarily have one and only one role. A role is typically associated with multiple employees but may not have any. For example, the "intern" role can be created but without having hired anyone in that position yet.

An employee must work in at least one department. Each department can have multiple workers, but none if the department is new and newly created.

A manager is an employee with role equals to "Manager". Only they are allowed to stipulate one or more contracts with many suppliers. A supplier can stipulate many contracts with the manager as well, but a new supplier can also not have stipulated a contract yet. Our system, therefore, is able to also store information relating to suppliers with whom the company has not yet entered into agreements.

Each contract specifies one or more items (e.g., ingredients, packaging materials, etc.) and the respective quantity. An item can be specified in at least one contract, so it can be provided by many different suppliers. Each item belongs to only one item category, and to an item category can belong zero or many items. The stock quantity of each item is tracked. It will therefore be increased upon receipt of the items, after purchase from one or more suppliers, and decreased upon the preparation of lots of products that are made up of the items. The delivery date of the items is specified in each contract, so that the respective quantity in stock is automatically updated only upon arrival of the goods. The company does not use periodic delivery contracts, so every time it becomes necessary to purchase certain ingredients or packaging material, a new contract is signed with the supplier.

A product, which is a finished good ready to be sold, is made up of one or more items (e.g., one glass bottle, a hundred grams of sugar, a hundred milliliters of water, etc.) with the respective quantities. For example, a product called "Coke J" can consist of one aluminum can, 50ml of water, 10g of sugar, etc. Another product, called "Coke B" for example, may have the same ingredients as the previous example but can be packaged with a glass bottle. The expiration date of a product is specified in the various lots (that include that particular product) and it may differ in each lot. The stock quantity of a product is not explicitly specified, but it can be obtained by checking the specified product quantities in each lot not yet sold or shipped. An item can be utilized in many products (also none if, for example, the item is brand new). Each product belongs to one and only one product category, that is used to distinguish them. To a product category can belong zero or many products. The expiration date of the ingredients (items) is not tracked as the company guarantees to keep them stored for a short period of time because the ingredients are used shortly after their purchase and a FIFO policy is being implemented.

A package is composed by one or more packaging materials (i.e., an item used for packaging, such as a box, a meter of plastic tape, a kilogram of polystyrene, etc.) with the respective quantities. For example, a package named "PK1" can consist of 4 boxes of dimensions 30cm x 30cm x 10cm, 2 meters of plastic tape and 200 g of polystyrene. A "PK2" package can consist of 6 boxes of dimensions 30cm x 30cm x 10cm, 4 meters of plastic tape and 300 g of polystyrene. An item (e.g., packaging material in this case) can be utilized in many packages (also none if, for example, the package is brand new and not yet used). Each package belongs to one and only one package category, that is used to distinguish them. To a package category can belong zero or many packages.

In a lot there can be stocked a certain amount of only a product and a certain amount of only a package. The quantity of products in each lot depends both on the dimensions of the package of the individual product (e.g., bottle of glass) and on the features of the package (in particular, the size of the box and the number of boxes that make up the package). Each type of product can be stocked in many lots (in none if, for example,

the product is brand new) and the same holds true for packages. Each lot is also characterized by an expiration date. As some lots may be produced in advance to reduce lead times, some of them may not sell on time and therefore expire. The data analyst will perform half-yearly analysis in this regard to reduce waste. When a lot is produced, the company specifies the current price and VAT. The cost of the packages is not explicitly charged to the customer. A discount can also be associated with each lot.

The customer decides with the seller regarding the products to be bought. The salesman, then, after communicating the products (with respective quantity) to the warehouse worker, will place the order only when all the lots included in the order are ready. A seller can place zero or many orders for a customer, so a customer can make many orders (none if, for example, the customer is new). An order can be placed by only one salesman for only one customer (i.e., an order for a customer cannot be placed by two or more sellers, but by only one of them). An order includes one or more lots. Each lot can be included by only one order (none if the lot is produced in advanced and waiting to be ordered). The invoice will be automatically generated by the application linked to the system as soon as the order is placed. The total net amount of the order must be explicitly specified, as motivated in the load analysis. It is calculated as the sum of the prices of the lots, taking into account the discount applied. The total taxes are calculated as the sum of the taxes of each lot. When the order is ready, a worker will ship it: a worker can ship zero or many orders, and an order can be shipped by at most one worker (none if the order is waiting to be shipped). The cancellation and modification of the order is not accepted since the goods can be produced on commission and the company wants to minimize the waste caused by the expiry of the products. The customer, which is a business, must necessarily pay within 60 days and can be informed about the status of the order by contacting the seller.




Figure 1: Entity-Relationship schema.

## **Data Dictionary**

### **Entities Table**

Entity	Description	Attributes	Identifier
Employee	Represents data of an employee who works in the company and needs access to the system	<ul> <li>TAX_number: TAX code of the employee, text</li> <li>First_name: name of the employee, text</li> </ul>	TAX_number
		Last_name: surname of the employee, text	
		<ul> <li>Phone_number: phone number (prefix included) of the employee, text</li> </ul>	
		Email_address: email address of the employee, text	
		Birth_date: birthdate of the employee, Datetime	
		<ul> <li>Hiring_date: hiring date of the employee, Datetime</li> </ul>	
		<ul> <li>Still_working: flag used to know if employee is still working for the company, boolean</li> </ul>	
Role	Represents data on the role of employees	• ID: role identifier, serial	ID
	who work in the com- pany	Name: name of the role, text	
		Description: technical description of the role, text	
Department	Represents data on the departments in which employees work	ID: department identifier of the company, serial	ID
		Name: name of the depart- ment, text	
		<ul> <li>Description: description of the department's function, text</li> </ul>	

Customer	Represents data about a customer of the company	<ul> <li>VAT_number: VAT number of the customer, int</li> <li>Customer_name: name of the customer, text</li> <li>Phone_number: phone number (prefix included) of the customer, text</li> <li>Address: billing address of the customer, text</li> <li>Registration_date: customer registration date in the database, Datetime</li> </ul>	VAT_number
Contract	Represents data about a contract stipulated between a supplier and a manager for the supply of items	<ul> <li>ID: contract identifier, serial</li> <li>Description: description of the contract, text</li> <li>Contract_date: date of signature of the contract with the supplier, Datetime</li> <li>Delivery_date: expected date of delivery of the goods, Datetime</li> <li>Expiration_date: expiration date of the contract with the supplier, Datetime</li> </ul>	ID

Supplier	Represents data about a supplier of the company	<ul> <li>VAT_number: VAT number of the supplier company, int</li> <li>Supplier_name: name of the supplier company, text</li> <li>Phone_number: phone number (prefix included) of the supplier company, text</li> <li>Email_address: email address of the supplier company, text</li> <li>Address: address of the supplier company, text</li> <li>Registration_date: recording date of the supplier</li> </ul>	VAT_number
Order	Represents the order placed by a salesman for a customer	<ul> <li>Ing date of the supplier company, Datetime</li> <li>ID: order identifier, serial</li> <li>Order_date: date in which the order has been processed, Datetime</li> <li>Order_paid: status of the payment, boolean</li> <li>Net_price: total net amount including discount (VAT excluded), float</li> <li>Taxes: total amount of taxes to be payed, float</li> </ul>	ID

Represents a lot in the inventory of the company, containing final products and packaging  Product  Represents the final product that is marketed  Product  Represents the final product that is marketed  Represents the final product that is marketed  Product  Represents the final product that is marketed  Represents the final product that is marketed  Product  Represents the final product that is marketed  Product in milliliters, erial  Name: name of the product, text  Poscription: description of the product, text  Nutritional Facts: description of nutritional facts of the specific product, text  Volume: volume of the product in milliliters, int  Net weight: net weight of the product in grams, int  Package.weight: package weight of the product in grams, int  Production.cost: cost of the production for a product, float  Price_increase: price increase price increase factor, float				
Product  Represents the final product that is marketed  ID: product identifier, serial  Name: name of the product, text  Description: description of the product, text  Nutritional.Facts: description of nutritional facts of the specific product, text  Volume: volume of the product in milliliters, int  Net.weight: net weight of the product in grams, int  Package_weight: package weight of the product in grams, int  Production.cost: cost of the production for a product, float  Price_increase: price in-	Lot	inventory of the com- pany, containing final products and packag-	<ul> <li>Expiration_date: expiration date of the included products, Datetime</li> <li>Lot_price: lot price (without the discount) at the</li> </ul>	ID
Product that is marketed  • ID: product identifier, serial  • Name: name of the product, text  • Description: description of the product, text  • Nutritional_Facts: description of nutritional facts of the specific product, text  • Volume: volume of the product in milliliters, int  • Net_weight: net weight of the product in grams, int  • Package_weight: package weight of the product in grams, int  • Production_cost: cost of the production for a product, float  • Price_increase: price in-			<ul><li>of discount of a lot, int</li><li>VAT: value added tax (percentage) at the time of sale,</li></ul>	
	Product	product that is mar-	<ul> <li>Name: name of the product, text</li> <li>Description: description of the product, text</li> <li>Nutritional_Facts: description of nutritional facts of the specific product, text</li> <li>Volume: volume of the product in milliliters, int</li> <li>Net_weight: net weight of the product in grams, int</li> <li>Package_weight: package weight of the product in grams, int</li> <li>Production_cost: cost of the production for a product, float</li> <li>Price_increase: price in-</li> </ul>	ID

Item	Represents materials provided by suppliers	<ul> <li>ID: identifier of the item, serial</li> <li>Name: name of the item, text</li> <li>Description: description of the item, text</li> <li>Quantity: stock quantity of the item (automatically updates), int</li> </ul>	ID
Package	Represents packaging of finished products which are made up of boxes, tapes, and other packaging materials	<ul> <li>ID: identifier of the package, serial</li> <li>Name: name of the package, text</li> <li>Description: description of the package, text</li> <li>Weight: weight dimension of the package in grams, int</li> <li>Height: height dimension of the package in centimeters, int</li> <li>Width: width dimension of the package in centimeters, int</li> <li>Depth: depth dimension of the package in centimeters, int</li> </ul>	ID
Product_Category	Represents the category of a product	<ul> <li>ID: identifier of the product category, serial</li> <li>Name: name of the product category, text</li> <li>Description: description of the product category, text</li> </ul>	ID

Item_Category	Represents the category of an item	<ul> <li>ID: identifier of the item category, serial</li> <li>Name: name of the item category, text</li> <li>Description: description of the item category, text</li> </ul>	ID
Package_Category	Represents the category of a package	<ul> <li>ID: identifier of the package category, serial</li> <li>Name: name of the package category, text</li> <li>Description: description of the package category, text</li> </ul>	ID

## **Relationships Table**

Relationship	Description	Component Entities	Attributes
Have	Relates each employee to a role	<ul><li>Employee (1,1)</li><li>Role (0,N)</li></ul>	None
Work	Assigns each employee to a department	<ul><li>Employee (1,N)</li><li>Department (0,N)</li></ul>	None
Stipulate	Links the supplier with the company and the contract stipulated	<ul><li>Supplier (0,N)</li><li>Employee (0,N)</li><li>Contract (1,1)</li></ul>	None
Place	Links the order made by the employee	<ul><li>Employee (0,N)</li><li>Order (1,1)</li><li>Customer (0,N)</li></ul>	None

Ships	Relates the employee shipping the order with the order itself and the shipment details	<ul><li>Employee (0,N)</li><li>Order (0,1)</li></ul>	<ul> <li>Track_num: tracking code of the shipment provided by the external shipment service, int</li> <li>Shipping_date: date on which the company ships the goods, Datetime</li> </ul>
Specify	Describes which items are provided by a contract	<ul><li>Contract (1,N)</li><li>Item (1,N)</li></ul>	<ul> <li>Purchased_quantity:         the quantity of items         which are purchased,         int</li> </ul>
Belong (1)	Links items to the category	<ul><li>Item (1,1)</li><li>Item_Category (0,N)</li></ul>	None
Belong (2)	Links products to the category	<ul><li>Product (1,1)</li><li>Product_Category (0,N)</li></ul>	None
Belong (3)	Links packages to the category	<ul><li>Package (1,1)</li><li>Package_Category (0,N)</li></ul>	None
Made up of (1)	Describes what items are involved in creating the product	<ul><li>Item (0,N)</li><li>Product (1,N)</li></ul>	Quantity: the quantity of items composing a specific product
Made up of (2)	Describes what items are involved in creating the package	<ul><li>Item (0,N)</li><li>Package (1,N)</li></ul>	Quantity: the quantity of items composing a specific package
Stocked	Specifies the products and packages stocked in the lots	<ul><li>Package (0,N)</li><li>Product (0,N)</li><li>Lot (1,1)</li></ul>	<ul> <li>Product_quantity:         quantity of the         included product, int</li> <li>Package_quantity:         quantity of the         included package, int</li> </ul>

Draws from	Associates the lots to an order	• Order (1,N)	None
		• Lot (0,1)	

#### **External Constraints**

- The company decides the total discount to apply to a specific lot. This discount expresses a percentage and is a number between 0 and 100. Furthermore, the company is able to take into account changes in VAT.
- The company decides the value of the price increase according to company policies. This increase ("Price\_increase") must take on a value greater than or equal to 1. The price of a product is calculated as a multiplication between the cost of production and the price increase.
- The price of a specific lot ("Lot\_price") is calculated as the multiplication of the price of the product (stored in the lot) multiplied by its quantity. It is important to underline that the "Lot\_price" attribute cannot be derived through an online operation as the fields on which it depends ("Production\_Cost" and "Price\_increase") can be modified over time and therefore give discordant results at different times.
- The total net amount of the order ("Net\_price") must be calculated as the sum, for each lot i included, of the Lot\_price<sub>i</sub> \* (1 Lot\_discount<sub>i</sub> / 100). The total taxes are calculated as the sum, for each lot i, of the Lot\_price<sub>i</sub> \* VAT<sub>i</sub> / 100.
- The units of measure used by the company are specified in detail in the entity table.
- Only employees that are sill working (i.e. those who have the "Still\_working" attribute set to "True") in the company can access the system.
- Sellers can keep track of the order status on their own, also updating the payment status once the bill is settled. By default, the boolean "Order\_paid" is false.
- Only the Manager can insert new contracts, so the Employee who takes part in the "stipulate" relationship must have the role equal to "Manager".
- Only the Salesman can insert new orders, so the Employee who takes part in the "place" relationship must have the role equal to "Salesman".
- Only the Worker can ship orders, so the Employee who takes part in the "ship" relationship must have the role equal to "Worker".
- A product must consist of one or more items having a certain Item\_Category (e.g., "ingredient" or "glass bottle"). A package must consist of one or more items having a certain Item\_Category (e.g., "box", "plastic tape" or "polystyrene").
- The quantities of products contained in a lot belong to a finite set (e.g. 25, 50, 100), so the customer cannot order a lot with an arbitrary quantity of products.
- An expired lot cannot be sold.

#### **Functional Requirements Satisfaction Check**

The DBMS has to be able to:

• store all the details of the employees, customers and suppliers in the organization: Employee entity stores data related to the employees. Customer entity has details about the customers and Supplier entity has data related to suppliers.

- allow the employees to update their personal information: Employee entity has some attributes as Email\_address, Password or Phone\_number that can be changed. Employees can access the system using their credentials and change this data.
- store details of all on-hand products in the inventory such as item code, item description, quantity and expiration date: The inventory is represented by the entities Item, Product, Package and Lot. The Item entity contains information relating to materials (e.g., ingredients, packaging materials, ...) with their respective descriptions and quantities. Likewise, the Product entity contains information relating to finished products and the Package entity contains information relating to packaging. The products are packed in lots. Each lot is also characterized by an expiry date.
- allow the employees to log into the system and enter the inbound items they received with information item code, item description, quantity, expiration date and supplier: Employees can log in the database and insert data about new items in the system. An employee can also update an existing Item and its respective quantity.
- show and generate the list of inbound and outbound transactions: The inbound transactions can be generated by inspecting the instances of the Contract entity, while the outbound transactions can be obtained by inspecting the instances of the Order entity.
- allow the employees to log into the system and enter the outbound transaction needed for the issuance of the products in the production and shipment to the customers; inventory stocks will be automatically updated whenever there are inbound and outbound transactions; show and generate the current inventory balance or stock inquiries: Regarding items, the update is executed automatically when an inbound transaction occurs by inspecting the new Contract: for each Item the quantity "Item\_Quantity" is increased accordingly. Regarding the outbound transaction, the value of "Item\_Quantity" is decreased when a new lot (which stocks a product that is made up of that Item) is prepared. Regarding products, the stock quantity can be obtained by inspecting the lots produced but not yet ordered or expired. The same holds true for packages.
- receive and process the Customers order, specifying which products they want and respective quantity: Salesmen are able to access the database and enter an instance of the Order entity reporting the lots containing the desired products only when all lots are ready.
- allow users to view order and shipment status of finished products; create tracking code for orders: With the unique tracking number (attribute "Track\_num" of the Ship relationship), and the unique ID attribute of the Order entity, the users can get information about the order and shipment.
- generate invoice whenever payment has been made: When an order is placed, the invoice is automatically generated by the application connected to the system. The data is extracted from the entities Order and Lot, and from the "Draws from" relationship. The total amount, net price, taxes and the list of ordered Lots are specified.
- grant Cycle Counting in order to validate the accuracy of inventory: Cycle counting is a periodic check done by a warehouse worker on the items in the physical inventory. After acquiring the real quantities for each item, a check will be made on the system. In case of mismatch, the "Quantity" attribute of the Item is updated.
- re-ordering the previous orders is allowed: The system allows salesmen to access past orders and lots using the ID attribute and retrieve information about the lots, the products, and their quantities. In this way, the customer can order the same goods.

## **Logical Design**

### Transformation of the Entity-Relationship Schema

#### **Redundancy Analysis**

The Employee and Order entities, related to each other through the relationships Place and Ship, do not form a cycle because:

- Only the Employee with the Salesman role can place the order;
- Only the Employee with the Worker role can ship the order;
- Eliminating the Place or Ship relationship implies a violation of functional requirements and a loss of information (e.g., who is the seller who places the order or who is the worker who ships it).

The Lot, Product, Package, and Item entities do not form a loop because:

- Eliminating a "Made up of" relationship implies a violation of functional requirements and a loss of information (eg, from which items, and in what quantity, a product or package is composed);
- Eliminating the "Stocked" relationship implies a violation of functional requirements and a loss of information (e.g., it is not possible to know which products and packages are contained in a lot).

The ER schema presents the derivate attributes:

- "Quantity" (of Item): used to keep in memory the current quantity of items;
- "Net\_price" (of Order): used to keep in memory the total net price of an order;
- "Taxes" (of Order): used to keep in memory the total taxes of an order.

We report below the analysis of the database load to check whether keeping these attributes or not.

#### **Choice of Principal Identifiers**

The schema does not contain external identification cycles and the main identifiers comply with the selection criteria.

#### Analysis of Database Load

The load analysis is divided in two parts: the first, to decide whether to store "lot\_price" into the "Lot" entity, or computing it when necessary via the relationship "Stocked"; the second, to decide whether to store "quantity" into the "Made up of (2)" relationship, or computing it when necessary via the relationship "Made up of (2)". The second part of the analysis is done also for the other relationship "Made up of (1)" and leads to the same results.

Operation	Description		Туре
$\mathrm{O}_1$ : Insert new lot	Store data about a newly packaged lot.	25/week	Online
$\mathrm{O}_2$ : Compute order price	Compute order price from lot price	25/week	Online
$\mathrm{O}_3$ : Create new order	Create new package from items	100/week	Online
$O_4$ : Compute order price	Compute the price of the order, which is composed of several lots	7/week	Online

We can see that  $\mathrm{O}_1$ , with or without redundancy, necessitate the same amount of operations, while from  $\mathrm{O}_2$  we can assess that the number of operations without redundancy is tripled with respect to the case with redundancy. Hence, the attribute "lot\_price" of the entity "Lot" should to be kept.

Table 4:  $\mathrm{O}_1$  Without redundancy

Concept	Construct	Access	Type	Average Access
Product	Entity	1	R	$1 \times 25 \times 1 = 25$
Lot	Entity	1	W	$1 \times 25 \times 2 = 25$
Stocked	Relationship	1	W	$1 \times 25 \times 2 = 25$
Total Access			75	

Table 5:  $O_1$  With redundancy

Concept	Construct	Access	Type Average Acce	
Product	Entity	1	R	$1 \times 25 \times 1 = 25$
Lot	Entity	1	W	$1 \times 25 \times 2 = 25$
Stocked	Relationship	1	W	$1 \times 25 \times 2 = 25$
	Total Access		75	

Table 6:  ${\rm O}_2$  Without redundancy

Concept	Construct	Access	Type Average Access		
Product	Entity	1	R	$1 \times 25 \times 1 = 25$	
Lot	Entity	1	W	$1 \times 25 \times 2 = 25$	
Stocked	Relationship	1	W	$1 \times 25 \times 2 = 25$	
Total Access				75	

Table 7:  $O_2$  With redundancy

Concept	Construct	Access	Type   Average Access		
Lot	Entity	1	W	$1 \times 25 \times 2 = 25$	
Total Access				25	

Table 8:  $O_3$  Without redundancy

Concept Construct		Access	Type	Average Access
Order	Entity	1	R	$1 \times 100 \times 1 = 100$
Draws from	Relationship	1	R	$1 \times 100 \times 1 = 100$
Lot	Entity	1	R	$1 \times 100 \times 1 = 100$
Т	otal Access		300	

We can see that  $O_3$ , with or without redundancy, necessitate the same amount of operations, while from  $O_4$  we can assess that the number of operations without redundancy is tripled with respect to the case with redundancy, as well. Hence, the attribute "quantity" of the relationship "made up of (2)" should to be kept.

### **Relational Schema**

# **Data Dictionary**

Relation	Attribute	Description	Domain	Constraints
	ID	Identifier of a product	Serial	PRIMARY KEY
	Name	Name of a product	Text	NOT NULL
	Description	Description of a product	Text	
	Production_Cost	Production cost of a product	Float	NOT NULL
Product	Price_increase	Price increase factor of a product	Float	NOT NULL
Product	Volume	Volume of a product in milliliters	Int	NOT NULL
	Net_Weight	Net weight of a product in grams	Int	NOT NULL
	Package_weight	Package weight of a product in grams	Int	NOT NULL
	Nutritional_Facts	Description of nutritional facts of a product	Text	NOT NULL
	Product_Category_ID	Identifier of a Product Category	Serial	NOT NULL, Foreign Key to Product_Category
	ID	Identifier of a Product Category	Serial	PRIMARY KEY
Product_Category	Name	Name of a Product Category	Text	NOT NULL
	Description	Description of a Product Category	Text	
	ID	Identifier of an item	Serial	PRIMARY KEY
	Name	Name of an item	Text	NOT NULL
Item	Description	Description of an item	Text	
	Quantity	Stock quantity of an item	Int	NOT NULL
	Item_Category_ID	Identifier of an Item Category	Serial	NOT NULL, Foreign Key to Item_Category
	ID	Identifier of an Item Category	Serial	PRIMARY KEY
Item_Category	Name	Name of an Item Category	Text	NOT NULL
rtem_category	Description	Description of an Item Category	Text	NOT NOLL
	Item_ID	Identifier of an item	Foreign	
Specify			Key to Item, Pri- mary key with Con- tract_ID	
	Contract_ID	Identifier of a contract	Serial	Foreign Key to Contract, Primary key with Item_ID
	Purchased_Quantity	Amount of each item which is purchased	Int	NOT NULL
	ID	Identifier of a contract	Serial	PRIMARY KEY
	Description	Description of a contract	Text	
Contract	Contract_date	Date of signature of a contract with the supplier	Datetime	NOT NULL
	Delivery_date	Expected date of delivery of the goods	Datetime	NOT NULL
	Expiration_date	Expiration date of a contract	Datetime	NOT NULL
	Supplier_ID	Identifier of a supplier	Int	Foreign Key to Sup- plier

	Employee_ID	Identifier of an employee	Text	Foreign Key to Employee
	ID	Identifier of a package	Serial	PRIMARY KEY
	Name	Name of a package	Text	NOT NULL
	Description	Description of a package	Text	
Package	Weight	Weight of a package in grams	Int	NOT NULL
J	Height	Height of a package in centimeters	Int	NOT NULL
	Width	Width of a package in centimeters	Int	NOT NULL
	Depth	Depth of a package in centimeters	Int	NOT NULL
	Package_Category_ID	Identifier of a Package Category	Serial	Foreign Key to Package_Category
	ID	Identifier of a Package Category	Serial	PRIMARY KEY
Package_Category	Name	Name of a Package Category	Text	NOT NULL
3 3	Description	Description of a Package Category	Text	
	ID	Identifier of a lot	Serial	PRIMARY KEY
	Expiration_date	Expiration date of the included products	Datetime	NOT NULL
	Product_Quantity	Amount of a product in each lot	Int	NOT NULL
Lot	Package_Quantity	Amount of a package in each lot	Int	NOT NULL
	Lot_Discount	Percentage of discount of a lot	Int	NOT NULL
	VAT	Value added tax (percentage)	NOT	
		(( 3 )	NULL	
	Lot_price	Lot price without discount	Float	NOT NULL
	Package_ID	Identifier of a package in each lot	Serial	Foreign Key to Package
	Product_ID	Identifier of a product in each lot	Serial	Foreign Key to Prod- uct
	ID	Identifier of an order	Serial	PRIMARY KEY
	Net_price	Total net amount including discount (VAT excluded)	Float	NOT NULL
Order	Taxes	Amount of taxes to be paid	Float	NOT NULL
	Order_date	Date in which the order has been processed	Datetime	NOT NULL
	Order_paid	Status of the order payment	Boolean	NOT NULL
	Employee_ID	Identifier of the employee that places the order	Text	Foreign key to Employee
	Customer_ID	Identifier of the customer that places the order	Int	Foreign key to Customer
	Product_ID	Identifier of a product	Serial	Foreign key to Prod-
Made_Up_Of (1)		,		uct, Primary key with Item_Id
	VAT_number	VAT_number of the customer	Text	PRIMARY KEY
	Customer_name	Name of the customer	Text	NOT NULL
Custo	Phone_number	Phone number (prefix included) of the customer	Text	NOT NULL
Customer	Address	Billing address of the customer	Text	NOT NULL
	Registration_date_ID	Customer registration date	Datetime	NOT NULL
	rregisti ation_date_iD	Custoffici registration date		
	Lot_ID	Identifier of a lot	Serial	Foreign Key to Lot

	Product_ID	Identifier of a product	Serial	Foreign key to Prod-
Made_Up_Of (1)				uct, Primary key with Item_Id
	Item_ID	Identifier of an item	Serial	Foreign key to Item, Primary key with Product_Id
	Quantity	Amount of each item in a product	Int	NOT NULL
	Package_ID	Identifier of a package	Serial	Foreign key to Pack-
Made_Up_Of (2)	-			age, Primary key with Item_Id
	Item_ID	Identifier of an item	Serial	Foreign key to Item, Primary key with Package_Id
	Quantity	Amount of each item in a package	Int	NOT NULL
Ship	Order_ID	Identifier of the shipped order	Serial	Foreign key to Order, Primary key with Employee_ID
	Employee_ID	Identifier of employee that ships the order	Serial	Foreign key to Employee
	Shipping_date	Date of when the order leaves to be shipped	Datetime	NOT NULL
	Track_num	Shipment code given by the third- party shipping company	Text	
	TAX_number	TAX code of the employee	Text	PRIMARY KEY
	First_name	Name of the employee	Text	NOT NULL
	Last_name	Surname of the employee	Text	NOT NULL
Employee	Phone_number	Phone number (prefix included) of the employee	Text	NOT NULL
	Email_address	Email address of the employee	Text	NOT NULL
	Birth_date	Birthdate of the employee	Datetime	
	Hiring_date	Hiring date of the employee	Datetime	NOT NULL
	Still_working	Flag used to know if employee is still working for the company	Boolean	NOT NULL
	Role_ID	Identifier of the role that an employee has	Serial	Foreign Key to Role
	ID	Role identifier	Serial	PRIMARY KEY
Role	Name	Name of the role	Text	NOT NULL
	Description	Technical description of the role	Text	
Work	Department_ID	Identifier of a department	Serial	Foreign key to Department, Primary key with Employee_ID
	Employee_ID	Identifier of an employee	Text	Foreign key to Employee, Primary key with Department_ID
Department	ID	Department identifier of the company	Serial	PRIMARY KEY
	Name	Name of the department	Text	NOT NULL
	Description	Description of the department's function	Text	
	VAT_number	VAT number of the supplier company	Int	PRIMARY KEY

Supplier_name	Name of the supplier company	Text	NOT NULL
Phone_number	Phone number (prefix included)	Text	NOT NULL
	of the supplier company		
Email_address	Email address of the supplier	Text	NOT NULL
	company		
Address	Address of the supplier company	Text	NOT NULL
Registration_date	Recording date of the supplier	Datetime	NOT NULL
	company		

#### **External Constraints**

# **Group Members Contributions**

## **Conceptual Design**

• Variations to the Requirement Analysis: Esposito, Basso

• Entity-Relationship Schema: Esposito, Basso, Zanini, Collado, Giuliani

• Entities Table: Esposito, Basso

• Relationships Table: Zanini e Giuliani

• External Constraints: Quiroz, Collado, Esposito, Basso

• Functional Requirements Satisfaction Check: Cimarosto, Collado, Arslan, Esposito, Basso

## **Logical Design**

• Transformation of the Entity-Relationship Schema: Esposito, Basso

• Analysis of Database Load: Giuliani, Zanini

• Transformation of the Entity-Relationship Schema: Esposito, Basso

• Analysis of Database Load: Giuliani e Zanini

• Relational Schema: Esposito, Basso, Quiroz, Collado

• Data Dictionary: Collado, Arslan, Cimarosto

• External Constraints: