

Университет ИТМО
Факультет программной инженерии и компьютерной техники

Распределённые системы хранения данных. Лабораторная работа №1.

Группа: Р33131
Студент: Смирнов Виктор Игоревич
Преподаватель: Афанасьев Дмитрий Борисович
Вариант: 776

Ключевые слова

База данных, PostgreSQL, системный каталог.

Содержание

1	Цель работы	1
2	Текст задания	1
3	Создание локального окружения для тестирования	2
4	Реализация скрипта	2
5	Вывод	6
6	Вывод	7

1 Цель работы

Научиться проектировать базы данных, составлять инфологические и даталогические модели данных, реализовывать их в БД PostgreSQL, научиться выполнять запросы.

2 Текст задания

Используя сведения из системных каталогов получить информацию о любой таблице: Номер по порядку, Имя столбца, Атрибуты (в атрибуты столбца включить тип данных, ограничение типа ЧЕКС).

Пример вывода:

Таблица: Н_ЛЮДИ

Но.	Имя столбца	Атрибуты
1	ИД	Type : NUMBER(9) NOT NULL Comment : 'Уникальный номер человека'
2	ФАМИЛИЯ	Type : VARCHAR2(25) NOT NULL Comment : 'Фамилия человека'
3	ИМЯ	Type : VARCHAR2(2000) NOT NULL Comment : 'Имя человека'
4	ОТЧЕСТВО	Type : VARCHAR2(20) Comment : 'Отчество человека'
5	ДАТА_РОЖДЕНИЯ	Type : DATE NOT NULL Comment : 'Дата рождения человека'
6	ПОЛ	Type : CHAR(1) NOT NULL Constr : "AVCON_378561_ПОЛ_000" CHECK (ПОЛ IN ('М', 'Ж')) Constr : "AVCON_388176_ПОЛ_000" CHECK (ПОЛ IN ('М', 'Ж')) Comment : 'Пол человека'
7	ИНОСТРАН	Type : VARCHAR2(3) NOT NULL
8	КТО_СОЗДАЛ	Type : VARCHAR2(40) NOT NULL
9	КОГДА_СОЗДАЛ	Type : DATE NOT NULL
10	КТО_ИЗМЕНИЛ	Type : VARCHAR2(40) NOT NULL
11	КОГДА_ИЗМЕНИ	Type : DATE NOT NULL
12	ДАТА_СМЕРТИ	Type : DATE Comment : 'Дата смерти человека'
13	ПИН	Type : VARCHAR2(20)
14	ИНН	Type : VARCHAR2(20)

3 Создание локального окружения для тестирования

Для локального взаимодействия я решил поднять PostgreSQL в Docker контейнере.

```
1 version: '3.8'
2 services:
3   database:
4     container_name: database
5     image: postgres
6     restart: always
7     ports:
8       - 5432:5432
9     volumes:
10      - ../workspace
11     environment:
12       POSTGRES_USER: postgres
13       POSTGRES_PASSWORD: postgres
14       POSTGRES_DB: postgres
15     networks:
16       - common
17 networks:
18   common:
19     name: common
20     driver: bridge
```

Далее был написан SQL скрипт, создающий таблицу, аналогичную той, что в примере.

```
1 drop table person;
2 create table person (
3   id numeric(9, 2) primary key,
4   last_name varchar(25) not null,
5   first_name varchar(2000) not null,
6   patronymic varchar(20),
7   birth_date date not null,
8   gender char(1) not null,
9   foreigner varchar(3) not null,
10  created_who varchar(40) not null,
11  created_when date not null,
12  edited_who varchar(40) not null,
13  edited_when date not null,
14  death_date date,
15  pin varchar(20),
16  inn varchar(20),
17
18  check (gender in ('M', 'F')),
19  check (gender in ('M', 'F'))
20 );
21
22 comment on column person.id is 'The unique number of the person';
23 comment on column person.id is 'The unique number of the person';
24 comment on column person.last_name is 'Last name of the person';
25 comment on column person.first_name is 'The name of the person';
26 comment on column person.patronymic is 'The patronymic of the person';
27 comment on column person.birth_date is 'Date of birth of a person';
28 comment on column person.death_date is 'Date of death of a person';
```

4 Реализация скрипта

```
1 create or replace function table_column(
2   table_schema text,
3   table_name text
4 ) returns table (
5   number integer,
6   name text,
7   type text,
8   is_nullable boolean,
9   comment text,
10  constraint_name text,
11  check_clause text
12 ) as $$
13 select
```

```

14 attnum as number,
15 information_schema.columns.column_name as name,
16 (
17     data_type || (
18         case
19             when character_maximum_length is not null then
20                 ' (' || cast(character_maximum_length as text) || ')',
21             else
22                 ''
23         end
24     ) || (
25         (
26             case
27                 when (
28                     numeric_precision is not null or
29                     numeric_scale is not null
30                 ) then
31                     ' ('
32                 else
33                     ''
34             end
35         ) || (
36             case
37                 when numeric_precision is not null then
38                     cast(numeric_precision as text)
39                 else
40                     ''
41             end
42         ) || (
43             case
44                 when numeric_scale is not null then
45                     ', ' || cast(numeric_scale as text)
46                 else
47                     ''
48             end
49         ) || (
50             case
51                 when (
52                     numeric_precision is not null or
53                     numeric_scale is not null
54                 ) then
55                     '),'
56                 else
57                     ''
58             end
59         )
60     )
61 ) as type,
62 (
63     information_schema.columns.is_nullable = 'YES'
64 ) as is_nullable,
65 pg_description.description as comment,
66 information_schema.check_constraints.constraint_name as constraint_name,
67 information_schema.check_constraints.check_clause as check_clause
68 from information_schema.columns
69 left join information_schema.constraint_column_usage on (
70     constraint_column_usage.table_schema = table_column.table_schema and
71     constraint_column_usage.table_name = table_column.table_name and
72     constraint_column_usage.column_name = information_schema.columns.column_name
73 )
74 left join information_schema.check_constraints on (
75     check_constraints.constraint_schema = constraint_column_usage.constraint_schema and
76     check_constraints.constraint_name = constraint_column_usage.constraint_name
77 )
78 left join pg_attribute on (
79     pg_attribute.attrelid = (
80         SELECT oid
81         FROM pg_class
82         WHERE (
83             pg_class.relname = table_column.table_name and
84             pg_class.relnamespace = (
85                 select oid
86                 from pg_namespace

```

```

87         where pg_namespace.nspname = table_column.table_schema
88     )
89 )
90 ) and
91 pg_attribute.attname = information_schema.columns.column_name
92 )
93 left join pg_description on (
94     pg_description.objoid = pg_attribute.attrelid and
95     pg_description.objsubid = pg_attribute.attnum
96 )
97 where (
98     information_schema.columns.table_schema = table_column.table_schema and
99     information_schema.columns.table_name = table_column.table_name
100 );
101 $$ language sql;
102
103 create or replace function table_column_pretty(
104     table_schema text,
105     table_name text
106 ) returns table (
107     number integer,
108     name text,
109     attributes text
110 ) as $$
111 select
112     number,
113     name,
114     type || (
115         case
116             when constr is not null then
117                 e'\n' || constr
118             else
119                 ''
120         end
121     ) || (
122         case
123             when comment is not null then
124                 e'\n' || comment
125             else
126                 ''
127         end
128     ) as attributes
129 from (
130     select
131         number,
132         name,
133         'Type: ' || cast(type as text) || ' ' || (
134             case
135                 when not is_nullable then
136                     'NOT NULL'
137             else
138                 ''
139             end
140         ) as type,
141         string_agg(
142             ('Constr: ' || constraint_name || ' ' || check_clause), e'\n'
143         ) as constr,
144         ('Comment: ' || comment) as comment
145     from table_column(table_schema, table_name)
146     group by number, name, type, comment, is_nullable
147 ) as qqq
148 order by number;
149 $$ language sql;
150
151 create or replace function print_table_info(
152     table_schema text,
153     table_name text
154 ) returns void as $$
155 declare
156     col record;
157     col_contr record;
158
159     CiW integer;

```

```

160 C2W integer;
161 C31W integer;
162 C32W integer;
163 REM integer;
164 begin
165 C1W := 2;
166 C2W := 12;
167 C31W := 8;
168 C32W := 64 + 8;
169 REM := 11;
170
171 if not exists (
172     select *
173     from table_column(table_schema, table_name)
174     limit 1
175 ) then
176     raise exception '%', ('Table " ' || table_schema || '.' || table_name || '" was not
177     found!');
178 end if;
179
179 raise info
180 '%',
181 rpad(
182     '|--- Table " ' || table_schema || '.' || table_name || '" Information ',
183     C1W + C2W + C31W + C32W + REM,
184     '-');
185 ) || '|';
186 raise info
187 '| % | % | % |',
188 rpad('N', C1W, ' '),
189 rpad('Name', C2W, ' '),
190 rpad('Attributes', C31W + C32W + 2, ' ');
191 raise info '%', rpad('|', C1W + C2W + C31W + C32W + REM, '-') || '|';
192 for col in
193     select distinct number, name, type, comment
194     from table_column(table_schema, table_name)
195     order by number
196 loop
197     raise info
198     '| % | % | % |',
199     rpad(cast(col.number as text), C1W, ' '),
200     rpad(col.name, C2W, ' '),
201     (rpad('Type', C31W, ' ') || ': ' || rpad(col.type, C32W, ' '));
202     for col_contr in
203         select
204             constraint_name as name,
205             check_clause as clause
206         from table_column(table_schema, table_name)
207         where (
208             table_column.number = col.number and
209             constraint_name is not null
210         )
211     loop
212         raise info
213         '| % | % | % |',
214         rpad('', C1W, ' '),
215         rpad('', C2W, ' '),
216         (
217             rpad('Constr', C31W, ' ') || ': ' || rpad(
218                 (col_contr.name || ' ' || col_contr.clause), C32W, ' '
219             )
220         );
221     end loop;
222     if col.comment is not null then
223         raise info
224         '| % | % | % |',
225         rpad('', C1W, ' '),
226         rpad('', C2W, ' '),
227         (rpad('Comment', C31W, ' ') || ': ' || rpad(col.comment, C32W, ' '));
228     end if;
229     raise info '%', rpad('|', C1W + C2W + C31W + C32W + REM, '-') || '|';
230 end loop;
231 end;

```

```

232 $$ language plpgsql;
233
234 create or replace procedure solution(
235     table_name text
236 ) as $$
237 declare
238     table_schema text;
239 begin
240     select information_schema.tables.table_schema into table_schema
241     from information_schema.tables
242     where information_schema.tables.table_name = solution.table_name
243     limit 1;
244
245     perform print_table_info(table_schema, table_name);
246 end;
247 $$ language plpgsql;
248
249 select solution('person');

```

5 ВЫВОД

```

1 psql:get_table_info.sql:249: INFO:  |--- Table "public.person" Information
   |-----|
2 psql:get_table_info.sql:249: INFO:  | N | Name          | Attributes
   |
3 psql:get_table_info.sql:249: INFO:
   |-----|
4 psql:get_table_info.sql:249: INFO:  | 1 | id            | Type      : numeric (9, 2)
   |
5 psql:get_table_info.sql:249: INFO:  |   |               | Comment   : The unique number of
   | the person
6 psql:get_table_info.sql:249: INFO:
   |-----|
7 psql:get_table_info.sql:249: INFO:  | 2 | last_name     | Type      : character varying
   | (25)
8 psql:get_table_info.sql:249: INFO:  |   |               | Comment   : Last name of the
   | person
9 psql:get_table_info.sql:249: INFO:
   |-----|
10 psql:get_table_info.sql:249: INFO:  | 3 | first_name    | Type      : character varying
   | (2000)
11 psql:get_table_info.sql:249: INFO:  |   |               | Comment   : The name of the
   | person
12 psql:get_table_info.sql:249: INFO:
   |-----|
13 psql:get_table_info.sql:249: INFO:  | 4 | patronymic    | Type      : character varying
   | (20)
14 psql:get_table_info.sql:249: INFO:  |   |               | Comment   : The patronymic of
   | the person
15 psql:get_table_info.sql:249: INFO:
   |-----|
16 psql:get_table_info.sql:249: INFO:  | 5 | birth_date    | Type      : date
   |
17 psql:get_table_info.sql:249: INFO:  |   |               | Comment   : Date of birth of a
   | person
18 psql:get_table_info.sql:249: INFO:
   |-----|
19 psql:get_table_info.sql:249: INFO:  | 6 | gender        | Type      : character (1)
   |
20 psql:get_table_info.sql:249: INFO:  |   |               | Constr    : person_gender_check
   | ((gender = ANY (ARRAY['M'::bpchar, 'F'::bpchar])))
21 psql:get_table_info.sql:249: INFO:  |   |               | Constr    : person_gender_check1
   | ((gender = ANY (ARRAY['M'::bpchar, 'F'::bpchar])))
22 psql:get_table_info.sql:249: INFO:
   |-----|

```

```

23 psql:get_table_info.sql:249: INFO: | 7 | foreigner | Type : character varying
    (3)
24 psql:get_table_info.sql:249: INFO:
    |-----|

25 psql:get_table_info.sql:249: INFO: | 8 | created_who | Type : character varying
    (40)
26 psql:get_table_info.sql:249: INFO:
    |-----|

27 psql:get_table_info.sql:249: INFO: | 9 | created_when | Type : date
    |
28 psql:get_table_info.sql:249: INFO:
    |-----|

29 psql:get_table_info.sql:249: INFO: | 10 | edited_who | Type : character varying
    (40)
30 psql:get_table_info.sql:249: INFO:
    |-----|

31 psql:get_table_info.sql:249: INFO: | 11 | edited_when | Type : date
    |
32 psql:get_table_info.sql:249: INFO:
    |-----|

33 psql:get_table_info.sql:249: INFO: | 12 | death_date | Type : date
    |
34 psql:get_table_info.sql:249: INFO: | | | Comment : Date of death of a
    person |
35 psql:get_table_info.sql:249: INFO:
    |-----|

36 psql:get_table_info.sql:249: INFO: | 13 | pin | Type : character varying
    (20)
37 psql:get_table_info.sql:249: INFO:
    |-----|

38 psql:get_table_info.sql:249: INFO: | 14 | inn | Type : character varying
    (20)
39 psql:get_table_info.sql:249: INFO:
    |-----|

```

6 Вывод

Данная лабораторная работа помогла мне изучить системный каталог PostgreSQL.

Список литературы