nEXT M Series Magnetically Levitated Turbomolecular Pumps

Model Series: nEXT M - Official Technical Datasheet

==========

EDWARDS VACUUM (BURGESS HILL, UK) | AUTHORIZED PARTNER: SYINCO TECHNOLOGIES
Central Depot: H.No. 2-50, Plot No. 194, Mattuguda, Nagole, Hyderabad 500068, India

==========

VERIFIED SYSTEM SPECIFICATIONS & OPERATING PARAMETERS:

* Pumping Speed (N): 2,800 3,200
* Ultimate Vacuum: < 1 x 10
* Bearing System: 5-axis active magnetic levitation with digital position control
* Lubricant: None (100% dry, hydrocarbon-free vacuum)
* Inlet Flange Standards: DN 250 / DN 320 (ISO-F / CF / ANSI)
* Mean Time Between Service: > 80,000 hours

STANDARD MODEL CONFIGURATIONS & VARIANTS:

* Model nEXT 2807M: Pumping Speed: 2,800 L/s, Flange: DN 250
* Model nEXT 3207M: Pumping Speed: 3,200 L/s, Flange: DN 320

COMMERCIAL & DELIVERY SCOPE - SYINCO HYDERABAD ADVANTAGE:

- Direct Domestic INR Supply & Customs Clearance Handled Ex-Hyderabad Depot
- Hyderabad Warehousing: Genuine Edwards Spares, Vacuum Oils & Fast Dispatch
- Certified Field Engineering: On-Site Installation, Commissioning & Annual Maintenance
- Factory Warranty: 12-Month Standard Coverage with OEM Certificate of Conformity

Inquiries: info@syinco.in | Desk: +91 73822 92929 | Web: www.syinco.in