Speedivalve Diaphragm Isolation Valves

Model Series: SPEEDIVALVE - Product Engineering Brochure

==========

EDWARDS VACUUM (BURGESS HILL, UK) | AUTHORIZED PARTNER: SYINCO TECHNOLOGIES
Central Depot: H.No. 2-50, Plot No. 194, Mattuguda, Nagole, Hyderabad 500068, India

==========

VERIFIED SYSTEM SPECIFICATIONS & OPERATING PARAMETERS:

* Flange Size: NW10 / NW16 / NW25 / NW40
* Conductance: 1.5 / 3.5 / 8.5 / 25.0
* Diaphragm Material: Fluoroelastomer (Viton)

STANDARD MODEL CONFIGURATIONS & VARIANTS:

* Model SP10K: Flange Size: NW10, Conductance: 1.5 L/s, Diaphragm Material: Fluoroelastom...
* Model SP16K: Flange Size: NW16, Conductance: 3.5 L/s, Diaphragm Material: Fluoroelastom...
* Model SP25K: Flange Size: NW25, Conductance: 8.5 L/s, Diaphragm Material: Fluoroelastom...
* Model SP40K: Flange Size: NW40, Conductance: 25.0 L/s, Diaphragm Material: Fluoroelasto...

COMMERCIAL & DELIVERY SCOPE - SYINCO HYDERABAD ADVANTAGE:

- Direct Domestic INR Supply & Customs Clearance Handled Ex-Hyderabad Depot
- Hyderabad Warehousing: Genuine Edwards Spares, Vacuum Oils & Fast Dispatch
- Certified Field Engineering: On-Site Installation, Commissioning & Annual Maintenance
- Factory Warranty: 12-Month Standard Coverage with OEM Certificate of Conformity

Inquiries: info@syinco.in | Desk: +91 73822 92929 | Web: www.syinco.in