PRODUCT DATA SHEET

nEXT TURBOMOLECULAR PUMPING STATION TIC CART XL

edwardsvacuum.com

nEXT TIC Cart XL is a large volume turbomolecular pumping station, fully mobile, and is required where fast, reliable pump down to low pressure is essential.

Configurable with turbomolecular pump speeds ranging from 240 to 930 ls^{-1} and a choice of dry backing nXRi multistage roots or dry scroll pumps that enables the range to pump from 15 to 90 m^3h^{-1}.

All our nEXT turbomolecular pumping stations feature an integrated TIC turbo and instrument controller offering full control of the package via a simple intuitive interface.

Supplied fully assembled and ready to run straight out of the box providing a customer friendly interface using only one power cable. As fully featured high end stations they include RS232 serial communications and Windows® software for monitoring and control.



FEATURES AND BENEFITS

Range of turbomolecular pump options
Choice of turbomolecular pump with speeds ranging from 240 to 930 ls^{-1} and inlet flanges from DN100 to DN200.

Fully controllable
TIC turbo and instrument controller offers full control of pumps and up to 3 Active gauges as well as offering full serial remote communications.

Vent valve option
Optional turbomolecular pump vent valve can be ordered as part of cart assembly.

User serviceable
All nEXT turbomolecular pumps and backing pumps are fully user serviceable.

Mobile system
All metal frame with locking castors for a robust but easily mobile system.

Choice of backing pumps
Choice of dry backing pumps with capacities ranging from 15 to 90 m^3h^{-1}.

Low vibration
Backing pump mounted on anti-vibration mounts for low levels of transmitted vibration.

TECHNICAL DATA

Pumping station	nEXT240	nEXT300	nEXT400	nEXT730	nEXT930
Inlet connection	DN100/ISO-K/DN100CF	DN100/ISO-K/DN100CF	DN160/ISO-K/DN160CF	DN160/ISO-K/DN160CF	DN200/ISO-K/DN200CF
Forevacuum connection	DN 25 ISO-KF (NW25)	DN 25 ISO-KF (NW25)	DN 25 ISO-KF (NW25)	DN 25 ISO-KF (NW25)	DN 25 ISO-KF (NW25)
Inlet pumping speed N_2	240 l/s	300 l/s	390 l/s	730 l/s	930 l/s
Ultimate pressure mbar	6×10^{-8} 5×10^{-10}	6×10^{-8} 5×10^{-10}	1×10^{-8} 1×10^{-10}	2×10^{-8} 3×10^{-10}	2×10^{-8} 3×10^{-10}
Mains supply V	110 / 230	110 / 230	110 / 230	110 / 230	110 / 230

PLUG AND PUMP' TURBOMOLECULAR PUMPING STATION

Everything about our range of nEXT turbomolecular pumping stations has been developed to provide a comprehensive vacuum solution with the latest technological advances for easy installation and operation.

A simplified ordering matrix and expanded range, to include turbopumps with speeds from 240 ls^{-1} to 930 ls^{-1}, enables you to select the most appropriate combination for your application, fully assembled and ready to go.

1 Choose your turbopump


nEXT240 (240 ls^{-1})


nEXT300 (300 ls^{-1})


nEXT400 (400 ls^{-1})


nEXT930 (930 ls^{-1})


nEXT730 (730 ls^{-1})

2 Choose your backing pump



nXR30i (30 m^3h^{-1}) nXR40i (40 m^3h^{-1})
nXR60i (60 m^3h^{-1}) nXR90i (90 m^3h^{-1})
nXDS15i (15 m^3h^{-1})

3 Select your voltage



Vacuum isolation valve VIV and the APG200 fitted as a standard accessory

ORDERING INFORMATION

nEXT turbomolecular pumping cart xl:

TC □□ - □□ - 0 0 □

Turbo
B nEXT240
C nEXT300
D nEXT400
E nEXT240T
F nEXT300T
G nEXT400T
H nEXT730
I nEXT930

Inlet
1 ISO 100
2 CF 100
3 ISO 160
4 CF 160
5 ISO 200
6 CF 200

Backing
1 nXR30i
2 nXR40i
3 nXR60i
4 nXR90i
5 nXDS15i

Vent options
0 Manual vent
1 TAV5 vent valve

Electrical supply
1 220-240V 50/60 Hz Europe
2 110-120V 50/60 Hz USA
3 200V 50/60 Hz Japan
4 220-240v 50/60 Hz UK
5 220-240v 50/60 Hz USA

nEXT730/930 variants cannot be used with 110-120V 50/60 Hz USA voltage
Important note: System is not UL certified.

Publication Number: 3601 0705 01
© Edwards Limited 2025. All rights reserved Edwards and the Edwards logo are trademarks of Edwards Limited.
Whilst we make every effort to ensure that we accurately describe our products and services, we give no guarantee as to the accuracy or completeness of any information provided in this datasheet.
Edwards Ltd, registered in England and Wales No. 6124750, registered office: Innovation Drive, Burgess Hill, West Sussex, RH15 9TW, UK.