PRODUCT DATA SHEET

P4 and P5 (Bluetooth LE) Handheld Gauges

edwardsvacuum.com

Innovative Vacuum Measurement at Your Fingertips.

The P4 and P5 Series represent the pinnacle of handheld vacuum measurement technology, combining precision, reliability, and advanced connectivity.

Designed to excel in diverse industrial environments, these gauges deliver unparalleled performance and data management.

Engineered for professionals, the P4 and P5 ensure accurate pressure readings and seamless integration, empowering you to meet the challenges of modern vacuum applications with confidence.



FEATURES AND BENEFITS

1 **Wide Measurement Range:**
Capable of measuring absolute pressures from 2000 to $5x10^{-5}$ mbar and relative pressures from -1060 to +1200 mbar.

2 **High Precision:**
Advanced piezoresistive and heat conducting Pirani sensors provide accurate and reproducible measurements.

3 **User-Friendly Interface:**
Large graphic display with intuitive menu navigation for easy operation.

4 **Versatile Connectivity:**
USB-C interface and optional Bluetooth® LE for flexible data management.

5 **Data Logging:**
Integrated data logger with USB-C and optional Bluetooth® LE for seamless data transfer and analysis.

6 **Durable Construction:**
Built with high-quality materials including stainless steel and ceramic for long-lasting performance.

7 **VacuGraph™ Included:**
A full VacuGraph™ software license is now included with all P4 and P5 gauges (including Bluetooth® versions), providing advanced data logging and analysis tools.

Measurement Principle

The Edwards P4 and P5 Handheld Gauges are precision instruments designed for monitoring vacuum pressures and are the ideal tools for spot-checking equipment across a wide range of applications. Their advanced sensor technology ensures reliable performance, making them essential for technicians conducting quick diagnostics and maintenance in the field.

The Edwards P4 utilizes a piezoresistive sensor for high-pressure measurements, operating by detecting changes in electrical resistance as pressure is applied. This provides highly accurate readings for absolute pressures up to 2000 mbar.

The Edwards P5 takes this a step further by combining a piezoresistive sensor for high-pressure measurements with a heat-conducting Pirani sensor for low-pressure measurements. The Pirani sensor measures the thermal conductivity of the gas, which varies with pressure, allowing for precise measurements down to $5x10^{-5}$ mbar.


TYPICAL APPLICATIONS

- **Vacuum Systems Monitoring:**
  Ideal for continuous monitoring of vacuum chambers and systems to ensure optimal performance and tightness.
- **Industrial Processes:**
  Suitable for controlling and monitoring processes in manufacturing and research environments.
- **Quality Assurance:**
  Essential for documenting and comparing pump down characteristics for audits and quality control.
- **Leak Detection:**
  Effective for identifying and addressing leaks in vacuum systems.





Edwards P4 | P5 pressure range



TECHNICAL SPECIFICATIONS

	P4 (Bluetooth)	P5 (Bluetooth)
Measurement Principle	Piezoresistive (independent on gas type)	Piezoresistive / Heat conducting Pirani (depending on gas type)
Measurement Range	Abs. 2000 - 1 mbar (1500 - 1 Torr) Rel. -1060 bis +1200 mbar (-795 ... +900 Torr)	Abs. 1200 - 5 x 10^{-5} mbar (900 - 5 x10^{-5} Torr) Rel. -1060 bis +340 mbar (-795 ... +255 Torr)
Max. Overload	4 bar abs.	10 bar abs.
Accuracy	Absolute pressure: 0.25% of scaled value Relative pressure: 0.3% of span	Absolute pressure: 1200 - 40 mbar: 0.3% of scaled value 40 - 10^{-3} mbar: 10% of measured value Relative pressure: 0.25% of span
Resolution	1 mbar	1200 ... 1000 mbar: 1 mbar 1000 ... 2.0 mbar: 0.1 mbar 2.0 ... 10^{-2} mbar: 3 digits 10^{-2} ... 10^{-4} mbar: 2 digits 10^{-4}... 5 x 10^{-5} mbar: 1 digit
Repeatability	0.1% of scaled value + 1 digit	1200 - 40 mbar: 0.1 % of scaled value 40 - 10^{-2} mbar: 2 % of measured value
Materials with Vac. Contact	Stainless steel 1.4305, Al2 O3 ceramic, FKM	Stainless steel 1.4307, nickel, tungsten 2 3 SiO2, glass, SnAg Lot, 2 Polyimid, Epoxid
Logging Rate	20 ms ... 60 s	20 ms ... 60 s
Operating Temperature	+5...+50 °C	+5...+50 °C
Storage Temperature	-20...+60 °C	-20...+60 °C
Power Supply	5 VDC via USB-C	5 VDC via USB-C
Operating Time	> 1000 h	> 48 h
Interfaces	USB 2.0 optional Bluetooth® LE	USB 2.0 optional Bluetooth® LE
Vacuum Connection	DN 16 ISO-KF, G1/4	DN 16 ISO-KF
Weight	250 g	250 g
Dimensions	70 x 105 x 46,4 mm	70 x 105 x 46,4 mm
IP rating	IP40, not certified	IP40, not certified
Display size	2.75"	2.75"

Order Information

	Order Number
P4 Gauge (Bluetooth) – NW16	D03000550
P4 Gauge – NW16	D03000500
P5 Gauge (Bluetooth) – NW16	D03000650
P5 Gauge – NW16	D03000600
Protective case only – P4|P5 Gauge	D03000500-A
USB C – Interface cable - P4|P5 Gauge	D03000500-B
Charger Kit - P4|P5 Gauge	D03000500-C

Publication Number: 3601 0815 01
© Edwards Limited 2025. All rights reserved.
Edwards and the Edwards logo are trademarks of Edwards Limited.

Whilst we make every effort to ensure that we accurately describe our products and services, we give no guarantee as to the accuracy or completeness of any information provided in this datasheet.

Edwards Ltd, registered in England and Wales
No. 6124750, registered office: Innovation Drive,
Burgess Hill, West Sussex, RH15 9TW, UK.