25 Series Pilot & Industrial Spark Plasma Sintering Systems

High-Capacity Sintering Systems for Pilot Scaling and Medium-Scale Production - Official System Brochure

==========

OEM: FUJI ELECTRONIC INDUSTRIAL CO., LTD. (JAPAN) | SPS TECHNOLOGY DIVISION (fdc.co.jp/sps)
INDIAN TECHNICAL SALES & DEPOT SUPPORT: SYINCO TECHNOLOGIES, HYDERABAD, TELANGANA, INDIA

==========

VERIFIED TECHNICAL SPECIFICATIONS & OPERATING PARAMETERS:

* Technology: Spark Plasma Sintering (SPS) with Proportional Hydraulic Control
* Press Force Range: 100 kN to 250 kN (10.2 tf to 25.5 tf)
* Minimum Forming Pressure: 5 kN (standard) / 2 kN (optional low-pressure control)
* Maximum Sintering Temperature: 2,500 deg C (Working envelope: 2,200 deg C)
* Sintering DC Pulse Generator: 3,000 A to 10,000 A Output Capacity
* Hydraulic Stroke: 150 mm standard stroke
* Open Height: 250 mm Daylight Clearance
* Vacuum Chamber: Water-Cooled Stainless Steel (Bore: 450 mm, Front Door Cylindrical)
* Pulse Timing: ON: 1 to 99 digit / OFF: 1 to 9 digit

CANONICAL MODEL CONFIGURATIONS & FORCE ENVELOPES:

> Model 615: 100 kN Press Force, 3,000 A DC Pulse Generator
> Model 625: 100 kN / 250 kN Press Force, 5,000 A DC Pulse Generator
> Model 725: 250 kN Press Force, 5,000 A DC Pulse Generator
> Model 825: 250 kN Press Force, 8,000 A DC Pulse Generator
> Model 925: 250 kN Press Force, 10,000 A DC Pulse Generator

SCOPE OF DELIVERY & SYINCO LOCAL SUPPORT ADVANTAGE:

- Complete OEM Furnace Body, Chamber, Electrode Assembly & DC Pulse Power Supply
- In-Country INR Supply & Customs Clearance Handled Ex-Hyderabad Central Logistics Depot
- Certified Field Installation, Commissioning, Calibration & Preventive Maintenance (AMC)
- Dedicated Inventory of High-Purity Graphite Tooling (Dies & Punches), Thermocouples & Seals

Technical Consultation Desk: info@syinco.in | Mobile: +91 73822 92929 | Official Portal: www.syinco.in