25 Series Pilot & Industrial Spark Plasma Sintering Systems

Technical Datasheet & Engineering Specifications - Engineering Technical Datasheet

==========

OEM: FUJI ELECTRONIC INDUSTRIAL CO., LTD. (JAPAN) | SPS TECHNOLOGY DIVISION (fdc.co.jp/sps)
INDIAN TECHNICAL SALES & DEPOT SUPPORT: SYINCO TECHNOLOGIES, HYDERABAD, TELANGANA, INDIA

==========

VERIFIED TECHNICAL SPECIFICATIONS & OPERATING PARAMETERS:

* Hydraulic System: Proportional relief valve hydraulic unit with closed-loop pressure feedback
* Max Forming Pressure: 615: 100 kN | 625: 100/250 kN | 725: 250 kN | 825: 250 kN | 925: 250 kN
* DC Pulse Current: 615: 3,000 A | 625: 5,000 A | 725: 5,000 A | 825: 8,000 A | 925: 10,000 A
* Chamber Bore: phi 450 mm cylindrical water-cooled stainless steel vessel
* Vacuum Level: Standard: < 0.006 Pa with high-vacuum diffusion pump / roots blower
* Electrode Diameter: Heavy-duty water-cooled copper-alloy electrode rams
* Sample Diameter: Consolidates specimens up to 150 mm diameter in standard graphite dies

CANONICAL MODEL CONFIGURATIONS & FORCE ENVELOPES:

> 615: General pilot R&D unit with 3,000 A output
> 625: Industry-standard 5,000 A flagship workhorse
> 725: High-force 250 kN platform with 5,000 A power
> 825: Scaled 8,000 A generator for large-area sintering
> 925: High-power 10,000 A generator for refractory billets

SCOPE OF DELIVERY & SYINCO LOCAL SUPPORT ADVANTAGE:

- Complete OEM Furnace Body, Chamber, Electrode Assembly & DC Pulse Power Supply
- In-Country INR Supply & Customs Clearance Handled Ex-Hyderabad Central Logistics Depot
- Certified Field Installation, Commissioning, Calibration & Preventive Maintenance (AMC)
- Dedicated Inventory of High-Purity Graphite Tooling (Dies & Punches), Thermocouples & Seals

Technical Consultation Desk: info@syinco.in | Mobile: +91 73822 92929 | Official Portal: www.syinco.in