DR. SINTER LAB Jr. Series Spark Plasma Sintering Systems

Technical Datasheet & Engineering Specifications - Engineering Technical Datasheet

==========

OEM: FUJI ELECTRONIC INDUSTRIAL CO., LTD. (JAPAN) | SPS TECHNOLOGY DIVISION (fdc.co.jp/sps)
INDIAN TECHNICAL SALES & DEPOT SUPPORT: SYINCO TECHNOLOGIES, HYDERABAD, TELANGANA, INDIA

==========

VERIFIED TECHNICAL SPECIFICATIONS & OPERATING PARAMETERS:

* Press Mechanism: AC Servo Motor Mechanical Loading System
* Force Capacities: MS-1: 20 kN | 212Lx: 20 kN | 322Lx: 30 kN | 632Lx: 60 kN
* Ram Stroke: 50 mm (MS-1, 212Lx) / 150 mm (322Lx, 632Lx)
* Open Daylight Height: 200 mm across all models
* Vacuum Performance: Ultimate Vacuum: < 0.01 Pa with standard diffusion/turbo package
* DC Pulse Output: MS-1: 1,000 A | 212Lx: 1,000 A | 322Lx: 2,000 A | 632Lx: 3,000 A
* Cooling Water Requirement: Clean circulating water: >= 30 L/min, pressure 0.2 to 0.3 MPa
* Inert Gas Atmosphere: High-purity Argon / Nitrogen purge capability

CANONICAL MODEL CONFIGURATIONS & FORCE ENVELOPES:

> MS-1: Micro SPS for exploratory nanomaterials synthesis
> 212Lx: Standard laboratory research unit for rapid sintering
> 322Lx: Mid-force laboratory system with extended 150 mm stroke
> 632Lx: High-force laboratory consolidation unit up to 60 kN

SCOPE OF DELIVERY & SYINCO LOCAL SUPPORT ADVANTAGE:

- Complete OEM Furnace Body, Chamber, Electrode Assembly & DC Pulse Power Supply
- In-Country INR Supply & Customs Clearance Handled Ex-Hyderabad Central Logistics Depot
- Certified Field Installation, Commissioning, Calibration & Preventive Maintenance (AMC)
- Dedicated Inventory of High-Purity Graphite Tooling (Dies & Punches), Thermocouples & Seals

Technical Consultation Desk: info@syinco.in | Mobile: +91 73822 92929 | Official Portal: www.syinco.in