Multi Process SPS System (MPSL) with RF Induction Heating

Dual-Energy Hybrid Spark Plasma Sintering & High-Frequency Induction Platform - Official System Brochure

==========

OEM: FUJI ELECTRONIC INDUSTRIAL CO., LTD. (JAPAN) | SPS TECHNOLOGY DIVISION (fdc.co.jp/sps)
INDIAN TECHNICAL SALES & DEPOT SUPPORT: SYINCO TECHNOLOGIES, HYDERABAD, TELANGANA, INDIA

==========

VERIFIED TECHNICAL SPECIFICATIONS & OPERATING PARAMETERS:

* Technology: Hybrid Pulsed DC Joule Sintering + 4.5 kW RF Induction Heating
* Press Force Range: 20 kN to 100 kN (2,040 kgf to 10,200 kgf)
* Pressure Drive Mechanisms: AC Servo Motor (212HF, 322HF, 632HF) / Hydraulic Control (625HF)
* Maximum Sintering Temperature: 2,500 deg C (Working Temperature: 2,200 deg C)
* Radio Frequency Generator: 4.5 kW Output at 100 kHz / 200 kHz Dual Frequency
* DC Pulse Current Output: 1,000 A (212HF), 2,000 A (322HF), 3,000 A (632HF), 5,000 A (625HF)
* Vacuum Chamber: Vertical Stainless Steel Cylinder (Bore: 200 mm to 450 mm)
* Hybrid Operating Modes: Simultaneous Dual-Energy, Sequential DC-then-RF, or Independent RF...

CANONICAL MODEL CONFIGURATIONS & FORCE ENVELOPES:

> Model 212HF: 20 kN AC Servo Drive, 1,000 A DC Pulse, 4.5 kW RF Generator, 200 mm Bore
> Model 322HF: 30 kN AC Servo Drive, 2,000 A DC Pulse, 4.5 kW RF Generator, 200 mm Bore
> Model 632HF: 60 kN AC Servo Drive, 3,000 A DC Pulse, 4.5 kW RF Generator, 200 mm Bore
> Model 625HF: 100 kN Hydraulic Drive, 5,000 A DC Pulse, 4.5 kW RF Generator, 450 mm Bore

SCOPE OF DELIVERY & SYINCO LOCAL SUPPORT ADVANTAGE:

- Complete OEM Furnace Body, Chamber, Electrode Assembly & DC Pulse Power Supply
- In-Country INR Supply & Customs Clearance Handled Ex-Hyderabad Central Logistics Depot
- Certified Field Installation, Commissioning, Calibration & Preventive Maintenance (AMC)
- Dedicated Inventory of High-Purity Graphite Tooling (Dies & Punches), Thermocouples & Seals

Technical Consultation Desk: info@syinco.in | Mobile: +91 73822 92929 | Official Portal: www.syinco.in