Standard System for Research & Production SPS Systems

Heavy-Duty Production Sintering Presses from 200 kN up to 6,000 kN Force - Official System Brochure

==========

OEM: FUJI ELECTRONIC INDUSTRIAL CO., LTD. (JAPAN) | SPS TECHNOLOGY DIVISION (fdc.co.jp/sps)
INDIAN TECHNICAL SALES & DEPOT SUPPORT: SYINCO TECHNOLOGIES, HYDERABAD, TELANGANA, INDIA

==========

VERIFIED TECHNICAL SPECIFICATIONS & OPERATING PARAMETERS:

* Technology: Heavy Industrial Spark Plasma Sintering (SPS) Mega-Press System
* Press Force Range: 200 kN to 6,000 kN (20.4 tf to 612 tf)
* Minimum Pressure: 2 kN to 30 kN (model-dependent low-pressure throttling)
* Maximum Sintering Temperature: 2,500 deg C across all models
* Sintering DC Pulse Generator: 3,000 A up to 45,000 A continuous pulse output
* Chamber Architecture: Upper & Lower Split Water-Cooled Vacuum Chamber
* Hydraulic Stroke: 250 mm to 350 mm heavy stroke capacity
* Daylight Clearance: 300 mm to 600 mm for massive multi-tier tooling

CANONICAL MODEL CONFIGURATIONS & FORCE ENVELOPES:

> MODEL 3.20: 200 kN Press Force (20.4 tf), 250 mm Stroke, 300 mm Open Height
> MODEL 5.40: 500 kN Press Force (51.0 tf), 250 mm Stroke, 400 mm Open Height
> MODEL 7.40: 1,000 kN Press Force (102 tf), 300 mm Stroke, 400 mm Open Height
> MODEL 8.40: 2,000 kN Press Force (204 tf), 300 mm Stroke, 600 mm Open Height
> MODEL 9.40: 3,000 kN Press Force (306 tf), 350 mm Stroke, 600 mm Open Height
> MODEL 10.40: 6,000 kN Press Force (612 tf), 350 mm Stroke, 600 mm Open Height

SCOPE OF DELIVERY & SYINCO LOCAL SUPPORT ADVANTAGE:

- Complete OEM Furnace Body, Chamber, Electrode Assembly & DC Pulse Power Supply
- In-Country INR Supply & Customs Clearance Handled Ex-Hyderabad Central Logistics Depot
- Certified Field Installation, Commissioning, Calibration & Preventive Maintenance (AMC)
- Dedicated Inventory of High-Purity Graphite Tooling (Dies & Punches), Thermocouples & Seals

Technical Consultation Desk: info@syinco.in | Mobile: +91 73822 92929 | Official Portal: www.syinco.in