Power Generation Efficiency Characteristics Evaluation System PEM-2

System Engineering & Application Reference Brochure - Product Brochure

==========

ADVANCE RIKO, INC. (YOKOHAMA, JAPAN) | AUTHORIZED INDIAN PARTNER: SYINCO TECHNOLOGIES
Central Depot: H.No. 2-50, Plot No. 194, Mattuguda, Nagole, Hyderabad 500068, India

==========

VERIFIED SYSTEM SPECIFICATIONS & CAPABILITIES:

* Measurement value: Conversion efficiency, Power generation amount, Penetration heat...
* Measurement method: One dimensional heat flow input method
* Module size: Square 30mm 5 to 30mm t (negotiable)
* Heating surface temperature Max.: Max. 800
* Sample temperature gradient: Approx. 300 in case of thermal conductivity of Stain...
* Pressure on contact surface: 2MPa
* Atmosphere: In inert gas
* Required floor space: Approx. W 3000 D 1000 (mm)
* Weight: Approx. 300 kg
* Power source: Power : AC 200 V, 1 phase, 4 kVA, One location PC, Pump : AC 100 V, 1...
* Grounding: Resistance 100 max. one location

COMMERCIAL & DELIVERY SCOPE - SYINCO HYDERABAD ADVANTAGE:

- Direct Domestic INR Supply & Customs Clearance Handled Ex-Hyderabad
- Hyderabad Warehousing: Genuine OEM Spare Parts Buffer & Fast Dispatch
- Certified Field Engineering: On-site Installation, Training & Annual Maintenance (AMC)
- Factory Warranty: 12-Month Standard Coverage with OEM Calibration Certificate

Inquiries: info@syinco.in | Tel: +91 (40) 24142929, 24143939 | Web: www.syinco.in