Thermal Diffusivity measurement system by Xe flash method TD-1

System Engineering & Application Reference Brochure - Product Brochure

==========

ADVANCE RIKO, INC. (YOKOHAMA, JAPAN) | AUTHORIZED INDIAN PARTNER: SYINCO TECHNOLOGIES
Central Depot: H.No. 2-50, Plot No. 194, Mattuguda, Nagole, Hyderabad 500068, India

==========

VERIFIED SYSTEM SPECIFICATIONS & CAPABILITIES:

* Model: TD-1 HTV
* Temperature range: RT 350 C (max.)
* Temperature Range: RT to Max. 350 C
* Temperature Range: RT to Max. 350 C
* Sample Size: 10mm (Round samples, normal direction measurements) Sample thickness ...
* Number of sample per a measurement: 4 pieces
* Atmosphere: Air, Vacuum, Inert gas
* Power requirements: AC100V, 15A (PC excluded)
* Footprint: about 710mm(W) x about 620mm(D) HTV model (Protruding parts excluded)
* Equipment weight: about 40kg
* Thickness (m): 25
* Thermal diffusivity (10-6m22s-1): 0.14

COMMERCIAL & DELIVERY SCOPE - SYINCO HYDERABAD ADVANTAGE:

- Direct Domestic INR Supply & Customs Clearance Handled Ex-Hyderabad
- Hyderabad Warehousing: Genuine OEM Spare Parts Buffer & Fast Dispatch
- Certified Field Engineering: On-site Installation, Training & Annual Maintenance (AMC)
- Factory Warranty: 12-Month Standard Coverage with OEM Calibration Certificate

Inquiries: info@syinco.in | Tel: +91 (40) 24142929, 24143939 | Web: www.syinco.in