

VERIQTA

VERIQTA




20-PAGE
FLAGSHIP
HANDBOOK

GITOPS

PRODUCTION HANDBOOK

BUILDING ENTERPRISE GITOPS PLATFORMS WITH
ARGO CD, FLUX, KUBERNETES, AND PRODUCTION OPERATIONS

- ✓ ENTERPRISE GITOPS ARCHITECTURE
- ✓ ARGO CD & FLUX DEEP DIVE
- ✓ MULTI-ENVIRONMENT STRATEGIES
- ✓ SECURITY & COMPLIANCE
- ✓ OBSERVABILITY & DRIFT DETECTION
- ✓ SCALING & HIGH AVAILABILITY
- ✓ TROUBLESHOOTING & RECOVERY
- ✓ PRODUCTION CASE STUDIES
- ✓ SENIOR ENGINEER BEST PRACTICES



GITOPS PRINCIPLES

1. Git is the Source of Truth
2. Declarative Everything
3. Automated Reconciliation
4. Continuous Verification
5. Secure by Design
6. Observable & Auditable



argo



flux



kubernetes

ARCHITECT. AUTOMATE. SECURE. OBSERVE. SCALE. RECOVER.

OPERATE GITOPS PLATFORMS LIKE A SENIOR ENGINEER.



VERIQTA

LEARN. PRACTICE. BUILD. DEPLOY. SUCCEED.

veriqta
youtubeveriqta
githubveriqta
linkedinveriqta
xveriqta
instagramveriqta
telegram

1. GITOPS FOUNDATIONS



GitOps uses Git as the single source of truth for defining, deploying, and operating infrastructure and applications. It brings version control, auditability, automation, and continuous reconciliation to your Kubernetes environments.

KEY IDEA



The system continuously reconciles the live state with the desired state defined in Git.




GITOPS PRINCIPLES

- Declarative Everything**
Define the desired state using declarative manifests (YAML / JSON).
- Git is the Source of Truth**
All configurations, environments, and applications live in Git.
- Automated Reconciliation**
Controllers continuously compare desired state (Git) with live state (Cluster) and make changes automatically.
- Versioned & Immutable**
Every change is versioned, traceable, and revertible through Git history.
- Pull-Based Model**
Agents in the cluster pull changes from Git; nothing needs to be pushed into the cluster.
- Continuous Delivery**
Safe automation enables fast, reliable, and repeatable deployments.



DESIRED STATE

- The desired state is the configuration stored in Git.
- It represents how your system should look.
- Controllers ensure the live state matches this exactly.
- Drift is detected and corrected.



DESIRED STATE



Declarative manifests define the target system state.



DECLARATIVE INFRASTRUCTURE

- Infrastructure and applications are defined as code (YAML/JSON).
- Kubernetes manifests, Helm charts, Kustomize, and other tools are used.
- Changes are reviewed, versioned, and applied automatically.
- Promotes consistency, repeatability, and compliance.

example: deployment.yaml

```

apiVersion: apps/v1
kind: Deployment
metadata:
  name: payment-service
spec:
  replicas: 3
  selector:
    matchLabels:
      app: payment-service
  template:
    metadata:
      labels:
        app: payment-service
    spec:
      containers:
        - name: app
          image: myapp:v1.2.0
          ports:
            - containerPort: 8080
  
```



PULL VS PUSH DEPLOYMENTS

PULL (GITOPS)

- ✓ Cluster pulls changes from Git.
- ✓ No inbound access required.
- ✓ More secure by design.
- ✓ Continuous reconciliation.
- ✓ Self-healing and drift correction.

PUSH (TRADITIONAL)

- ✗ Changes pushed to the cluster.
- ✗ Requires access to API server.
- ✗ Manual approvals & steps.
- ✗ No continuous reconciliation.
- ✗ Drift is common and hard to detect.

GITOPS = PULL MODEL = MORE SECURE, MORE RELIABLE



WHY ENTERPRISES ADOPT GITOPS

- ✓ Single Source of Truth
- ✓ Full Audit Trail
- ✓ Faster & Safer Deployments
- ✓ Rollback with Git History
- ✓ Reduced Human Error
- ✓ Compliance & Governance
- ✓ Scalability Across Clusters
- ✓ Self-Healing & Drift Correction



SPEED



SECURITY



RELIABILITY



GOVERNANCE



SCALABILITY



AUTOMATION



PRODUCTION ARCHITECTURE OVERVIEW



ARCHITECT.

AUTOMATE.

SECURE.

OBSERVE.

SCALE.

RECOVER.

SUCCEED.

VERIQTA.



veriqta
youtube



veriqta
github



veriqta
linkedin



veriqta
x



veriqta
instagram



veriqta
telegram

2. ENTERPRISE GITOPS ARCHITECTURE



Enterprise GitOps architecture provides a scalable, secure, and observability-rich platform for managing Kubernetes environments using Git as the single source of truth.

KEY IDEA



Git is the Source of Truth.
Everything else is automated from it.



1. GIT REPOSITORY STRATEGY

1. Monorepo (Single Repository)

One repo for all apps & environments.
Easy to manage, strong consistency.

2. Polyrepo (Multiple Repositories)

Separate repos per app or domain.
Better isolation, suitable at scale.

3. Environment Repositories

Dedicated repos per environment
(dev, staging, prod).

4. Strategy Recommendation (Enterprise)

Application code → Polyrepo
Deployments → Env repositories
Platform components → Shared infra repo

STRATEGY PATTERN



Application
Repositories




Environment
Repositories




Platform / Infra
Repository




2. ARGO CD ARCHITECTURE




3. FLUX ARCHITECTURE




4. REPOSITORY HIERARCHY (EXAMPLE)



5. CONTROL PLANE OVERVIEW



6. DEPLOYMENT WORKFLOW



ENTERPRISE GITOPS BENEFITS

- Single Source of Truth
- Automated Deployments
- Consistent & Standardized
- Self-Healing & Drift Detection
- Security & Compliance
- Scalable & Observable



SENIOR ENGINEER TIP

A strong GitOps architecture is built on clear repository boundaries, automated workflows, and continuous reconciliation to keep clusters in the desired state.



ARCHITECT.

AUTOMATE.

SECURE.


OBSERVE.

SCALE.

RECOVER.

SUCCEED.

VERIQTA.

veriqta
youtubeveriqta
githubveriqta
linkedinveriqta
xveriqta
instagramveriqta
telegram

3. GIT REPOSITORY DESIGN



A well-designed Git repository structure is the foundation of scalable, secure, and maintainable GitOps operations. Design for clarity, separation of concerns, automation, and long-term growth.

KEY IDEA



Good repository design makes GitOps simple to operate, easy to automate, and safe to scale.



1. MONOREPO

- ✓ Single repository for all applications and environments.
- ✓ Easy refactoring and shared components.
- ✓ Consistent governance and policies.
- ✓ Best for organizations with many teams and shared platforms.

BEST FOR:

Large enterprises, platform teams, organization-wide standards.



2. POLYREPO

- ✓ Separate repositories per application or domain.
- ✓ Stronger isolation and access control.
- ✓ Teams own their repositories.
- ✓ Better for independent deployment and scaling.

BEST FOR:

Independent teams, different lifecycles, third-party or regulated workloads.



3. ENVIRONMENT REPOSITORIES

- ✓ Store environment-specific configurations (dev, staging, prod).
- ✓ Reference application repositories using Kustomize or Helm.
- ✓ Centralized environment management.
- ✓ Promotes consistency and governance.

BEST FOR:

Managing environments, promotions, and cross-application configurations.



4. APPLICATION REPOSITORIES

- ✓ Holds application manifests, Helm charts, Kustomize bases, and templates.
- ✓ Source of truth for application configuration.
- ✓ Version-controlled and traceable.
- ✓ Used by GitOps controllers (Argo CD / Flux) to deploy workloads.

EXAMPLE APP REPO STRUCTURE

```

my-app/
├── charts/
├── kustomize/
│   ├── base/
│   └── overlays/
│       ├── dev/
│       ├── staging/
│       └── prod/
├── manifests/
│   ├── deployment.yaml
│   ├── service.yaml
│   ├── ingress.yaml
│   └── values.yaml
└── README.md
  
```

5. FOLDER CONVENTIONS (RECOMMENDED)

```

gitops-repos/
├── apps/
│   ├── app-one/
│   ├── app-two/
│   └── app-n/
├── environments/
│   ├── dev/
│   ├── staging/
│   └── prod/
├── platform/
│   ├── argocd/
│   ├── monitoring/
│   ├── security/
│   └── network/
├── libraries/
│   ├── helm-charts/
│   ├── kustomize-components/
│   └── policies/
├── docs/
├── scripts/
└── README.md
  
```

FOLDER	PURPOSE
apps/	Application repositories or references.
environments/	Environment-specific overlays and configs.
platform/	Platform services and infrastructure components.
libraries/	Reusable charts, components, and policies.
docs/	Architecture, runbooks, and documentation.
scripts/	Automation, validation, and maintenance scripts.



6. PRODUCTION REPOSITORY STANDARDS

- ✓ **SECURITY:** Enforce branch protection, signed commits, and least privilege access.
- ✓ **CONSISTENCY:** Follow standardized folder structure and naming conventions.
- ✓ **AUTOMATION:** All changes via Pull Requests and CI validation.
- ✓ **TRACEABILITY:** Every change must be versioned and auditable.
- ✓ **SEPARATION:** Enforce separation of apps, environments, and platform.
- ✓ **REUSABILITY:** Use shared libraries and components.
- ✓ **OBSERVABILITY:** Monitor repository health and activity.
- ✓ **DOCUMENTATION:** Maintain clear README and runbooks.
- ✓ **COMPLIANCE:** Meet audit, compliance, and governance requirements.

★ STANDARD REPOS = PREDICTABLE DEPLOYMENTS = RELIABLE PLATFORMS




7. REPOSITORY DESIGN DECISION MATRIX

CRITERIA	MONOREPO	POLYREPO
Scalability	High (with good tooling)	High
Team Autonomy	Medium	High
Access Control	Medium	High
Operational Overhead	Lower	Higher
Shared Components	Easy	Harder
Security Isolation	Lower	Higher
Best Fit	Large orgs, platform teams	Independent teams, startups



8. REPOSITORY TO PRODUCTION WORKFLOW



ARCHITECT.

AUTOMATE.

SECURE.

OBSERVE.

SCALE.

RECOVER.

SUCCEED.

VERIQTA.



veriqta
youtube



veriqta
github



veriqta
linkedin



veriqta
x



veriqta
instagram



veriqta
telegram

4. GITOPS DEPLOYMENT WORKFLOW


KEY IDEA




Automate everything after the merge. People approve changes, GitOps delivers them safely to production.



GitOps makes Git the single source of truth. Every change goes through a secure workflow before it is automatically reconciled and deployed to Kubernetes. This workflow ensures consistency, auditability, and reliability in production.



GITOPS DEPLOYMENT LIFECYCLE (END TO END)



MERGE STRATEGY COMPARISON

STRATEGY	DESCRIPTION	BEST FOR	PROS	CONS
Merge Commit	Preserves history with merge commit	Teams requiring full history	Full audit trail, easy tracking	History can be noisy
Squash Merge	Combines all commits into one	Clean history, preference	Clean history, simple	Loses individual commit details
Rebase + Merge	Linear history (realtach commits)	Small teams, strict history	Linear history, clean	Rewriting history risk

APPROVAL WORKFLOW EXAMPLES

- ✓ At least 1 approve from code owners
- ✓ Security scan must pass
- ✓ CI/CD pipeline must succeed
- ✓ Policy checks (OPA / Conftest) must pass
- ✓ All conversations resolved
- ✓ Manual approval for production environments

RECONCILIATION BEHAVIOR

- ✓ Continuous reconciliation loop
- ✓ Detects drift automatically
- ✓ Self-heals unintended changes
- ✓ Supports pruning of deleted resources
- ✓ Respects sync policies and waves
- ✓ Ensures desired state is always match

PRODUCTION DEPLOYMENT LIFECYCLE DETAILS

- SYNC START** Controller starts sync after detecting new commit.
- PRE-SYNC HOOKS** Run jobs or checks before applying changes.
- APPLY CHANGES** Resources are created, updated, or deleted.
- HEALTH CHECK** Controller verifies resources are healthy.
- POST-SYNC HOOKS** Run tests, notifications, cleanup tasks.
- SYNC COMPLETE** Application reports Healthy and Synced.

BEST PRACTICES

- ✓ Protect main branch and environments
- ✓ Use feature branches for all changes
- ✓ Automate tests and policy validations
- ✓ Use separate repos for environments
- ✓ Enforce least privilege access
- ✓ Monitor and alert on sync failures
- ✓ Document everything in Git
- ✓ Keep manifests DRY and modular
- ✓ Use sync waves for complex apps
- ✓ Review drift and fix root cause

COMMON ANTI-PATTERNS

- ✗ Direct commits to main
- ✗ Manual changes in cluster
- ✗ Skipping code reviews
- ✗ No automated policy checks
- ✗ Overly large repositories
- ✗ Secrets in plain manifests
- ✗ Ignoring sync failures
- ✗ Disable self-healing
- ✗ Not versioning changes
- ✗ Poor repository structure

KEY BENEFITS OF THIS WORKFLOW

- AUDITABLE** Every change is tracked.
- SECURE** Approvals and policy checks.
- AUTOMATED** No manual deployments.
- CONSISTENT** Same process always.
- SELF-HEALING** Drift is detected and fixed.
- SCALABLE** Handles many apps and clusters.

SENIOR ENGINEER TIP

Design your GitOps workflow like a production system: observable, secure, automated, and built for failure recovery.



5. ARGO CD DEEP DIVE

KEY IDEA

Argo CD continuously compares the desired state in Git with the live state in the cluster and reconciles the difference.



Argo CD is a declarative, GitOps continuous delivery tool for Kubernetes. It automates deployment, maintains desired state, and provides visibility, control, and auditability.



1. APPLICATION CRD

The Application custom resource defines what Argo CD should deploy and how.

```
apiVersion: argoproj.io/v1alpha1
kind: Application
metadata:
  name: payment-service
  namespace: argocd
spec:
  project: default
  source:
    repoURL: https://github.com/org/payment-service.git
    targetRevision: main
    path: manifests/
  destination:
    server: https://kubernetes.default.svc
    namespace: payment
  syncPolicy:
    automated:
      prune: true
      selfHeal: true
    syncOptions:
      - CreateNamespace=true
```

KEY FIELDS

- source: Git repo, path, and revision.
- destination: Cluster and namespace.
- syncPolicy: Automated sync, prune, self-heal.
- project: Access control boundary.



2. PROJECTS

Projects provide logical boundaries and RBAC for Applications.

- Group applications.
- Define who can deploy.
- Restrict clusters, repositories, and namespaces.
- Enforce governance and isolation.

EXAMPLE PROJECT RULES

Name: production

Source Repos:

- https://github.com/org/*

Destinations:

- https://kubernetes.prod.svc

Namespaces:

- prod-*

Cluster Resource Blacklist:

- CustomResourceDefinition/*
- ClusterRole/*



3. SYNC POLICIES

Define how and when Argo CD syncs changes.

MANUAL



Sync is triggered manually by a user.

```
argocd app sync my-app
```

AUTOMATED



Sync happens automatically.

```
automated:
  prune: true
  selfHeal: true
```

SYNC OPTIONS

- ✓ Prune: Remove resources not in Git.
- ✓ Self-Heal: Revert manual changes.
- ✓ CreateNamespace=true
- ✓ ApplyOutOfSyncOnly=true



4. HEALTH CHECKS

Argo CD evaluates the health of applications and resources.

HEALTH STATUS	ICON	DESCRIPTION	EXAMPLES
Healthy		Resource is running as expected.	Deployments, Pods, Services
Progressing		Resource is in the process of changing.	Deployments rolling update
Degraded		Resource is not in the desired state.	Failed Pods, CrashLoop, Config errors
Missing		Resource not found in cluster.	Deleted resource, Not created
Unknown		Health cannot be determined.	Custom resources, No health rule




5. APPLICATIONSETS

Generate multiple Applications from templates.

TYPES

- List Generator
- Git Generator
- Cluster Generator
- Matrix Generator
- SCM Provider Generator

EXAMPLE: CLUSTER GENERATOR




Use ApplicationSets for multi-cluster, multi-environment, and multi-tenant deployments.




6. PRODUCTION PRACTICES

- ✓ Use Projects to enforce boundaries and RBAC.
- ✓ Enable automated sync with prune and self-heal.
- ✓ Use ApplicationSets for scale and consistency.
- ✓ Store sensitive data in External Secrets / Vault.
- ✓ Enforce signed commits and protected branches.
- ✓ Monitor Argo CD with metrics and alerts.
- ✓ Use sync windows to control change timing.
- ✓ Backup Argo CD and Application resources.
- ✓ Document application ownership and runbooks.
- ✓ Continuously review access, repos, and policies.

ARGO CD ARCHITECTURE OVERVIEW



ARCHITECT.



veriqta
youtube

AUTOMATE.



veriqta
github

SECURE.



veriqta
linkedin

OBSERVE.



veriqta
x

SCALE.

RECOVER.



veriqta
instagram

SUCCEED.



veriqta
telegram

VERIQTA.

6. FLUX DEEP DIVE



Flux is a CNCF GitOps toolset that keeps your Kubernetes clusters in sync with Git. It is built on controllers that continuously reconcile the desired state with the live state.


KEY IDEA



Each Flux controller has a specific responsibility. Together they create a secure, scalable, and automated GitOps platform.

1. SOURCE CONTROLLER

Fetches and monitors Git repositories and artifacts.




KEY FEATURES

- ✓ Supports Git, Helm repository, OCI, Bucket.
- ✓ Detects changes via polling or webhooks.
- ✓ Stores artifacts in the cluster.
- ✓ Provides version metadata to other controllers.

2. KUSTOMIZE CONTROLLER

Builds and applies Kubernetes manifests using Kustomize.




KEY FEATURES

- ✓ Renders Kustomize manifests.
- ✓ Supports patches, overlays, and transformers.
- ✓ Validates manifests.
- ✓ Applies changes to cluster.

3. HELM CONTROLLER

Installs and upgrades Helm charts in the cluster.




KEY FEATURES

- ✓ Installs / upgrades Helm releases.
- ✓ Manages values and chart versions.
- ✓ Handles rollbacks and remediation.
- ✓ Supports CRDs and dependencies.

4. NOTIFICATION CONTROLLER

Sends alerts and notifications based on events.




KEY FEATURES

- ✓ Configurable alert triggers.
- ✓ Multiple receiver integrations.
- ✓ Templates and severity levels.
- ✓ Silencing and inhibition rules.

5. IMAGE AUTOMATION

Automatically updates container image versions in Git.




KEY FEATURES


- ✓ Scans registries for new image tags.
- ✓ Updates manifests / Helm values in Git.
- ✓ Creates Pull Requests automatically.
- ✓ Supports policies and filters.
- ✓ Reduces manual updates.
- ✓ Improves security and speed.

6. ENTERPRISE DEPLOYMENT MODEL

Flux in an enterprise multi-cluster, multi-team environment.



FLUX RECONCILIATION LOOP



FLUX ENTERPRISE BENEFITS

- Declarative and Git-driven infrastructure.
- Continuous reconciliation and self-healing.
- Scalable for thousands of clusters and apps.
- Strong security and audit capabilities.
- Separation of duties and governance.
- Automated updates and reduced toil.
- Observability and alerting built-in.
- Cloud-native and CNCF trusted ecosystem.

ARCHITECT.

AUTOMATE.

SECURE.


OBSERVE.

SCALE.

RECOVER.

SUCCEED.

VERIQTA.



7. MULTI-ENVIRONMENT GITOPS



Enterprise GitOps platforms manage multiple environments with consistent configuration, controlled promotions, and strong governance to deliver software safely and reliably at scale.

KEY IDEA

Promote changes through environments using Git as the single source of truth. Every environment is consistent, auditable, and reproducible.

1. ENVIRONMENT LIFECYCLE

DEVELOPMENT



Purpose: Rapid development and feature testing.

- ✓ Fast iterations
- ✓ Lower reliability requirements
- ✓ Shared clusters allowed
- ✓ Auto-sync enabled

TESTING



Purpose: Functional and integration testing.

- ✓ Automated testing
- ✓ Integration validation
- ✓ Feature validation
- ✓ Auto or manual sync

STAGING



Purpose: Pre-production validation and UAT.

- ✓ Production-like environment
- ✓ Performance validation
- ✓ Security validation
- ✓ Manual sync preferred

PRODUCTION



Purpose: Live customer workloads.

- ✓ High availability
- ✓ Security hardened
- ✓ Change controlled
- ✓ Manual sync + approvals



KEY PRINCIPLE

Same manifests, different values. Promote, don't recreate.

2. PROMOTION STRATEGIES

STRATEGY	DESCRIPTION	BEST FOR	PROS	CONS
Git Branch Promotion	Changes move from dev branch → main → prod branch.	Teams using branch-based workflow	Simple, familiar, good audit trail	Branch sprawl risk
Environment Repository Promotion	Changes merged in dev repo, then promoted to next env repo.	Teams using separate env repos	Clear separation, strong control	More repos to manage
Git Tag Promotion	Tagged release in Git promoted across environments.	Release-driven organizations	Immutable releases, reproducible	Requires discipline
Pull Request Promotion	PR from lower env to higher env repo.	Teams with strict approval needs	Built-in review and approvals	More manual effort
Image Digest Promotion	Promote exact container image digest.	Critical systems	Immutable, exact version control	More complex pipeline

3. ENVIRONMENT CONFIGURATION APPROACHES

APPROACH	DESCRIPTION	TOOLS / EXAMPLE	WHEN TO USE
Kustomize Overlays	Base manifests with environment-specific overlays.	Kustomize	Most common, simple, powerful
Helm Values Per Environment	Same chart with different values files.	Helm, Helmfile	When using Helm charts
Separate Values Repo	Environment-specific config stored in separate repo.	Flux + Git Repos	Large enterprises, strong separation
Config Management Tools	External tools for managing configs and secrets.	SOPS, Sealed Secrets, Vault	High security requirements
ApplicationSets / Generators	Generate applications for multiple environments.	Argo CD ApplicationSets, Flux Kustomize Generators	Many envs, scalable model


4. RELEASE GOVERNANCE

- ✓ Define who can promote changes to each environment.
- ✓ Use Pull Requests for all promotions.
- ✓ Require mandatory code reviews and approvals.
- ✓ Enforce policies with branch protection and RBAC.
- ✓ Require status checks / tests before merge.
- ✓ Use audit logs for all promotions and changes.
- ✓ Document release policies and procedures.

APPROVAL MATRIX (EXAMPLE)

ENVIRONMENT	APPROVERS
Development	Developer / Lead
Testing	QA Lead
Staging	Release Manager
Production	Engineering Manager + Security (if required)

5. RELEASE FLOW EXAMPLE



KEY BEST PRACTICES

- ✓ Use Git as the single source of truth.
- ✓ Separate environments with clear boundaries.
- ✓ Promote the same artifacts and manifests.
- ✓ Automate testing at every stage.
- ✓ Keep environments consistent and production-like.
- ✓ Monitor and alert on all deployments.
- ✓ Use immutable infrastructure patterns.
- ✓ Document and enforce policies.



COMMON ANTI-PATTERNS

- ✗ Direct commits to main / prod.
- ✗ Manual kubectl changes in production.
- ✗ Skipping environments (dev → prod).
- ✗ No approvals for promotions.
- ✗ Environment drift.
- ✗ Storing configs outside Git.
- ✗ Using mutable tags in production.
- ✗ No testing before production.

8. HELM AND KUSTOMIZE



Helm and Kustomize are powerful tools in the GitOps ecosystem, enabling consistent, flexible and maintainable application deployments across multiple environments.

KEY IDEA



Use Helm for application packaging and Kustomize for environment customization to achieve flexible, declarative and GitOps-friendly deployments.



1. HELM CHARTS

Helm packages Kubernetes applications into reusable charts.

- ✓ Simplifies application deployment.
- ✓ Handles complex Kubernetes manifests.
- ✓ Provides versioning and dependency management.
- ✓ Supports templating and values.

KEY FEATURES

- Chart templates
- Values file
- Dependencies
- Lifecycle management



2. KUSTOMIZE OVERLAYS

Kustomize customizes resources using patches and overlays.

- ✓ No templating required.
- ✓ Keeps base manifests clean.
- ✓ Applies environment-specific changes.
- ✓ Works with existing manifests.

KEY FEATURES

- Overlays
- Patches
- Strategic merge
- JSON6902 patches



3. ENVIRONMENT CUSTOMIZATION

Customize deployments per environment.

ENVIRONMENT	VALUES (HELM)	KUSTOMIZE OVERLAY
Development	values-dev.yaml	overlays/dev/
Testing	values-test.yaml	overlays/test/
Staging	values-staging.yaml	overlays/stage/
Production	values-prod.yaml	overlays/prod/

BEST PRACTICES

- ✓ Keep environment configs separate.
- ✓ Use clear naming conventions.
- ✓ Avoid hardcoded values.
- ✓ Use overlays for small changes.



4. CONFIGURATION MANAGEMENT

Manage configuration in a secure and consistent way.

- ✓ Use ConfigMaps for non-sensitive config.
- ✓ Use Secrets for sensitive data.
- ✓ Keep configuration in version control.
- ✓ Apply environment overlays for differences.
- ✓ Use RBAC and least privilege access.

CONFIG SOURCES

- ConfigMaps (non-sensitive)
- Secrets (sensitive)
- Git Repository (versioned)



5. SECRET REFERENCES

Securely inject and manage sensitive data.

```
apiVersion: v1
kind: Secret
metadata:
  name: app-secret
type: Opaque
data:
  password: ZnJlc3QtcGFzc3dvcmQ=
```

BEST PRACTICES

- ✓ Use Kubernetes Secrets.
- ✓ Integrate with external secret managers.
- ✓ Avoid hardcoding credentials.
- ✓ Use sealed-secrets or external vaults.



6. PRODUCTION PATTERNS

Proven patterns for reliable production deployments.

- ✓ Use Helm for application packaging.
- ✓ Use Kustomize for environment overlays.
- ✓ Combine Helm + Kustomize when needed.
- ✓ Implement GitOps with automated sync.
- ✓ Use progressive delivery (canary/blue-green).
- ✓ Apply policies and validations.

KEY BENEFITS

- ✓ Consistent deployments across environments.
- ✓ Faster configuration changes.
- ✓ Stronger security.
- ✓ Better maintainability.

HELM + KUSTOMIZE IN GITOPS



ARCHITECT.

AUTOMATE.

SECURE.

OBSERVE.

SCALE.

RECOVER.

SUCCEED.

VERIQTA.



veriqta
youtube



veriqta
github



veriqta
linkedin



veriqta
x



veriqta
instagram



veriqta
telegram

9. SECRETS MANAGEMENT



Secrets management in GitOps ensures sensitive data is never stored in plain text in Git repositories and is securely delivered to workloads at runtime.


KEY IDEA

- ✓ Keep secrets out of Git.
- ✓ Encrypt, externalize, or reference secrets securely.
- ✓ Rotate regularly and audit access continuously.

VERIQTA

1. EXTERNAL SECRETS OPERATOR

Synchronizes secrets from external stores into Kubernetes as native Secrets.



KEY FEATURES

- ✓ Pull secrets dynamically.
- ✓ Auto refresh on change.
- ✓ Fine-grained access control.
- ✓ No secrets stored in Git.

VERIQTA

2. SEALED SECRETS

Encrypts Kubernetes Secrets so they can be stored in Git safely.




KEY FEATURES

- ✓ Encrypted with cluster public key.
- ✓ Decrypted only in target cluster.
- ✓ GitOps-friendly secret workflow.
- ✓ Prevents accidental secret exposure.

VERIQTA

3. HASHICORP VAULT

Centralized secrets management with dynamic secrets, lease rotation, and strong access control.



KEY BENEFITS

- ✓ Dynamic, short-lived secrets.
- ✓ Strong auth (OIDC, LDAP, AWS IAM).
- ✓ Fine-grained policies.
- ✓ Centralized audit and revocation.

VERIQTA

4. AWS SECRETS MANAGER

Fully managed secrets service with rotation and auditing.



KEY FEATURES

- ✓ Native integration with AWS services.
- ✓ Automatic secret rotation.
- ✓ Fine-grained IAM access.
- ✓ CloudWatch audit and monitoring.

VERIQTA

5. SECRET ROTATION

Regular rotation reduces the risk of long-lived credentials.



BEST PRACTICES

- ✓ Use short TTL for dynamic secrets.
- ✓ Rotate database, API, and cloud keys.
- ✓ Automate rotation with minimal downtime.

VERIQTA

6. PRODUCTION SECURITY


Security controls for enterprise secret management.

- ✓ KEEP SECRETS OUT OF GIT
Use external stores or encryption.
- ✓ LEAST PRIVILEGE ACCESS
Grant only what is required.
- ✓ ENCRYPT IN TRANSIT & AT REST
Use TLS, KMS, and strong ciphers.
- ✓ AUDIT & MONITOR
Log access, changes, and anomalies.
- ✓ SEGREGATE DUTIES
Separate teams for ops and dev.

SECURITY CHECKLIST

- ✓ No plain-text secrets in Git.
- ✓ External store integration hardened.
- ✓ Access via IAM / RBAC.
- ✓ Regular secret rotation.
- ✓ Audit logs enabled.
- ✓ Alerts for secret access.
- ✓ Backup and disaster recovery validated.

SECRETS MANAGEMENT ARCHITECTURE EXAMPLE



10. GITOPS SECURITY



Security in GitOps protects your code, configurations, and delivery pipelines from commit to production. Trust, verify, and enforce everything.

KEY IDEA



- ✓ Secure the Git repository.
- ✓ Verify every change and artifact.
- ✓ Enforce least privilege everywhere.
- ✓ Protect the supply chain end-to-end.




1. RBAC (ROLE BASED ACCESS CONTROL)

Enforce least privilege across Git, Kubernetes, and GitOps tools.

WHO (IDENTITIES)

- Developers
- Operators
- Security Team
- Automation
- Service Accounts



ACCESS



SCOPE (RESOURCES)

- Repositories
- Branches
- Environments
- Clusters
- Applications

BEST PRACTICES

- ✓ Use fine-grained Git permissions.
- ✓ Separate duties for dev, ops, and security.
- ✓ Restrict cluster access using Kubernetes RBAC.
- ✓ Use OIDC / SSO for all human access.



2. REPOSITORY SECURITY

Protect your Git repositories and configuration code.

- ✓ Enforce branch protection (main / prod branches).
- ✓ Require pull request reviews.
- ✓ Require status checks to pass.
- ✓ Restrict who can push and merge.
- ✓ Disable force push on protected branches.
- ✓ Scan for secrets in commits.
- ✓ Use CODEOWNERS for approvals.

REPOSITORY CONTROLS

- ✓ Branch Protection
- ✓ Required Reviews
- ✓ Status Checks
- ✓ Signed Commits
- ✓ Secret Scanning
- ✓ Audit Logging



3. SIGNED COMMITS

Ensure every commit is signed and verifiable.

DEVELOPER



Create Commit
Sign with GPG Key



GIT REPOSITORY



Store Signed Commit



VERIFY SIGNATURE



Validate Signature on Pull / Sync

BEST PRACTICES

- ✓ Require signed commits for all changes.
- ✓ Use GPG keys managed securely.
- ✓ Enable commit signature verification in Git platform.
- ✓ Block unsigned commits on protected branches.



GPG KEY MANAGEMENT

- Generate strong keys.
- Store private keys securely.
- Rotate keys periodically.
- Revoke compromised keys.



4. GPG VERIFICATION

Verify commit signatures before merging or deploying.

SIGNED COMMIT



CI / POLICY CHECK



GPG VERIFICATION



MERGE / DEPLOY



BEST PRACTICES

- ✓ Enforce signature verification in CI pipeline.
- ✓ Use trusted GPG keyring.
- ✓ Reject commits with invalid or unknown signatures.
- ✓ Audit signature verification failures.



5. IMAGE VERIFICATION

Verify container images before deployment.



IMAGE BUILD



SIGN IMAGE



PUSH TO REGISTRY

VERIFY BEFORE DEPLOY

- ✓ Signature Valid
- ✓ Not Tampered
- ✓ Trusted Publisher

BEST PRACTICES

- ✓ Sign images using tools like cosign or Notary v2.
- ✓ Enforce signature verification in admission controller.
- ✓ Use trusted registries and retention policies.
- ✓ Block unsigned or untrusted images.

TOOLS

- cosign
- Notary v2
- ✓ Kyverno / OPA
- ✓ Atlantis / Connaiseur



6. SUPPLY CHAIN SECURITY

Protect the entire GitOps delivery supply chain.

- ✓ Secure source code (commits, branches).
- ✓ Verify dependencies and base images.
- ✓ Scan IaC and manifests for vulnerabilities.
- ✓ Use SBOM for all artifacts.
- ✓ Pin versions and digests.
- ✓ Automate security scanning in CI.
- ✓ Continuously monitor and audit.

SUPPLY CHAIN LAYERS

- Source Code
- Dependencies
- Build & Artifacts
- Container Images
- Kubernetes Manifests
- Production Deployment

GITOPS SECURITY CONTROLS AT A GLANCE



ACCESS CONTROL
Enforce RBAC and least privilege



CODE SECURITY
Protect repositories and branches



COMMIT SECURITY
Signed commits only



VERIFICATION
Verify GPG signatures and identities



IMAGE SECURITY
Sign and verify container images



SUPPLY CHAIN
Secure the entire delivery pipeline

11. GITOPS OBSERVABILITY



Observability in GitOps ensures your desired state matches the actual state, issues are detected early, and your applications stay healthy in production.

KEY IDEA



- ✓ See what GitOps is doing.
- ✓ Know the health of your apps.
- ✓ Detect drift and failures early.
- ✓ Alert the right people.
- ✓ Measure everything.

VERIQTA

1. SYNC STATUS

Track the synchronization state between Git (desired) and cluster (actual).

STATUS TYPES

- | | |
|---------------|-----------------------------|
| ● Synced | ✓ Actual state matches Git |
| ● OutOfSync | ✗ Actual state differs |
| ● Unknown | ? Unable to determine state |
| ● Progressing | ⌚ Operation in progress |
| ● Error | ! Sync operation failed |

BEST PRACTICES

- ✓ Monitor sync status continuously.
- ✓ Alert on OutOfSync > 5 minutes.
- ✓ Auto-heal to maintain desired state.

VERIQTA

2. HEALTH STATUS

Monitor the health of applications and resources managed by GitOps.

HEALTH STATES

- | | |
|-------------|---------------------------------|
| ♥ Healthy | ✓ Application is healthy |
| ⚠ Degraded | ⚠ Some components are unhealthy |
| ⏸ Suspended | ○ Application is suspended |
| ❓ Missing | ? Required resource missing |
| ❓ Unknown | ? Health cannot be determined |

BEST PRACTICES

- ✓ Use custom health checks for critical apps.
- ✓ Define meaningful health check rules.
- ✓ Alert on Degraded or Missing states.

VERIQTA

3. DRIFT MONITORING

Detect and track configuration drift between Git and live cluster.

DRIFT SOURCES

- 👤 Manual changes in cluster
- 📄 `kubectl apply / edit`
- ⚙ Autoscaling or controllers
- ✂ Out-of-band changes
- 🕒 expired configs / secrets

BEST PRACTICES

- ✓ Enable auto-detection of drift.
- ✓ Alert on persistent drift.
- ✓ Reconcile or revert unauthorized changes.

VERIQTA

4. ALERTS

Alert the right people at the right time for the right problems.

COMMON ALERTS

- OutOfSync for > 5 min
- Application health Degraded
- Sync operation failed
- Application missing
- Repository unreachable
- Drift detected
- Secret sync failed
- Sync latency high



BEST PRACTICES

- ✓ Alert on symptoms, not noise.
- ✓ Use severity levels (Critical, Warning, Info).
- ✓ Route alerts to the right team.
- ✓ Avoid alert fatigue.

VERIQTA

5. METRICS

Collect metrics to measure performance, reliability, and adoption.

KEY METRICS

- | | |
|------------------------|---------------------------|
| sync_total | Total sync operations |
| sync_duration_seconds | Sync duration (histogram) |
| sync_failed_total | Failed sync operations |
| applications_total | Total applications |
| applications_healthy | Healthy applications |
| applications_outofsync | OutOfSync applications |
| drift_total | Detected drift count |
| reconcile_count | Auto-heals performed |
| repo_request_duration | Git repo API latency |
| kubectl_exec_duration | Cluster API latency |

BEST PRACTICES

- ✓ Monitor trends over time.
- ✓ Set SLOs for sync latency and success rate.
- ✓ Track both controller and application metrics.

VERIQTA

6. DASHBOARDS

Visualize the state of your GitOps platform and applications.

DASHBOARD PANELS


- | | |
|------------------------|----------------------|
| 📊 Application Overview | 🕒 Sync Duration |
| 🔄 Sync Status | ! Failure Rate |
| ♥ Health Status | 🔑 Repository Status |
| ⊗ OutOfSync Apps | 🏠 Cluster Status |
| 🔍 Drift Overview | 🔔 Alerts / Incidents |

BEST PRACTICES

- ✓ Use role-based dashboards.
- ✓ Show high-level + drill-down views.
- ✓ Keep dashboards simple and actionable.
- ✓ Review dashboards with stakeholders.

VERIQTA

GITOPS OBSERVABILITY FLOW



VERIQTA

12. DRIFT DETECTION & SELF-HEALING

KEY IDEA

- ✓ Git is the source of truth.
- ✓ Live state is continuously compared to desired state.
- ✓ Drift is detected and healed automatically.
- ✓ Humans intervene only when necessary.

VERIQTA




Drift happens. What matters is how fast you detect it, how safely you handle it, and how quickly you recover to the desired state.

1. CONFIGURATION DRIFT

Drift occurs when the live state in the cluster differs from the desired state defined in Git.

COMMON DRIFT CAUSES


- Manual kubectl changes
- Out-of-band modifications
- Autoscaler changes
- Expired secrets / configs
- Third-party controllers
- Direct DB / storage edits



VERIQTA

2. CONTINUOUS RECONCILIATION

GitOps controllers continuously reconcile the live state to match the desired state.



BEST PRACTICES


- ✓ Set appropriate sync intervals.
- ✓ Use automated pruning of removed resources.
- ✓ Enable self-healing to fix drift automatically.
- ✓ Monitor reconciliation success and failures.

VERIQTA

3. AUTOMATIC ROLLBACK

If a change causes unhealthy state, GitOps tools can automatically rollback to the last known good state.

ROLLBACK FLOW



BEST PRACTICES

- ✓ Use health checks and readiness gates.
- ✓ Define rollback limits and conditions.
- ✓ Keep revision history for fast recovery.
- ✓ Test rollback process regularly.

VERIQTA

4. MANUAL INTERVENTION

Some situations require human decision and controlled action.

WHEN TO INTERVENE

- Persistent reconciliation failures
- Breaking changes or schema migrations
- External dependency issues
- Security incidents
- Complex cross-system dependencies

MANUAL ACTIONS

- ☒ Pause sync
- ☒ Investigate cause
- ☒ Apply hotfix (if needed)
- ☒ Update Git
- ☒ Resume sync

BEST PRACTICES

- ✓ Pause auto-sync before manual changes.
- ✓ Document reason and expected outcome.
- ✓ Commit changes back to Git after resolution.
- ✓ Resume sync and verify state.

VERIQTA

5. DRIFT INVESTIGATION

Understand what changed, when, why, and by whom.

INVESTIGATION STEPS

1. Detect drift alert
2. Identify affected resource(s)
3. Check live vs desired diff
4. Review audit logs
5. Identify source of change
6. Decide fix or rollback

TOOLS & COMMANDS

```
# Argo CD
argocd app diff <app-name>


# Flux
flux diff kustomization <name>

# Kubernetes
kubectl diff -f <manifest>
kubectl get events --sort-by=.lastTimestamp
```

VERIQTA

6. RECOVERY WORKFLOW

A repeatable process to restore and verify the desired state.




BEST PRACTICES

- ✓ Keep runbooks for common drift scenarios.
- ✓ Automate recovery where safe.
- ✓ Validate after recovery is complete.
- ✓ Perform post-incident review.

VERIQTA

DRIFT DETECTION & SELF-HEALING ARCHITECTURE



13. PRODUCTION TROUBLESHOOTING



When something goes wrong, speed and accuracy matter. Follow a structured approach to identify the issue, understand the impact, and restore the desired state safely.

KEY IDEA



- ✓ Systematic troubleshooting saves time.
- ✓ Observe before you act.
- ✓ Identify the layer causing the issue.
- ✓ Fix the root cause, not the symptom.
- ✓ Learn and improve after every incident.

VERIQTA

1. FAILED SYNC

The GitOps controller cannot apply the desired state successfully.

COMMON CAUSES

- Invalid manifests (YAML errors)
- Missing resources (CRDs, Namespaces)
- Permission / RBAC issues
- Webhook / admission controller rejection
- Kubernetes API errors or quota limits

COMMANDS

```
# Check application status
argocd app get <app-name>

# View sync details
argocd app sync <app-name> --dry-run

# View application events
argocd app events <app-name>
```

CHECKLIST

- ✓ Check sync status
- ✓ Review error message
- ✓ Validate manifests
- ✓ Check cluster events
- ✓ Re-sync after fix

VERIQTA

2. REPOSITORY ERRORS

The controller cannot access or read the Git repository.

COMMON CAUSES

- Repository URL is incorrect
- Network / DNS issues
- Git credentials expired or invalid
- Repository not accessible
- Branch / path does not exist

COMMANDS

```
# Test repository connectivity
argocd repo list

# Refresh repository
argocd repo refresh

# Check repository details
argocd repo get <repo-url>
```

CHECKLIST

- ✓ Verify repository URL
- ✓ Test network connectivity
- ✓ Check credentials / token
- ✓ Verify branch / path
- ✓ Check repo permissions

VERIQTA

3. AUTHENTICATION FAILURES

The controller or user cannot authenticate to Git, cluster, or external services.

COMMON CAUSES

- Expired tokens / certificates
- Incorrect credentials
- OIDC / SSO misconfiguration
- Kubeconfig expired
- Missing permissions

COMMANDS

```
# Test login
argocd login <server>

# Check user permissions
argocd account can-i <action> --as <user>

# Validate cluster access
kubectl auth can-i list pods
```

CHECKLIST

- ✓ Check credentials / token
- ✓ Check OIDC / SSO config
- ✓ Validate kubeconfig
- ✓ Check RBAC permissions
- ✓ Test login manually

VERIQTA

4. HEALTH FAILURES

Application or resources are not healthy.

COMMON CAUSES

- Pods crashing / not ready
- Missing dependencies
- Probes failing
- Config / secret issues
- External service down

COMMANDS

```
# Check health
argocd app get <app-name>

# View resource tree
argocd app tree <app-name>

# Check pod status & logs
kubectl get pods -A
kubectl logs <pod> -n <ns>
```

CHECKLIST

- ✓ Check application health
- ✓ Inspect pods / logs
- ✓ Check events
- ✓ Validate dependencies
- ✓ Verify probes & configs

VERIQTA

5. RESOURCE CONFLICTS

Resources cannot be applied due to conflicts.

COMMON CAUSES

- Resource already exists
- Immutable field change
- Multiple sources managing same resource
- Finalizers blocking deletion
- CRD version mismatch

COMMANDS

```
# View resource details
kubectl describe <resource> -n <ns>

# Check managed fields
kubectl get <resource> -o yaml


# Force replace (use carefully)
argocd app gnt <app> --force
```

CHECKLIST

- ✓ Check conflict message
- ✓ Identify conflicting owner
- ✓ Verify resource ownership
- ✓ Remove state resources
- ✓ Re-sync after resolution

VERIQTA

6. DEBUGGING WORKFLOW (FOLLOW THIS FLOW)



LEARN → DOCUMENT → IMPROVE

VERIQTA

TOOLS & COMMANDS QUICK REFERENCE


Application argocd app get <app>	Logs kubectl logs <pod> -n <ns>	Repos argocd repo list
Sync argocd app sync <app>	Describe kubectl describe <res> -n <ns>	Clusters argocd cluster list
Events argocd app events <app>	Tree argocd app tree <app>	Health argocd app get <app>

TROUBLESHOOTING PRINCIPLES

- ✓ Follow a repeatable process.
- ✓ Gather evidence before making changes.
- ✓ Minimize blast radius of any action.
- ✓ Communicate clearly with your team.
- ✓ Document root cause and resolution.

VERIQTA


ARCHITECT.

veriqta
youtube


AUTOMATE.

veriqta
github

SECURE.

veriqta
linkedin

OBSERVE.

veriqta
x

SCALE.

RECOVER.

veriqta
instagram

SUCCEED.

veriqta
telegram

VERIQTA.

14. SCALING ENTERPRISE GITOPS



Scaling GitOps is about people, processes, and platforms. Design for scale from day one to manage thousands of applications and clusters reliably and securely.

KEY IDEA



- ✓ Standardize everything.
- ✓ Automate at scale.
- ✓ Observe and optimize continuously.
- ✓ Design for multi-tenancy and resilience.
- ✓ Scale the platform, not the pain.

VERIQTA




1. THOUSANDS OF APPLICATIONS

Organize, structure, and automate to manage thousands of workloads.

STRUCTURE PATTERNS

- App-of-Apps Pattern
- Hierarchical Repositories
- Team or Domain Ownership
- Standardized Templates
- Environment Segmentation

APP-OF-APPS PATTERN



BEST PRACTICES

- ✓ Use consistent naming and labeling.
- ✓ Enforce folder and repo standards.
- ✓ Automate onboarding with templates.
- ✓ Use ApplicationSets to generate at scale.
- ✓ Document ownership and responsibilities.

VERIQTA




2. MULTI-CLUSTER MANAGEMENT

Manage applications across multiple clusters and environments.

KEY CAPABILITIES

- Multi-cluster deployment
- Cluster registration
- Centralized visibility
- Consistent policies
- Cross-cluster health

MULTI-CLUSTER VIEW



BEST PRACTICES

- ✓ Register clusters with consistent naming.
- ✓ Use namespaces to separate tenants.
- ✓ Enforce baseline policies on all clusters.
- ✓ Monitor and alert per cluster.
- ✓ Plan for cluster onboarding and offboarding.

VERIQTA




3. FLEET MANAGEMENT

Use fleet management to manage clusters as a platform.

FLEET CAPABILITIES

- Cluster Lifecycle
- Policy Distribution
- Add-on Management
- Compliance & Drift
- Bulk Operations

FLEET MANAGEMENT FLOW



BEST PRACTICES

- ✓ Use Argo CD Cluster API / Fleet / Rancher.
- ✓ Group clusters by business unit or region.
- ✓ Standardize add-ons and versions.
- ✓ Enforce security and compliance policies.
- ✓ Automate cluster provisioning and updates.

VERIQTA




4. REPOSITORY OPTIMIZATION

Optimize Git repositories for performance and maintainability.

OPTIMIZATION STRATEGIES

- Split repos by domain or team
- Use shallow structures
- Avoid large binary files
- Enable sparse checkouts
- Archive inactive manifests

REPOSITORY LAYOUT EXAMPLE



BEST PRACTICES

- ✓ Keep repositories small and focused.
- ✓ Use Kubernetes bases and overlays.
- ✓ Automate cleanup of stale resources.
- ✓ Enforce PR reviews and branch protection.
- ✓ Use semantic commits and clear messages.

VERIQTA



5. PERFORMANCE TUNING

Tune the GitOps platform for scale and responsiveness.

TUNING AREAS

- Controller concurrency
- Repo server caching
- Application sharding
- Resource limits
- Network optimization

KEY COMPONENT TUNING

Component	Tune For
Application Controller	Concurrency, Rate limits
Repo Server	Cache, Parallel requests
API Server	QPS/Burst limits
Redis	Memory, Eviction policy

BEST PRACTICES

- ✓ Increase controller concurrency carefully.
- ✓ Enable repo server caching.
- ✓ Set resource requests and limits.
- ✓ Monitor CPU, memory, latency.
- ✓ Load test before large scale rollout.

VERIQTA




6. HIGH AVAILABILITY

Ensure GitOps platform is highly available and resilient.

HA PRINCIPLES

- Multi-replica components
- Stateless controllers
- Redis HA
- DB backups
- Disaster recovery

HIGH AVAILABILITY ARCHITECTURE




BEST PRACTICES

- ✓ Run multiple replicas for all components.
- ✓ Use Redis Sentinel or Cluster mode.
- ✓ Backup Git repos and configs regularly.
- ✓ Test disaster recovery strategies.
- ✓ Monitor availability and set SLOs.


VERIQTA

ENTERPRISE GITOPS SCALING ARCHITECTURE OVERVIEW




VERIQTA

ARCHITECT.




AUTOMATE.



SECURE.



OBSERVE.



SCALE.

RECOVER.



SUCCEED.



VERIQTA.



15. DISASTER RECOVERY



Disaster recovery ensures your GitOps platform and applications can be restored quickly after failures, accidents, or disasters with minimal downtime and maximum data integrity.

KEY IDEA

- ✓ Plan before disaster, not during.
- ✓ Automate recovery as much as possible.
- ✓ Test recovery regularly.
- ✓ Document everything.
- ✓ RTO and RPO drive decisions.

VERIQTA




1. REPOSITORY BACKUP

Your Git repositories are the source of truth. Protect them with regular backups.

BACKUP STRATEGIES

- Scheduled backups (daily/hourly)
- Multiple storage locations
- Versioned backups
- Test restore capability
- Immutable storage (WORM)

BACKUP FLOW



BEST PRACTICES

- ✓ Store backups in separate AWS account/region.
- ✓ Enable object lock / immutability.
- ✓ Automate and monitor backup jobs.
- ✓ Test restore procedures regularly.

VERIQTA



2. ARGO CD RECOVERY

Recover Argo CD components, configurations and applications.

WHAT TO BACKUP

- Argo CD GitOps repositories
- Argo CD applications and projects (in Git)
- Argo CD config (argocd-secret, cm)
- TLS certificates and keys
- Argo CD database (if using external DB)

RECOVERY STEPS

- 1 Restore infrastructure (EKS / Cluster)
- 2 Install Argo CD (Helm / manifests)
- 3 Restore secrets and configurations
- 4 Verify Argo CD server health
- 5 Sync applications from Git
- 6 Validate all applications

BEST PRACTICES

- ✓ Keep Argo CD declarative in Git.
- ✓ Back up argocd-secret securely.
- ✓ Use HA setup for Argo CD components.
- ✓ Test recovery in isolated environment.

VERIQTA



3. FLUX RECOVERY

Recover Flux components and re-establish GitOps reconciliation.

WHAT TO BACKUP

- Flux Git repositories
- Flux system configuration (Kustomizations)
- Flux secret manifests (SOPS/SealedSecrets)
- SSH keys / tokens
- Helm releases (values in Git)

RECOVERY STEPS

- 1 Restore cluster infrastructure
- 2 Install Flux (Bootstrap / manifests)
- 3 Restore secrets (decrypt if needed)
- 4 Verify controllers are running
- 5 Reconcile Kustomizations / HelmReleases
- 6 Validate workloads and health

BEST PRACTICES

- ✓ Encrypt secrets (SOPS / SealedSecrets).
- ✓ Store keys securely and backup.
- ✓ Use HA for critical controllers.
- ✓ Regularly test disaster recovery.

VERIQTA



4. CLUSTER REBUILD

Rebuild clusters quickly and consistently.

REBUILD APPROACH

- Infrastructure as Code (Terraform, CDK)
- GitOps bootstrap (Argo CD / Flux)
- Automated add-ons installation
- Network and security setup
- Application sync and validation

REBUILD FLOW



BEST PRACTICES

- ✓ Automate everything with IaC and GitOps.
- ✓ Use consistent naming and tagging.
- ✓ Document all dependencies.
- ✓ Validate cluster health before app sync.

VERIQTA



5. BOOTSTRAP PROCESS

Bootstrap GitOps platform after cluster creation or recovery.

BOOTSTRAP COMPONENTS

- GitOps controller (Argo CD / Flux)
- CRDs and Custom Resources
- Ingress / Load Balancer
- TLS certificates
- Monitoring and logging
- ExternalSecrets / Secret management

BOOTSTRAP FLOW



BEST PRACTICES

- ✓ Keep bootstrap manifests in a dedicated repo.
- ✓ Use minimal dependencies.
- ✓ Idempotent and repeatable setup.
- ✓ Automate bootstrap as part of IaC.

VERIQTA



6. BUSINESS CONTINUITY

Ensure business operations continue during and after disasters.

BUSINESS CONTINUITY PLAN

- Define RTO (Recovery Time Objective)
- Define RPO (Recovery Point Objective)
- Prioritize critical applications
- Multi-region / multi-AZ strategy
- Regular DR drills and reviews

CONTINUITY PRINCIPLES

- People: Clear roles and communication
- Process: Documented procedures
- Technology: Automated and resilient systems
- Data: Backups and replication

BEST PRACTICES

- ✓ Test DR plan regularly.
- ✓ Keep documentation up to date.
- ✓ Monitor systems and backups.
- ✓ Improve plan after each drill.

VERIQTA

DISASTER RECOVERY WORKFLOW OVERVIEW



VERIQTA

16. PRODUCTION CASE STUDY



Real-world example of an enterprise GitOps platform running thousands of applications across multiple clusters and regions with secure, automated, and observable operations.


KEY TAKEAWAYS

- ✓ GitOps powers consistency at scale.
- ✓ Automation + policy = security.
- ✓ Observability drives reliability.
- ✓ Progressive delivery reduces risk.
- ✓ People, process, and tools together create resilient systems.

VERIQTA



1. ENTERPRISE PLATFORM ARCHITECTURE




2. MULTI-CLUSTER GITOPS

GLOBAL DEPLOYMENT TOPOLOGY




3. SECURE PROMOTION PIPELINE

ENVIRONMENT PROMOTION FLOW



4. OPERATIONAL WORKFLOW



5. LESSONS LEARNED

- ✓ Keep Git repositories clean, structured, and modular.
- ✓ Enforce policies early and automate enforcement.
- ✓ Use progressive delivery to reduce deployment risk.
- ✓ Observability is critical for large-scale operations.
- ✓ Simplicity in design reduces operational complexity.
- ✓ Continuous improvement is key to platform maturity.



VERIQTA



6. BUSINESS IMPACT

- ✓ Faster Delivery: Deploy changes safely and frequently.
- ✓ High Reliability: Self-healing and automated rollback.
- ✓ Security by Default: Policy-driven and verifiable.



Global Scalability
Manage thousands of apps across regions.




Operational Efficiency
Automated workflows reduce manual effort.



Cost Optimization
Standardization and automation reduce costs.

VERIQTA

ARCHITECT.

veriqta
youtube

AUTOMATE.

veriqta
github

SECURE.

veriqta
linkedin

OBSERVE.

veriqta
x

SCALE.

RECOVER.

veriqta
instagram

SUCCEED.

veriqta
telegram

VERIQTA.

17. GITOPS ANTI-PATTERNS



Avoid these common mistakes that break GitOps principles, create risk, and lead to production incidents. Design for automation, consistency, and recoverability.

KEY IDEA

- ✓ Automation fails when humans bypass it.
- ✓ Drift today = incident tomorrow.
- ✓ Keep Git the single source of truth.
- ✓ Secure, simple, observable, and recoverable.
- ✓ Standardize to scale safely.

VERIQTA

1. MANUAL CLUSTER CHANGES



Making changes directly on the cluster instead of through Git.

WHAT HAPPENS

- Changes are not tracked in Git.
- GitOps controller overwrites changes.
- Hidden configuration and drift.
- Inconsistent environments.


RISKS

- Drift
- Outages
- Confusion
- Data loss

HOW TO FIX

- ✓ Enforce Git as the only path.
- ✓ RBAC: restrict direct cluster access.
- ✓ Use pull requests for all changes.
- ✓ Audit cluster with OPA / Gatekeeper.

2. CONFIGURATION DRIFT



Cluster state differs from the desired state in Git.

WHAT HAPPENS

- Manual changes create drift.
- Controllers fight or rollback.
- Unknown source of truth.
- Hard to troubleshoot.


RISKS

- Incidents
- Instability
- Downtime
- Compliance risk

HOW TO FIX

- ✓ Continuous reconciliation enabled.
- ✓ Alert on drift (Argo CD / Flux alerts).
- ✓ Regular drift detection reports.
- ✓ Fix root cause and remove manual changes.

3. REPOSITORY SPRAWL



Too many repos with inconsistent structure and standards.

WHAT HAPPENS

- Hard to manage.
- Inconsistent policies.
- Duplicate manifests.
- Slow onboarding

RISKS

- Complexity
- Mistakes
- Security gaps
- Scalability issues

HOW TO FIX

- ✓ Use a clear repo strategy (mono vs multi).
- ✓ Standardize structure and naming
- ✓ Use ApplicationSets / Helm for scale.
- ✓ Document and enforce conventions.

4. SECRET EXPOSURE



Storing secrets in Git repositories or using weak secret management.

WHAT HAPPENS

- Secrets leaked in commits.
- Public exposure risk
- Compliance violations.
- Credential compromise.


RISKS

- Breach
- Data loss
- Compliance
- Reputation

HOW TO FIX

- ✓ Use external secret stores (Vault, AWS SM, SOPS)
- ✓ Encrypt secrets with SOPS / SealedSecrets.
- ✓ Never commit plain text secrets.
- ✓ Rotate secrets regularly.

5. POOR BRANCHING STRATEGY



Unclear or overly complex branching causes confusion and deployment errors.

WHAT HAPPENS

- Wrong code promoted
- Merge conflicts.
- Slow releases.
- Lack of traceability

RISKS

- Wrong deploys
- Delays
- Rollback pain
- Human error

HOW TO FIX

- ✓ Use environment-based branches.
- ✓ Protect main and environment branches.
- ✓ Use PR + code review + policies.
- ✓ Automate promotions with guardrails.

6. RECOVERY MISTAKES



Poor recovery process makes incidents worse and increases downtime.

WHAT HAPPENS

- Wrong rollback.
- Manual hotfix in cluster.
- Lost changes.
- Longer outages.

RISKS

- Extended downtime
- Data loss
- Business impact
- Loss of trust

HOW TO FIX

- ✓ Follow a tested recovery runbook.
- ✓ Rollback via Git (never manual).
- ✓ Keep backups of repos and clusters.
- ✓ Run regular recovery drills.

ANTI-PATTERN IMPACT SUMMARY

ANTI-PATTERN	IMPACT	OUTCOME
Manual Cluster Changes	Breaks Git as single source of truth	Drift, outages, inconsistencies
Configuration Drift	Controllers fight, unknown state	Instability, incident risk
Repository Sprawl	Hard to manage and secure	Complexity, mistakes
Secret Exposure	Secrets leaked or compromised	Security breach, compliance failure
Poor Branching Strategy	Wrong promotions, conflicts	Deploy errors, delays
Recovery Mistakes	Slow or incorrect recovery	Long downtime, data loss

GITOPS ANTI-PATTERN PREVENTION CHECKLIST

- ☒ Git is the single source of truth.
- ☒ No direct cluster edits (RBAC enforced).
- ☒ Drift monitoring and alerts enabled
- ☒ Secrets managed securely.
- ☒ Standardized repo and app structure.
- ☒ Environment-based branching strategy.
- ☒ Automated promotion with approvals.
- ☒ Tested recovery procedures and runbooks.
- ☒ Regular audits and policy enforcement.
- ☒ Team trained on GitOps best practices.

REMEMBER

GitOps is not just a tool, it's a discipline. Break the discipline, you break production.

VERIQTA




GOLDEN RULE

AUTOMATE EVERYTHING. TRACK EVERYTHING. RECOVER EVERYTHING.
GIT IS TRUTH. AUTOMATION IS POWER. OBSERVABILITY IS SAFETY.

VERIQTA


ARCHITECT.




AUTOMATE.



SECURE.



OBSERVE.



SCALE.

RECOVER.



SUCCEED.



VERIQTA.

18. SENIOR PLATFORM ENGINEER BEST PRACTICES



These best practices help you build and operate GitOps platforms that are secure, reliable, scalable, and maintainable in enterprise environments.

VERIQTA

KEY IDEA



- ✓ Build platforms that are reliable, scalable, and secure by design.
- ✓ Automation + GitOps = consistency at massive scale.
- ✓ Operate like a product. Improve continuously.

VERIQTA



1. IMMUTABLE DEPLOYMENTS

Deploy immutable artifacts. Never change what is already running.

BEST PRACTICES

- ✓ Use container images with immutable tags (no latest).
- ✓ Never modify resources in-place.
- ✓ Use rolling / blue-green / canary updates.
- ✓ Roll back by redeploying a previous version.
- ✓ Automate health checks and promotion.

OUTCOME



Predictable releases, fast rollbacks, and zero configuration drift.

VERIQTA



2. GIT AS THE SOURCE OF TRUTH

All desired states, policies, and configurations live in Git.

BEST PRACTICES

- ✓ All changes via Pull Requests.
- ✓ Peer review for every change.
- ✓ Protect main branch.
- ✓ Enforce signed commits.
- ✓ Use clear commit messages.
- ✓ Keep repos clean and structured.

OUTCOME



Auditability, traceability, and a complete change history.

VERIQTA



3. PROGRESSIVE DELIVERY

Ship changes safely using small, controlled steps.

BEST PRACTICES

- ✓ Use canary or blue-green deployments.
- ✓ Automate analysis with metrics.
- ✓ Promote automatically on success.
- ✓ Use feature flags for safe rollouts.
- ✓ Have automatic rollback on failure.

OUTCOME



Lower risk, higher velocity, and better user experience.

VERIQTA



4. AUTOMATION PRINCIPLES

Automate everything that can be automated.

BEST PRACTICES

- ✓ Infrastructure as Code (IaC) for everything.
- ✓ Automate testing in CI/CD.
- ✓ Policy as Code for governance.
- ✓ Automate notifications and alerts.
- ✓ Reduce manual steps to zero.
- ✓ Use reusable modules and templates.

OUTCOME



Consistency, speed, and reduced human error.

VERIQTA



5. DOCUMENTATION

Document decisions, systems, processes, and runbooks.

BEST PRACTICES

- ✓ Maintain architecture decision records (ADRs).
- ✓ Document platform architecture.
- ✓ Keep runbooks for common operations.
- ✓ Update documentation with every change.
- ✓ Store docs in the same repo or portal.
- ✓ Use clear diagrams and examples.

OUTCOME



Knowledge sharing, faster onboarding, and fewer mistakes.

VERIQTA



6. OPERATIONAL EXCELLENCE

Operate the platform like a product at scale.

BEST PRACTICES

- ✓ Monitor everything (apps, clusters, GitOps, infra).
- ✓ Set SLOs and SLIs.
- ✓ Have incident response playbooks.
- ✓ Run regular DR and backup tests.
- ✓ Continuously review and improve.
- ✓ Blameless postmortems.

OUTCOME



High reliability, happy users, and world-class platforms.

VERIQTA

SENIOR PLATFORM ENGINEER MINDSET



Think in Systems. Understand the whole system, not just individual parts.



Plan for Failure. Design for failure, test it, and recover automatically.



Automate Relentlessly. Remove manual work. Automate, integrate, and validate.



Secure by Default. Security is not a phase. It is built in from day one.



Measure and Improve. Use data to make decisions and drive continuous improvement.

VERIQTA



Great platform engineers don't just deploy systems. They build reliable, secure, and scalable foundations that empower teams.

VERIQTA

ARCHITECT.

veriqta
youtube

AUTOMATE.

veriqta
github

SECURE.

veriqta
linkedin

OBSERVE.

veriqta
x

SCALE.

RECOVER.

veriqta
instagram

SUCCEED.

veriqta
telegram

VERIQTA.

19. ENTERPRISE GITOPS CHECKLIST



Use this checklist to validate your GitOps platform before production rollout. Each section must be completed and validated to ensure a secure, reliable, and observable enterprise GitOps environment.

VERIQTA

KEY IDEA



- ✓ Validate everything before production.
- ✓ Automation is only as good as the checks.
- ✓ Security, visibility, and recovery are non-negotiable.
- ✓ A great checklist prevents great incidents.

VERIQTA



1. REPOSITORY READINESS

- ☐ Repository structure is standard and clean
- ☐ Application manifests are modular
- ☐ Kustomize/Helm is used correctly
- ☐ Environments are well separated
- ☐ Branch protection rules are enabled
- ☐ Pull request workflow is enforced
- ☐ Secrets are not stored in Git
- ☐ README and docs are up to date
- ☐ Policies (OPA/Conftest) are defined
- ☐ CI linting and validation are enabled



SUCCESS CRITERIA

Repository is clean, secure, well-structured, and policy compliant.



2. CLUSTER READINESS

- ☐ Clusters are registered in GitOps
- ☐ Cluster connectivity is stable
- ☐ RBAC is properly configured
- ☐ Namespace strategy is defined
- ☐ Resource quotas are configured
- ☐ Network policies are enforced
- ☐ Helm/Kustomize versions are validated
- ☐ CNI and core components are healthy
- ☐ Cluster autoscaling is configured
- ☐ Cluster baseline hardening applied



SUCCESS CRITERIA

Cluster is secure, stable, and ready for GitOps management.



3. SECURITY VALIDATION

- ☐ RBAC follows least privilege
- ☐ Service accounts are locked down
- ☐ Secrets are encrypted (SOPS/Vault)
- ☐ Image scanning is enabled
- ☐ Vulnerability scanning is automated
- ☐ Policy enforcement (OPA/Gatekeeper)
- ☐ Network policies validated
- ☐ Audit logging is enabled
- ☐ External access is restricted
- ☐ Dependency versions are reviewed



SUCCESS CRITERIA

Security controls are enforced and validated end-to-end.

VERIQTA



4. DEPLOYMENT VALIDATION

- ☐ Argo CD / Flux is healthy
- ☐ Sync policies are configured
- ☐ Automated sync rules are tested
- ☐ Helm/Kustomize builds successfully
- ☐ Dry-run deployments are validated
- ☐ Rollbacks are automatically tested
- ☐ Progressive delivery is configured
- ☐ Manual approval gates work
- ☐ Health checks and probes are validated
- ☐ Drift detection is enabled



SUCCESS CRITERIA

Applications deploy reliably with controlled, automated workflows.



5. OBSERVABILITY CHECKLIST

- ☐ Centralized logging is enabled
- ☐ Metrics collection is active
- ☐ Dashboards exist for all clusters
- ☐ Alerting rules are configured
- ☐ GitOps controller metrics monitored
- ☐ Application metrics are available
- ☐ Audit logs are shipped centrally
- ☐ Tracing is enabled (if required)
- ☐ SLOs / SLIs are defined
- ☐ Runbooks and dashboards tested



SUCCESS CRITERIA

You can see, alert, and respond before users feel the impact.



6. DISASTER RECOVERY VALIDATION

- ☐ Git repositories are backed up
- ☐ GitOps controller backup validated
- ☐ Cluster backup strategy tested
- ☐ Restore process is documented
- ☐ Bootstrap process tested
- ☐ Secrets recovery tested
- ☐ RTO and RPO are defined
- ☐ DR runbooks are reviewed
- ☐ Cross-region recovery tested
- ☐ Communication plan is ready



SUCCESS CRITERIA

You can recover quickly, confidently, and with minimal data loss.

VERIQTA



FINAL READINESS GATE

- ☐ All checklist sections are complete
- ☐ All success criteria are met
- ☐ Security and compliance validated
- ☐ Team trained and runbooks ready
- ☐ Sign-off from Platform, Security, and Operations



GITOPS PLATFORM
PRODUCTION READY




VERIQTA



A GREAT GITOPS PLATFORM IS BUILT WITH AUTOMATION, SECURED BY DESIGN,
AND OPERATED WITH OBSERVABILITY AND EXCELLENCE.

VERIQTA

ARCHITECT.

veriqta
youtube

AUTOMATE.

veriqta
github

SECURE.

veriqta
linkedin

OBSERVE.

veriqta
x

RECOVER.

veriqta
instagram

SUCCEED.

veriqta
telegram

VERIQTA.

20. PRODUCTION READINESS REVIEW



This page brings everything together.
Use it as your final review before operating
a production GitOps platform at scale.


KEY IDEA



- ✓ Operate GitOps like a product.
- ✓ Automate everything possible.
- ✓ Observe everything that matters.
- ✓ Improve continuously.

VERIQTA

1. END-TO-END GITOPS ARCHITECTURE



2. DEPLOYMENT LIFECYCLE SUMMARY

	PLAN	Define requirements, design, and policies.
	CODE	Write manifests, review & validate.
	COMMIT	Push changes to Git repository.
	SYNCHRONIZE	GitOps controller reconciles state.
	VERIFY	Validate deployments, run tests & checks.
	OPERATE	Monitor, maintain, and optimize.

3. PRODUCTION OPERATIONS CHECKLIST

- ☐ Git repositories are protected and backed up
- ☐ GitOps controllers are highly available
- ☐ Clusters are healthy and monitored
- ☐ RBAC, network policies, and secrets validated
- ☐ Automated sync, drift detection, and alerts enabled
- ☐ Observability stack is active and validated
- ☐ Backup and restore processes tested
- ☐ Change management and approvals configured
- ☐ Runbooks are documented and accessible
- ☐ Disaster recovery plan is tested and up-to-date
- ☐ Team training completed and access reviewed



SUCCESS CRITERIA:

All operational checks passed.
Platform is stable, secure, and observable.

VERIQTA

4. COMMON ENTERPRISE FAILURE PATTERNS

- ✗ Manual changes on clusters (drift)
- ✗ Over-permissive RBAC and access
- ✗ Storing secrets in Git repositories
- ✗ No branch or promotion strategy
- ✗ Skipping code review or policies
- ✗ Single GitOps controller or cluster
- ✗ Poor observability and alerting
- ✗ No backups or DR validation
- ✗ Unclear ownership and documentation
- ✗ Ignoring security scans and updates

VERIQTA

5. SENIOR ENGINEER PRINCIPLES



AUTOMATE EVERYTHING

Eliminate manual steps and human error.



GIT IS THE SOURCE OF TRUTH

Everything flows from Git.



OBSERVE EVERYTHING

You cannot improve what you cannot see.



DESIGN FOR FAILURE

Assume failure, build resilience.




DOCUMENT AND SHARE

Knowledge is a force multiplier.

VERIQTA

6. CONTINUOUS IMPROVEMENT ROADMAP



VERIQTA



PRODUCTION READINESS IS NOT A DESTINATION.

IT IS A CONTINUOUS DISCIPLINE OF AUTOMATION, OBSERVABILITY, AND EXCELLENCE.

VERIQTA

ARCHITECT.

veriqta
youtube

AUTOMATE.

veriqta
github

SECURE.

veriqta
linkedin

OBSERVE.

veriqta
x

SCALE.

RECOVER.

veriqta
instagram

SUCCEED.

veriqta
telegram

VERIQTA.