Infosys - Coding 13

There are N items at auction and M bidders. Each bidder j has a budget b[j] and submits one bid per item; bid[j][i] is bidder j's bid on item i.

Each item is awarded to the highest bidder who can afford it (bid[j][i] ≤ b[j] — a bidder cannot bid more than their budget). Ties are broken by lower bidder index.

Each bidder wins at most one item: once a bidder wins an item, their budget is exhausted and they cannot win another. Items are auctioned in order from 1 to N.

Find the total revenue (sum of winning bids across all items).

Input Format

First line: integer n, the number of items.

Second line: integer m, the number of bidders.

Next m lines: integer b[i], the budget of bidder i.

Next m lines: n space-separated integers each, representing row i of bid.

Constraints

1 <= n, m (upper bounds not fully legible; small)

bids and budgets are positive integers

Output Format

The output contains an integer value

Sample Input 0

```
3
3
10
20
30
5 5 5
10 15 10
5 20 25
```

Sample Output 0

```
35
```

Explanation 0

Budgets 10, 20, 30. Item 1: bids 5≤10, 10≤20, 5≤30 → max 10 (bidder 1). Item 2: remaining bids 5≤10, 20≤30 → max 20 (bidder 2). Item 3: remaining bid 5≤10 → bidder 0 wins (5). Total = 10 + 20 +

5 = 35.

Sample Input 1

```
4
2
100
100
10 20 30 40
40 30 20 10
```

Sample Output 1

```
60
```

Explanation 1

Item 1: bids 10 and 40, both ≤ 100 → bidder 1 wins (40). Item 2: only bidder 0 left → wins (20). Items 3 and 4: no bidders left → skipped. Total = 40 + 20 = 60.