


No. HQ/EN/Track/RRM (Comp.No.E-28550)

Date:08.08.2025

To
All CGMs
EDFC & WDFC.

Subject: Correction Slip No.2 to the DFC Railroad Manual 2024.

Competent Authority has decided that correction/addition as indicated in the enclosed Correction Slip No.2 dated 03.08.2025, to relevant para of DFC RRM-2024 be made.


(Arun Kumar Tiwari)
GGM/ Track (CTE)

Copy to:

- i) Dir/PP & Dir/Infra for kind information please.
- ii) ED/Projects for kind information please.
- iii) GGM/Bridge for kind information please.

Addendum & Corrigendum Slip No. 2
To
The DFC Railroad Manual (July-2024)

1. Existing para 620 of DFC RRM 2024 for Hot weather patrolling shall be read as follows: -

Hot Weather Patrolling: Period for hot weather patrolling shall be laid down by the Corporate Office for each section and patrol charts shall be prepared by Dy. CPM of concerned RMU Unit where necessary. Patrolling shall be organised by IMSD Sectional accordingly. In addition, the IMSD Sectional and other track officials shall be vigilant during summer and on hot days. **Hot Weather Patrolling is to be done on days when actual rail temperature reaches 2°C (safety cushion) below ($t_a + 25^\circ\text{C}$) i.e. ($t_a + 23^\circ\text{C}$) during summer season.** The beat of one Patrolman on single line is 2 km and on double line it is 1 km due to inspection on both the lines. Changes in beat length and manpower deployment as given above, if found necessary, may be decided by the Dy.CPM of the CGM/RMU unit depending on prevailing local conditions, frequency of train service, weather conditions etc. The patrolman shall preferably be provided with a GPS tracking device, to monitor his movements to ensure effective patrolling. During Patrolling, the Patrolman will walk over his beat slowly over one rail/on sleeper non gauge side of rail in one direction and on the other rail/ on sleeper non gauge sleeper side of rail in the return direction. On double lines, he will repeat this procedure alternately on UP and DN tracks. When a kink is observed, he shall immediately examine at least 100 sleepers ahead and in the rear of the kink for any floating condition of track. He should visually check each sleeper, 100 sleepers on either side of the kink, to determine any floating condition. If the patrolman has detected actual buckling of track, he will take immediate steps to protect the affected portion by display of hand signals as per rules in force. After protecting the track, the patrolman will arrange to advise the IMSD Sectional of his apprehension of a buckle/ actual buckle. The IMSD Sectional on receipt of advice of a danger of buckle will proceed to the site quickly with all available men. On arrival at site, he will first ensure protection of affected portion. He should then inspect the condition of track 100 m on either side of this suspected zone and commence heaping of surplus ballast, if available, on the shoulders and upto the rail head and keep on compacting the ballast with available tool. No attempt should be made to slew or align the track or disturb the existing ballast section. The rail temperature will also be noted by one of these officials at the place of apprehended/actual buckle. The rail facing the sun will be covered up to the level of rail head on the outside by ballast or leaves etc. to bring down the temperature of the rail.

The hot weather patrolman should always carry the following equipment:

- a) HS Flags - Red 2
- b) Staff for Flags 1
- c) Detonators 10

For estimating the Rail temperature, unit should study the correlation between ambient temperature and rail temperature in their region. With this correlation and forecast for ambient temperature available with Indian Meteorological Department, unit may be able to predict the rail temperature for their region.

As the temperature may vary, patrolling should be discontinued if the temperature is expected to stay away from the threshold value for more than 3 days. For the period in between the deployment of patrolmen and starting of patrolling & also in for intermittent discontinuity in patrolling, patrolmen may be engaged in other P-way works like removal of grass from Track, de-weeding of bushes, greasing of ERCs, cess cleaning, cess repairing & any other P. Way related works.



2. Existing para 621 of DFC RRM 2024 for Cold weather patrolling shall be read as follows: -

Cold Weather Patrolling: Cold weather patrolling shall be started when **rail temperature reaches 2°C (safety cushion) above ($t_d - 30^\circ\text{C}$) i.e. ($t_d - 28^\circ\text{C}$) during winter season.** Patrol charts will be prepared, and Patrolling shall be organized by Dy. CPM accordingly. Period and section where cold weather patrolling is to be done shall be laid down by Dy.CPM of the RMU based on Rail /weld fracture analysis. The patrolman shall preferably be provided with a GPS tracking device, to monitor his movements to ensure effective patrolling. The beat of one Patrolman on single line is 4 km and on double line it is 2 km due to inspection on both the lines. Changes in beat length and manpower deployment as given above, if found necessary, may be decided by the Dy.CPM of the RMU depending on prevailing local conditions, frequency of train service, weather conditions etc. He shall patrol the track during the coldest part of the night and lookout for weld/rail fractures and excessive gaps at SEJ. He shall protect the track at the site of weld/rail fractures or excessive gaps at SEJ and report the same to nearest Station Master/IMSD Sectional/IMSD In-charge. He will walk over his beat slowly along one rail in one direction and on the other rail in the return direction. On double line, he will repeat this procedure alternately on UP and DN tracks. He will be vigilant and look out for rail/weld failure. He will also notice the gaps at SEJs if they fall in his beat. In case he notices a rail/weld failure or gap at SEJ becomes more than the designed maximum gap, he will take immediate action to suspend the traffic and protect the line as per Para 1113. After protecting the track, the patrolman will arrange to report to Keyman, IMSD Sectional who shall arrange for making emergency repairs to pass the traffic. Cold weather patrolman should carry the following equipment's:

- a) 10 fog signals in a tin case
- b) Two tri-colour hand signal lamps/Rechargeable LED torch
- c) One match box
- d) Two red flags and one green flag
- e) One three-cell electric torch
- f) One staff
- g) Number plate
- h) Spanner
- i) Protective clothing according to local dress regulations including industrial safety shoe/
Gum boots, Safety jacket, Raincoat, Helmet with Head light.

For estimating the Rail temperature, unit should study the correlation between ambient temperature and rail temperature in their region. With this correlation and forecast for ambient temperature available with Indian Meteorological Department, unit may be able to predict the rail temperature for their region.

As the temperature may vary, patrolling should be discontinued if the temperature is expected to stay away from the threshold value for more than 3 days. For the period in between the deployment of patrolmen and starting of patrolling & also in for intermittent discontinuity in patrolling, patrolmen may be engaged in other P-way works like removal of grass from Track, de-weeding of bushes, greasing of ERCs, cess cleaning, cess repairing & any other P. Way related works.

