



Safety Plan Lane Assistance

Document Version: 1.0

Template Version 1.0, Released on 2017-06-21



Document history

Date	Version	Editor	Description
22 May 2018	1.0	Vivekkumar Mehta	First version of safety plan

Table of Contents

[Document history](#)

[Table of Contents](#)

[Introduction](#)

[Purpose of the Safety Plan](#)

[Scope of the Project](#)

[Deliverables of the Project](#)

[Item Definition](#)

[Goals and Measures](#)

[Goals](#)

[Measures](#)

[Safety Culture](#)

[Safety Lifecycle Tailoring](#)

[Roles](#)

[Development Interface Agreement](#)

[Confirmation Measures](#)

Introduction

Purpose of the Safety Plan

Safety plan guides how to achieve a safe system. Safety plan also provides a reference when modifying a system. The safety plan forces us to define roles then outline the steps we will take to achieve functional safety. Structured safety plan sets timelines and deadlines which helps to complete project on time.

Scope of the Project

For the lane assistance project, the following safety lifecycle phases are in scope:

- Concept phase
- Product Development at the System Level
- Product Development at the Software Level

The following phases are out of scope:

- Product Development at the Hardware Level
- Production and Operation

Deliverables of the Project

The deliverables of the project are:


- Safety Plan
- Hazard Analysis and Risk Assessment
- Functional Safety Concept
- Technical Safety Concept
- Software Safety Requirements and Architecture

Item Definition

The Item being discussed is Lane assistance system. The System's lane departure warning function vibrates steering wheel if driver changes lane without giving lane change signal.

A lane assistance system generally has two functions:

- lane departure warning
- lane keeping assistance



If a driver departs a lane without using a turn signal, the system assumes that the driver has become distracted and did not mean to leave the lane. The system will vibrate the steering (lane departure warning) and also move the steering wheel back towards the lane center (lane keeping assistance). Location of the car with respect to lane will be detected by camera sensor subsystem. Driver steering torque system will give input to steering ECU. Car display subsystem will provide visual information to driver. While all these subsystems are part of the item, steering wheel is outside the item.

Goals and Measures

Goals

Goal of the project is to achieve a safe and reliable components of Lane assistance system according to ISO 26262. ISO 26262 compliance is not legally required. But most if not all automotive companies and automotive parts suppliers strive to make their products compliant with the standard. The standard provides a methodical, state-of-the-art framework for ensuring a safe electrical/electronic system.

Measures

Measures and Activities	Responsibility	Timeline
Follow safety processes	All Team Members	Constantly
Create and sustain a safety culture	All Team Members	Constantly
Coordinate and document the planned safety activities	Safety Manager	Constantly
Allocate resources with adequate functional safety competency	Project Manager	Within 2 weeks of start of project
Tailor the safety lifecycle	Safety Manager	Within 4 weeks of start of project
Plan the safety activities of the safety lifecycle	Safety Manager	Within 4 weeks of start of project
Perform regular functional safety audits	Safety Auditor	Once every 2 months
Perform functional safety pre-assessment prior to audit by external functional safety assessor	Safety Manager	3 months prior to main assessment
Perform functional safety assessment	Safety Assessor	Conclusion of functional safety activities

Safety Culture

Here are some characteristics of a good safety culture:

- **High priority:** safety has the highest priority among competing constraints like cost and productivity
- **Accountability:** processes ensure accountability such that design decisions are traceable back to the people and teams who made the decisions
- **Rewards:** the organization motivates and supports the achievement of functional safety
- **Penalties:** the organization penalizes shortcuts that jeopardize safety or quality
- **Independence:** teams who design and develop a product should be independent from the teams who audit the work
- **Well defined processes:** company design and management processes should be clearly defined
- **Resources:** projects have necessary resources including people with appropriate skills
- **Diversity:** intellectual diversity is sought after, valued and integrated into processes
- **Communication:** communication channels encourage disclosure of problems

An organization should develop clear policies and strategies to support the development, production, and operation of safe systems. Good safety culture, put safety as the highest priority over competing constraints, like cost and productivity. Without a good safety culture, functional safety is difficult to achieve.

Safety Lifecycle Tailoring

For the lane assistance project, the following safety lifecycle phases are in scope:

- Concept phase
- Product Development at the System Level
- Product Development at the Software Level

The following phases are out of scope:

- Product Development at the Hardware Level
- Production and Operation

Roles

Role	Org
Functional Safety Manager- Item Level	OEM
Functional Safety Engineer- Item Level	OEM
Project Manager - Item Level	OEM
Functional Safety Manager- Component Level	Tier-1
Functional Safety Engineer- Component Level	Tier-1
Functional Safety Auditor	OEM or external
Functional Safety Assessor	OEM or external

Development Interface Agreement

A DIA (development interface agreement) defines the roles and responsibilities between OEM and tier-1 involved in developing a product. All involved parties need to agree on the contents of the DIA before the project begins.

The DIA also specifies what evidence and work products each party will provide to prove that work was done according to the agreement.

The ultimate goal is to ensure that all parties are developing safe vehicles in compliance with ISO 26262.

Here are major sections of a DIA:

- Appointment of customer and supplier safety managers
- Joint tailoring of the safety lifecycle
- Activities and processes to be performed by the customer; activities and processes to be performed by the supplier
- Information and work products to be exchanged
- Parties or persons responsible for each activity in design and production

- Any supporting processes or tools to ensure compatibility between customer and supplier technologies

Confirmation Measures

Confirmation measures serve two purposes:

- that a functional safety project conforms to ISO 26262, and
- that the project really does make the vehicle safer.

The people who carry out confirmation measures need to be independent from the people who actually developed the project.

Confirmation review

Ensures that the project complies with ISO 26262. As the product is designed and developed, an independent person would review the work to make sure ISO 26262 is being followed.

Functional safety audit

Checking to make sure that the actual implementation of the project conforms to the safety plan is called a functional safety audit.

Functional safety assessment

Confirming that plans, designs and developed products actually achieve functional safety is called a functional safety assessment.