

Modification Log – By Vivek Vellaiyappan Surulimuthu

<https://github.com/vivekVells/MSCS721-roomScheduler>

lastUpdated: 22nd Feb 2018

(Have to format and update function block. Will update this soon. **(best viewable in ms-word with Navigation Pane enabled (click View->check 'Navigation Pane'))**)

THINGS TO CONSIDER

Function:

Common Function Usage: (lots added. Have to update)

- Clear screen of console in windows command prompt
 - o To clear previous statements
- Thread usage to sleep
 - o Used thread.sleep() func
- Input Integrity Check (IIC) (**Applies to wherever possible**)
 - o Numbers
 - o Strings

New Function Added? (many added. Have to update)

Under roomscheduler.RoomScheduler.java

- isRoomExists(ArrayList<Room>, String)
- isStartDateBeforeCurrentDate(String, String)
- isStartDate30DaysAfterCurrentDate(String, String)
- isMinutesRounded15Increments(String)
- isMinutesDurationNotExceed60(String, String)
- isSameRoomAndTimeBooked(ArrayList<Room>, String, String, String,String)
- isSameDateTimeDurationBooked(ArrayList<Room>, String, String, String, String)
- isRoomExists()
 - o returns true if the room already exists.

Under utility.Utility.java (to be updated soon)

Under test.RoomSchedulerTest (to be updated soon)

Main Function: (many added. Have to update)

- Choice selection (IIC)
 - o Accepts only numbers but not any string value
 - If numbers that are not available in the given choices being inputted, the system will not accept and redirects back to main menu
-

Add Room Choice Option:

- Room Capacity arg
 - o Maximum allowed room capacity is 10. If user inputs negative or above 10, the system will not allow and redirects to main menu
- What if room already exists and user trying to add again, the same room name with capacity
 - o Can two rooms have same name but different capacity?
 - Naaaah!!! Should not allow. Confusing. Unique room name with its capacity

List Room Choice Option:

- Whether room exists condition

Remove Room Choice Option:

- Whether room exists condition
- Check whether the room is scheduled by anyone if so
 - o Override
 - o Do not override and exit

Schedule Room Choice Option:

- IIC
- TimeStamp Integrity check
 - o Time + day integrity
 - o Note:
 - Refer Today's date time stamp at top left corner and schedule accordingly.
 - Input of Date should be in "YYYY-mm-dd" - (e-g): 2018-02-28
 - Input of Time should be in "HH:MM" - (e-g): 10:10
 - Start and End Time should have minutes such that minutes are of round figures like HH:00 or HH:15 or HH:30 or HH:45
 - Start and End Time difference should be minimum of 15 minutes and maximum of 60 minutes
- o
- Timezone based scheduling check (ultimate)
- Daylight saving consideration (ultimate)
- Should not schedule
 - o Past timings
 - o Very far future timings (lets keep limit like 30 days from the booked day)
 - o Scheduling for same day same timing
 - o Scheduling for removed rooms which were previously used for a meeting (have to handle this well)
 - o Leap year + month end day 31 or 30 thingy + minutes hour thingy (12:60:60)
- Conflict scheduling timings of same date

Scheduled Date: 2018-02-05 Timing: 06:00 to 06:45 (startTime to stopTime)=> diff: 45 mts		
Case A (target1 – target2)	06:00 – 06:45	Same timing diff => 45 mts
Case B	06:00 – 07:15	More than 60 minutes diff => 75 mts
Case C	05:45 – 06:15	Target1 before startTime and Target2 before stopTime diff => 30 mts
Case D	05:45 – 06:45	Wrapping already booked timing

Case E	06:15 – 06:30	Target1 & Target2 inside the startTime and stopTime such that Target1 after startTime and Target2 before stopTime
Case F	06:30 – 07:15	Target1 after startTime and Target2 after stopTime
Case G		

	startTime	stopTime
Target1	Before	Before
Target1	Before	After
Target1	After	Before
Target1	After	After
Target2	Before	Before
Target2	Before	After
Target2	After	Before
Target2	After	After

TEST CASES CHART to have consistent Room Scheduling

Date: 2018-02-05 Timing (start – stop): 06:00 – 06:30 (dev mindset to break the code cases)						
	startTime	stopTime	Cases (target1 – target2 for Target1 Focussed) (target2 – target1 for Target2 Focussed)	Status	Remarks (NP – No Probs Bug - Bug)	Code Review and Output Review
Target1 Focussed	Target1 before	Target2 before	05:30 – 05:45 04:15 – 05:30	PASS PASS	NP NP	
	Target1 before	Target2 after	05:30 – 06:30	FAIL	NP	
	Target1 after	Target2 before	06:15 – 06:30	FAIL	Bug	False Alarm. Not a bug (06:00 – 06:30 was not booked prior to this test case). Rechecked and verified (09:00 – 09:30 booked then 09:15 – 09:30 case done -> result PASS FAIL).
	Target1 after	Target2 after	06:15 – 06:45 06:30 – 07:00	FAIL PASS	NP NP	
Target2 Focussed	Target2 before	Target1 before	05:45 – 05:30 08:30 – 08:15	FAIL FAIL	NP NP	
	Target2 before (03:15 – 03:30)	Target1 after (03:15 – 03:30)	03:30 – 03:00	FAIL	NP	
	Target2 after	Target1 before	06:30 – 06:15	FAIL	NP	
	Target2 after	Target1 after	06:45 – 06:15 07:00 – 06:30	FAIL	NP NP	
Common	Target1 equals	Target2 equals	06:00 – 06:30	FAIL	NP	

	Target2 equals	Target1 equals	06:30 – 06:00	FAIL	NP	
Booked range between target1 and target2			Book 1 st 02:00 – 02:15 Then 01:45 – 02:30	PASS FAIL	NP	

Console output Verify:

```

MINGW64/e/Marist/Semester2/SoftwareVerificationAndMaintenance
*****
***** ROOM SCHEDULER PAGE *****
*****
Today: 2018/02/04 14:02:57

***** SCHEDULED ROOM INFORMATION PAGE *****

Room Name: a
a's Schedule:
1) 2018-02-05 | A: 05:30:00 - 05:45:00
2) 2018-02-05 | PASS: 04:15:00 - 04:30:00
3) 2018-02-05 | BUGHERE: 06:15:00 - 06:30:00
4) 2018-02-05 | PASS: 06:30:00 - 07:00:00
5) 2018-02-05 | PASS: 03:15:00 - 03:30:00
6) 2018-02-05 | PASS: 02:00:00 - 02:15:00

Redirecting to Home Page Menu...

```

- Only one bug.. good start.
 - o False alarm. Not a bug

```
C:\MINGW64\bin\Marist\Semester2\SoftwareVerificationAndMaintenance
*****
ROOM SCHEDULER PAGE
*****
Today: 2018/02/04 14:02:41

SCHEDULED ROOM INFORMATION PAGE

Room Name: a

a's Schedule:

1) 2018-02-05 | A: 05:30:00 - 05:45:00
2) 2018-02-05 | PASS: 04:15:00 - 04:30:00
3) 2018-02-05 | BUGHERE: 06:15:00 - 06:30:00
4) 2018-02-05 | PASS: 06:30:00 - 07:00:00
5) 2018-02-05 | PASS: 03:15:00 - 03:30:00
6) 2018-02-05 | PASS: 02:00:00 - 02:15:00
7) 2018-02-05 | PASS: 09:00:00 - 09:30:00

Redirecting to Home Page Menu...
```

- Handle if someone changed their local time in their system and try to schedule. How do I handle it???? Hmmmmm

List Scheduled Room Choice Option:

- isRoomExists()
- Existed Room have schedules?
- IIC

Old date time api vs new one:

- ZonedDateTime.getAvailableZoneIds()
 - o To print all time zone
- Date (old):
 - o Java.sql and java.util
 - o Not Thread safe (multiple threads working on same date object, then if one thread completes work faster, the other suffers)
 - o Import java.text.*; to format the date
- (new):
 - o Immutable (changing existing value will create a new object for you??? **Ask someone to explain this well.. unable to understand well**)
 - o Simple to use
 - o LocalDate
 - System defined date java.time.LocalDate;
 - o LocalTime
 - Java.time.LocalTime;
 - LocalTime.now()
 - LocalTime.now(ZoneId.of("Asia/Kuwait"))
 - o Instant

- Instant.now()
- LocalDateTime

EXTRAS

File Write Operation Options

- <https://www.journaldev.com/878/java-write-to-file>
- Let's have a brief look at four options we have for java write to file operation.
 - FileWriter: FileWriter is the simplest way to write a file in java, it provides overloaded write method to write int, byte array and String to the File. You can also write part of the String or byte array using FileWriter. FileWriter writes directly into Files and should be used only when number of writes are less.
 - BufferedWriter: BufferedWriter is almost similar to FileWriter but it uses internal buffer to write data into File. So if the number of write operations are more, the actual IO operations are less and performance is better. You should use BufferedWriter when number of write operations are more.
 - FileOutputStream: FileWriter and BufferedWriter are meant to write text to the file but when you need raw stream data to be written into file, you should use FileOutputStream to write file in java.
 - Files: Java 7 introduced Files utility class and we can write a file using it's write function, internally it's using OutputStream to write byte array into file.

JSON Selection

- <https://blog.takipi.com/the-ultimate-json-library-json-simple-vs-gson-vs-jackson-vs-json/>
- Parsing speed isn't the only consideration when choosing a JSON library, but it is an important one. Upon running this benchmark test, what we found was that there is no one library that blows the others away on parsing speed across all file sizes and all runs. The libraries that performed best for big files suffered for small files and vice versa.
- Choosing which library to use on the merit of parsing speed comes down to your environment then.
 - If you have an environment that deals often or primarily with big JSON files, then Jackson is your library of interest. GSON struggles the most with big files.
 - If your environment primarily deals with lots of small JSON requests, such as in a micro services or distributed architecture setup, then GSON is your library of interest. Jackson struggles the most with small files.
 - If you end up having to often deal with both types of files, JSON.simple came in a very close 2nd place in both tests, making it a good workhorse for a variable environment. Neither Jackson nor GSON perform as well across multiple files sizes.
 - As far as parsing speed goes, JSONP doesn't have much to recommend for it in any scenario. It performs poorly for both big and small files compared to other available options. Fortunately, Java 9 is reportedly getting native JSON implementation, which one would imagine is going to be an improvement over the reference implementation.
- So there you have it. If you're concerned about parsing speed for your JSON library, choose Jackson for big files, GSON for small files, and JSON.simple for handling both. Let me know if you have any thoughts on this benchmark in the comments.

The JSON file we got at first try:

Room Name: a

```
[
  {
    "name": "a",
    "capacity": 6,
    "meetings": [
      {
        "startDate": "2018-02-15",
        "startTime": "10:15:00",
        "stopTime": "10:30:00",
        "subject": "ShortMeeting"
      },
      {
        "startDate": "2018-02-20",
        "startTime": "11:00:00",
        "stopTime": "12:00:00",
        "subject": "LongMeeting"
      },
      {
        "startDate": "2018-02-25",
        "startTime": "01:15:00",
        "stopTime": "02:00:00",
        "subject": "FunMeeting"
      }
    ]
  }
]
```

]

Redirecting to Home Page Menu...

- File autoclose using try with resource block.

Things to do:

- File path independent resolve
- Room export suggestion thingy
- Lock file before writing

STATIC TOOL ANALYSIS RESULTS

SonarLint eclipse plugin results:

RoomScheduler.java

Issue	Issue Summary	Issue Description	Issue Correction
// Advantages include -> @ExposeAnnotation serializing nulls custom instance creators set version support pretty printing custom serialize & deserialize	This block of commented- out lines of code should be removed.	Sections of code should not be "commented out" (squid:CommentedO utCodeLine) Code smell Major Programmers should not comment out code as it bloats programs and reduces readability. Unused code should be deleted and can be retrieved from source control history if required.	// Advantages include ExposeAnnotation - serializing nulls - custom instance creators - set version support - pretty printing - custom serialize and deserialize

<pre>ArrayList<Room> rooms = new ArrayList<Room>();</pre>	<p>Replace the type specification in this constructor call with the diamond operator ("<>").</p>	<p>The diamond operator ("<>") should be used (squid:S2293)</p> <p>CODE_SMELL Code smell MINOR Minor</p> <p>Java 7 introduced the diamond operator (<>) to reduce the verbosity of generics code. For instance, instead of having to declare a List's type in both its declaration and its constructor, you can now simplify the constructor declaration with <>, and the compiler will infer the type.</p> <p>Note that this rule is automatically disabled when the project's sonar.java.source is lower than 7</p>	<pre>ArrayList<Room> rooms = new ArrayList<>();</pre>
<pre>while (!end) {...}</pre>	<p>Remove this expression which always evaluates to "true"</p>	<p>Boolean expressions should not be gratuitous (squid:S2589)</p> <p>Code smell Major</p> <p>If a boolean expression doesn't</p>	<pre>case 8: Log.info("Quitting the program..."); utility.Utility.sleepFor(2000);</pre>

		change the evaluation of the condition, then it is entirely unnecessary, and can be removed. If it is gratuitous because it does not match the programmer's intent, then it's a bug and the expression should be fixed.	<pre>utility.Utility.clearScreen(); end = true;</pre>
<p>case 8:</p> <pre> System.out.println("Quitting the program..."); System.exit(0); default:</pre>	End this switch case with an unconditional break, return or throw statement.	<p>Switch cases should end with an unconditional "break" statement (squid:S128)</p> <p>Code smell Blocker</p> <p>When the execution is not explicitly terminated at the end of a switch case, it continues to execute the statements of the following case. While this is sometimes intentional, it often is a mistake which leads to unexpected behavior.</p>	<pre> case 8: Log.info("Quitting the program..."); utility.Utility.sleepFor(2000); utility.Utility.clearScreen(); end = true;</pre>
<pre> System.out.println("Quitting the program...");</pre>	Replace this use of System.out or System.err by a logger.	<p>Standard outputs should not be used directly to log anything (squid:S106)</p> <p>Code smell Major</p> <p>When logging a message there are several important requirements which must be fulfilled:</p>	<pre> Log.info("Quitting the program...");</pre>

		<ul style="list-style-type: none"> • The user must be able to easily retrieve the logs • The format of all logged message must be uniform to allow the user to easily read the log • Logged data must actually be recorded • Sensitive data must only be logged securely <p>If a program directly writes to the standard outputs, there is absolutely no way to comply with those requirements. That's why defining and using a dedicated logger is highly recommended.</p>	
<code>e.printStackTrace();</code>	Use a logger to log this exception.	<p><code>Throwable.printStackTrace(...)</code> should not be called (squid:S1148)</p> <p>Vulnerability Minor</p> <p><code>Throwable.printStackTrace(...)</code> prints a <code>Throwable</code> and its stack trace to some stream. By default that stream <code>System.Err</code>, which could inadvertently expose sensitive information.</p>	<code><i>Log</i>.trace(e);</code>

		<p>Loggers should be used instead to print Throwables, as they have many advantages:</p> <ul style="list-style-type: none"> • Users are able to easily retrieve the logs. • The format of log messages is uniform and allow users to browse the logs easily. <p>This rule raises an issue when <code>printStackTrace</code> is used without arguments, i.e. when the stack trace is printed to the default stream.</p>	
<pre>System.out.print(" Room Name: ");</pre>	<p>Define a constant instead of duplicating this literal "Room Name:" 3 times.</p>	<p>String literals should not be duplicated (squid:S1192)</p> <p>Code smell Critical</p> <p>Duplicated string literals make the process of refactoring error-prone, since you must be sure to update all occurrences.</p> <p>On the other hand, constants can be referenced from many places, but only need to be updated in a single place.</p>	<pre>private static final String ROOM_NAME = "Room Name: "; Log.info(ROOM_NAME);</pre>

<pre> if (roomList.size() == 0 !isRoomExists(roomList, name)) { </pre>	<p>Use isEmpty() to check whether the collection is empty or not.</p>	<p>Collection.isEmpty() should be used to test for emptiness (squid:S1155)</p> <p>Code smell Minor</p> <p>Using Collection.size() to test for emptiness works, but using Collection.isEmpty() makes the code more readable and can be more performant. The time complexity of any isEmpty() method implementation should be O(1) whereas some implementations of size() can be O(n).</p>	<pre> if (roomList.isEmpty() !isRoomExists(roomList, name)) { </pre>
<pre> String minuteStamp = time.split(":")[1]; if (minuteStamp.equals("00")) minuteStamp.equals("15") minuteStamp.equals("30") minuteStamp.equals("45")) { </pre>	<p>Replace this if-then-else statement by a single return statement.</p>	<p>Return of boolean expressions should not be wrapped into an "if-then-else" statement (squid:S1126)</p> <p>Code smell Minor</p> <p>Return of boolean literal statements wrapped into if-then-else ones should be simplified.</p>	<pre> Boolean status = true; if (!minuteStamp.equals("00") minuteStamp.equals("15") minuteStamp.equals("30") minuteStamp.equals("45"))) { status = false; } return status; </pre>
<pre> protected static boolean isSameRoomAndTimeBooked(ArrayList<Room> roomList, String name, String startDate, String startTime, String endTime) { </pre>	<p>Remove this unused method parameter "startDate".</p>	<p>Unused method parameters should be removed (squid:S1172)</p>	<pre> protected static boolean isSameRoomAndTimeBooked(ArrayList<Room> roomList, String name, String startTime, String endTime) { </pre>

		<p>Code smell Major</p> <p>Unused parameters are misleading. Whatever the values passed to such parameters, the behavior will be the same.</p>	
<pre> for (Meeting m : currentRoom.getMeetings()) { ...} </pre>	<p>A "NullPointerException" could be thrown; "currentRoom" is nullable here.</p>	<p>Null pointers should not be dereferenced (squid:S2259)</p> <p>Bug Major</p> <p>A reference to null should never be dereferenced/accessed. Doing so will cause a NullPointerException to be thrown. At best, such an exception will cause abrupt program termination. At worst, it could expose debugging information that would be useful to an attacker, or it could allow an attacker to bypass security measures.</p> <p>Note that when they are present, this rule takes advantage of @CheckForNull and @Nonnull annotations defined in JSR-305 to understand which values are and are not nullable except when @Nonnull is used on the parameter to equals, which by contract</p>	<pre> if (currentRoom == null) { return false; } </pre>

		should always work with null.	
<pre> protected static void scheduleRoom(ArrayList<Room> roomList) { ..} </pre>	<p>Refactor this method to reduce its Cognitive Complexity from 38 to the 15 allowed.</p>	<p>Cognitive Complexity of methods should not be too high (squid:S3776)</p> <p>Code smell Critical</p> <p>Cognitive Complexity is a measure of how hard the control flow of a method is to understand. Methods with high Cognitive Complexity will be difficult to maintain.</p> <p>See</p> <ul style="list-style-type: none"> • Cognitive Complexity 	
<pre> Room curRoom = getRoomFromName(roomList, name); Meeting meeting = new Meeting(startDate, startTime, endTime, subject); curRoom.addMeeting (meeting); </pre>	<p>A "NullPointerException" could be thrown; "curRoom" is nullable here.</p>	<p>Null pointers should not be dereferenced (squid:S2259)</p> <p>Bug Major</p> <p>A reference to null should never be dereferenced/accessed. Doing so will cause a NullPointerException to be thrown. At best, such an exception will cause abrupt program termination. At worst, it could expose debugging information that would be useful to an</p>	<pre> if (curRoom != null) { curRoom.addMeeting (meeting); Log.info("\nSuccessfully scheduled meeting!"); } </pre>

		<p>attacker, or it could allow an attacker to bypass security measures.</p> <p>Note that when they are present, this rule takes advantage of @CheckForNull and @Nonnull annotations defined in JSR-305 to understand which values are and are not nullable except when @Nonnull is used on the parameter to equals, which by contract should always work with null.</p>	<pre> } else { Log.error("Error occurred while scheduling the meeting..."); } </pre>
<pre> if (getRoomFromName(roomList, roomName).getMeetings(). size() == 0) { ..} </pre>	<p>A "NullPointerException" could be thrown; "getRoomFromName" is nullable here.</p>	<p>Null pointers should not be dereferenced (squid:S2259)</p> <p>Bug Major</p> <p>A reference to null should never be dereferenced/accessed. Doing so will cause a NullPointerException to be thrown. At best, such an exception will cause abrupt program termination. At worst, it could expose debugging information that would be useful to an attacker, or it could allow an attacker to bypass security measures.</p> <p>Note that when they are present, this rule takes advantage of</p>	

		@CheckForNull and @Nonnull annotations defined in JSR-305 to understand which values are and are not nullable except when @Nonnull is used on the parameter to equals, which by contract should always work with null.	

Utility.java

Issue	Issue Summary	Issue Description	Issue Correction
<code>public class <u>Utility</u> { ...}</code>	Add a private constructor to hide the implicit public one.	<p>Utility classes should not have public constructors (squid:S1118)</p> <p>Code smell Major</p> <p>Utility classes, which are collections of static members, are not meant to be instantiated. Even abstract utility classes, which can be extended, should not have public constructors.</p>	<pre>private Utility() { throw new IllegalStateException("Utility class"); }</pre>

		<p>Java adds an implicit public constructor to every class which does not define at least one explicitly. Hence, at least one non-public constructor should be defined.</p> <p>...</p> <p>Exceptions</p> <p>When class contains public static void main(String[] args) method it is not considered as utility class and will be ignored by this rule.</p>	
<pre> public static void clearScreen() { try { if (System.getProperty("os.name") .contains("Windows")) try { new ProcessBuilder("cmd", "/c", "cls").inheritIO().start().wai tFor(); } catch (InterruptedException e) { // TODO Auto-generated catch block e.printStackTrace(); } ... } </pre>	<p>Extract this nested try block into a separate method.</p>	<p>Try-catch blocks should not be nested (squid:S1141)</p> <p>Code smell Major</p> <p>Nesting try/catch blocks severely impacts the readability of source code because it makes it too difficult to understand which block will catch which exception.</p>	
<pre> // TODO Auto-generated catch block </pre>	<p>Complete the task associated to this TODO comment.</p>	<p>Track uses of "TODO" tags (squid:S1135)</p> <p>Code smell Info</p> <p>TODO tags are commonly used to mark places where</p>	<p>deleted</p>

		<p>some more code is required, but which the developer wants to implement later.</p> <p>Sometimes the developer will not have the time or will simply forget to get back to that tag.</p> <p>This rule is meant to track those tags and to ensure that they do not go unnoticed.</p>	
<pre>e.printStackTrace();</pre>	<p>Use a logger to log this exception.</p>	<p>Throwable.printStackTrace(...) should not be called (squid:S1148)</p> <p>Vulnerability Minor</p> <p>Throwable.printStackTrace(...) prints a Throwable and its stack trace to some stream. By default that stream System.Err, which could inadvertently expose sensitive information.</p> <p>Loggers should be used instead to print Throwables, as they have many advantages:</p> <ul style="list-style-type: none"> • Users are able to easily retrieve the logs. • The format of log messages is 	<pre>Log.trace(e);</pre>

		<p>uniform and allow users to browse the logs easily.</p> <p>This rule raises an issue when <code>printStackTrace</code> is used without arguments, i.e. when the stack trace is printed to the default stream.</p>	
<pre> try { new ProcessBuilder("cmd", "/c", "cls").inheritIO().start().wait tFor(); } catch (InterruptedException e) { Log.trace(e); } </pre>	<p>Either re-interrupt this method or rethrow the "InterruptedException".</p>	<p>"InterruptedException" should not be ignored (squid:S2142)</p> <p>Bug Major</p> <p>InterruptedExceptions should never be ignored in the code, and simply logging the exception counts in this case as "ignoring". The throwing of the InterruptedException clears the interrupted state of the Thread, so if the exception is not handled properly the fact that the thread was interrupted will be lost. Instead, InterruptedExceptions should either be rethrown - immediately or after cleaning up the method's state - or the thread should be re-interrupted by calling <code>Thread.interrupt()</code> even if this is</p>	<pre> } catch (InterruptedException e) { // Restore interrupted state... Thread.currentThread ().interrupt(); Log.trace(e); } </pre>

		<p>supposed to be a single-threaded application. Any other course of action risks delaying thread shutdown and loses the information that the thread was interrupted - probably without finishing its task.</p> <p>Similarly, the ThreadDeath exception should also be propagated. According to its JavaDoc:</p> <p>If ThreadDeath is caught by a method, it is important that it be rethrown so that the thread actually dies.</p>	
<pre>String jsonPrettyPrint = gson.toJson(obj);</pre>	<p>Immediately return this expression instead of assigning it to the temporary variable "jsonPrettyPrint".</p>	<p>Local variables should not be declared and then immediately returned or thrown (squid:S1488)</p> <p>Code smell Minor</p> <p>Declaring a variable only to immediately return or throw it is a bad practice.</p> <p>Some developers argue that the practice improves code readability, because it enables them to explicitly name what is being</p>	

		returned. However, this variable is an internal implementation detail that is not exposed to the callers of the method. The method name should be sufficient for callers to know exactly what will be returned.	

Room.java

Issue	Issue Summary	Issue Description	Issue Correction
public <u>ArrayList<Meeting></u> getMeetings() { ...}	The return type of this method should be an interface such as "List" rather than the implementation "ArrayList".	<p>Declarations should use Java collection interfaces such as "List" rather than specific implementation classes such as "LinkedList" (squid:S1319)</p> <p>Code smell Minor</p> <p>The purpose of the Java Collections API is to provide a well defined hierarchy of interfaces in order to hide implementation details.</p> <p>Implementing classes must be used to instantiate new collections, but the result of an instantiation should ideally be stored in a variable whose type</p>	<pre>import java.util.List; public class Room { private String name; private int capacity; private List<Meeting> meetings; public List<Meeting> getMeetings() { return meetings; } public void setMeetings(List<Meeting> meetings) { this.meetings = meetings; } }</pre>

		<p>is a Java Collection interface.</p> <p>This rule raises an issue when an implementation class:</p> <ul style="list-style-type: none"> • is returned from a public method. • is accepted as an argument to a public method. • is exposed as a public member. 	

Meeting.java

Issue	Issue Summary	Issue Description	Issue Correction
<pre> public String toString() { return getDate() + " " + getSubject() + ": " + this.getTime().toString() + " - " + this.getTime(); } </pre>	<p>"getTime" returns a string, there's no need to call "toString".</p>	<p>"toString()" should never be called on a String object (squid:S1858)</p> <p>Code smell Minor</p> <p>Invoking a method designed to return a string representation of an object which is already a string is a waste of keystrokes. This redundant construction may be optimized by the compiler, but</p>	<pre> public String toString() { return getDate() + " " + getSubject() + ": " + this.getTime() + " - " + this.getTime(); } </pre>

		will be confusing in the meantime.	

Code Coverage Pro

PMD

- Report being generated.
 - o Link:

SonarQube Analysis

Take 1: Analysis result:

The screenshot displays the SonarQube web interface at the URL `localhost:9000/projects?sort=-analysis_date`. The interface is divided into a left sidebar with filters and a main content area showing the project analysis results.

Filters (Left Sidebar):

- Quality Gate:** Passed (1), Warning (0), Failed (0).
- Reliability (Bugs):** A (0), B and worse (1), C and worse (1), D and worse (0), E (0).
- Security (Vulnerabilities):** A (0), B and worse (1), C and worse (0), D and worse (0), E (0).
- Maintainability (Code Smells):** A (0), B and worse (1).

Main Content Area:

- Perspective:** Overall Status
- Sort by:** Last analysis date
- Search by project name or key:** (Empty search bar)
- 1 projects**

Project Analysis Results (roomscheduler):

- Status:** Passed
- Last analysis:** February 11, 2018, 2:48 PM
- Metrics:**
 - Bugs: 6 (C)
 - Vulnerabilities: 5 (B)
 - Code Smells: 103 (B)
 - Coverage: 0.0%
 - Duplications: 0.0%
- Language:** 531 Java

Footer:

Embedded database should be used for evaluation purpose only
The embedded database will not scale, it will not support upgrading to newer versions of SonarQube, and there is no support for migrating your data out of it into a different database engine.

SonarQube™ technology is powered by SonarSource SA
Version 7.0 (build 36138) - LGPL v3 - Community - Documentation - Get Support - Plugins - Web API - About

Take 2: Analysis after modification:

← → ↻

localhost:9000/dashboard?id=roomscheduler

☆

🔌 📄 📄 📄 📄 📄 📄

🌐

sonarqube

Projects Issues Rules Quality Profiles Quality Gates Administration More ▾

🔍 Search for projects, sub-projects and files... A

roomscheduler master ⓘ

February 11, 2018, 6:47 PM Version 1.0

★

Overview Issues Measures Code Activity Administration ▾ More ▾

Quality Gate Passed

Bugs Vulnerabilities

0 A

0 A

0 A

0 A

Bugs Vulnerabilities

New Bugs New Vulnerabilities

Leak Period: since previous version
started 4 hours ago

Code Smells

0 A

0 A

0 A

0 A


Debt Code Smells

New Debt New Code Smells

started 4 hours ago

No tags ▾

Activity



February 11, 2018

1.0

February 11, 2018

Quality Profile: Stop using 'Sonar way' (JavaScript)

February 11, 2018

Project Analyzed

Show More



Quality Gate

(Default) Sonar way

Key

roomscheduler

Take 1 vs Take 2 Analysis after code modification:






Maven checkstyle results

Take 1: as of 15th feb 2018

Summary

Files	 Info	 Warnings	 Errors
4	0	0	600

Files

File	 I	 W	 E
roomscheduler/Meeting.java	0	0	73
roomscheduler/Room.java	0	0	55
roomscheduler/RoomScheduler.java	0	0	351
utility/Utility.java	0	0	121

Take 2: as of 22nd Feb 2018

Room Scheduler

Last Published: 2018-02-22 | Version: 0.0.1-SNAPSHOT

Room Scheduler

Project Documentation

Project Reports
Checkstyle
Surefire Report






Checkstyle Results

The following document contains the results of [Checkstyle](#) 6.18 with sun_checks.xml ruleset. [XML](#)

Summary

Files	 Info	 Warnings	 Errors
6	0	0	799

Files

File	 I	 W	 E
roomscheduler/Meeting.java	0	0	74
roomscheduler/Room.java	0	0	56
roomscheduler/RoomScheduler.java	0	0	409
test/java/RoomSchedulerTest.java	0	0	135
test/java/UtilityTest.java	0	0	2
utility/Utility.java	0	0	123

Maven SureFire Report
Take 1: as of 22nd Feb 2018

Room Scheduler

Last Published: 2018-02-22 | Version: 0.0.1-SNAPSHOT

Room Scheduler

Project Documentation

Project Reports
Checkstyle
Surefire Report



Surefire Report

Summary

[\[Summary\]](#) [\[Package List\]](#) [\[Test Cases\]](#)

Tests	Errors	Failures	Skipped	Success Rate	Time
13	0	0	0	100%	0.142

Note: failures are anticipated and checked for with assertions while errors are unanticipated.

test.java

	Class	Tests	Errors	Failures	Skipped	Success Rate	Time
	RoomSchedulerTest	13	0	0	0	100%	0.142

Test Cases

[\[Summary\]](#) [\[Package List\]](#) [\[Test Cases\]](#)

RoomSchedulerTest

	testIsStartDateBeforeCurrentDate	0.125
	testMeetingStartDateAndTimeEndTimeSubject	0
	testAddRoom	0
	testIsMinutesRounded15Increments	0
	testScheduleRooms	0
	testIsRoomExists	0
	testIsSameDateTimeDurationBooked	0.002
	testIsStartDate30DaysAfterCurrentDate	0.007
	testRemoveRoom	0
	testGetRoomFromName	0
	testIsMinutesDurationNotExceed60	0.008
	testListSchedule	0
	testListRoom	0

Issues Reported (Tested on Windows & Eclipse IDE & gitbash cmd)

Issue List (Total: 4) by Vivek Vellaiyappan

Issue 1:

Title: Unable to schedule room if similar time duration exists between 2 or more dates bug #1 ||

Type: bug

Replication steps:

- schedule room for a date 2018/02/20 with time duration as 10:15 to 11:00
- schedule room for different date 2018/02/21 with previous time duration (similar or range)

Issue:

- Unable to schedule room

Expected:

- Able to schedule a room

Issue 2:

Title: Import room conflicts #2

Type: bug

While importing, if the imported room and already present room is available, the imported room gets added and its schedule and stuffs are messy. Advise on how to correct this. Either

- remove all previous entries and make the fresh batch of imported ones or
- handle the conflicts properly

Issue 3:

Title: Unable to list all room's schedule #3 || type: enhancement

Able to list only specified room's schedule. What if the client wants to view what all rooms are available and their schedules?

Issue 4:

Title: Import feature remodify - files imported from & rooms imported info missing #4 || type: enhancement

Reported:

User Unable to view anything after the import feature is executed. Unable to do the followings

- the status of completion - success or failure (increase the redirecting timing)
- where this file is imported from
- which rooms and associated schedules

Kindly refer the screenshot attached

For user gentig – Issues reported by me

Issue list (Total: 6)

Issues reported by me:

1. Unable to test import and export feature #9 opened 12 minutes ago by vivekVells || type: bug
2. List Schedule- program breakdown or exits with errors #8 opened 14 minutes ago by vivekVells || type: bug
3. Schedule Room - Invalid input acceptance & Program Breakdown #7 opened 18 minutes ago by vivekVells || type: bug
4. Remove Room - program breakdown or program exits with errors #6 opened 22 minutes ago by vivekVells || type: bug

5. Add Room Option - Program Breakdown or Exits with errors #5 opened 25 minutes ago by vivekVells || type: bug
6. Add Room Option - Invalid Room Capacity Acceptance #4 opened 28 minutes ago by vivekVells || type: bug

For user priyankagadde – Issues reported by me

Issue list (total: 3)

Issues reported by me:

1. Add Room Option - Invalid Room Capacity Acceptance & weird 0 input behavior #6 opened just now by vivekVells || type: bug
2. Schedule Room - Invalid input acceptance & Program Breakdown #5 opened 4 minutes ago by vivekVells || type: bug
3. Import rooms option - program breakdown or exits with errors #4 opened 7 minutes ago by vivekVells || type: bug

Issues Resolved by me:

Issue 1:

Title: Unable to schedule room if similar time duration exists between 2 or more dates bug #1 ||
Type: bug

Replication steps:

- schedule room for a date 2018/02/20 with time duration as 10:15 to 11:00
- schedule room for different date 2018/02/21 with previous time duration (similar or range)

Issue:

- Unable to schedule room

Expected:

- Able to schedule a room

Action Taken by me:

- Added a new function 'isSameDateTimeDurationBooked' that resolved this issue by first checking if the same room or different room is being booked and the same time duration check is done only when the result is same room else the same time duration check 'isSameRoomAndTimeBooked' not checked

Issue 2:

Title: Import room conflicts #2

Type: bug

While importing, if the imported room and already present room is available, the imported room gets added and its schedule and stuffs are messy. Advise on how to correct this. Either

- remove all previous entries and make the fresh batch of imported ones or
- handle the conflicts properly

Action Taken:

- thinking of removing all previous entries... not coded yet

Issue 3:

Title: Unable to list all room's schedule #3 || type: enhancement

Able to list only specified room's schedule. What if the client wants to view what all rooms are available and their schedules?

Coder Comment:

Gave a thought and decided to do the followings

- **Case 1:** User might want to watch all room's schedules
 - To do this, use 'ALL_ROOMS' to view all room's schedules
- **Case 2:** User might want to view a specific room's schedules
 - To do this, just type the corresponding room to view that particular room's schedules alone

Action Taken:

- Fixed the issues. Handled the stuffs properly.
- Used function 'listRoomSchedule' function to handle this situation well.
- Kindly refer the screenshot attached. (you may also find the issues fixed log in MSCS721-roomScheduler/src/resources/log/IssuesFixed/)

Issue 4:

Title: Import feature remodify - files imported from & rooms imported info missing #4 || type: enhancement

Reported:

User Unable to view anything after the import feature is executed. Unable to do the followings

- the status of completion - success or failure (increase the redirecting timing)
- where this file is imported from
- which rooms and associated schedules

Kindly refer the screenshot attached:

Coder Comment:

Awesome. Fixed this one.

Action taken:

- Added a condition to check whether the imported file is empty or not and handled correctly
Used the listRoomSchedule() function feature (very useful for me now) to view the room information
- Kindly refer the corrected screenshot for reference. (check in issues fixed inside log folder)